

Creation Date 24-Nov-2010

Revision Date 22-Mar-2024

Revision Number 2

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Methylamine 40 wt% solution in water
Cat No. : **R21706**
Synonyms Aqueous solution of methanamine; Monomethylamine in water.; Aminomethane in water
REACH registration number -

Unique Formula Identifier (UFI) **P0QF-MTWH-NW0R-RXNR**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Sector of use SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites
Product category PC21 - Laboratory chemicals
Process categories PROC15 - Use as a laboratory reagent
Environmental release category ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

Thermo Fisher (Kandel) GmbH
 Erlenbachweg 2, 76870 Kandel, Germany
 Tel: +49 (0) 721 84007 280
 Fax: +49 (0) 721 84007 300

Swiss distributor - Fisher Scientific AG
 Neuhoferstrasse 11, CH 4153 Reinach
 Tel: +41 (0) 56 618 41 11
<https://www.fishersci.ch/ch/en/customer-help-support/forms/email-us.html>

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:
 Tox Info Suisse Emergency Number: **145 (24hr)**
 Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
 Chemtrec (24h) Toll-Free: 0800 564 402
 Chemtrec Local: +41-43 508 20 11 (Zurich)

Poison Centre - Emergency information services

Ireland : National Poisons Information Centre (NPIC) -
01 809 2166 (8am-10pm, 7 days a week)
Malta : +356 2395 2000
Cyprus : +357 2240 5611

SAFETY DATA SHEET

Methylamine 40 wt% solution in water

Revision Date 22-Mar-2024

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Flammable liquids

Category 2 (H225)

Health hazards

Acute oral toxicity

Category 4 (H302)

Acute Inhalation Toxicity - Vapors

Category 4 (H332)

Skin Corrosion/Irritation

Category 1 B (H314)

Serious Eye Damage/Eye Irritation

Category 1 (H318)

Specific target organ toxicity - (single exposure)

Category 3 (H335)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H314 - Causes severe skin burns and eye damage

H335 - May cause respiratory irritation

H302 + H332 - Harmful if swallowed or if inhaled

Precautionary Statements

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P301 + P330 + P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P260 - Do not breathe dust/fume/gas/mist/vapors/spray

P310 - Immediately call a POISON CENTER or doctor/physician

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

2.3. Other hazards

SAFETY DATA SHEET

Methylamine 40 wt% solution in water

Revision Date 22-Mar-2024

Toxicity to Soil Dwelling Organisms
Toxic to terrestrial vertebrates
This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Water	7732-18-5	231-791-2	57-60	-
Methylamine	74-89-5	EEC No. 200-820-0	40-43	Flam. liq. 1 (H224) Acute Tox. 4 (H302) Acute Tox; 4 (H332) Skin Corr. 1B (H314) Eye Dam. 1 (H318) STOT SE 3 (H335)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Methylamine	STOT SE 3 :: C>=5%	-	-

REACH registration number		-
Components	Reach Registration Number	
Methylamine	01-2119475496-25	

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Eye Contact	Immediate medical attention is required. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately.
Inhalation	Remove to fresh air. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required. If not breathing, give artificial respiration.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. Difficulty in breathing. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

SAFETY DATA SHEET

Methylamine 40 wt% solution in water

Revision Date 22-Mar-2024

Notes to Physician

Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Water mist may be used to cool closed containers. Carbon dioxide (CO₂). Dry chemical. Chemical foam.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Flammable. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air.

Hazardous Combustion Products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂), Ammonia.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges. Avoid contact with skin, eyes or clothing. Do not breathe dust/fume/gas/mist/vapors/spray. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area)

6.2. Environmental precautions

See Section 12 for additional Ecological Information. Should not be released into the environment.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal. Wear self-contained breathing apparatus and protective suit. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Keep combustibles (wood, paper, oil, etc) away from spilled material.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not breathe mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Handle product only in closed system or provide appropriate exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Use only non-sparking tools. Use only in well-ventilated areas. Keep away from open flames, hot surfaces and sources of ignition. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static

SAFETY DATA SHEET

Methylamine 40 wt% solution in water

Revision Date 22-Mar-2024

discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a dry, cool and well-ventilated place. Keep container tightly closed. Keep away from heat, sparks and flame. Flammables area. Keep away from oxidizing agents. Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Class 3

Switzerland - Storage of hazardous substances

Storage class - SC 3

<https://www.kvu.ch/de/themen/stoffe-und-produkte>

<https://www.kvu.ch/fr/themes/substances-et-produits>

<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): IRE - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001.

Published by the Health and Safety Authority.

CH - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Methylamine			STEL / VLCT: 10 ppm. STEL / VLCT: 12 mg/m ³ .	TWA: 5 ppm 8 uren TWA: 6.6 mg/m ³ 8 uren STEL: 15 ppm 15 minuten STEL: 19 mg/m ³ 15 minuten	STEL / VLA-EC: 15 ppm (15 minutos). STEL / VLA-EC: 19 mg/m ³ (15 minutos). TWA / VLA-ED: 5 ppm (8 horas) TWA / VLA-ED: 6.5 mg/m ³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
Methylamine		TWA: 5 ppm (8 Stunden). AGW - ceiling factor 2; exposure factor 2 TWA: 6.4 mg/m ³ (8 Stunden). AGW - ceiling factor 2; exposure factor 2 TWA: 5 ppm (8 Stunden). MAK an instantaneous value of 10 ppm corresponding to 13 mg/m ³ should not be exceeded; even if the MAK value is adhered to, "odor-associated" symptoms cannot be	STEL: 15 ppm 15 minutos TWA: 5 ppm 8 horas		STEL: 10 ppm 15 minuutteina STEL: 13 mg/m ³ 15 minuutteina

SAFETY DATA SHEET

Methylamine 40 wt% solution in water

Revision Date 22-Mar-2024

		ruled out in individual cases TWA: 6.4 mg/m ³ (8 Stunden). MAK an instantaneous value of 10 ppm corresponding to 13 mg/m ³ should not be exceeded; even if the MAK value is adhered to, "odor-associated" symptoms cannot be ruled out in individual cases Höhepunkt: 10 ppm Höhepunkt: 12.8 mg/m ³			
--	--	---	--	--	--

Component	Austria	Denmark	Switzerland	Poland	Norway
Methylamine	MAK-KZGW: 10 ppm 15 Minuten MAK-KZGW: 12 mg/m ³ 15 Minuten MAK-TMW: 10 ppm 8 Stunden MAK-TMW: 12 mg/m ³ 8 Stunden Ceiling: 10 ppm Ceiling: 12 mg/m ³	TWA: 5 ppm 8 timer TWA: 6.4 mg/m ³ 8 timer STEL: 10 ppm 15 minutter STEL: 12.8 mg/m ³ 15 minutter Hud	STEL: 10 ppm 15 Minuten STEL: 13 mg/m ³ 15 Minuten TWA: 10 ppm 8 Stunden TWA: 13 mg/m ³ 8 Stunden	STEL: 15 mg/m ³ 15 minutach TWA: 5 mg/m ³ 8 godzinach	TWA: 10 ppm 8 timer TWA: 12 mg/m ³ 8 timer STEL: 20 ppm 15 minutter. value calculated STEL: 18 mg/m ³ 15 minutter. value calculated

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Methylamine	TWA: 12.0 mg/m ³		TWA: 5 ppm 8 hr. TWA: 6 mg/m ³ 8 hr. STEL: 15 ppm 15 min STEL: 19 mg/m ³ 15 min		TWA: 10 mg/m ³ 8 hodinách. Potential for cutaneous absorption Ceiling: 20 mg/m ³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Methylamine	Nahk TWA: 10 ppm 8 tundides. TWA: 13 mg/m ³ 8 tundides. STEL: 20 ppm 15 minutites. STEL: 25 mg/m ³ 15 minutites.		TWA: 10 ppm TWA: 12 mg/m ³		TWA: 5 ppm 8 klukkustundum. TWA: 6.4 mg/m ³ 8 klukkustundum. Skin notation Ceiling: 10 ppm Ceiling: 12.8 mg/m ³

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Methylamine		TWA: 10 ppm IPRD TWA: 13 mg/m ³ IPRD Oda STEL: 20 ppm STEL: 25 mg/m ³			TWA: 8 ppm 8 ore TWA: 10 mg/m ³ 8 ore STEL: 12 ppm 15 minute STEL: 15 mg/m ³ 15 minute

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Methylamine	Skin notation MAC: 1 mg/m ³	TWA: 10 ppm TWA: 13 mg/m ³	TWA: 10 ppm 8 urah TWA: 13 mg/m ³ 8 urah STEL: 10 ppm 15 minutah STEL: 13 mg/m ³ 15 minutah	Indicative STEL: 20 ppm 15 minuter Indicative STEL: 25 mg/m ³ 15 minuter TLV: 10 ppm 8 timmar. NGV TLV: 13 mg/m ³ 8 timmar. NGV Hud	

Biological limit values

SAFETY DATA SHEET

Methylamine 40 wt% solution in water

Revision Date 22-Mar-2024

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Methylamine 74-89-5 (40-43)				DNEL = 0.1mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Methylamine 74-89-5 (40-43)			DNEL = 0.427mg/m ³	DNEL = 0.72mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Methylamine 74-89-5 (40-43)	PNEC = 0.016mg/L	PNEC = 0.776mg/kg sediment dw	PNEC = 0.016mg/L	PNEC = 0.1263mg/L	PNEC = 0.126mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Methylamine 74-89-5 (40-43)	PNEC = 0.0016mg/L	PNEC = 0.0776mg/kg sediment dw			

8.2. Exposure controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting/equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Neoprene	See manufacturers	-		(minimum requirement)

SAFETY DATA SHEET

Methylamine 40 wt% solution in water

Revision Date 22-Mar-2024

recommendations	EN 374
-----------------	--------

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced
Recommended Filter type: Inorganic gases and vapours filter Type B Grey Ammonia and organic ammonia derivatives filter Type K Green

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141
When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls No information available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Colorless	
Odor	Fishy	
Odor Threshold	No data available	
Melting Point/Range	-38 °C / -36.4 °F	
Softening Point	No data available	
Boiling Point/Range	48 °C / 118.4 °F	@ 760 mmHg
Flammability (liquid)	Highly flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	Lower 4.9 Upper 20.8	
Flash Point	-15 °C / 5 °F	Method - No information available
Autoignition Temperature	430 °C / 806 °F	
Decomposition Temperature	No data available	
pH	14	
Viscosity	No data available	
Water Solubility	Completely soluble	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Methylamine	-0.713	
Vapor Pressure	No data available	
Density / Specific Gravity	0.900	
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

SAFETY DATA SHEET

Methylamine 40 wt% solution in water

Revision Date 22-Mar-2024

Molecular Weight 31.05
Explosive Properties Vapors may form explosive mixtures with air

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity None known, based on information available

10.2. Chemical stability Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization No information available.
Hazardous Reactions No information available.

10.4. Conditions to avoid Keep away from open flames, hot surfaces and sources of ignition. Incompatible products.

10.5. Incompatible materials Acids. Strong oxidizing agents. sodium hypochlorite. Acid anhydrides. Acid chlorides. Carbon dioxide (CO₂).

10.6. Hazardous decomposition products Nitrogen oxides (NO_x). Carbon monoxide (CO). Carbon dioxide (CO₂). Ammonia.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;
Oral Category 4
Dermal Based on available data, the classification criteria are not met
Inhalation Category 4

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Water	-	-	-
Methylamine	698 mg/kg (Rat)	-	2.9 mg/L/4h (Rat)

(b) skin corrosion/irritation; Category 1 B

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;
Respiratory Based on available data, the classification criteria are not met
Skin Based on available data, the classification criteria are not met

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

(f) carcinogenicity; Based on available data, the classification criteria are not met

SAFETY DATA SHEET

Methylamine 40 wt% solution in water

Revision Date 22-Mar-2024

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; Based on available data, the classification criteria are not met

(h) STOT-single exposure; Category 3

Results / Target organs Respiratory system.

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

Target Organs None known.

(j) aspiration hazard; Based on available data, the classification criteria are not met

Symptoms / effects, both acute and delayed Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

Component	Freshwater Fish	Water Flea	Freshwater Algae
Methylamine		EC50: 147 - 180 mg/L, 48h Static (Daphnia magna) EC50: = 163 mg/L, 48h (Daphnia magna)	

12.2. Persistence and degradability Readily biodegradable
Persistence Persistence is unlikely, based on information available.

12.3. Bioaccumulative potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Methylamine	-0.713	2860 - 6910 dimensionless

12.4. Mobility in soil The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air.

12.5. Results of PBT and vPvB assessment No data available for assessment.

SAFETY DATA SHEET

Methylamine 40 wt% solution in water

Revision Date 22-Mar-2024

12.6. Endocrine disrupting properties

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant This product does not contain any known or suspected substance
Ozone Depletion Potential This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms. Solutions with high pH-value must be neutralized before discharge.

Switzerland - Waste Ordinance Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number UN1235
14.2. UN proper shipping name METHYLAMINE, AQUEOUS SOLUTION
14.3. Transport hazard class(es) 3
 Subsidiary Hazard Class 8
14.4. Packing group II

ADR

14.1. UN number UN1235
14.2. UN proper shipping name METHYLAMINE, AQUEOUS SOLUTION
14.3. Transport hazard class(es) 3
 Subsidiary Hazard Class 8
14.4. Packing group II

IATA

14.1. UN number UN1235
14.2. UN proper shipping name METHYLAMINE, AQUEOUS SOLUTION
14.3. Transport hazard class(es) 3
 Subsidiary Hazard Class 8
14.4. Packing group II

ALFAAR21706

SAFETY DATA SHEET

Methylamine 40 wt% solution in water

Revision Date 22-Mar-2024

- 14.5. Environmental hazards** No hazards identified
- 14.6. Special precautions for user** No special precautions required.
- 14.7. Maritime transport in bulk according to IMO instruments** Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Water	7732-18-5	231-791-2	-	-	X	X	KE-35400	X	-
Methylamine	74-89-5	200-820-0	-	-	X	X	KE-23421	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Water	7732-18-5	X	ACTIVE	X	-	X	X	X
Methylamine	74-89-5	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Water	7732-18-5	-	-	-
Methylamine	74-89-5	-	Use restricted. See item 75. (see link for restriction details)	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Water	7732-18-5	Not applicable	Not applicable
Methylamine	74-89-5	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

SAFETY DATA SHEET

Methylamine 40 wt% solution in water

Revision Date 22-Mar-2024

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification Water endangering class = 2 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Methylamine	WGK2	Class I : 20 mg/m ³ (Massenkonzentration)

Component	France - INRS (Tables of occupational diseases)
Methylamine	Tableaux des maladies professionnelles (TMP) - RG 49,RG 49bis

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has not been conducted

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H224 - Extremely flammable liquid and vapor
H225 - Highly flammable liquid and vapor
H302 - Harmful if swallowed
H332 - Harmful if inhaled
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H335 - May cause respiratory irritation
H335 - May cause respiratory irritation

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

SAFETY DATA SHEET

Methylamine 40 wt% solution in water

Revision Date 22-Mar-2024

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Prepared By

Health, Safety and Environmental Department

Creation Date

24-Nov-2010

Revision Date

22-Mar-2024

Revision Summary

New emergency telephone response service provider.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006 .

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet