

Creation Date 10-Nov-2009

Revision Date 11-Oct-2023

Revision Number 6

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: **[Bis(2-methoxyethyl)amino]sulfur trifluoride, 50% solution in toluene**
Cat No. : **428980000; 428981000**
Synonyms **Deoxo-Fluor**
Molecular Formula **C6 H14 F3 N O2 S**

Unique Formula Identifier (UFI) **GW25-FUW6-UW0M-3QJQ**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use **Laboratory chemicals.**
Uses advised against **No Information available**

1.3. Details of the supplier of the safety data sheet

Company

EU entity/business name
Thermo Fisher Scientific
Janssen Pharmaceuticaaan 3a, 2440 Geel, Belgium

UK entity/business name
Fisher Scientific UK
Bishop Meadow Road,
Loughborough, Leicestershire LE11 5RG, United Kingdom

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
e-mail - infoch@thermofisher.com

E-mail address **begel.sdsdesk@thermofisher.com**

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

Poison Centre - Emergency information services

Ireland : National Poisons Information Centre (NPIC) -
01 809 2166 (8am-10pm, 7 days a week)
Malta : +356 2395 2000
Cyprus : +357 2240 5611

SAFETY DATA SHEET

[Bis(2-methoxyethyl)amino]sulfur trifluoride, 50% solution in toluene

Revision Date 11-Oct-2023

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Flammable liquids

Category 2 (H225)

Health hazards

Aspiration Toxicity

Category 1 (H304)

Acute oral toxicity

Category 3 (H301)

Skin Corrosion/Irritation

Category 1 A (H314)

Serious Eye Damage/Eye Irritation

Category 1 (H318)

Reproductive Toxicity

Category 2 (H361d)

Specific target organ toxicity - (single exposure)

Category 3 (H336)

Specific target organ toxicity - (repeated exposure)

Category 2 (H373)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H301 - Toxic if swallowed

H304 - May be fatal if swallowed and enters airways

H314 - Causes severe skin burns and eye damage

H336 - May cause drowsiness or dizziness

H361d - Suspected of damaging the unborn child

H373 - May cause damage to organs through prolonged or repeated exposure

EUH014 - Reacts violently with water

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

SAFETY DATA SHEET

[Bis(2-methoxyethyl)amino]sulfur trifluoride, 50% solution in toluene

Revision Date 11-Oct-2023

P310 - Immediately call a POISON CENTER or doctor/physician

2.3. Other hazards

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Sulfur, trifluoro[2-methoxy-N-(2-methoxyethyl)ethaniminato- κ .N]-, (T-4)-	202289-38-1	478-190-3	50	Skin Corr. 1A (H314) Acute Tox. 3 (H301) (EUH014)
Toluene	108-88-3	203-625-9	50	Flam. Liq. 2 (H225) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 (H336) Repr. 2 (H361d) STOT RE 2 (H373)

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
Inhalation	If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Remove to fresh air. Immediate medical attention is required. Risk of serious damage to the lungs (by aspiration).
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

SAFETY DATA SHEET

[Bis(2-methoxyethyl)amino]sulfur trifluoride, 50% solution in toluene

Revision Date 11-Oct-2023

Causes burns by all exposure routes. Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Water.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Reacts violently with water. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂), Nitrogen oxides (NO_x), Sulfur oxides, Hydrogen fluoride.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Do not expose spill to water. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

SAFETY DATA SHEET

[Bis(2-methoxyethyl)amino]sulfur trifluoride, 50% solution in toluene

Revision Date 11-Oct-2023

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Flammables area. Keep away from heat, sparks and flame. Keep refrigerated. Keep away from water or moist air. Store under an inert atmosphere. Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Class 3

Switzerland - Storage of hazardous substances

Storage class - SC 3
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Toluene	TWA: 50 ppm (8hr) TWA: 192 mg/m ³ (8hr) STEL: 100 ppm (15min) STEL: 384 mg/m ³ (15min) Skin	STEL: 100 ppm 15 min STEL: 384 mg/m ³ 15 min TWA: 50 ppm 8 hr TWA: 191 mg/m ³ 8 hr Skin	TWA / VME: 20 ppm (8 heures). restrictive limit TWA / VME: 76.8 mg/m ³ (8 heures). restrictive limit TWA / VME: 1000 mg/m ³ (8 heures). restrictive limit STEL / VLCT: 100 ppm. restrictive limit STEL / VLCT: 384 mg/m ³ . restrictive limit STEL / VLCT: 1500 mg/m ³ . Peau	TWA: 20 ppm 8 uren TWA: 77 mg/m ³ 8 uren STEL: 100 ppm 15 minuten STEL: 384 mg/m ³ 15 minuten Huid	STEL / VLA-EC: 100 ppm (15 minutos). STEL / VLA-EC: 384 mg/m ³ (15 minutos). TWA / VLA-ED: 50 ppm (8 horas) TWA / VLA-ED: 192 mg/m ³ (8 horas) Piel

Component	Italy	Germany	Portugal	The Netherlands	Finland
Toluene	TWA: 50 ppm 8 ore.	TWA: 50 ppm (8	STEL: 100 ppm 15	STEL: 384 mg/m ³ 15	TWA: 25 ppm 8 tunteina

SAFETY DATA SHEET

[Bis(2-methoxyethyl)amino]sulfur trifluoride, 50% solution in toluene

Revision Date 11-Oct-2023

	Time Weighted Average TWA: 192 mg/m ³ 8 ore. Time Weighted Average Pelle	Stunden). AGW - exposure factor 2 TWA: 190 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 50 ppm (8 Stunden). MAK TWA: 190 mg/m ³ (8 Stunden). MAK Höhepunkt: 100 ppm Höhepunkt: 380 mg/m ³ Haut	minutos STEL: 384 mg/m ³ 15 minutos TWA: 50 ppm 8 horas TWA: 192 mg/m ³ 8 horas Pele	minuten TWA: 150 mg/m ³ 8 uren	TWA: 81 mg/m ³ 8 tunteina STEL: 100 ppm 15 minuutteina STEL: 380 mg/m ³ 15 minuutteina Iho
--	--	--	--	--	--

Component	Austria	Denmark	Switzerland	Poland	Norway
Toluene	Haut MAK-KZGW: 100 ppm 15 Minuten MAK-KZGW: 380 mg/m ³ 15 Minuten MAK-TMW: 50 ppm 8 Stunden MAK-TMW: 190 mg/m ³ 8 Stunden	TWA: 25 ppm 8 timer TWA: 94 mg/m ³ 8 timer STEL: 384 mg/m ³ 15 minutter STEL: 100 ppm 15 minutter Hud	Haut/Peau STEL: 200 ppm 15 Minuten STEL: 760 mg/m ³ 15 Minuten TWA: 50 ppm 8 Stunden TWA: 190 mg/m ³ 8 Stunden	STEL: 200 mg/m ³ 15 minutach TWA: 100 mg/m ³ 8 godzinach	TWA: 25 ppm 8 timer TWA: 94 mg/m ³ 8 timer STEL: 37.5 ppm 15 minutter. value calculated STEL: 141 mg/m ³ 15 minutter. value calculated Hud

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Toluene	TWA: 50 ppm TWA: 192.0 mg/m ³ STEL : 100 ppm STEL : 384.0 mg/m ³ Skin notation	kože TWA-GVI: 50 ppm 8 satima. TWA-GVI: 192 mg/m ³ 8 satima. STEL-KGVI: 100 ppm 15 minutama. STEL-KGVI: 384 mg/m ³ 15 minutama.	TWA: 192 mg/m ³ 8 hr. TWA: 50 ppm 8 hr. STEL: 384 mg/m ³ 15 min STEL: 100 ppm 15 min Skin	Skin-potential for cutaneous absorption STEL: 100 ppm STEL: 384 mg/m ³ TWA: 50 ppm TWA: 192 mg/m ³	TWA: 200 mg/m ³ 8 hodinách. Potential for cutaneous absorption Ceiling: 500 mg/m ³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Toluene	Nahk TWA: 50 ppm 8 tundides. TWA: 192 mg/m ³ 8 tundides. STEL: 100 ppm 15 minutites. STEL: 384 mg/m ³ 15 minutites.	Skin notation TWA: 50 ppm 8 hr TWA: 192 mg/m ³ 8 hr STEL: 100 ppm 15 min STEL: 384 mg/m ³ 15 min	skin - potential for cutaneous absorption STEL: 100 ppm STEL: 384 mg/m ³ TWA: 50 ppm TWA: 192 mg/m ³	STEL: 380 mg/m ³ 15 percekben. CK TWA: 190 mg/m ³ 8 óraban. AK lehetséges borön keresztüli felszívódás	STEL: 50 ppm STEL: 188 mg/m ³ TWA: 25 ppm 8 klukkustundum. TWA: 94 mg/m ³ 8 klukkustundum. Skin notation

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Toluene	skin - potential for cutaneous exposure STEL: 40 ppm STEL: 150 mg/m ³ TWA: 14 ppm TWA: 50 mg/m ³	TWA: 50 ppm IPRD TWA: 192 mg/m ³ IPRD Oda STEL: 100 ppm STEL: 384 mg/m ³	Possibility of significant uptake through the skin TWA: 50 ppm 8 Stunden TWA: 192 mg/m ³ 8 Stunden STEL: 100 ppm 15 Minuten STEL: 384 mg/m ³ 15 Minuten	possibility of significant uptake through the skin TWA: 50 ppm TWA: 192 mg/m ³ STEL: 100 ppm 15 minuti STEL: 384 mg/m ³ 15 minuti	Skin notation TWA: 50 ppm 8 ore TWA: 192 mg/m ³ 8 ore STEL: 100 ppm 15 minute STEL: 384 mg/m ³ 15 minute

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Toluene	TWA: 50 mg/m ³ 1264 MAC: 150 mg/m ³	Ceiling: 384 mg/m ³ Potential for cutaneous absorption TWA: 50 ppm TWA: 192 mg/m ³	TWA: 50 ppm 8 urah TWA: 192 mg/m ³ 8 urah Koža STEL: 100 ppm 15 minutah STEL: 384 mg/m ³ 15 minutah	Binding STEL: 100 ppm 15 minuter Binding STEL: 384 mg/m ³ 15 minuter TLV: 50 ppm 8 timmar. NGV TLV: 192 mg/m ³ 8 timmar. NGV Hud	Deri TWA: 50 ppm 8 saat TWA: 192 mg/m ³ 8 saat STEL: 100 ppm 15 dakika STEL: 384 mg/m ³ 15 dakika

SAFETY DATA SHEET

[Bis(2-methoxyethyl)amino]sulfur trifluoride, 50% solution in toluene

Revision Date 11-Oct-2023

Biological limit values

List source(s):

Component	European Union	United Kingdom	France	Spain	Germany
Toluene			Toluene: 1 mg/L venous blood end of shift Hippuric acid: 2500 mg/g creatinine urine end of shift	o-Cresol: 0.6 mg/L urine end of shift Toluene: 0.05 mg/L blood start of last shift of workweek Toluene: 0.08 mg/L urine end of shift	Toluene: 600 µg/L whole blood (immediately after exposure) Toluene: 75 µg/L urine (end of shift) o-Cresol (after hydrolysis): 1.5 mg/L urine (for long-term exposures: at the end of the shift after several shifts) o-Cresol (after hydrolysis): 1.5 mg/L urine (end of shift)

Component	Italy	Finland	Denmark	Bulgaria	Romania
Toluene		Toluene: 500 nmol/L blood in the morning after a working day.		Hippuric acid: 1.6 mmol/mmol Creatinine urine at the end of exposure or end of work shift	Hippuric acid: 2 g/L urine end of shift o-Cresol: 3 mg/L urine end of shift

Component	Gibraltar	Latvia	Slovak Republic	Luxembourg	Turkey
Toluene		Hippuric acid: 1.6 g/g Creatinine urine end of shift Toluene: 0.05 mg/L blood end of shift	Toluene: 600 µg/L blood end of exposure or work shift o-Cresol: 1.5 mg/L urine after all work shifts for long-term exposure o-Cresol: 1.5 mg/L urine end of exposure or work shift Hippuric acid: 1600 mg/g creatinine end of exposure or work shift		

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Toluene 108-88-3 (50)				DNEL = 384mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Toluene	DNEL = 384mg/m ³	DNEL = 384mg/m ³	DNEL = 192mg/m ³	DNEL = 192mg/m ³

SAFETY DATA SHEET

[Bis(2-methoxyethyl)amino]sulfur trifluoride, 50% solution in toluene

Revision Date 11-Oct-2023

108-88-3 (50)				
-----------------	--	--	--	--

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Toluene 108-88-3 (50)	PNEC = 0.68mg/L	PNEC = 16.39mg/kg sediment dw	PNEC = 0.68mg/L	PNEC = 13.61mg/L	PNEC = 2.89mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Toluene 108-88-3 (50)	PNEC = 0.68mg/L	PNEC = 16.39mg/kg sediment dw			

8.2. Exposure controls

Engineering Measures

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Viton (R) Nitrile rubber	See manufacturers recommendations	-	EN 374	(minimum requirement)

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387

Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system.

SAFETY DATA SHEET

[Bis(2-methoxyethyl)amino]sulfur trifluoride, 50% solution in toluene

Revision Date 11-Oct-2023

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Yellow-orange	
Odor	Characteristic	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flammability (liquid)	Highly flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	4 °C / 39.2 °F	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	No data available	
Water Solubility	No information available	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Toluene	2.73	
Vapor Pressure	No data available	
Density / Specific Gravity	1.200	
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

Molecular Formula	C6 H14 F3 N O2 S
Molecular Weight	221.24
Explosive Properties	Vapors may form explosive mixtures with air

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Yes

10.2. Chemical stability

Reacts violently with water.

10.3. Possibility of hazardous reactions

Hazardous Polymerization	No information available.
Hazardous Reactions	None under normal processing. Reacts violently with water.

10.4. Conditions to avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition. Exposure to moist air or water. Exposure to moisture.

10.5. Incompatible materials

Strong oxidizing agents. Strong bases. Alcohols.

SAFETY DATA SHEET

[Bis(2-methoxyethyl)amino]sulfur trifluoride, 50% solution in toluene

Revision Date 11-Oct-2023

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂). Nitrogen oxides (NO_x). Sulfur oxides.
Hydrogen fluoride.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral

Category 3

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Toluene	> 5000 mg/kg (Rat)	LD50 = 12000 mg/kg (Rabbit)	26700 ppm (Rat) 1 h

(b) skin corrosion/irritation; Category 1 A

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

No data available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity;

Teratogenicity

Category 2

Possible risk of harm to the unborn child.

(h) STOT-single exposure;

Category 3

Results / Target organs

Central nervous system (CNS).

(i) STOT-repeated exposure;

Category 2

Target Organs

Neuropsychological effects, Eyes, Ears.

(j) aspiration hazard;

Category 1

Other Adverse Effects

The toxicological properties have not been fully investigated.

Symptoms / effects, both acute and delayed

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be

SAFETY DATA SHEET

[Bis(2-methoxyethyl)amino]sulfur trifluoride, 50% solution in toluene

Revision Date 11-Oct-2023

investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

The product contains following substances which are hazardous for the environment. Contains a substance which is: Toxic to aquatic organisms.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Toluene	50-70 mg/L LC50 96 h 5-7 mg/L LC50 96 h 15-19 mg/L LC50 96 h 28 mg/L LC50 96 h 12 mg/L LC50 96 h	EC50: = 11.5 mg/L, 48h (Daphnia magna) EC50: 5.46 - 9.83 mg/L, 48h Static (Daphnia magna)	EC50: = 12.5 mg/L, 72h static (Pseudokirchneriella subcapitata) EC50: > 433 mg/L, 96h (Pseudokirchneriella subcapitata)

Component	Microtox	M-Factor
Toluene	EC50 = 19.7 mg/L 30 min	

12.2. Persistence and degradability

No information available

Component	Degradability
Toluene 108-88-3 (50)	86% (20d)

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential

No information available

Component	log Pow	Bioconcentration factor (BCF)
Toluene	2.73	90

12.4. Mobility in soil

No information available .

12.5. Results of PBT and vPvB assessment

No data available for assessment.

12.6. Endocrine disrupting properties

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant

This product does not contain any known or suspected substance

Ozone Depletion Potential

This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

SAFETY DATA SHEET

[Bis(2-methoxyethyl)amino]sulfur trifluoride, 50% solution in toluene

Revision Date 11-Oct-2023

Waste from Residues/Unused Products	Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.
Contaminated Packaging	Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.
European Waste Catalogue (EWC)	According to the European Waste Catalog, Waste Codes are not product specific, but application specific.
Other Information	Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms.
Switzerland - Waste Ordinance	Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600 https://www.fedlex.admin.ch/eli/cc/2015/891/en

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number	UN3286
14.2. UN proper shipping name Technical Shipping Name	Flammable liquid, toxic, corrosive, n.o.s. ((BIS(2-METHOXYETHYL)AMINO)SULFUR TRIFLUORIDE, 2.7M SOLUTION IN TOLUENE)
14.3. Transport hazard class(es) Subsidiary Hazard Class	3 6.1, 8
14.4. Packing group	II

ADR

14.1. UN number	UN3286
14.2. UN proper shipping name Technical Shipping Name	Flammable liquid, toxic, corrosive, n.o.s. ((BIS(2-METHOXYETHYL)AMINO)SULFUR TRIFLUORIDE, 2.7M SOLUTION IN TOLUENE)
14.3. Transport hazard class(es) Subsidiary Hazard Class	3 6.1, 8
14.4. Packing group	II

IATA

14.1. UN number	UN3286
14.2. UN proper shipping name Technical Shipping Name	FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S.* ((BIS(2-METHOXYETHYL)AMINO)SULFUR TRIFLUORIDE, 2.7M SOLUTION IN TOLUENE)
14.3. Transport hazard class(es) Subsidiary Hazard Class	3 6.1, 8
14.4. Packing group	II

14.5. Environmental hazards	No hazards identified
14.6. Special precautions for user	No special precautions required.
14.7. Maritime transport in bulk according to IMO instruments	Not applicable, packaged goods

SAFETY DATA SHEET

[Bis(2-methoxyethyl)amino]sulfur trifluoride, 50% solution in toluene

Revision Date 11-Oct-2023

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Sulfur, trifluoro[2-methoxy-N-(2-methoxyethyl)ethanaminato-.kappa.N]-, (T-4)-	202289-38-1	-	478-190-3	-	X	X	-	-	-
Toluene	108-88-3	203-625-9	-	-	X	X	KE-33936	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Sulfur, trifluoro[2-methoxy-N-(2-methoxyethyl)ethanaminato-.kappa.N]-, (T-4)-	202289-38-1	X	ACTIVE	-	X	-	-	-
Toluene	108-88-3	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Sulfur, trifluoro[2-methoxy-N-(2-methoxyethyl)ethanaminato-.kappa.N]-, (T-4)-	202289-38-1	-	-	-
Toluene	108-88-3	-	Use restricted. See item 48. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Sulfur, trifluoro[2-methoxy-N-(2-methoxyethyl)ethanaminato-.kappa.N]-, (T-4)-	202289-38-1	Not applicable	Not applicable
Toluene	108-88-3	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

SAFETY DATA SHEET

[Bis(2-methoxyethyl)amino]sulfur trifluoride, 50% solution in toluene

Revision Date 11-Oct-2023

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

Take note of Directive 94/33/EC on the protection of young people at work

Take note of Dir 92/85/EC on the protection of pregnant and breastfeeding women at work

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification Water endangering class = 2 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Toluene	WGK3	

Component	France - INRS (Tables of occupational diseases)
Toluene	Tableaux des maladies professionnelles (TMP) - RG 4bis, RG 84

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Toluene 108-88-3 (50)	Prohibited and Restricted Substances	Group I	

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H301 - Toxic if swallowed

H304 - May be fatal if swallowed and enters airways

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H336 - May cause drowsiness or dizziness

H361d - Suspected of damaging the unborn child

H373 - May cause damage to organs through prolonged or repeated exposure

EUH014 - Reacts violently with water

H225 - Highly flammable liquid and vapor

H315 - Causes skin irritation

Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical

SAFETY DATA SHEET

[Bis(2-methoxyethyl)amino]sulfur trifluoride, 50% solution in toluene

Revision Date 11-Oct-2023

Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances
IECSC - Chinese Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances
AICS - Australian Inventory of Chemical Substances
NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Creation Date 10-Nov-2009

Revision Date 11-Oct-2023

Revision Summary SDS sections updated.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006 .

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet