

Creation Date 01-Apr-2010

Revision Date 03-Jan-2021

Revision Number 15

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

**Product Description:** **INDUSTRIAL METHYLATED SPIRIT 99%**  
**Cat No. :** **SP/2277**  
**Synonyms** IDA, Industrial Denatured Alcohol, Ethanol IDA, IMS, Industrial methylated spirit, Methylated spirits 74 O P

**Unique Formula Identifier (UFI)** 926A-K265-TX08-TVVN

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended Use** Laboratory chemicals.  
**Uses advised against** No Information available

### 1.3. Details of the supplier of the safety data sheet

**Company** **UK entity/business name**  
 Fisher Scientific UK  
 Bishop Meadow Road, Loughborough,  
 Leicestershire LE11 5RG, United Kingdom

**EU entity/business name**  
 Acros Organics BVBA  
 Janssen Pharmaceuticaaan 3a  
 2440 Geel, Belgium

**E-mail address** begel.sdsdesk@thermofisher.com

### 1.4. Emergency telephone number

Tel: 01509 231166  
 Chemtrec US: (800) 424-9300  
 Chemtrec EU: 001 (202) 483-7616

**Poison Centre - Emergency information services** **Ireland** : National Poisons Information Centre (NPIC) - **01 809 2166** (8am-10pm, 7 days a week)  
**Malta** : +356 2395 2000  
**Cyprus** : +357 2240 5611

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

**CLP Classification - Regulation (EC) No 1272/2008**

**Physical hazards**

Flammable liquids

Category 2 (H225)

# SAFETY DATA SHEET

INDUSTRIAL METHYLATED SPIRIT 99%

Revision Date 03-Jan-2021

## Health hazards

Acute oral toxicity  
Acute Inhalation Toxicity - Vapors  
Serious Eye Damage/Eye Irritation  
Specific target organ toxicity - (single exposure)

Category 4 (H302)  
Category 4 (H332)  
Category 2 (H319)  
Category 2 (H371)

## Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

## 2.2. Label elements

Contains ETHANOL, METHANOL.



Signal Word

Danger

## Hazard Statements

H225 - Highly flammable liquid and vapor  
H302 + H332 - Harmful if swallowed or if inhaled  
H319 - Causes serious eye irritation  
H371 - May cause damage to organs

## Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P280 - Wear eye protection/ face protection  
P301 + P330 + P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting  
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower  
P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
P312 - Call a POISON CENTER or doctor/physician if you feel unwell

## 2.3. Other hazards

This preparation contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This preparation contains no substance considered to be very persistent nor very bioaccumulating (vPvB)

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

| Component     | CAS-No  | EC-No.    | Weight % | CLP Classification - Regulation (EC) No 1272/2008 |
|---------------|---------|-----------|----------|---------------------------------------------------|
| Ethyl alcohol | 64-17-5 | 200-578-6 | > 94     | Flam. Liq. 2 (H225)                               |

# SAFETY DATA SHEET

INDUSTRIAL METHYLATED SPIRIT 99%

Revision Date 03-Jan-2021

|                |           |           |       |                                                                                                                                     |
|----------------|-----------|-----------|-------|-------------------------------------------------------------------------------------------------------------------------------------|
| Methyl alcohol | 67-56-1   | 200-659-6 | 3 - 6 | Eye Irrit. 2 (H319)<br>Flam. Liq. 2 (H225)<br>Acute Tox. 3 (H301)<br>Acute Tox. 3 (H311)<br>Acute Tox. 3 (H331)<br>STOT SE 1 (H370) |
| Water          | 7732-18-5 | 231-791-2 | 1     | -                                                                                                                                   |

| Component      | Specific concentration limits (SCL's)         | M-Factor | Component notes |
|----------------|-----------------------------------------------|----------|-----------------|
| Ethyl alcohol  | Eye Irrit. 2 :: C>=50%                        | -        | -               |
| Methyl alcohol | STOT SE 1 :: C>=10%<br>STOT SE 2 :: 3%<=C<10% | -        | -               |

| Components | Reach Registration Number |
|------------|---------------------------|
| Ethanol    | 01-2119457610-43          |
| Methanol   | 01-2119433307-44          |

Full text of Hazard Statements: see section 16

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

|                                           |                                                                                                                                                  |
|-------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>General Advice</b>                     | If symptoms persist, call a physician.                                                                                                           |
| <b>Eye Contact</b>                        | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.                                  |
| <b>Skin Contact</b>                       | Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.                                |
| <b>Ingestion</b>                          | Clean mouth with water and drink afterwards plenty of water.                                                                                     |
| <b>Inhalation</b>                         | Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.                                     |
| <b>Self-Protection of the First Aider</b> | Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. |

### 4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

### 4.3. Indication of any immediate medical attention and special treatment needed

|                           |                                                 |
|---------------------------|-------------------------------------------------|
| <b>Notes to Physician</b> | Treat symptomatically. Symptoms may be delayed. |
|---------------------------|-------------------------------------------------|

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

#### Suitable Extinguishing Media

Water spray, carbon dioxide (CO<sub>2</sub>), dry chemical, alcohol-resistant foam.

#### Extinguishing media which must not be used for safety reasons

No information available.

# SAFETY DATA SHEET

INDUSTRIAL METHYLATED SPIRIT 99%

Revision Date 03-Jan-2021

## **5.2. Special hazards arising from the substance or mixture**

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

### **Hazardous Combustion Products**

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>).

## **5.3. Advice for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment as required. Ensure adequate ventilation. Take precautionary measures against static discharges.

### **6.2. Environmental precautions**

Should not be released into the environment.

### **6.3. Methods and material for containment and cleaning up**

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

### **6.4. Reference to other sections**

Refer to protective measures listed in Sections 8 and 13.

## **SECTION 7: HANDLING AND STORAGE**

### **7.1. Precautions for safe handling**

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Ensure adequate ventilation.

### **Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

### **7.2. Conditions for safe storage, including any incompatibilities**

Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area. Keep away from heat, sparks and flame. Keep away from oxidizing agents.

**Technical Rules for Hazardous Substances (TRGS) 510 Storage Class (LGK)**  
(Germany)

Class 3

### **7.3. Specific end use(s)**

Use in laboratories

# SAFETY DATA SHEET

INDUSTRIAL METHYLATED SPIRIT 99%

Revision Date 03-Jan-2021

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Third edition. Published 2018. **IRE** - 2018 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

| Component      | The United Kingdom                                                                                        | European Union                                               | Ireland                                                                                                                      |
|----------------|-----------------------------------------------------------------------------------------------------------|--------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Ethyl alcohol  | TWA: 1000 ppm TWA; 1920 mg/m <sup>3</sup> TWA<br>WEL - STEL: 3000 ppm STEL; 5760 mg/m <sup>3</sup> STEL   |                                                              | STEL: 1000 ppm 15 min                                                                                                        |
| Methyl alcohol | WEL - TWA: 200 ppm TWA; 266 mg/m <sup>3</sup> TWA<br>WEL - STEL: 250 ppm STEL; 333 mg/m <sup>3</sup> STEL | TWA: 200 ppm 8 hr<br>TWA: 260 mg/m <sup>3</sup> 8 hr<br>Skin | TWA: 200 ppm 8 hr.<br>TWA: 260 mg/m <sup>3</sup> 8 hr.<br>STEL: 600 ppm 15 min<br>STEL: 780 mg/m <sup>3</sup> 15 min<br>Skin |

#### Biological limit values

List source(s):

#### Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

**Derived No Effect Level (DNEL)** See table for values

| Route of exposure            | Acute effects (local) | Acute effects (systemic) | Chronic effects (local) | Chronic effects (systemic)                      |
|------------------------------|-----------------------|--------------------------|-------------------------|-------------------------------------------------|
| Oral<br>Dermal<br>Inhalation |                       | 915.5 mg/m <sup>3</sup>  |                         | 328 mg/kg bw/day<br>1818 mg/m <sup>3</sup> /day |

**Predicted No Effect Concentration (PNEC)** See values below.

|                      |            |
|----------------------|------------|
| Fresh water          | 0.96 mg/L  |
| Fresh water sediment | 3.6 mg/kg  |
| Marine water         | 0.79 mg/L  |
| Soil (Agriculture)   | 0.63 mg/kg |

### 8.2. Exposure controls

#### Engineering Measures

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

#### Personal protective equipment

# SAFETY DATA SHEET

INDUSTRIAL METHYLATED SPIRIT 99%

Revision Date 03-Jan-2021

**Eye Protection** Wear safety glasses with side shields (or goggles) (European standard - EN 166)

**Hand Protection** Protective gloves

| Glove material | Breakthrough time | Glove thickness   | EU standard | Glove comments                                                                 |
|----------------|-------------------|-------------------|-------------|--------------------------------------------------------------------------------|
| Butyl rubber   | > 480 minutes     | 0.38 mm - 0.56 mm | Level 6     | As tested under EN374-3 Determination of Resistance to Permeation by Chemicals |
| Neoprene       | > 480 minutes     | 0.45 mm           | EN 374      |                                                                                |
| PVC            | < 60 minutes      | 0.18 mm           |             |                                                                                |
| Viton (R)      | > 480 minutes     | 0.7 mm            |             |                                                                                |

**Skin and body protection** Long sleeved clothing

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

**Respiratory Protection** When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

**Large scale/emergency use** Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced  
**Recommended Filter type:** Organic gases and vapours filter Type A Brown conforming to EN14387 Brown

**Small scale/Laboratory use** Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. Maintain adequate ventilation  
**Recommended half mask:-** Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141

**Environmental exposure controls** Prevent product from entering drains. Do not allow material to contaminate ground water system.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

|                                  |                                     |                                          |
|----------------------------------|-------------------------------------|------------------------------------------|
| <b>Physical State</b>            | Liquid                              |                                          |
| <b>Appearance</b>                | Colorless                           |                                          |
| <b>Odor</b>                      | Alcohol                             |                                          |
| <b>Odor Threshold</b>            | No data available                   |                                          |
| <b>Melting Point/Range</b>       | -114.1 °C / -173.4 °F               |                                          |
| <b>Softening Point</b>           | No data available                   |                                          |
| <b>Boiling Point/Range</b>       | 78.2 °C / 172.8 °F                  | 760 mmHg                                 |
| <b>Flammability (liquid)</b>     | Highly flammable                    | On basis of test data                    |
| <b>Flammability (solid,gas)</b>  | Not applicable                      | Liquid                                   |
| <b>Explosion Limits</b>          | <b>Lower</b> 3.3<br><b>Upper</b> 19 |                                          |
| <b>Flash Point</b>               | 14 °C / 57.2 °F                     | <b>Method -</b> No information available |
| <b>Autoignition Temperature</b>  | 365 °C / 689 °F                     |                                          |
| <b>Decomposition Temperature</b> | No data available                   |                                          |
| <b>pH</b>                        | No information available            |                                          |
| <b>Viscosity</b>                 | 1.52 cSt 20 °C                      |                                          |
| <b>Water Solubility</b>          | Soluble in water                    |                                          |

# SAFETY DATA SHEET

INDUSTRIAL METHYLATED SPIRIT 99%

Revision Date 03-Jan-2021

|                                         |                          |             |
|-----------------------------------------|--------------------------|-------------|
| Solubility in other solvents            | No information available |             |
| Partition Coefficient (n-octanol/water) |                          |             |
| Component                               | log Pow                  |             |
| Ethyl alcohol                           | -0.32                    |             |
| Methyl alcohol                          | -0.74                    |             |
| Vapor Pressure                          | 5.81 kPa 20 °C           |             |
| Density / Specific Gravity              | 0.787 - 0.791            |             |
| Bulk Density                            | Not applicable           | Liquid      |
| Vapor Density                           | No data available        | (Air = 1.0) |
| Particle characteristics                | Not applicable (liquid)  |             |

## 9.2. Other information

**Explosive Properties** Vapors may form explosive mixtures with air

## SECTION 10: STABILITY AND REACTIVITY

**10.1. Reactivity** None known, based on information available

**10.2. Chemical stability** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous Polymerization** Hazardous polymerization does not occur.  
**Hazardous Reactions** None under normal processing.

**10.4. Conditions to avoid** Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition.

**10.5. Incompatible materials** Acids. Acid anhydrides. Oxidizing agent.

**10.6. Hazardous decomposition products** Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Product Information

(a) acute toxicity;  
Oral No data available  
Dermal No data available  
Inhalation No data available

#### Toxicology data for the components

| Component      | LD50 Oral                                                    | LD50 Dermal                   | LC50 Inhalation                                                   |
|----------------|--------------------------------------------------------------|-------------------------------|-------------------------------------------------------------------|
| Ethyl alcohol  | LD50 = 10470 mg/kg<br>OECD 401 (Rat)<br>3450 mg/kg ( Mouse ) | -                             | LC50 = 117-125 mg/l (4h)<br>OECD 403 (rat)<br>20000 ppm/10H (rat) |
| Methyl alcohol | LD50 > 1187 – 2769 mg/kg ( Rat )                             | LD50 = 17100 mg/kg ( Rabbit ) | LC50 = 128.2 mg/L ( Rat ) 4 h                                     |

# SAFETY DATA SHEET

INDUSTRIAL METHYLATED SPIRIT 99%

Revision Date 03-Jan-2021

|       |   |   |   |
|-------|---|---|---|
| Water | - | - | - |
|-------|---|---|---|

(b) skin corrosion/irritation; No data available

(c) serious eye damage/irritation; No data available

(d) respiratory or skin sensitization;

Respiratory No data available  
Skin No data available

| Component                           | Test method                                                    | Test species | Study result    |
|-------------------------------------|----------------------------------------------------------------|--------------|-----------------|
| Ethyl alcohol<br>64-17-5 ( > 94 )   | Mouse Ear Swelling Test (MEST)                                 | mouse        | non-sensitising |
|                                     | OECD Test Guideline 429<br>Local Lymph Node Assay              | mouse        | non-sensitising |
| Methyl alcohol<br>67-56-1 ( 3 - 6 ) | OECD Test Guideline 406<br>Guinea Pig Maximisation Test (GPMT) | guinea pig   | non-sensitising |

(e) germ cell mutagenicity; No data available

| Component                         | Test method                                   | Test species          | Study result |
|-----------------------------------|-----------------------------------------------|-----------------------|--------------|
| Ethyl alcohol<br>64-17-5 ( > 94 ) | AMES test<br>OECD Test Guideline 471          | in vitro<br>Bacteria  | negative     |
|                                   | Gene cell mutation<br>OECD Test Guideline 476 | in vitro<br>Mammalian | negative     |

(f) carcinogenicity; No data available

The table below indicates whether each agency has listed any ingredient as a carcinogen

(g) reproductive toxicity; No data available

| Component                           | Test method             | Test species / Duration          | Study result              |
|-------------------------------------|-------------------------|----------------------------------|---------------------------|
| Ethyl alcohol<br>64-17-5 ( > 94 )   | OECD Test Guideline 416 | Oral / mouse<br>2 Generation     | NOAEL = 13.8 g/kg/day     |
|                                     | OECD Test Guideline 414 | Inhalation / Rat                 | NOAEC =<br>16000 ppm      |
| Methyl alcohol<br>67-56-1 ( 3 - 6 ) | OECD Test Guideline 416 | Rat / Inhalation<br>2 Generation | NOAEC =<br>1.3 mg/l (air) |

(h) STOT-single exposure; Category 2

Results / Target organs Optic nerve, Central nervous system (CNS).

(i) STOT-repeated exposure; No data available

Target Organs No information available.

(j) aspiration hazard; No data available

Symptoms / effects, both acute and delayed Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.



# SAFETY DATA SHEET

INDUSTRIAL METHYLATED SPIRIT 99%

Revision Date 03-Jan-2021

## 11.2. Information on other hazards

**Endocrine Disrupting Properties** Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

#### Ecotoxicity effects

Contains no substances known to be hazardous to the environment or that are not degradable in waste water treatment plants.

| Component      | Freshwater Fish                                            | Water Flea                                    | Freshwater Algae                           |
|----------------|------------------------------------------------------------|-----------------------------------------------|--------------------------------------------|
| Ethyl alcohol  | Fathead minnow (Pimephales promelas) LC50 = 14200 mg/l/96h | EC50 = 9268 mg/L/48h<br>EC50 = 10800 mg/L/24h | EC50 (72h) = 275 mg/l (Chlorella vulgaris) |
| Methyl alcohol | Pimephales promelas: LC50 > 10000 mg/L 96h                 | EC50 > 10000 mg/L 24h                         |                                            |

| Component      | Microtox                                                                                                    | M-Factor |
|----------------|-------------------------------------------------------------------------------------------------------------|----------|
| Ethyl alcohol  | Photobacterium phosphoreum: EC50 = 34634 mg/L/30 min<br>Photobacterium phosphoreum: EC50 = 35470 mg/L/5 min |          |
| Methyl alcohol | EC50 = 39000 mg/L 25 min<br>EC50 = 40000 mg/L 15 min<br>EC50 = 43000 mg/L 5 min                             |          |

### 12.2. Persistence and degradability

#### Persistence

Persistence is unlikely, based on information available.

| Component                         | Degradability                  |
|-----------------------------------|--------------------------------|
| Ethyl alcohol<br>64-17-5 (> 94)   | OECD 301E = 94%                |
| Methyl alcohol<br>67-56-1 (3 - 6) | DT50 ~ 17.2d<br>>94% after 20d |

### 12.3. Bioaccumulative potential

Bioaccumulation is unlikely

| Component      | log Pow | Bioconcentration factor (BCF) |
|----------------|---------|-------------------------------|
| Ethyl alcohol  | -0.32   | No data available             |
| Methyl alcohol | -0.74   | <10                           |

### 12.4. Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air

### 12.5. Results of PBT and vPvB assessment

This preparation contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This preparation contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

### 12.6. Endocrine disrupting properties

#### Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

### 12.7. Other adverse effects

#### Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance  
This product does not contain any known or suspected substance

# SAFETY DATA SHEET

INDUSTRIAL METHYLATED SPIRIT 99%

Revision Date 03-Jan-2021

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

#### Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

#### Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

#### European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

#### Other Information

Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations.

## SECTION 14: TRANSPORT INFORMATION

### IMDG/IMO

|                                         |                  |
|-----------------------------------------|------------------|
| <u>14.1. UN number</u>                  | UN1170           |
| <u>14.2. UN proper shipping name</u>    | Ethanol solution |
| <u>14.3. Transport hazard class(es)</u> | 3                |
| <u>14.4. Packing group</u>              | II               |

### ADR

|                                         |                  |
|-----------------------------------------|------------------|
| <u>14.1. UN number</u>                  | UN1170           |
| <u>14.2. UN proper shipping name</u>    | Ethanol solution |
| <u>14.3. Transport hazard class(es)</u> | 3                |
| <u>14.4. Packing group</u>              | II               |

### IATA

|                                         |                  |
|-----------------------------------------|------------------|
| <u>14.1. UN number</u>                  | UN1170           |
| <u>14.2. UN proper shipping name</u>    | Ethanol solution |
| <u>14.3. Transport hazard class(es)</u> | 3                |
| <u>14.4. Packing group</u>              | II               |

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required

14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Inventories

X = listed, Europe (EINECS/ELINCS/NLP), U.S.A. (TSCA), Canada (DSL/NDSL), Philippines (PICCS), China (IECSC), Japan (ENCS), Australia (AICS), Korea (ECL).

| Component     | EINECS    | ELINCS | NLP | TSCA | DSL | NDSL | PICCS | ENCS | IECSC | AICS | KECL         |
|---------------|-----------|--------|-----|------|-----|------|-------|------|-------|------|--------------|
| Ethyl alcohol | 200-578-6 | -      |     | X    | X   | -    | X     | X    | X     | X    | KE-1321<br>7 |

# SAFETY DATA SHEET

INDUSTRIAL METHYLATED SPIRIT 99%

Revision Date 03-Jan-2021

|                |           |   |  |   |   |   |   |   |   |   |          |
|----------------|-----------|---|--|---|---|---|---|---|---|---|----------|
| Methyl alcohol | 200-659-6 | - |  | X | X | - | X | X | X | X | KE-23193 |
| Water          | 231-791-2 | - |  | X | X | - | X | X | X | X | KE-35400 |

| Component      | REACH (1907/2006) - Annex XIV - Substances Subject to Authorization | REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances                                                                                                                                                        | REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC) |
|----------------|---------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------|
| Methyl alcohol |                                                                     | Use restricted. See item 69. (see <a href="http://eur-lex.europa.eu/LexUriServ/LexUriServ.do?uri=CELEX:32006R1907:EN:NOT">http://eur-lex.europa.eu/LexUriServ/LexUriServ.do?uri=CELEX:32006R1907:EN:NOT</a> for restriction details) |                                                                                                       |

| Component      | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements |
|----------------|-------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|
| Methyl alcohol | 500 tonne                                                                                 | 5000 tonne                                                                               |

**Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals**

Not applicable

## National Regulations

### WGK Classification

Water endangering class = 2 (self classification)

| Component      | Germany - Water Classification (VwVwS) | Germany - TA-Luft Class |
|----------------|----------------------------------------|-------------------------|
| Ethyl alcohol  | WGK1                                   |                         |
| Methyl alcohol | WGK 2                                  |                         |

| Component      | France - INRS (Tables of occupational diseases)      |
|----------------|------------------------------------------------------|
| Ethyl alcohol  | Tableaux des maladies professionnelles (TMP) - RG 84 |
| Methyl alcohol | Tableaux des maladies professionnelles (TMP) - RG 84 |

**UK** - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

## 15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

## SECTION 16: OTHER INFORMATION

### Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor

H301 - Toxic if swallowed

H311 - Toxic in contact with skin

H319 - Causes serious eye irritation

H331 - Toxic if inhaled

H370 - Causes damage to organs

### Legend

**CAS** - Chemical Abstracts Service

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

# SAFETY DATA SHEET

INDUSTRIAL METHYLATED SPIRIT 99%

Revision Date 03-Jan-2021

**WEL** - Workplace Exposure Limit  
**ACGIH** - American Conference of Governmental Industrial Hygienists  
**DNEL** - Derived No Effect Level  
**RPE** - Respiratory Protective Equipment  
**LC50** - Lethal Concentration 50%  
**NOEC** - No Observed Effect Concentration  
**PBT** - Persistent, Bioaccumulative, Toxic

**TWA** - Time Weighted Average  
**IARC** - International Agency for Research on Cancer  
Predicted No Effect Concentration (PNEC)  
**LD50** - Lethal Dose 50%  
**EC50** - Effective Concentration 50%  
**POW** - Partition coefficient Octanol:Water  
**vPvB** - very Persistent, very Bioaccumulative

**ADR** - European Agreement Concerning the International Carriage of Dangerous Goods by Road  
**IMO/IMDG** - International Maritime Organization/International Maritime Dangerous Goods Code  
**OECD** - Organisation for Economic Co-operation and Development  
**BCF** - Bioconcentration factor

**ICAO/IATA** - International Civil Aviation Organization/International Air Transport Association  
**MARPOL** - International Convention for the Prevention of Pollution from Ships  
**ATE** - Acute Toxicity Estimate  
VOC (volatile organic compound)

## Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>  
Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

## Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

|                              |                       |
|------------------------------|-----------------------|
| <b>Physical hazards</b>      | On basis of test data |
| <b>Health Hazards</b>        | Calculation method    |
| <b>Environmental hazards</b> | Calculation method    |

## Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

|                         |                       |
|-------------------------|-----------------------|
| <b>Creation Date</b>    | 01-Apr-2010           |
| <b>Revision Date</b>    | 03-Jan-2021           |
| <b>Revision Summary</b> | Update to CLP Format. |

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006  
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No  
1907/2006**

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**