

Creation Date 22-Sep-2009

Revision Date 10-Feb-2024

Revision Number 3

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description:	<u>n-Butyl acetate</u>
Cat No. :	A19412
Synonyms	Butyl acetate; Acetic acid, butyl ester; 1-Butyl acetate
Index No	607-025-00-1
CAS No	123-86-4
EC No	204-658-1
Molecular Formula	C6H12O2
REACH registration number	-

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use	Laboratory chemicals.
Sector of use	SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites
Product category	PC21 - Laboratory chemicals
Process categories	PROC15 - Use as a laboratory reagent
Environmental release category	ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)
Uses advised against	No Information available

1.3. Details of the supplier of the safety data sheet

Company

Thermo Fisher (Kandel) GmbH
Erlenbachweg 2, 76870 Kandel, Germany
Tel: +49 (0) 721 84007 280
Fax: +49 (0) 721 84007 300

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
<https://www.fishersci.ch/ch/en/customer-help-support/forms/email-us.html>

E-mail address

begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

SECTION 2: HAZARDS IDENTIFICATION

SAFETY DATA SHEET

n-Butyl acetate

Revision Date 10-Feb-2024

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Flammable liquids

Category 3 (H226)

Health hazards

Specific target organ toxicity - (single exposure)

Category 3 (H336)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Warning

Hazard Statements

H226 - Flammable liquid and vapor

H336 - May cause drowsiness or dizziness

EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P312 - Call a POISON CENTER or doctor if you feel unwell

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

ALFAAA19412

SAFETY DATA SHEET

n-Butyl acetate

Revision Date 10-Feb-2024

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
n-Butyl acetate	123-86-4	EEC No. 204-658-1	<=100	Flam. Liq. 3 (H226) STOT SE 3 (H336) EUH066

REACH registration number	-
---------------------------	---

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	If symptoms persist, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Ingestion	Clean mouth with water and drink afterwards plenty of water.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.
Self-Protection of the First Aider	No special precautions required.

4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically. Symptoms may be delayed.
--------------------	---

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂).

SAFETY DATA SHEET

n-Butyl acetate

Revision Date 10-Feb-2024

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Should not be released into the environment. Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Avoid ingestion and inhalation. Do not get in eyes, on skin, or on clothing. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Class 3

Switzerland - Storage of hazardous substances

Storage class - SC 3
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

SAFETY DATA SHEET

n-Butyl acetate

Revision Date 10-Feb-2024

8.1. Control parameters

Exposure limits

List source(s): **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
n-Butyl acetate		STEL: 200 ppm 15 min STEL: 966 mg/m ³ 15 min TWA: 150 ppm 8 hr TWA: 724 mg/m ³ 8 hr	TWA / VME: 50 ppm (8 heures). restrictive limit TWA / VME: 241 mg/m ³ (8 heures). restrictive limit STEL / VLCT: 150 ppm. restrictive limit STEL / VLCT: 723 mg/m ³ . restrictive limit	TWA: 50 ppm 8 uren TWA: 238 mg/m ³ 8 uren STEL: 150 ppm 15 minuten STEL: 712 mg/m ³ 15 minuten	STEL / VLA-EC: 150 ppm (15 minutos). STEL / VLA-EC: 723 mg/m ³ (15 minutos). TWA / VLA-ED: 50 ppm (8 horas) TWA / VLA-ED: 241 mg/m ³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
n-Butyl acetate	TWA: 241 mg/m ³ 8 ore. Time Weighted Average TWA: 50 ppm 8 ore. Time Weighted Average STEL: 723 mg/m ³ 15 minuti. Short-term STEL: 150 ppm 15 minuti. Short-term	TWA: 62 ppm (8 Stunden). AGW - exposure factor 2 TWA: 300 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 100 ppm (8 Stunden). MAK TWA: 480 mg/m ³ (8 Stunden). MAK Höhepunkt: 200 ppm Höhepunkt: 960 mg/m ³	STEL: 150 ppm 15 minutos STEL: 723 mg/m ³ 15 minutos TWA: 50 ppm 8 horas TWA: 241 mg/m ³ 8 horas	STEL: 723 mg/m ³ 15 minuten TWA: 241 mg/m ³ 8 uren	TWA: 50 ppm 8 tunteina TWA: 240 mg/m ³ 8 tunteina STEL: 150 ppm 15 minuutteina STEL: 725 mg/m ³ 15 minuutteina

Component	Austria	Denmark	Switzerland	Poland	Norway
n-Butyl acetate	MAK-KZGW: 100 ppm 15 Minuten MAK-KZGW: 480 mg/m ³ 15 Minuten MAK-TMW: 50 ppm 8 Stunden MAK-TMW: 241 mg/m ³ 8 Stunden	TWA: 50 ppm 8 timer TWA: 241 mg/m ³ 8 timer STEL: 723 mg/m ³ 15 minutter STEL: 150 ppm 15 minutter	STEL: 150 ppm 15 Minuten STEL: 720 mg/m ³ 15 Minuten TWA: 50 ppm 8 Stunden TWA: 240 mg/m ³ 8 Stunden	STEL: 720 mg/m ³ 15 minutach TWA: 240 mg/m ³ 8 godzinach	TWA: 241 mg/m ³ 8 timer TWA: 50 ppm 8 timer STEL: 723 mg/m ³ 15 minutter. value from the regulation STEL: 150 ppm 15 minutter. value from the regulation

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
n-Butyl acetate	TWA: 241 mg/m ³ TWA: 50 ppm STEL : 723 mg/m ³ STEL : 150 ppm	TWA-GVI: 50 ppm 8 satima. TWA-GVI: 241 mg/m ³ 8 satima. STEL-KGVI: 150 ppm 15 minutama. STEL-KGVI: 723 mg/m ³ 15 minutama.	STEL: 150 ppm 15 min STEL: 723 mg/m ³ 15 min	STEL: 723 mg/m ³ STEL: 150 ppm TWA: 241 mg/m ³ TWA: 50 ppm	TWA: 241 mg/m ³ 8 hodinách. Ceiling: 723 mg/m ³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
n-Butyl acetate	TWA: 241 mg/m ³ 8 tundides. TWA: 50 ppm 8 tundides. STEL: 723 mg/m ³ 15 minutites. STEL: 150 ppm 15 minutites.		STEL: 150 ppm STEL: 723 mg/m ³ TWA: 50 ppm TWA: 241 mg/m ³	STEL: 723 mg/m ³ 15 percekben. CK TWA: 241 mg/m ³ 8 órában. AK	STEL: 150 ppm STEL: 723 mg/m ³ TWA: 50 ppm 8 klukkustundum. TWA: 241 mg/m ³ 8 klukkustundum. Ceiling: 300 ppm Ceiling: 1400 mg/m ³

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
n-Butyl acetate	STEL: 723 mg/m ³ STEL: 150 ppm	TWA: 241 mg/m ³ IPRD TWA: 50 ppm IPRD	TWA: 241 mg/m ³ 8 Stunden	TWA: 50 ppm TWA: 214 mg/m ³	TWA: 150 ppm 8 ore TWA: 715 mg/m ³ 8 ore

SAFETY DATA SHEET

n-Butyl acetate

Revision Date 10-Feb-2024

	TWA: 241 mg/m ³ TWA: 50 ppm	STEL: 723 mg/m ³ STEL: 150 ppm	TWA: 50 ppm 8 Stunden STEL: 723 mg/m ³ 15 Minuten STEL: 150 ppm 15 Minuten	STEL: 150 ppm 15 minuti STEL: 723 mg/m ³ 15 minuti	STEL: 200 ppm 15 minute STEL: 950 mg/m ³ 15 minute
--	---	--	--	--	--

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
n-Butyl acetate	TWA: 50 mg/m ³ 0429 MAC: 200 mg/m ³	Ceiling: 700 mg/m ³ TWA: 100 ppm TWA: 500 mg/m ³	TWA: 241 mg/m ³ 8 urah TWA: 50 ppm 8 urah STEL: 150 ppm 15 minutah STEL: 723 mg/m ³ 15 minutah	Binding STEL: 150 ppm 15 minuter Binding STEL: 723 mg/m ³ 15 minuter TLV: 50 ppm 8 timmar. NGV TLV: 241 mg/m ³ 8 timmar. NGV	

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
n-Butyl acetate 123-86-4 (<=100)	PNEC = 0.18mg/L	PNEC = 0.981mg/kg sediment dw	PNEC = 0.36mg/L	PNEC = 35.6mg/L	PNEC = 0.0903mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
n-Butyl acetate 123-86-4 (<=100)	PNEC = 0.018mg/L	PNEC = 0.0981mg/kg sediment dw			

8.2. Exposure controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or

SAFETY DATA SHEET

n-Butyl acetate

Revision Date 10-Feb-2024

equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Wear safety glasses with side shields (or goggles) (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Butyl rubber	< 125 minutes	0.63 mm	Level 4	Permeation rate 83 µg/cm ² /min
Nitrile rubber	< 78 minutes	0.38 mm	Level 3 EN 374	Permeation rate 135 µg/cm ² /min As tested under EN374-3 Determination of Resistance to Permeation by Chemicals

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced
Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to EN14387

Small scale/Laboratory use

Maintain adequate ventilation. Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141

Environmental exposure controls

Prevent product from entering drains.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Colorless	
Odor	sweet	
Odor Threshold	7 - 20 ppm	
Melting Point/Range	-90 °C / -130 °F	
Softening Point	No data available	
Boiling Point/Range	126 °C / 258.8 °F	
Flammability (liquid)	Flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	Lower 1.2 Upper 7.5	
Flash Point	27 °C / 80.6 °F	Method - No information available
Autoignition Temperature	415 °C / 779 °F	
Decomposition Temperature	No data available	
pH	6.2 @ 20°C	
Viscosity	0.83 mPas @ 20°C	

SAFETY DATA SHEET

n-Butyl acetate

Revision Date 10-Feb-2024

Water Solubility	Insoluble	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
n-Butyl acetate	2.3	
Vapor Pressure	No data available	
Density / Specific Gravity	0.881 @ 20C	
Bulk Density	Not applicable	Liquid
Vapor Density	4	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

Molecular Formula	C6H12O2
Molecular Weight	116.16
Explosive Properties	Not explosive (no chemical groups associated with explosive properties) explosive air/vapour mixtures possible
Oxidizing Properties	Not oxidising (based on the chemical structure of the substance and oxidation states of the constituent elements)
Evaporation Rate	1.0 (ether = 1)
Refractive index	1.393

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

10.4. Conditions to avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

SAFETY DATA SHEET

n-Butyl acetate

Revision Date 10-Feb-2024

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
n-Butyl acetate	LD50 = 10768 mg/kg (Rat)	LD50 > 17600 mg/kg (Rabbit)	LC50 = 0.74 mg/L (Rat) 4 h

(b) skin corrosion/irritation; Based on available data, the classification criteria are not met

(c) serious eye damage/irritation; Based on available data, the classification criteria are not met

(d) respiratory or skin sensitization;

Respiratory
Skin

Based on available data, the classification criteria are not met

Based on available data, the classification criteria are not met

(e) germ cell mutagenicity;

Based on available data, the classification criteria are not met

(f) carcinogenicity;

Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity;

Based on available data, the classification criteria are not met

(h) STOT-single exposure;

Category 3

Results / Target organs

Central nervous system (CNS).

(i) STOT-repeated exposure;

Based on available data, the classification criteria are not met

Target Organs

None known.

(j) aspiration hazard;

Based on available data, the classification criteria are not met

Symptoms / effects, both acute and delayed

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

11.2. Information on other hazards

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

Contains no substances known to be hazardous to the environment or that are not degradable in waste water treatment plants.

Component	Freshwater Fish	Water Flea	Freshwater Algae
n-Butyl acetate	Lepomis macrochirus: LC50: 100 mg/L/96h Pimephales promelas: LC50:17-19 mg/L/96h		EC50: = 674.7 mg/L, 72h (Desmodesmus subspicatus)

Component	Microtox	M-Factor
n-Butyl acetate	EC50 = 70.0 mg/L 5 min EC50 = 82.2 mg/L 15 min	

SAFETY DATA SHEET

n-Butyl acetate

Revision Date 10-Feb-2024

	EC50 = 959 mg/L 18 h EC50 = 98.9 mg/L 30 min	
--	---	--

12.2. Persistence and degradability

Persistence

Readily biodegradable

Degradation in sewage treatment plant

Persistence is unlikely, based on information available.

Contains no substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
n-Butyl acetate	2.3	No data available

12.4. Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Spillage unlikely to penetrate soil. Will likely be mobile in the environment due to its volatility. Highly mobile in soils

12.5. Results of PBT and vPvB assessment

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB).

12.6. Endocrine disrupting properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance

This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information

Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations.

Switzerland - Waste Ordinance

Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

SAFETY DATA SHEET

n-Butyl acetate

Revision Date 10-Feb-2024

14.1. UN number	UN1123
14.2. UN proper shipping name	BUTYL ACETATES
14.3. Transport hazard class(es)	3
14.4. Packing group	III

ADR

14.1. UN number	UN1123
14.2. UN proper shipping name	BUTYL ACETATES
14.3. Transport hazard class(es)	3
14.4. Packing group	III

IATA

14.1. UN number	UN1123
14.2. UN proper shipping name	BUTYL ACETATES
14.3. Transport hazard class(es)	3
14.4. Packing group	III

14.5. Environmental hazards	No hazards identified
14.6. Special precautions for user	No special precautions required.
14.7. Maritime transport in bulk according to IMO instruments	Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
n-Butyl acetate	123-86-4	204-658-1	-	-	X	X	KE-04179	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
n-Butyl acetate	123-86-4	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Not applicable

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
n-Butyl acetate	123-86-4	-	-	-

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report
-----------	--------	--	---

ALFAAA19412

SAFETY DATA SHEET

n-Butyl acetate

Revision Date 10-Feb-2024

		Notification	Requirements
n-Butyl acetate	123-86-4	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

See table for values

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
n-Butyl acetate	WGK1	

Component	France - INRS (Tables of occupational diseases)
n-Butyl acetate	Tableaux des maladies professionnelles (TMP) - RG 84

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
n-Butyl acetate 123-86-4 (<=100)		Group I	

15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has not been conducted

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H226 - Flammable liquid and vapor

H336 - May cause drowsiness or dizziness

EUH066 - Repeated exposure may cause skin dryness or cracking

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

ALFAAA19412

SAFETY DATA SHEET

n-Butyl acetate

Revision Date 10-Feb-2024

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Chemical incident response training.

Prepared By

Health, Safety and Environmental Department

Creation Date

22-Sep-2009

Revision Date

10-Feb-2024

Revision Summary

New emergency telephone response service provider.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No
1907/2006 .**

**For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2,
Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and
Preparations).**

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet