

Creation Date 01-Sep-2009

Revision Date 05-Mar-2025

Revision Number 2

## Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

|                                  |                                                              |
|----------------------------------|--------------------------------------------------------------|
| <b>Product Description:</b>      | <b>Iso-Propanol</b>                                          |
| <b>Cat No. :</b>                 | <b>TS/0227/17, TS/0227/17, TS/0227/99SS</b>                  |
| <b>Synonyms</b>                  | 2-Propanol; IPA; Isopropyl alcohol; Propan-2-ol; Isopropanol |
| <b>Index No</b>                  | 603-117-00-0                                                 |
| <b>CAS No</b>                    | 67-63-0                                                      |
| <b>EC No</b>                     | 200-661-7                                                    |
| <b>Molecular Formula</b>         | C3 H8 O                                                      |
| <b>REACH registration number</b> | 01-2119457558-25                                             |

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

|                                       |                                                                                             |
|---------------------------------------|---------------------------------------------------------------------------------------------|
| <b>Recommended Use</b>                | Laboratory chemicals.                                                                       |
| <b>Sector of use</b>                  | SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites    |
| <b>Product category</b>               | PC21 - Laboratory chemicals                                                                 |
| <b>Process categories</b>             | PROC15 - Use as a laboratory reagent                                                        |
| <b>Environmental release category</b> | ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates) |
| <b>Uses advised against</b>           | No Information available                                                                    |

### 1.3. Details of the supplier of the safety data sheet

#### Company

**EU entity/business name**  
Thermo Fisher Scientific  
Janssen Pharmaceuticaaan 3a  
2440 Geel, Belgium

**UK entity/business name**  
Fisher Scientific UK  
Bishop Meadow Road, Loughborough,  
Leicestershire LE11 5RG, United Kingdom

**Swiss distributor** - Fisher Scientific AG  
Neuhofstrasse 11, CH 4153 Reinach  
Tel: +41 (0) 56 618 41 11  
e-mail - infoch@thermofisher.com

#### E-mail address

begel.sdsdesk@thermofisher.com

### 1.4. Emergency telephone number

Tel: 01509 231166  
Chemtrec US: (800) 424-9300  
Chemtrec EU: 001-703-527-3887

For customers in Switzerland:  
Tox Info Suisse Emergency Number: **145 (24hr)**  
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)  
Chemtrec (24h) Toll-Free: 0800 564 402  
Chemtrec Local: +41-43 508 20 11 (Zurich)

# SAFETY DATA SHEET

Iso-Propanol

Revision Date 05-Mar-2025

## Section 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

#### CLP Classification - Regulation (EC) No 1272/2008

##### Physical hazards

Flammable liquids

Category 2 (H225)

##### Health hazards

Serious Eye Damage/Eye Irritation

Category 2 (H319)

Specific target organ toxicity - (single exposure)

Category 3 (H336)

##### Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

### 2.2. Label elements



Signal Word

Danger

#### **Hazard Statements**

H225 - Highly flammable liquid and vapor

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

#### **Precautionary Statements**

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P240 - Ground and bond container and receiving equipment

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

### 2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

This product does not contain any known or suspected endocrine disruptors

# SAFETY DATA SHEET

Iso-Propanol

Revision Date 05-Mar-2025

## Section 3: Composition/information on ingredients

### 3.1. Substances

| Component         | CAS No  | EC No     | Weight % | CLP Classification - Regulation (EC) No 1272/2008              |
|-------------------|---------|-----------|----------|----------------------------------------------------------------|
| Isopropyl alcohol | 67-63-0 | 200-661-7 | >95      | Flam. Liq. 2 (H225)<br>Eye Irrit. 2 (H319)<br>STOT SE 3 (H336) |

|                           |                  |
|---------------------------|------------------|
| REACH registration number | 01-2119457558-25 |
|---------------------------|------------------|

Full text of Hazard Statements: see section 16

## Section 4: First aid measures

### 4.1. Description of first aid measures

|                                           |                                                                                                                                                  |
|-------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Eye Contact</b>                        | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.                                  |
| <b>Skin Contact</b>                       | Wash off immediately with plenty of water for at least 15 minutes. Get medical attention if symptoms occur.                                      |
| <b>Ingestion</b>                          | Do NOT induce vomiting. Get medical attention.                                                                                                   |
| <b>Inhalation</b>                         | Remove to fresh air. Get medical attention. If not breathing, give artificial respiration.                                                       |
| <b>Self-Protection of the First Aider</b> | Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. |

### 4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. May cause central nervous system depression: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

### 4.3. Indication of any immediate medical attention and special treatment needed

|                           |                                                 |
|---------------------------|-------------------------------------------------|
| <b>Notes to Physician</b> | Treat symptomatically. Symptoms may be delayed. |
|---------------------------|-------------------------------------------------|

## Section 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable Extinguishing Media

CO<sub>2</sub>, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

#### Extinguishing media which must not be used for safety reasons

Do not use water jetstream. Do not use a solid water stream as it may scatter and spread fire.

### 5.2. Special hazards arising from the substance or mixture

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.

# SAFETY DATA SHEET

Iso-Propanol

Revision Date 05-Mar-2025

## Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), peroxides.

### 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

## Section 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges. Avoid contact with skin, eyes or clothing.

### 6.2. Environmental precautions

Should not be released into the environment. See Section 12 for additional Ecological Information.

### 6.3. Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. Keep in suitable, closed containers for disposal.

### 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Keep away from open flames, hot surfaces and sources of ignition. Use spark-proof tools and explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Do not get in eyes, on skin, or on clothing. Do not breathe mist/vapors/spray. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

### Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and flame. Flammables area. Keep container tightly closed in a dry and well-ventilated place.

Technical Rules for Hazardous Substances (TRGS) 510  
Storage Class (LGK) (Germany)

Class 3

Switzerland - Storage of hazardous substances

Storage class - SC 3  
<https://www.kvu.ch/de/themen/stoffe-und-produkte>  
<https://www.kvu.ch/fr/themes/substances-et-produits>  
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

### 7.3. Specific end use(s)

# SAFETY DATA SHEET

Iso-Propanol

Revision Date 05-Mar-2025

Use in laboratories

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits

List source(s): **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

| Component         | European Union | The United Kingdom                                                                                                  | France                                                        | Belgium                                                                                                                         | Spain                                                                                                                                                                           |
|-------------------|----------------|---------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Isopropyl alcohol |                | STEL: 500 ppm 15 min<br>STEL: 1250 mg/m <sup>3</sup> 15 min<br>TWA: 400 ppm 8 hr<br>TWA: 999 mg/m <sup>3</sup> 8 hr | STEL / VLCT: 400 ppm.<br>STEL / VLCT: 980 mg/m <sup>3</sup> . | TWA: 200 ppm 8 uren<br>TWA: 500 mg/m <sup>3</sup> 8 uren<br>STEL: 400 ppm 15 minuten<br>STEL: 1000 mg/m <sup>3</sup> 15 minuten | STEL / VLA-EC: 400 ppm (15 minutos).<br>STEL / VLA-EC: 1000 mg/m <sup>3</sup> (15 minutos).<br>TWA / VLA-ED: 200 ppm (8 horas)<br>TWA / VLA-ED: 500 mg/m <sup>3</sup> (8 horas) |

| Component         | Italy | Germany                                                                                                                                                                                                                                                         | Portugal                                         | The Netherlands | Finland                                                                                                                                        |
|-------------------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| Isopropyl alcohol |       | TWA: 200 ppm (8 Stunden). AGW - exposure factor 2<br>TWA: 500 mg/m <sup>3</sup> (8 Stunden). AGW - exposure factor 2<br>TWA: 200 ppm (8 Stunden). MAK<br>TWA: 500 mg/m <sup>3</sup> (8 Stunden). MAK<br>Höhepunkt: 400 ppm<br>Höhepunkt: 1000 mg/m <sup>3</sup> | STEL: 400 ppm 15 minutos<br>TWA: 200 ppm 8 horas |                 | TWA: 200 ppm 8 tunteina<br>TWA: 500 mg/m <sup>3</sup> 8 tunteina<br>STEL: 250 ppm 15 minuutteina<br>STEL: 620 mg/m <sup>3</sup> 15 minuutteina |

| Component         | Austria                                                                                                                                               | Denmark                                                                                                                            | Switzerland                                                                                                                           | Poland                                                                             | Norway                                                                                                                                                                    |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Isopropyl alcohol | MAK-KZGW: 800 ppm 15 Minuten<br>MAK-KZGW: 2000 mg/m <sup>3</sup> 15 Minuten<br>MAK-TMW: 200 ppm 8 Stunden<br>MAK-TMW: 500 mg/m <sup>3</sup> 8 Stunden | TWA: 200 ppm 8 timer<br>TWA: 490 mg/m <sup>3</sup> 8 timer<br>STEL: 400 ppm 15 minutter<br>STEL: 980 mg/m <sup>3</sup> 15 minutter | STEL: 400 ppm 15 Minuten<br>STEL: 1000 mg/m <sup>3</sup> 15 Minuten<br>TWA: 200 ppm 8 Stunden<br>TWA: 500 mg/m <sup>3</sup> 8 Stunden | STEL: 1200 mg/m <sup>3</sup> 15 minutach<br>TWA: 900 mg/m <sup>3</sup> 8 godzinach | TWA: 100 ppm 8 timer<br>TWA: 245 mg/m <sup>3</sup> 8 timer<br>STEL: 150 ppm 15 minutter. value calculated<br>STEL: 306.25 mg/m <sup>3</sup> 15 minutter. value calculated |

| Component         | Bulgaria                                                        | Croatia                                                                                                                                                     | Ireland                                         | Cyprus | Czech Republic                                                                                                  |
|-------------------|-----------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------|--------|-----------------------------------------------------------------------------------------------------------------|
| Isopropyl alcohol | TWA: 980.0 mg/m <sup>3</sup><br>STEL : 1225.0 mg/m <sup>3</sup> | TWA-GVI: 400 ppm 8 satima.<br>TWA-GVI: 999 mg/m <sup>3</sup> 8 satima.<br>STEL-KGVI: 500 ppm 15 minutama.<br>STEL-KGVI: 1250 mg/m <sup>3</sup> 15 minutama. | TWA: 200 ppm 8 hr.<br>STEL: 400 ppm 15 min Skin |        | TWA: 500 mg/m <sup>3</sup> 8 hodinách.<br>Potential for cutaneous absorption<br>Ceiling: 1000 mg/m <sup>3</sup> |

| Component         | Estonia                                                                                                                                        | Gibraltar | Greece                                                                                      | Hungary                                                                                                                                                 | Iceland                                                                                                                                             |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------------|-----------|---------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| Isopropyl alcohol | TWA: 150 ppm 8 tundides.<br>TWA: 350 mg/m <sup>3</sup> 8 tundides.<br>STEL: 250 ppm 15 minutites.<br>STEL: 600 mg/m <sup>3</sup> 15 minutites. |           | STEL: 500 ppm<br>STEL: 1225 mg/m <sup>3</sup><br>TWA: 400 ppm<br>TWA: 980 mg/m <sup>3</sup> | STEL: 1000 mg/m <sup>3</sup> 15 percekben. CK<br>STEL: 400 ppm 15 percekben. CK<br>TWA: 500 mg/m <sup>3</sup> 8 órában. AK<br>TWA: 200 ppm 8 órában. AK | TWA: 200 ppm 8 klukkustundum.<br>TWA: 490 mg/m <sup>3</sup> 8 klukkustundum.<br>Skin notation<br>Ceiling: 400 ppm<br>Ceiling: 980 mg/m <sup>3</sup> |

# SAFETY DATA SHEET

Iso-Propanol

Revision Date 05-Mar-2025

|  |  |  |  |                                         |  |
|--|--|--|--|-----------------------------------------|--|
|  |  |  |  | lehetséges bőrön keresztüli felszívódás |  |
|--|--|--|--|-----------------------------------------|--|

| Component         | Latvia                                                    | Lithuania                                                                                            | Luxembourg | Malta | Romania                                                                                                                   |
|-------------------|-----------------------------------------------------------|------------------------------------------------------------------------------------------------------|------------|-------|---------------------------------------------------------------------------------------------------------------------------|
| Isopropyl alcohol | STEL: 600 mg/m <sup>3</sup><br>TWA: 350 mg/m <sup>3</sup> | TWA: 150 ppm IPRD<br>TWA: 350 mg/m <sup>3</sup> IPRD<br>STEL: 250 ppm<br>STEL: 600 mg/m <sup>3</sup> |            |       | TWA: 81 ppm 8 ore<br>TWA: 200 mg/m <sup>3</sup> 8 ore<br>STEL: 203 ppm 15 minute<br>STEL: 500 mg/m <sup>3</sup> 15 minute |

| Component         | Russia                                                      | Slovak Republic                                                               | Slovenia                                                                                                                        | Sweden                                                                                                                                                             | Turkey |
|-------------------|-------------------------------------------------------------|-------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|
| Isopropyl alcohol | TWA: 10 mg/m <sup>3</sup> 1761<br>MAC: 50 mg/m <sup>3</sup> | Ceiling: 1000 mg/m <sup>3</sup><br>TWA: 200 ppm<br>TWA: 500 mg/m <sup>3</sup> | TWA: 200 ppm 8 urah<br>TWA: 500 mg/m <sup>3</sup> 8 urah<br>STEL: 400 ppm 15 minutah<br>STEL: 1000 mg/m <sup>3</sup> 15 minutah | Indicative STEL: 250 ppm 15 minuter<br>Indicative STEL: 600 mg/m <sup>3</sup> 15 minuter<br>TLV: 150 ppm 8 timmar. NGV<br>TLV: 350 mg/m <sup>3</sup> 8 timmar. NGV |        |

## Biological limit values

List source(s):

| Component         | European Union | United Kingdom | France | Spain                                  | Germany                                                                                |
|-------------------|----------------|----------------|--------|----------------------------------------|----------------------------------------------------------------------------------------|
| Isopropyl alcohol |                |                |        | Acetone: 40 mg/L urine end of workweek | Acetone: 25 mg/L whole blood (end of shift )<br>Acetone: 25 mg/L urine (end of shift ) |

| Component         | Italy | Finland | Denmark | Bulgaria | Romania                             |
|-------------------|-------|---------|---------|----------|-------------------------------------|
| Isopropyl alcohol |       |         |         |          | Acetone: 50 mg/L urine end of shift |

## Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

## Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

| Component                            | Acute effects local (Dermal) | Acute effects systemic (Dermal) | Chronic effects local (Dermal) | Chronic effects systemic (Dermal) |
|--------------------------------------|------------------------------|---------------------------------|--------------------------------|-----------------------------------|
| Isopropyl alcohol<br>67-63-0 ( >95 ) |                              |                                 |                                | DNEL = 888mg/kg bw/day            |

| Component                            | Acute effects local (Inhalation) | Acute effects systemic (Inhalation) | Chronic effects local (Inhalation) | Chronic effects systemic (Inhalation) |
|--------------------------------------|----------------------------------|-------------------------------------|------------------------------------|---------------------------------------|
| Isopropyl alcohol<br>67-63-0 ( >95 ) |                                  |                                     |                                    | DNEL = 500mg/m <sup>3</sup>           |

## Predicted No Effect Concentration (PNEC)

According to our experience and to the information provided to us, the product does not have any harmful effects if it is used and handled as specified. See values below.

# SAFETY DATA SHEET

Iso-Propanol

Revision Date 05-Mar-2025

| Component                          | Fresh water      | Fresh water sediment           | Water Intermittent | Microorganisms in sewage treatment | Soil (Agriculture)        |
|------------------------------------|------------------|--------------------------------|--------------------|------------------------------------|---------------------------|
| Isopropyl alcohol<br>67-63-0 (>95) | PNEC = 140.9mg/L | PNEC = 552mg/kg<br>sediment dw | PNEC = 140.9mg/L   | PNEC = 2251mg/L                    | PNEC = 28mg/kg<br>soil dw |

| Component                          | Marine water     | Marine water sediment          | Marine water Intermittent | Food chain              | Air |
|------------------------------------|------------------|--------------------------------|---------------------------|-------------------------|-----|
| Isopropyl alcohol<br>67-63-0 (>95) | PNEC = 140.9mg/L | PNEC = 552mg/kg<br>sediment dw |                           | PNEC = 160mg/kg<br>food |     |

## 8.2. Exposure controls

### Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

### Personal protective equipment

#### Eye Protection

Goggles (European standard - EN 166)

#### Hand Protection

Protective gloves

| Glove material | Breakthrough time   | Glove thickness | EU standard | Glove comments                                                                 |
|----------------|---------------------|-----------------|-------------|--------------------------------------------------------------------------------|
| Butyl rubber   | > 480 minutes       | 0.5 mm          | EN 374      | Permeation rate < 0.9 µg/cm <sup>2</sup> /min                                  |
| Nitrile rubber | > 360 - 480 minutes | 0.35 - 0.55 mm  |             | As tested under EN374-3 Determination of Resistance to Permeation by Chemicals |
| Viton (R)      | > 480 minutes       | 0.4 mm          |             |                                                                                |
| Neoprene       | < 40 minutes        | 0.7 mm          |             |                                                                                |

#### Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

#### Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.  
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

#### Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced  
**Recommended Filter type:** Organic gases and vapours filter Type A Brown conforming to EN14387

#### Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.  
**Recommended half mask:-** Valve filtering: EN405; Half mask: EN140; plus filter, EN 141  
When RPE is used a face piece Fit Test should be conducted

#### Environmental exposure controls

No information available.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

# SAFETY DATA SHEET

Iso-Propanol

Revision Date 05-Mar-2025

|                                                |                                             |                                                                                       |
|------------------------------------------------|---------------------------------------------|---------------------------------------------------------------------------------------|
| <b>Physical State</b>                          | Liquid                                      |                                                                                       |
| <b>Appearance</b>                              | Colorless                                   |                                                                                       |
| <b>Odor</b>                                    | Alcohol-like                                |                                                                                       |
| <b>Odor Threshold</b>                          | No data available                           |                                                                                       |
| <b>Melting Point/Range</b>                     | -89.5 °C / -129.1 °F                        |                                                                                       |
| <b>Softening Point</b>                         | No data available                           |                                                                                       |
| <b>Boiling Point/Range</b>                     | 81 - 83 °C / 177.8 - 181.4 °F               | @ 760 mmHg                                                                            |
| <b>Flammability (liquid)</b>                   | Highly flammable                            | On basis of test data                                                                 |
| <b>Flammability (solid,gas)</b>                | Not applicable                              | Liquid                                                                                |
| <b>Explosion Limits</b>                        | <b>Lower</b> 2 Vol%<br><b>Upper</b> 12 Vol% |                                                                                       |
| <b>Flash Point</b>                             | 12 °C / 53.6 °F                             | <b>Method</b> - Abel Closed Cup (BS 2000 Part 170, IP 170, AS/NZS 2106)<br>ASTM E-659 |
| <b>Autoignition Temperature</b>                | 425 °C / 797 °F                             |                                                                                       |
| <b>Decomposition Temperature</b>               | No data available                           |                                                                                       |
| <b>pH</b>                                      | 7                                           | 1% aq. sol                                                                            |
| <b>Viscosity</b>                               | 2.27 mPa.s at 20 °C                         |                                                                                       |
| <b>Water Solubility</b>                        | Miscible                                    |                                                                                       |
| <b>Solubility in other solvents</b>            | No information available                    |                                                                                       |
| <b>Partition Coefficient (n-octanol/water)</b> |                                             |                                                                                       |
| <b>Component</b>                               | <b>log Pow</b>                              |                                                                                       |
| Isopropyl alcohol                              | 0.05                                        |                                                                                       |
| <b>Vapor Pressure</b>                          | 43 mmHg @ 20 °C                             |                                                                                       |
| <b>Density / Specific Gravity</b>              | 0.785                                       | ASTM D-4052                                                                           |
| <b>Bulk Density</b>                            | Not applicable                              | Liquid                                                                                |
| <b>Vapor Density</b>                           | 2.1 @ 20 °C / 68 °F                         | (Air = 1.0)                                                                           |
| <b>Particle characteristics</b>                | Not applicable (liquid)                     |                                                                                       |

## 9.2. Other information

|                                 |                                                                                                  |
|---------------------------------|--------------------------------------------------------------------------------------------------|
| <b>Molecular Formula</b>        | C3 H8 O                                                                                          |
| <b>Molecular Weight</b>         | 60.1                                                                                             |
| <b>VOC Content(%)</b>           | 100% (Organic Carbon (by mass) = 59.9 %) (EC/1999/13)                                            |
| <b>Explosive Properties</b>     | Not explosive explosive air/vapour mixtures possible Vapors may form explosive mixtures with air |
| <b>Evaporation Rate</b>         | 1.7 - ASTM D 3539 (Butyl acetate = 1.0)                                                          |
| <b>Thermal conductivity</b>     | 0.137 W/m °C at 20 °C / 68 °F                                                                    |
| <b>Refractive index</b>         | 1.377 at 20 °C / 68 °F (ASTM D-1218)                                                             |
| <b>Surface tension</b>          | 22.7 mN/m at 20 °C / 68 °F                                                                       |
| <b>Coefficient of expansion</b> | 0.0009 / °C                                                                                      |
| <b>Specific heat capacity</b>   | 3 kJ/kg °C at 20 °C / 68 °F                                                                      |
| <b>Dielectric constant</b>      | 18.6 at 20 °C / 68 °F                                                                            |
| <b>Heat of vapourisation</b>    | 665 J/g                                                                                          |

## Section 10: Stability and reactivity

### 10.1. Reactivity

None known, based on information available

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

|                                 |                                          |
|---------------------------------|------------------------------------------|
| <b>Hazardous Polymerization</b> | Hazardous polymerization does not occur. |
| <b>Hazardous Reactions</b>      | None under normal processing.            |

### 10.4. Conditions to avoid



# SAFETY DATA SHEET

Iso-Propanol

Revision Date 05-Mar-2025

Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of ignition.

## 10.5. Incompatible materials

Strong oxidizing agents. Acids. Halogens. Acid anhydrides.

## 10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). peroxides.

## Section 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Product Information

##### (a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

| Component         | LD50 Oral                                  | LD50 Dermal         | LC50 Inhalation       |
|-------------------|--------------------------------------------|---------------------|-----------------------|
| Isopropyl alcohol | 5045 mg/kg ( Rat )<br>3600 mg/kg ( Mouse ) | 12800 mg/kg ( Rat ) | 72.6 mg/L ( Rat ) 4 h |

##### (b) skin corrosion/irritation;

Based on available data, the classification criteria are not met

##### (c) serious eye damage/irritation;

Category 2

##### (d) respiratory or skin sensitization;

Respiratory

Based on available data, the classification criteria are not met

Skin

Based on available data, the classification criteria are not met

##### (e) germ cell mutagenicity;

Based on available data, the classification criteria are not met

##### (f) carcinogenicity;

Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

##### (g) reproductive toxicity;

Based on available data, the classification criteria are not met

##### (h) STOT-single exposure;

Category 3

Results / Target organs

Central nervous system (CNS).

##### (i) STOT-repeated exposure;

Based on available data, the classification criteria are not met

Target Organs

None known.

##### (j) aspiration hazard;

Based on available data, the classification criteria are not met

Symptoms / effects, both acute and delayed

May cause central nervous system depression. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

# SAFETY DATA SHEET

Iso-Propanol

Revision Date 05-Mar-2025

## 11.2. Information on other hazards

**Endocrine Disrupting Properties** Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

## Section 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity effects** . Do not empty into drains.

| Component         | Freshwater Fish                                                                                                                                                                                                             | Water Flea                                      | Freshwater Algae                                                                                           |
|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------|------------------------------------------------------------------------------------------------------------|
| Isopropyl alcohol | LC50: = 9640 mg/L, 96h<br>flow-through (Pimephales<br>promelas)<br>LC50: > 1400000 µg/L, 96h<br>(Lepomis macrochirus)<br>LC50: = 11130 mg/L, 96h static<br>(Pimephales promelas)<br>LC50: = 10000000 µg/L, 96h<br>(Daphnia) | 13299 mg/L EC50 = 48 h<br>9714 mg/L EC50 = 24 h | EC50: > 1000 mg/L, 72h<br>(Desmodesmus subspicatus)<br>EC50: > 1000 mg/L, 96h<br>(Desmodesmus subspicatus) |

| Component         | Microtox                                              | M-Factor |
|-------------------|-------------------------------------------------------|----------|
| Isopropyl alcohol | = 35390 mg/L EC50 Photobacterium phosphoreum<br>5 min |          |

**12.2. Persistence and degradability** Expected to be biodegradable  
**Persistence** Persistence is unlikely, based on information available.

**12.3. Bioaccumulative potential** Bioaccumulation is unlikely

| Component         | log Pow | Bioconcentration factor (BCF) |
|-------------------|---------|-------------------------------|
| Isopropyl alcohol | 0.05    | No data available             |

**12.4. Mobility in soil** The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air.  
**Surface tension** 22.7 mN/m at 20 °C / 68 °F

**12.5. Results of PBT and vPvB assessment** Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB).

### 12.6. Endocrine disrupting properties

**Endocrine Disruptor Information** This product does not contain any known or suspected endocrine disruptors

**12.7. Other adverse effects**  
**Persistent Organic Pollutant**  
**Ozone Depletion Potential**

This product does not contain any known or suspected substance  
This product does not contain any known or suspected substance

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

# SAFETY DATA SHEET

Iso-Propanol

Revision Date 05-Mar-2025

|                                            |                                                                                                                                                                                                                                                                                                            |
|--------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Waste from Residues/Unused Products</b> | Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.                                                                                                                                     |
| <b>Contaminated Packaging</b>              | Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.                                                                   |
| <b>European Waste Catalogue (EWC)</b>      | According to the European Waste Catalog, Waste Codes are not product specific, but application specific.                                                                                                                                                                                                   |
| <b>Other Information</b>                   | Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations.                                                                                                    |
| <b>Switzerland - Waste Ordinance</b>       | Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600<br><a href="https://www.fedlex.admin.ch/eli/cc/2015/891/en">https://www.fedlex.admin.ch/eli/cc/2015/891/en</a> |

## Section 14: Transport information

### IMDG/IMO

|                                         |                                 |
|-----------------------------------------|---------------------------------|
| <b>14.1. UN number</b>                  | UN1219                          |
| <b>14.2. UN proper shipping name</b>    | Isopropanol (Isopropyl alcohol) |
| <b>14.3. Transport hazard class(es)</b> | 3                               |
| <b>14.4. Packing group</b>              | II                              |

### ADR

|                                         |                                 |
|-----------------------------------------|---------------------------------|
| <b>14.1. UN number</b>                  | UN1219                          |
| <b>14.2. UN proper shipping name</b>    | Isopropanol (Isopropyl alcohol) |
| <b>14.3. Transport hazard class(es)</b> | 3                               |
| <b>14.4. Packing group</b>              | II                              |

### IATA

|                                         |             |
|-----------------------------------------|-------------|
| <b>14.1. UN number</b>                  | UN1219      |
| <b>14.2. UN proper shipping name</b>    | Isopropanol |
| <b>14.3. Transport hazard class(es)</b> | 3           |
| <b>14.4. Packing group</b>              | II          |

|                                                                      |                                  |
|----------------------------------------------------------------------|----------------------------------|
| <b>14.5. Environmental hazards</b>                                   | No hazards identified            |
| <b>14.6. Special precautions for user</b>                            | No special precautions required. |
| <b>14.7. Maritime transport in bulk according to IMO instruments</b> | Not applicable, packaged goods   |

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

# SAFETY DATA SHEET

Iso-Propanol

Revision Date 05-Mar-2025

| Component         | CAS No  | EINECS    | ELINCS | NLP | IECSC | TCSI | KECL     | ENCS | ISHL |
|-------------------|---------|-----------|--------|-----|-------|------|----------|------|------|
| Isopropyl alcohol | 67-63-0 | 200-661-7 | -      | -   | X     | X    | KE-29363 | X    | X    |

  

| Component         | CAS No  | TSCA | TSCA Inventory notification - Active-Inactive | DSL | NDSL | AICS | NZIoC | PICCS |
|-------------------|---------|------|-----------------------------------------------|-----|------|------|-------|-------|
| Isopropyl alcohol | 67-63-0 | X    | ACTIVE                                        | X   | -    | X    | X     | X     |

**Legend:** X - Listed '-' - Not Listed

**KECL** - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

## Authorisation/Restrictions according to EU REACH

| Component         | CAS No  | REACH (1907/2006) - Annex XIV - Substances Subject to Authorization | REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances | REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC) |
|-------------------|---------|---------------------------------------------------------------------|-------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------|
| Isopropyl alcohol | 67-63-0 | -                                                                   | Use restricted. See entry 75. (see link for restriction details)              | -                                                                                                     |

## REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

## Seveso III Directive (2012/18/EC)

| Component         | CAS No  | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements |
|-------------------|---------|-------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|
| Isopropyl alcohol | 67-63-0 | Not applicable                                                                            | Not applicable                                                                           |

## Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

## Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

## National Regulations

**UK** - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

## WGK Classification

See table for values

| Component         | Germany - Water Classification (AwSV) | Germany - TA-Luft Class |
|-------------------|---------------------------------------|-------------------------|
| Isopropyl alcohol | WGK1                                  |                         |

| Component         | France - INRS (Tables of occupational diseases)      |
|-------------------|------------------------------------------------------|
| Isopropyl alcohol | Tableaux des maladies professionnelles (TMP) - RG 84 |

## Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

# SAFETY DATA SHEET

Iso-Propanol

Revision Date 05-Mar-2025

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

| Component                            | Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81) | Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC) | Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure |
|--------------------------------------|----------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|
| Isopropyl alcohol<br>67-63-0 ( >95 ) |                                                                                                                | Group I                                                                         |                                                                                             |

## 15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has been conducted by the manufacturer/importer

## Section 16: Other information

### Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness

### Legend

**CAS** - Chemical Abstracts Service

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

**WEL** - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

**RPE** - Respiratory Protective Equipment

**LC50** - Lethal Concentration 50%

**NOEC** - No Observed Effect Concentration

**PBT** - Persistent, Bioaccumulative, Toxic

**TWA** - Time Weighted Average

**IARC** - International Agency for Research on Cancer  
Predicted No Effect Concentration (PNEC)

**LD50** - Lethal Dose 50%

**EC50** - Effective Concentration 50%

**POW** - Partition coefficient Octanol:Water

**vPvB** - very Persistent, very Bioaccumulative

**ADR** - European Agreement Concerning the International Carriage of Dangerous Goods by Road

**IMO/IMDG** - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

### Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadviser - LOLI, Merck index, RTECS

**ICAO/IATA** - International Civil Aviation Organization/International Air Transport Association

**MARPOL** - International Convention for the Prevention of Pollution from Ships

**ATE** - Acute Toxicity Estimate

**VOC** - (volatile organic compound)

### Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

**Creation Date** 01-Sep-2009

**Revision Date** 05-Mar-2025

**Revision Summary** Not applicable.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.**

# **SAFETY DATA SHEET**

Iso-Propanol

Revision Date 05-Mar-2025

---

**COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006**

**For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, Chemo (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).**

## **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**