

## SAFETY DATA SHEET

Creation Date 13-Feb-2015

Revision Date 29-Jan-2019

Revision Number 72

### 1. Identification

**Product Name** Xylene

**Cat No. :** 6601, 6615, 6615SS, 6655, 9900-1, 9900-5

**Synonyms** Dimethylbenzene; Methyltoluene

**Recommended Use** Laboratory chemicals.

**Uses advised against** Food, drug, pesticide or biocidal product use

#### Details of the supplier of the safety data sheet

##### Company

Richard-Allan Scientific  
4481 Campus Drive  
Kalamazoo, MI 49008  
Tel: (800) 522-7270

##### **Emergency Telephone Number**

Chemtrec US: (800) 424-9300  
Chemtrec EU: 001 (202) 483-7616

### 2. Hazard(s) identification

#### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

|                                                      |            |
|------------------------------------------------------|------------|
| Flammable liquids                                    | Category 3 |
| Acute dermal toxicity                                | Category 4 |
| Acute Inhalation Toxicity - Vapors                   | Category 4 |
| Skin Corrosion/irritation                            | Category 2 |
| Serious Eye Damage/Eye Irritation                    | Category 2 |
| Carcinogenicity                                      | Category 2 |
| Specific target organ toxicity - (repeated exposure) | Category 2 |
| Target Organs - Kidney, Liver.                       |            |
| Aspiration Toxicity                                  | Category 1 |

#### Label Elements

##### **Signal Word**

Danger

##### **Hazard Statements**

Flammable liquid and vapor  
May be fatal if swallowed and enters airways  
Harmful in contact with skin  
Causes skin irritation  
Causes serious eye irritation  
Harmful if inhaled

Suspected of causing cancer  
May cause damage to organs through prolonged or repeated exposure



### Precautionary Statements

#### Prevention

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required  
Use only outdoors or in a well-ventilated area  
Wash face, hands and any exposed skin thoroughly after handling  
Wear eye/face protection  
Do not breathe dust/fume/gas/mist/vapors/spray  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
Keep container tightly closed  
Ground/bond container and receiving equipment  
Use explosion-proof electrical/ventilating/lighting/equipment  
Use only non-sparking tools  
Take precautionary measures against static discharge

#### Response

IF exposed or concerned: Get medical attention/advice

#### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

#### Skin

Call a POISON CENTER or doctor/physician if you feel unwell  
If skin irritation occurs: Get medical advice/attention  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
Wash contaminated clothing before reuse

#### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If eye irritation persists: Get medical advice/attention

#### Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
Do NOT induce vomiting

#### Fire

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

#### Storage

Store locked up  
Store in a well-ventilated place. Keep cool

#### Disposal

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

None identified

WARNING. Cancer and Reproductive Harm - <https://www.p65warnings.ca.gov/>.

## 3. Composition/Information on Ingredients

| Component                    | CAS-No    | Weight % |
|------------------------------|-----------|----------|
| Xylenes (o-, m-, p- isomers) | 1330-20-7 | 85       |
| Ethylbenzene                 | 100-41-4  | 10 - 15  |
| Toluene                      | 108-88-3  | 0 - 0.5  |

|         |         |          |
|---------|---------|----------|
| Benzene | 71-43-2 | 0 - 0.01 |
|---------|---------|----------|

#### 4. First-aid measures

|                                            |                                                                                                                                                                                                     |
|--------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>General Advice</b>                      | If symptoms persist, call a physician.                                                                                                                                                              |
| <b>Eye Contact</b>                         | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.                                                                                     |
| <b>Skin Contact</b>                        | If skin irritation persists, call a physician. Wash off immediately with plenty of water for at least 15 minutes.                                                                                   |
| <b>Inhalation</b>                          | Move to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur. Risk of serious damage to the lungs.                                                     |
| <b>Ingestion</b>                           | Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting. Call a physician or Poison Control Center immediately. If vomiting occurs naturally, have victim lean forward. |
| <b>Most important symptoms and effects</b> | Breathing difficulties. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting                                                         |
| <b>Notes to Physician</b>                  | Treat symptomatically                                                                                                                                                                               |

#### 5. Fire-fighting measures

|                                         |                                                                                                                            |
|-----------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| <b>Suitable Extinguishing Media</b>     | CO <sub>2</sub> , dry chemical, dry sand, alcohol-resistant foam. Cool closed containers exposed to fire with water spray. |
| <b>Unsuitable Extinguishing Media</b>   | Water may be ineffective                                                                                                   |
| <b>Flash Point</b>                      | 26.1 °C / 79 °F                                                                                                            |
| <b>Method -</b>                         | No information available                                                                                                   |
| <b>Autoignition Temperature</b>         | 565.56 °C / 1050 °F                                                                                                        |
| <b>Explosion Limits</b>                 |                                                                                                                            |
| <b>Upper</b>                            | 7.0 vol %                                                                                                                  |
| <b>Lower</b>                            | 1.1 vol %                                                                                                                  |
| <b>Sensitivity to Mechanical Impact</b> | No information available                                                                                                   |
| <b>Sensitivity to Static Discharge</b>  | No information available                                                                                                   |

#### Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Keep product and empty container away from heat and sources of ignition. Vapors may form explosive mixtures with air.

#### Hazardous Combustion Products

Carbon monoxide (CO) Carbon dioxide (CO<sub>2</sub>) Hydrocarbons Aldehydes

#### Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### NFPA

**Health**  
3

**Flammability**  
3

**Instability**  
0

**Physical hazards**  
N/A

#### 6. Accidental release measures

|                             |                                                                                                                                                        |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Personal Precautions</b> | Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition. Take precautionary measures against static discharges. |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|

**Environmental Precautions** Do not flush into surface water or sanitary sewer system.

**Methods for Containment and Clean Up** Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.  
Remove all sources of ignition. Take precautionary measures against static discharges.  
Use spark-proof tools and explosion-proof equipment.

## 7. Handling and storage

**Handling** Ensure adequate ventilation. Wear personal protective equipment. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Use explosion-proof equipment. Take precautionary measures against static discharges.

**Storage** Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep away from heat and sources of ignition. Keep containers tightly closed in a cool, well-ventilated place. Flammables area. Keep container tightly closed in a dry and well-ventilated place.

## 8. Exposure controls / personal protection

### Exposure Guidelines

| Component                    | ACGIH TLV                             | OSHA PEL                                                                                                                                                                         | NIOSH IDLH                                                                                                  | Mexico OEL (TWA)              |
|------------------------------|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|-------------------------------|
| Xylenes (o-, m-, p- isomers) | TWA: 100 ppm<br>STEL: 150 ppm         | (Vacated) TWA: 100 ppm<br>(Vacated) TWA: 435 mg/m <sup>3</sup><br>(Vacated) STEL: 150 ppm<br>(Vacated) STEL: 655 mg/m <sup>3</sup><br>TWA: 100 ppm<br>TWA: 435 mg/m <sup>3</sup> |                                                                                                             | TWA: 100 ppm<br>STEL: 150 ppm |
| Ethylbenzene                 | TWA: 20 ppm                           | (Vacated) TWA: 100 ppm<br>(Vacated) TWA: 435 mg/m <sup>3</sup><br>(Vacated) STEL: 125 ppm<br>(Vacated) STEL: 545 mg/m <sup>3</sup><br>TWA: 100 ppm<br>TWA: 435 mg/m <sup>3</sup> | IDLH: 800 ppm<br>TWA: 100 ppm<br>TWA: 435 mg/m <sup>3</sup><br>STEL: 125 ppm<br>STEL: 545 mg/m <sup>3</sup> | TWA: 20 ppm                   |
| Toluene                      | TWA: 20 ppm                           | (Vacated) TWA: 100 ppm<br>(Vacated) TWA: 375 mg/m <sup>3</sup><br>Ceiling: 300 ppm<br>(Vacated) STEL: 150 ppm<br>(Vacated) STEL: 560 mg/m <sup>3</sup><br>TWA: 200 ppm           | IDLH: 500 ppm<br>TWA: 100 ppm<br>TWA: 375 mg/m <sup>3</sup><br>STEL: 150 ppm<br>STEL: 560 mg/m <sup>3</sup> | TWA: 20 ppm                   |
| Benzene                      | TWA: 0.5 ppm<br>STEL: 2.5 ppm<br>Skin | (Vacated) TWA: 10 ppm<br>Ceiling: 25 ppm<br>(Vacated) STEL: 50 ppm<br>(Vacated) Ceiling: 25 ppm<br>TWA: 10 ppm<br>TWA: 1 ppm<br>STEL: 5 ppm                                      | IDLH: 500 ppm<br>TWA: 0.1 ppm<br>STEL: 1 ppm                                                                | TWA: 0.5 ppm<br>STEL: 2.5 ppm |

### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

**Engineering Measures** Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

### Personal Protective Equipment

**Eye/face Protection** Tightly fitting safety goggles. Face-shield.

|                                 |                                                                                                                                                                                                                                                   |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Skin and body protection</b> | Long sleeved clothing.                                                                                                                                                                                                                            |
| <b>Respiratory Protection</b>   | Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. |
| <b>Hygiene Measures</b>         | When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.                                                                                                                                            |

## 9. Physical and chemical properties

|                                               |                                   |
|-----------------------------------------------|-----------------------------------|
| <b>Physical State</b>                         | Liquid                            |
| <b>Appearance</b>                             | Clear, Colorless                  |
| <b>Odor</b>                                   | aromatic                          |
| <b>Odor Threshold</b>                         | No information available          |
| <b>pH</b>                                     | Not applicable                    |
| <b>Melting Point/Range</b>                    | -47.2 °C / -53 °F                 |
| <b>Boiling Point/Range</b>                    | 136.7 - 143 °C / 278.1 - 289.4 °F |
| <b>Flash Point</b>                            | 26.1 °C / 79 °F                   |
| <b>Evaporation Rate</b>                       | No information available          |
| <b>Flammability (solid,gas)</b>               | Not applicable                    |
| <b>Flammability or explosive limits</b>       |                                   |
| Upper                                         | 7.0 vol %                         |
| Lower                                         | 1.1 vol %                         |
| <b>Vapor Pressure</b>                         | 9 mmHg @ 25 °C                    |
| <b>Vapor Density</b>                          | 3.66 (Air = 1.0)                  |
| <b>Specific Gravity</b>                       | 0.87                              |
| <b>Solubility</b>                             | Insoluble in water                |
| <b>Partition coefficient; n-octanol/water</b> | No data available                 |
| <b>Autoignition Temperature</b>               | 565.56 °C / 1050 °F               |
| <b>Decomposition Temperature</b>              | No information available          |
| <b>Viscosity</b>                              | No information available          |
| <b>VOC Content(%)</b>                         | 100.51                            |

## 10. Stability and reactivity

|                                         |                                                                                   |
|-----------------------------------------|-----------------------------------------------------------------------------------|
| <b>Reactive Hazard</b>                  | None known, based on information available                                        |
| <b>Stability</b>                        | Stable under normal conditions.                                                   |
| <b>Conditions to Avoid</b>              | Heating in air. Keep away from open flames, hot surfaces and sources of ignition. |
| <b>Incompatible Materials</b>           | Strong oxidizing agents, Strong acids                                             |
| <b>Hazardous Decomposition Products</b> | Carbon monoxide (CO), Carbon dioxide (CO <sub>2</sub> ), Hydrocarbons, Aldehydes  |
| <b>Hazardous Polymerization</b>         | Hazardous polymerization does not occur.                                          |
| <b>Hazardous Reactions</b>              | None under normal processing.                                                     |

## 11. Toxicological information

### Acute Toxicity

#### Product Information

|                    |                                                                               |
|--------------------|-------------------------------------------------------------------------------|
| <b>Oral LD50</b>   | Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg. |
| <b>Dermal LD50</b> | Category 4. ATE = 1000 - 2000 mg/kg.                                          |
| <b>Vapor LC50</b>  | Category 4. ATE = 10 - 20 mg/l.                                               |

#### Component Information

| Component                    | LD50 Oral                 | LD50 Dermal                  | LC50 Inhalation                  |
|------------------------------|---------------------------|------------------------------|----------------------------------|
| Xylenes (o-, m-, p- isomers) | LD50 = 3500 mg/kg ( Rat ) | LD50 > 4350 mg/kg ( Rabbit ) | 29.08 mg/L [MOE Risk Assessment] |

|              |                                                       |                               |                               |
|--------------|-------------------------------------------------------|-------------------------------|-------------------------------|
|              |                                                       | LD50 > 1700 mg/kg ( Rabbit )  | Vol.1, 2002]                  |
| Ethylbenzene | 3500 mg/kg ( Rat )                                    | 15400 mg/kg ( Rabbit )        | 17.2 mg/L ( Rat ) 4 h         |
| Toluene      | > 5000 mg/kg ( Rat )                                  | LD50 = 12000 mg/kg ( Rabbit ) | 26700 ppm ( Rat ) 1 h         |
| Benzene      | LD50 = 810 mg/kg ( Rat )<br>LD50 = 1800 mg/kg ( Rat ) | LD50 > 8200 mg/kg ( Rabbit )  | LC50 = 44.66 mg/L ( Rat ) 4 h |

**Toxicologically Synergistic Products** No information available

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Irritation** Irritating to eyes and skin

**Sensitization** No information available

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen. This product contains one or more substances which are classified by IARC as carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly carcinogenic to humans (Group 2B).

| Component                   | CAS-No    | IARC       | NTP        | ACGIH      | OSHA       | Mexico     |
|-----------------------------|-----------|------------|------------|------------|------------|------------|
| Xylenes (o-, m-, p-isomers) | 1330-20-7 | Not listed | Not listed | Not listed | Not listed | Not listed |
| Ethylbenzene                | 100-41-4  | Group 2B   | Not listed | A3         | X          | A3         |
| Toluene                     | 108-88-3  | Not listed | Not listed | Not listed | Not listed | Not listed |
| Benzene                     | 71-43-2   | Group 1    | Known      | A1         | X          | A1         |

*IARC: (International Agency for Research on Cancer)*

*NTP: (National Toxicity Program)*

*ACGIH: (American Conference of Governmental Industrial Hygienists)*

*Mexico - Occupational Exposure Limits - Carcinogens*

*IARC: (International Agency for Research on Cancer)*

*Group 1 - Carcinogenic to Humans*

*Group 2A - Probably Carcinogenic to Humans*

*Group 2B - Possibly Carcinogenic to Humans*

*NTP: (National Toxicity Program)*

*Known - Known Carcinogen*

*Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen*

*A1 - Known Human Carcinogen*

*A2 - Suspected Human Carcinogen*

*A3 - Animal Carcinogen*

*ACGIH: (American Conference of Governmental Industrial Hygienists)*

*Mexico - Occupational Exposure Limits - Carcinogens*

*A1 - Confirmed Human Carcinogen*

*A2 - Suspected Human Carcinogen*

*A3 - Confirmed Animal Carcinogen*

*A4 - Not Classifiable as a Human Carcinogen*

*A5 - Not Suspected as a Human Carcinogen*

**Mutagenic Effects** No information available

**Reproductive Effects** No information available.

**Developmental Effects** No information available.

**Teratogenicity** No information available.

**STOT - single exposure** None known

**STOT - repeated exposure** Kidney Liver

**Aspiration hazard** No information available

**Symptoms / effects, both acute and delayed** Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

**Endocrine Disruptor Information** No information available

**Other Adverse Effects** Tumorigenic effects have been reported in experimental animals.

## 12. Ecological information

### Ecotoxicity

The product contains following substances which are hazardous for the environment. Contains a substance which is: Very toxic to aquatic organisms.

| Component                    | Freshwater Algae                                                                                                                                                                                                                                                                                    | Freshwater Fish                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Microtox                                       | Water Flea                                                                                                     |
|------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------|----------------------------------------------------------------------------------------------------------------|
| Xylenes (o-, m-, p- isomers) | Not listed                                                                                                                                                                                                                                                                                          | LC50: 13.1 - 16.5 mg/L, 96h flow-through ( <i>Lepomis macrochirus</i> )<br>LC50: = 19 mg/L, 96h ( <i>Lepomis macrochirus</i> )<br>LC50: 7.711 - 9.591 mg/L, 96h static ( <i>Lepomis macrochirus</i> )<br>LC50: 23.53 - 29.97 mg/L, 96h static ( <i>Pimephales promelas</i> )<br>LC50: = 780 mg/L, 96h semi-static ( <i>Cyprinus carpio</i> )<br>LC50: > 780 mg/L, 96h ( <i>Cyprinus carpio</i> )<br>LC50: 30.26 - 40.75 mg/L, 96h static ( <i>Poecilia reticulata</i> )<br>LC50: 13.5 - 17.3 mg/L, 96h ( <i>Oncorhynchus mykiss</i> )<br>LC50: = 13.4 mg/L, 96h flow-through ( <i>Pimephales promelas</i> )<br>LC50: 2.661 - 4.093 mg/L, 96h static ( <i>Oncorhynchus mykiss</i> ) | EC50 = 0.0084 mg/L 24 h                        | EC50: = 3.82 mg/L, 48h (water flea)<br>LC50: = 0.6 mg/L, 48h ( <i>Gammarus lacustris</i> )                     |
| Ethylbenzene                 | EC50: 1.7 - 7.6 mg/L, 96h static ( <i>Pseudokirchneriella subcapitata</i> )<br>EC50: 2.6 - 11.3 mg/L, 72h static ( <i>Pseudokirchneriella subcapitata</i> )<br>EC50: > 438 mg/L, 96h ( <i>Pseudokirchneriella subcapitata</i> )<br>EC50: = 4.6 mg/L, 72h ( <i>Pseudokirchneriella subcapitata</i> ) | LC50: 11.0 - 18.0 mg/L, 96h static ( <i>Oncorhynchus mykiss</i> )<br>LC50: 7.55 - 11 mg/L, 96h flow-through ( <i>Pimephales promelas</i> )<br>LC50: = 4.2 mg/L, 96h semi-static ( <i>Oncorhynchus mykiss</i> )<br>LC50: = 32 mg/L, 96h static ( <i>Lepomis macrochirus</i> )<br>LC50: 9.1 - 15.6 mg/L, 96h static ( <i>Pimephales promelas</i> )<br>LC50: = 9.6 mg/L, 96h static ( <i>Poecilia reticulata</i> )                                                                                                                                                                                                                                                                    | EC50 = 9.68 mg/L 30 min<br>EC50 = 96 mg/L 24 h | EC50: 1.8 - 2.4 mg/L, 48h ( <i>Daphnia magna</i> )                                                             |
| Toluene                      | EC50: = 12.5 mg/L, 72h static ( <i>Pseudokirchneriella subcapitata</i> )<br>EC50: > 433 mg/L, 96h ( <i>Pseudokirchneriella subcapitata</i> )                                                                                                                                                        | 50-70 mg/L LC50 96 h<br>5-7 mg/L LC50 96 h<br>15-19 mg/L LC50 96 h<br>28 mg/L LC50 96 h<br>12 mg/L LC50 96 h                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | EC50 = 19.7 mg/L 30 min                        | EC50: 5.46 - 9.83 mg/L, 48h Static ( <i>Daphnia magna</i> )<br>EC50: = 11.5 mg/L, 48h ( <i>Daphnia magna</i> ) |
| Benzene                      | EC50: = 29 mg/L, 72h ( <i>Pseudokirchneriella subcapitata</i> )                                                                                                                                                                                                                                     | LC50: 22330 - 41160 µg/L, 96h static ( <i>Pimephales promelas</i> )<br>LC50: 70000 - 142000 µg/L, 96h static ( <i>Lepomis macrochirus</i> )<br>LC50: = 28.6 mg/L, 96h static ( <i>Poecilia reticulata</i> )                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Not listed                                     | EC50: = 10 mg/L, 48h ( <i>Daphnia magna</i> )<br>EC50: 8.76 - 15.6 mg/L, 48h Static ( <i>Daphnia magna</i> )   |

|  |  |                                                                                                                                                                                    |  |  |
|--|--|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|
|  |  | LC50: 10.7 - 14.7 mg/L, 96h flow-through (Pimephales promelas)<br>LC50: = 5.3 mg/L, 96h flow-through (Oncorhynchus mykiss)<br>LC50: = 22.49 mg/L, 96h static (Lepomis macrochirus) |  |  |
|--|--|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|

**Persistence and Degradability** Persistence is unlikely

**Bioaccumulation/ Accumulation** No information available.

**Mobility** . Is not likely mobile in the environment due its low water solubility.

| Component                    | log Pow |
|------------------------------|---------|
| Xylenes (o-, m-, p- isomers) | 3.15    |
| Ethylbenzene                 | 3.2     |
| Toluene                      | 2.7     |
| Benzene                      | 2.1     |

### 13. Disposal considerations

**Waste Disposal Methods** Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

| Component                                | RCRA - U Series Wastes | RCRA - P Series Wastes |
|------------------------------------------|------------------------|------------------------|
| Xylenes (o-, m-, p- isomers) - 1330-20-7 | U239                   | -                      |
| Toluene - 108-88-3                       | U220                   | -                      |
| Benzene - 71-43-2                        | U019                   | -                      |

### 14. Transport information

#### DOT

UN-No UN1307  
 Proper Shipping Name XYLENES  
 Hazard Class 3  
 Packing Group III

#### TDG

UN-No UN1307  
 Proper Shipping Name XYLENES  
 Hazard Class 3  
 Packing Group III

#### IATA

UN-No UN1307  
 Proper Shipping Name XYLENES  
 Hazard Class 3  
 Packing Group III

#### IMDG/IMO

UN-No UN1307  
 Proper Shipping Name XYLENES  
 Hazard Class 3  
 Packing Group III

### 15. Regulatory information

#### United States of America Inventory

| Component                    | CAS-No    | TSCA | TSCA Inventory notification - Active/Inactive | TSCA - EPA Regulatory Flags |
|------------------------------|-----------|------|-----------------------------------------------|-----------------------------|
| Xylenes (o-, m-, p- isomers) | 1330-20-7 | X    | ACTIVE                                        | -                           |
| Ethylbenzene                 | 100-41-4  | X    | ACTIVE                                        | -                           |



|         |          |   |        |   |
|---------|----------|---|--------|---|
| Toluene | 108-88-3 | X | ACTIVE | - |
| Benzene | 71-43-2  | X | ACTIVE | - |

**Legend:**

TSCA - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

- - Not Listed

TSCA 12(b) - Notices of Export Not applicable

**International Inventories**

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Australia (AICS), China (IECSC), Korea (ECL).

| Component                    | CAS-No    | DSL | NDSL | EINECS    | PICCS | ENCS | AICS | IECSC | KECL     |
|------------------------------|-----------|-----|------|-----------|-------|------|------|-------|----------|
| Xylenes (o-, m-, p- isomers) | 1330-20-7 | X   | -    | 215-535-7 | X     | X    | X    | X     | KE-35427 |
| Ethylbenzene                 | 100-41-4  | X   | -    | 202-849-4 | X     | X    | X    | X     | KE-13532 |
| Toluene                      | 108-88-3  | X   | -    | 203-625-9 | X     | X    | X    | X     | KE-33936 |
| Benzene                      | 71-43-2   | X   | -    | 200-753-7 | X     | X    | X    | X     | KE-02150 |

**U.S. Federal Regulations****SARA 313**

| Component                    | CAS-No    | Weight % | SARA 313 - Threshold Values % |
|------------------------------|-----------|----------|-------------------------------|
| Xylenes (o-, m-, p- isomers) | 1330-20-7 | 85       | 1.0                           |
| Ethylbenzene                 | 100-41-4  | 10 - 15  | 0.1                           |
| Toluene                      | 108-88-3  | 0 - 0.5  | 1.0                           |
| Benzene                      | 71-43-2   | 0 - 0.01 | 0.1                           |

SARA 311/312 Hazard Categories See section 2 for more information

**CWA (Clean Water Act)**

| Component                    | CWA - Hazardous Substances | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants |
|------------------------------|----------------------------|-----------------------------|------------------------|---------------------------|
| Xylenes (o-, m-, p- isomers) | X                          | 100 lb                      | -                      | -                         |
| Ethylbenzene                 | X                          | 1000 lb                     | X                      | X                         |
| Toluene                      | X                          | 1000 lb                     | X                      | X                         |
| Benzene                      | X                          | 10 lb                       | X                      | X                         |

**Clean Air Act**

| Component                    | HAPS Data | Class 1 Ozone Depleters | Class 2 Ozone Depleters |
|------------------------------|-----------|-------------------------|-------------------------|
| Xylenes (o-, m-, p- isomers) | X         |                         | -                       |
| Ethylbenzene                 | X         |                         | -                       |
| Toluene                      | X         |                         | -                       |
| Benzene                      | X         |                         | -                       |

OSHA - Occupational Safety and Health Administration Not applicable

| Component | Specifically Regulated Chemicals                | Highly Hazardous Chemicals |
|-----------|-------------------------------------------------|----------------------------|
| Benzene   | 5 ppm STEL<br>0.5 ppm Action Level<br>1 ppm TWA | -                          |

**CERCLA**

| Component                    | Hazardous Substances RQs | CERCLA EHS RQs |
|------------------------------|--------------------------|----------------|
| Xylenes (o-, m-, p- isomers) | 100 lb                   | -              |
| Ethylbenzene                 | 1000 lb                  | -              |
| Toluene                      | 1000 lb 1 lb             | -              |

|         |       |   |
|---------|-------|---|
| Benzene | 10 lb | - |
|---------|-------|---|

**California Proposition 65** This product contains the following proposition 65 chemicals

| Component    | CAS-No   | California Prop. 65                              | Prop 65 NSRL            | Category                    |
|--------------|----------|--------------------------------------------------|-------------------------|-----------------------------|
| Ethylbenzene | 100-41-4 | Carcinogen                                       | 54 µg/day<br>41 µg/day  | Carcinogen                  |
| Toluene      | 108-88-3 | Developmental                                    | -                       | Developmental               |
| Benzene      | 71-43-2  | Carcinogen<br>Developmental<br>Male Reproductive | 6.4 µg/day<br>13 µg/day | Developmental<br>Carcinogen |

**U.S. State Right-to-Know Regulations**

| Component                   | Massachusetts | New Jersey | Pennsylvania | Illinois | Rhode Island |
|-----------------------------|---------------|------------|--------------|----------|--------------|
| Xylenes (o-, m-, p-isomers) | X             | X          | X            | X        | X            |
| Ethylbenzene                | X             | X          | X            | X        | X            |
| Toluene                     | X             | X          | X            | X        | X            |
| Benzene                     | X             | X          | X            | X        | X            |

**U.S. Department of Transportation**

Reportable Quantity (RQ): N  
DOT Marine Pollutant N  
DOT Severe Marine Pollutant N

**U.S. Department of Homeland Security**

This product does not contain any DHS chemicals.

**Other International Regulations**

**Mexico - Grade** Serious risk, Grade 3

## 16. Other information

**Prepared By** Regulatory Affairs  
Richard Allan Scientific  
A Subsidiary of Thermo Fisher Scientific  
Tel: (800) 522-7270

**Creation Date** 13-Feb-2015  
**Revision Date** 29-Jan-2019  
**Print Date** 29-Jan-2019  
**Revision Summary** This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**