

SAFETY DATA SHEET

Revision Date 10-September-2024

Revision Number 4

1. Identification

Product Name Beryllium foil

Cat No. : 41613

CAS-No 7440-41-7
Synonyms No information available

Recommended Use Laboratory chemicals.
Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Importer/Distributor

Fisher Scientific
112 Colonnade Road,
Ottawa, ON K2E 7L6,
Canada
Tel: 1-800-234-7437

Emergency Telephone Number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11

Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99

CHEMTREC Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

WHMIS 2015 Classification Classified as hazardous under the Hazardous Products Regulations (SOR/2015-17)

Acute oral toxicity	Category 3
Acute Inhalation Toxicity	Category 2
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Skin Sensitization	Category 1
Carcinogenicity	Category 1A
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Respiratory system.	
Specific target organ toxicity - (repeated exposure)	Category 1
Target Organs - Lungs.	

Label Elements

Signal Word

Danger

Hazard Statements

Toxic if swallowed
Fatal if inhaled
Causes skin irritation
May cause an allergic skin reaction
Causes serious eye irritation
May cause respiratory irritation
May cause cancer by inhalation
Causes damage to organs through prolonged or repeated exposure

**Precautionary Statements****Prevention**

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Do not breathe dust/fumes/gas/mist/vapours/spray
Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product
Use only outdoors or in a well-ventilated area
Contaminated work clothing should not be allowed out of the workplace
Wear protective gloves/protective clothing/eye protection/face protection
Wear respiratory protection

Response

IF ON SKIN: Wash with plenty of soap and water
IF INHALED: Remove person to fresh air and keep comfortable for breathing
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
Immediately call a POISON CENTER/doctor
Rinse mouth
Take off contaminated clothing and wash it before reuse

Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Beryllium	7440-41-7	> 99

4. First-aid measures

General Advice

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Eye Contact

In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required.
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately.
Most important symptoms/effects	None reasonably foreseeable. May cause allergic skin reaction. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	Dry chemical.
Unsuitable Extinguishing Media	No information available
Flash Point	No information available
Method -	No information available
Autoignition Temperature	Not applicable
Explosion Limits	
Upper	No data available
Lower	No data available
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Keep product and empty container away from heat and sources of ignition.

Hazardous Combustion Products

Beryllium oxide.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health
4

Flammability
0

Instability
0

Physical hazards
N/A

6. Accidental release measures

Personal Precautions	Ensure adequate ventilation. Use personal protective equipment as required. Avoid dust formation. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas.
Environmental Precautions	Should not be released into the environment. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system.
Methods for Containment and Clean Up	Sweep up and shovel into suitable containers for disposal. Avoid dust formation.

7. Handling and storage

Handling	Do not get in eyes, on skin, or on clothing. Wear personal protective equipment/face protection. Avoid dust formation. Use only under a chemical fume hood. Do not breathe
-----------------	--

(dust, vapor, mist, gas). Do not ingest. If swallowed then seek immediate medical assistance.

Storage.

Keep in a dry, cool and well-ventilated place. Keep container tightly closed. Incompatible Materials. Acids. Bases. Halogens. Metals.

8. Exposure controls / personal protection

Exposure Guidelines

Component	Alberta	British Columbia	Ontario TWAEV	Quebec	ACGIH TLV	OSHA PEL	NIOSH
Beryllium	TWA: 0.002 mg/m ³ STEL: 0.01 mg/m ³	TWA: 0.00005 mg/m ³ Skin	TWA: 0.00005 mg/m ³	TWA: 0.00015 mg/m ³	TWA: 0.00005 mg/m ³	(Vacated) TWA: 2 µg/m ³ Ceiling: 2 µg/m ³ (Vacated) STEL: 25 µg/m ³ (Vacated) Ceiling: 5 µg/m ³ TWA: 0.2 µg/m ³ STEL: 2 µg/m ³	IDLH: 4 mg/m ³ Ceiling: 0.0005 mg/m ³

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment**Eye Protection**

Goggles

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	Glove comments
Nitrile rubber	See manufacturers recommendations	-	Splash protection only
Neoprene			
PVC			
Natural rubber			

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Recommended Filter type: Particulates filter conforming to EN 143

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

No information available.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

9. Physical and chemical properties

Physical State	Solid
Appearance	Dark grey
Odor	Odorless
Odor Threshold	No information available
pH	No information available
Melting Point/Range	1278 °C / 2332.4 °F
Boiling Point/Range	2970 °C / 5378 °F @ 5 mmHg
Flash Point	No information available
Evaporation Rate	Not applicable
Flammability (solid,gas)	No information available
Flammability or explosive limits	
Upper	No data available
Lower	No data available
Vapor Pressure	1.85 mmHg
Vapor Density	Not applicable
Specific Gravity	No information available
Bulk Density	1.85 @ 20°C
Solubility	insoluble
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	Not applicable
Decomposition Temperature	No information available
Viscosity	Not applicable
Molecular Formula	Be
Molecular Weight	9.01

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable.
Conditions to Avoid	Incompatible products.
Incompatible Materials	Acids, Bases, Halogens, Metals
Hazardous Decomposition Products	Beryllium oxide
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information**Acute Toxicity****Product Information****Component Information**

Toxicologically Synergistic Products	No information available
--------------------------------------	--------------------------

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation	No information available
Sensitization	May cause sensitization by skin contact

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Beryllium	7440-41-7	Group 1	Known	A1	X	A1
<i>IARC (International Agency for Research on Cancer)</i>			<i>IARC (International Agency for Research on Cancer)</i> <i>Group 1 - Carcinogenic to Humans</i> <i>Group 2A - Probably Carcinogenic to Humans</i> <i>Group 2B - Possibly Carcinogenic to Humans</i>			
<i>NTP: (National Toxicity Program)</i>			<i>NTP: (National Toxicity Program)</i> <i>Known - Known Carcinogen</i> <i>Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen</i>			
<i>ACGIH: (American Conference of Governmental Industrial Hygienists)</i>			<i>A1 - Known Human Carcinogen</i> <i>A2 - Suspected Human Carcinogen</i> <i>A3 - Animal Carcinogen</i> <i>ACGIH: (American Conference of Governmental Industrial Hygienists)</i>			
<i>Mexico - Occupational Exposure Limits - Carcinogens</i>			<i>Mexico - Occupational Exposure Limits - Carcinogens</i> <i>A1 - Confirmed Human Carcinogen</i> <i>A2 - Suspected Human Carcinogen</i> <i>A3 - Confirmed Animal Carcinogen</i> <i>A4 - Not Classifiable as a Human Carcinogen</i> <i>A5 - Not Suspected as a Human Carcinogen</i>			

Mutagenic Effects No information available

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure Respiratory system
STOT - repeated exposure Lungs

Aspiration hazard No information available

Symptoms / effects, both acute and delayed Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

May cause long-term adverse effects in the environment. Do not allow material to contaminate ground water system.

Persistence and Degradability Insoluble in water May persist

Bioaccumulation/ Accumulation No information available.

Mobility Is not likely mobile in the environment due its low water solubility.

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Beryllium - 7440-41-7	-	powder

14. Transport information

<u>DOT</u>	Not regulated
<u>TDG</u>	Not regulated
<u>IATA</u>	Not regulated
<u>IMDG/IMO</u>	Not regulated

15. Regulatory information

International Inventories

Component	CAS-No	DSL	NDSL	TSCA	TSCA Inventory notification - Active-Inactive	EINECS	ELINCS	NLP
Beryllium	7440-41-7	X	-	X	ACTIVE	231-150-7	-	-

Component	CAS-No	IECSC	KECL	ENCS	ISHL	TCSI	AICS	NZIoC	PICCS
Beryllium	7440-41-7	X	KE-02829	X	-	X	X	X	X

Legend:

X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

Canada

SDS in compliance with provisions of information as set out in Canadian Standard - Part 4, Schedule 1 and 2 of the Hazardous Products Regulations (HPR) and meets the requirements of the HPR (Paragraph 13(1)(a) of the Hazardous Products Act (HPA)).

Other International Regulations

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Beryllium	-	Use restricted. See entry 28. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details)	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS-No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Beryllium	7440-41-7	Not applicable	Not applicable	Not applicable	Not applicable

Component	CAS-No	Seveso III Directive (2012/18/EC) - Qualifying Quantities	Seveso III Directive (2012/18/EC) - Qualifying Quantities	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)

		for Major Accident Notification	for Safety Report Requirements		
Beryllium	7440-41-7	Not applicable	Not applicable	Not applicable	Annex I - Y20

16. Other information

Prepared By

Product Safety Department
Email: chem.techinfo@thermofisher.com
www.thermofisher.com

Revision Date

10-September-2024

Print Date

10-September-2024

Revision Summary

New emergency telephone response service provider.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS