

Australian statement of hazardous nature : Classified as hazardous according to criteria of Safe Work Australia

Section 1 - Identification

Product Name	<u>Isooctane</u>
CAS No	540-84-1
Synonyms	2,2,4-Trimethylpentane; Isobutyltrimethylmethane (HPLC/Pesticide/Certified ACS/Spectranalyzed/Optima)

Product Code	O297-4
Address	ThermoFisher Scientific Australia Pty Ltd 5 Caribbean Drive, Scoresby VICTORIA 3179, Australia
Emergency Tel.	CHEMTREC® 03 9757 4559 or +613 9757 4559
Telephone / Fax Numbers	Tel: 1300 735 292 Fax: 1800 067 639
E-mail address	ANZinfo@thermofisher.com

Recommended Use Laboratory chemicals.

Uses advised against This product does not contain any substance(s) on the Illicit Drug Precursors/Reagents list. This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction. This product does not contain any substance(s) listed on the voluntary National Code of Practice for Chemicals of Security Concern.

Section 2 - Hazard(s) Identification

Classification under Safe Work Australia

Classified as hazardous according to criteria of Safe Work Australia

Physical hazards

Flammable liquids

Category 2

Health hazards

Aspiration Toxicity

Category 1

Skin Corrosion/Irritation

Category 2

Specific target organ toxicity - (single exposure)

Category 3

Environmental hazards

Acute aquatic toxicity

Category 1

Chronic aquatic toxicity

Category 1

Label Elements



Flame



Exclamation Mark



Health Hazard



Environment

Signal Word**Danger****Hazard Statements**

H225 - Highly flammable liquid and vapor
 H304 - May be fatal if swallowed and enters airways
 H315 - Causes skin irritation
 H336 - May cause drowsiness or dizziness
 H410 - Very toxic to aquatic life with long lasting effects

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
 P233 - Keep container tightly closed
 P240 - Ground and bond container and receiving equipment
 P241 - Use explosion-proof electrical/ ventilating/ lighting equipment
 P242 - Use non-sparking tools
 P243 - Take action to prevent static discharges
 P264 - Wash face, hands and any exposed skin thoroughly after handling
 P271 - Use only outdoors or in a well-ventilated area
 P280 - Wear protective gloves/protective clothing/eye protection/face protection
 P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor
 P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
 P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
 P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P312 - Call a POISON CENTER or doctor if you feel unwell
 P331 - Do NOT induce vomiting
 P363 - Wash contaminated clothing before reuse
 P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish
 P403 + P233 - Store in a well-ventilated place. Keep container tightly closed
 P501 - Dispose of contents/ container to an approved waste disposal plant

Other information

Section 3 - Composition and Information on Ingredients

Component	CAS No	Weight %
Isooctane	540-84-1	>95

Section 4 - First Aid Measures

Inhalation

Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur. Risk of serious damage to the lungs (by aspiration).

Ingestion

Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.

Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
General Advice	If symptoms persist, call a physician.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.
First Aid Facilities	Eyewash, safety shower and washroom.
Most important symptoms and effects	None reasonably foreseeable. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically. Symptoms may be delayed.

Section 5 - Fire Fighting Measures

Suitable Extinguishing Media

Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

Hazardous Decomposition Products

Carbon monoxide (CO), Carbon dioxide (CO₂).

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air. Do not allow run-off from fire-fighting to enter drains or water courses.

Special protective equipment and precautions for fire fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6 - Accidental Release Measures

Emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

Methods for Containment and Clean Up

Clean-up methods - small spillage

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Clean-up methods - large spillage

Typically only supplied in small quantities as packaged goods.

If extremely toxic or used in larger quantities ensure a spillage action plan is in place. Evacuate area. Control the source and/or contain the spill if safe and able to do so. Use temporary diking, sand bags, dry sand, earth or proprietary booms/absorbent pads if available. Obtain advice on containment, neutralisation and clean-up from local emergency responders.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

Section 7 - Handling and Storage

Precautions for Safe Handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Conditions for Safe Storage, Including any Incompatibilities

Keep away from open flames, hot surfaces and sources of ignition. Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area. Keep away from heat, sparks and flame.

AS/NZS 2243.10:2004, Safety in laboratories - Storage of chemicals

AS 1940-2004 - The storage and handling of flammable and combustible liquids

Section 8 - Exposure Controls and Personal Protection

Exposure limits

ACGIH - Threshold Limit Values - Ceiling (TLV-C) guidelines by the American Conference of Governmental Industrial Hygienists (ACGIH) for controlling worker exposure to airborne chemical concentrations in the workplace.

Component	Australia	New Zealand WEL	ACGIH TLV	The United Kingdom	Germany
Isooctane			TWA: 300 ppm		

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Exposure Controls**Engineering Measures**

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment**Eye Protection**

Wear safety glasses with side shields (or goggles) (Australian/New Zealand Standard AS/NZS 1337 - Eye protectors for Industrial applications)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	AUS/NZ Standard	Glove comments
Nitrile rubber	> 480 minutes	0.3 mm	AS/NZS 2161	As tested under EN374-3 Determination of Resistance to Permeation by Chemicals
Viton (R)	> 480 minutes	0.35 mm		
Neoprene				
Natural rubber				
PVC				
Neoprene gloves	> 480 minutes	0.45 mm		

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger

of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection Long sleeved clothing

Respiratory Protection Use an AS/NZS 1716 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained in line with AS/NZS 1715 on the use and maintenance of respiratory protective devices

Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to EN371 (or AUS/NZ equivalent)

Recommended half mask:- Valve filtering: EN405 or Half mask: EN140 plus filter, EN 371 (or AUS/NZ equivalent)

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls Prevent product from entering drains. Do not allow material to contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained.

Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	Colorless	
Physical State	Liquid	
Odor	Petroleum distillates	
Odor Threshold	No data available	
pH	Not applicable	
Melting Point/Range	-107 °C / -160.6 °F	
Softening Point	No data available	
Boiling Point/Range	98 - 99 °C / 208.4 - 210.2 °F	@ 760 mmHg
Flash Point	-12 °C / 10.4 °F	Method - No information available
Evaporation Rate	No data available	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	Lower 1.1 vol % Upper 6 vol %	
Vapor Pressure	51 mbar @ 20 °C	
Vapor Density	3.94	(Air = 1.0)
Specific Gravity / Density	0.690	
Bulk Density	Not applicable	Liquid
Water Solubility	Immiscible	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Autoignition Temperature	410 °C / 770 °F	
Decomposition Temperature	No data available	
Viscosity	0.51 mPa s at 22 °C	
Explosive Properties		Vapors may form explosive mixtures with air
Oxidizing Properties	No information available	
Other information		
Molecular Formula	C8 H18	
Molecular Weight	114.23	

Section 10 - Stability and Reactivity

Reactivity None known, based on information available

Stability Stable under normal conditions.

Conditions to Avoid	Incompatible products, Heat, flames and sparks, Keep away from open flames, hot surfaces and sources of ignition.
Incompatible Materials	Strong oxidizing agents, Strong acids, Strong bases.
Hazardous Decomposition Products	Carbon monoxide (CO). Carbon dioxide (CO ₂).
Hazardous Polymerization	Hazardous polymerization does not occur.

Section 11 - Toxicological Information

Information on Toxicological Effects

Product Information

(a) acute toxicity;	
Oral	Based on available data, the classification criteria are not met
Dermal	Based on available data, the classification criteria are not met
Inhalation	Based on available data, the classification criteria are not met

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Isooctane	LD50 5000 mg/kg (Rat)	2000 mg/kg (Rabbit)	LC50 = 33.52 mg/L (Rat) 4 h

(b) skin corrosion/irritation;	Category 2
(c) serious eye damage/irritation;	Based on available data, the classification criteria are not met
(d) respiratory or skin sensitization;	
Respiratory	Based on available data, the classification criteria are not met
Skin	Based on available data, the classification criteria are not met
(e) germ cell mutagenicity;	Based on available data, the classification criteria are not met
(f) carcinogenicity;	Based on available data, the classification criteria are not met There are no known carcinogenic chemicals in this product
(g) reproductive toxicity;	Based on available data, the classification criteria are not met
(h) STOT-single exposure;	Category 3
Effective dose	NOAEL 2220 ppm 6hr/day
Results / Target organs	Central nervous system (CNS)
(i) STOT-repeated exposure;	Based on available data, the classification criteria are not met
Target Organs	None known.
(j) aspiration hazard;	Category 1
Other Adverse Effects	The toxicological properties have not been fully investigated.
Symptoms / effects, both acute and delayed	Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Section 12 - Ecological Information

Ecotoxicity effects

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Isooctane	LC50 = 0.11 mg/l, 96h, (Rainbow trout)	EC50= 0.4 mg/l, 48h (Daphnia magna)	EC50= 2.94 mg/l, 72h	

Persistence and Degradability

Persistence

Insoluble in water, Persistence is unlikely, based on information available, Immiscible with water.

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

Bioaccumulative Potential

May have some potential to bioaccumulate

Bioconcentration factor (BCF)

231

Mobility

Spillage unlikely to penetrate soil. The product is insoluble and floats on water. The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility: Is not likely mobile in the environment due its low water solubility

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

Persistent Organic Pollutant

This product does not contain any known or suspected substance

Ozone Depletion Potential

This product does not contain any known or suspected substance

Section 13 - Disposal Considerations

Waste from Residues/Unused Products

Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with all federal, E.P.A., state and local regulations. Assure conformity with all applicable regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

Other Information

Chemical wastes should be disposed through a licensed commercial waste collection service. Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not let this chemical enter the environment. Do not empty into drains.

Section 14 - Transport Information

IMDG/IMO

UN-No UN1262
 Proper Shipping Name OCTANES
 Hazard Class 3
 Packing Group II

Component	IMDG Marine Pollutant
Isooctane 540-84-1 (>95)	IMDG regulated marine pollutant (Listed in the index) IMDG regulated marine pollutant (UN1262)

ADG

UN-No UN1262
 Proper Shipping Name OCTANES
 Hazard Class 3
 Packing Group II

IATA

UN-No UN1262
Proper Shipping Name OCTANES
Hazard Class 3
Packing Group II

Environmental hazards Dangerous for the environment
Product is a marine pollutant according to the criteria set by IMDG/IMO

Special Precautions No special precautions required

Additional information None known

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National Regulations Australia

See section 8 for national exposure control parameters.

Standard for the Uniform Scheduling of Medicines and Poisons

No poison schedule number allocated.

Australian Industrial Chemicals Introduction Scheme (AICIS)

Component	Australian Industrial Chemicals Introduction Scheme (AICIS)	Additional information
Isooctane - 540-84-1	Present	-

Australian - Illicit Drug Precursors/Reagents Substance List

This product does not contain any substance(s) on the Illicit Drug Precursors/Reagents list.

Chemicals of Security Concern

This product does not contain any substance(s) listed on the voluntary National Code of Practice for Chemicals of Security Concern

National pollutant inventory Not applicable

Prohibition or notification/licensing requirements

Shown below are details of specific prohibition/notifications or licencing requirements when they apply.

This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction.

International Inventories

Component	AICS	NZIoC	EINECS	ELINCS	TSCA	DSL	NDSL	PICCS	ENCS	ISHL	IECSC	KECL
Isooctane	X	X	208-759-1	-	X	X	-	X	X	X	X	KE-34634

Legend: X - Listed. '-' - Not Listed. **KECL** - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

International Regulations

Ozone Depletion Potential This product does not contain any known or suspected substance

Persistent Organic Pollutant This product does not contain any known or suspected substance

Rotterdam Convention (PIC) Not applicable

MARPOL - International Convention for the Prevention of Pollution from Ships

Component	IMDG Marine Pollutant
Isooctane - 540-84-1	IMDG regulated marine pollutant (Listed in the index) IMDG regulated marine pollutant (UN1262)

Basel convention on the control of transboundary movements of hazardous wastes and their disposal
Not applicable.

Component	CAS No	OECD HPV	Restriction of Hazardous Substances (RoHS)	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Isooctane	540-84-1	Listed	Not applicable	Not applicable	Not applicable

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Isooctane	-	Use restricted. See item 75. (see link for restriction details)	-

<https://echa.europa.eu/substances-restricted-under-reach>

Section 16 - Other Information

Legend

AICS - Australian Inventory of Chemical Substances
TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List
IECSC - Chinese Inventory of Existing Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
TWA - Time Weighted Average
IARC - International Agency for Research on Cancer
ICAO/IATA - International Civil Aviation Organization/International Air Transport Association
MARPOL - International Convention for the Prevention of Pollution from Ships
NZS 5433:2012 - Transport of Dangerous Goods on Land
LD50 - Lethal Dose 50%
EC50 - Effective Concentration 50%
WEL - Workplace Exposure Limit

NZIoC - New Zealand Inventory of Chemicals
EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
ENCS - Japanese Existing and New Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
CAS - Chemical Abstracts Service
ACGIH - American Conference of Governmental Industrial Hygienists
PNEC - Predicted No Effect Concentration
IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code
ADG Australian Code for the Transport of Dangerous Goods by Road and Rail
OECD - Organisation for Economic Co-operation and Development
LC50 - Lethal Concentration 50%
ATE - Acute Toxicity Estimate
RPE - Respiratory Protective Equipment

DNEL - Derived No Effect Level

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

VOC - (Volatile Organic Compound)

NOEC - No Observed Effect Concentration
231

PBT - Persistent, Bioaccumulative, Toxic

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Training Advice

Chemical incident response training.

Revision Date

21-Nov-2022

Revision Summary

Not applicable.

This Safety Data Sheet (SDS) is prepared in accordance to and complies with the requirements of Safe Work Australia - Work Health and Safety Regulations (WHS Regulations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet