

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product Identifier

Product Description: m-Xylene
Cat No. : C18086
Synonyms 1,3-Dimethylbenzene
CAS No 108-38-3
Molecular Formula C8 H10

Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

Details of the supplier of the safety data sheet

Importer Fisher Scientific Korea D5,D6, Incheon Airport Logistics Complex 150, Gonghangdong-Ro 296 Beon-Gil Jung-Gu, Incheon Tel: +82-1661-9555 Fax: +82-2-2023-0603	Supplier Thermo Fisher Scientific Chemicals, Inc. 30 Bond Street Ward Hill, MA 01835-8099
---	---

E-mail address Chem.KR@thermofisher.com

Emergency Telephone Number

Emergency telephone: Medical: +(82) 070-7686-0086 or + 1-703-741-5970
 CHEMTREC: 080 822 1374 (Local), CHEMTREC: 1-800-424-9300 or + 1-703-527-3887
 Korea: 00-308-13-2549 (24 hours a day, 7 days a week)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture
Physical hazards

Flammable liquids Category 3

Health hazards

Acute Dermal Toxicity	Category 4
Acute Inhalation Toxicity - Vapors	Category 4
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Specific target organ toxicity - (single exposure)	Category 3
Specific target organ toxicity - (repeated exposure)	Category 1

Environmental hazards

Based on available data, the classification criteria are not met

SAFETY DATA SHEET

m-Xylene

Revision Date 12-Jun-2024

Label Elements



Signal Word

Danger

Hazard Statements

H226 - Flammable liquid and vapor
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H372 - Causes damage to organs through prolonged or repeated exposure
H312 + H332 - Harmful in contact with skin or if inhaled

Precautionary Statements

Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P233 - Keep container tightly closed
P240 - Ground and bond container and receiving equipment
P241 - Use explosion-proof electrical/ ventilating/ lighting equipment
P242 - Use non-sparking tools
P243 - Take action to prevent static discharges
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray
P271 - Use only outdoors or in a well-ventilated area
P260 - Do not breathe dust/fume/gas/mist/vapors/spray
P264 - Wash face, hands and any exposed skin thoroughly after handling
P270 - Do not eat, drink or smoke when using this product

Response

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P337 + P313 - If eye irritation persists: Get medical advice/attention
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction
P312 - Call a POISON CENTER or doctor if you feel unwell
P321 - Specific treatment (see supplemental first aid instructions on this label)
P322 - Specific measures (see supplemental first aid instructions on this label)
P362 + P364 - Take off contaminated clothing and wash it before reuse
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P332 + P313 - If skin irritation occurs: Get medical advice/attention
P314 - Get medical advice/attention if you feel unwell

Storage

P403 + P235 - Store in a well-ventilated place. Keep cool
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed
P405 - Store locked up

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other Hazards

SAFETY DATA SHEET

m-Xylene

Revision Date 12-Jun-2024

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

NFPA

Health
3

Flammability
3

Instability
0

Physical hazards
N/A

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Component	Common Name	CAS No	Index No	Weight %
m-Xylene	1,3-Dimethylbenzene	108-38-3	KE-35428	99 - 100

SECTION 4: FIRST AID MEASURES

Description of first aid measures

General Advice

If symptoms persist, call a physician.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.

Ingestion

Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur. Risk of serious damage to the lungs (by aspiration).

Self-Protection of the First Aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

None reasonably foreseeable. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media

Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Water may be ineffective. Do not use a solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

SAFETY DATA SHEET

m-Xylene

Revision Date 12-Jun-2024

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂).

Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental precautions

Do not flush into surface water or sanitary sewer system.

Methods and Material for Containment and Cleaning Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges.

Conditions for Safe Storage, Including any Incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area. Keep away from heat, sparks and flame.

Specific End Uses

Use in laboratories.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	CAS No	Korea	ACGIH TLV	OSHA PEL
m-Xylene	108-38-3	STEL: 150 ppm TWA: 100 ppm	TWA: 20 ppm	Not listed

Component	CAS No	European Union	The United Kingdom	Germany
m-Xylene	108-38-3	TWA: 50 ppm (8h) TWA: 221 mg/m ³ (8h) STEL: 100 ppm (15min) STEL: 442 mg/m ³ (15min) Skin	STEL: 100 ppm 15 min STEL: 441 mg/m ³ 15 min TWA: 50 ppm 8 hr TWA: 220 mg/m ³ 8 hr Skin	TWA: 100 ppm (8 Stunden). AGW - exposure factor 2 TWA: 440 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 50 ppm (8 Stunden). MAK all isomers

SAFETY DATA SHEET

m-Xylene

Revision Date 12-Jun-2024

				TWA: 220 mg/m ³ (8 Stunden). MAK all isomers Höhepunkt: 100 ppm Höhepunkt: 440 mg/m ³ Haut Haut all isomers
--	--	--	--	---

ACGIH - Biological Exposure Indices

Component	CAS No	ACGIH - Biological Exposure Indices
m-Xylene	108-38-3	1.5 g/g creatinine Medium: urine Time: end of shift Determinant: Methylhippuric acids

Exposure Controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles

Hand Protection

Protective gloves

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Personal protective equipment

Respiratory Protection

Use only those certified by the Korea Occupational Safety and Health Administration.

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators

Recommended Filter type:

Organic gases and vapours filter Type A Brown conforming to EN14387

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

When RPE is used a face piece Fit Test should be conducted

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice

Environmental exposure controls

Prevent product from entering drains Do not allow material to contaminate ground water system

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance (Physical State, Color, etc.) Colorless Liquid

Odor

aromatic

Odor Threshold

No data available

pH

No information available

SAFETY DATA SHEET

m-Xylene

Revision Date 12-Jun-2024

Melting Point/Range -48 °C / -54.4 °F
Softening Point No data available
Boiling Point/Range 138 - 139 °C / 280.4 - 282.2 °F
Flash Point 25 °C / 77 °F **Method** - No information available

Evaporation Rate 0.7 (Ether = 1.0)
Flammability (solid,gas) Not applicable Liquid
Explosion Limits **Lower** 1.7 Vol%
Upper 7.6 Vol%

Vapor Pressure 8 mbar @ 20 °C
Vapor Density 3.66 (Air = 1.0)
Specific Gravity / Density 0.864
Bulk Density Not applicable Liquid
Water Solubility Insoluble
Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Component	CAS No	log Pow
m-Xylene	108-38-3	3.2

Autoignition Temperature 465 °C / 869 °F
Decomposition Temperature No data available
Viscosity 0.62 mPa.s at 20 °C
Explosive Properties explosive air/vapour mixtures possible
Oxidizing Properties No information available

Molecular Formula C8 H10
Molecular Weight 106.17

SECTION 10: STABILITY AND REACTIVITY

Reactivity None known, based on information available

Chemical Stability Stable under normal conditions.

Possibility of Hazardous Reactions

Hazardous Polymerization Hazardous polymerization does not occur.
Hazardous Reactions None under normal processing.

Conditions to Avoid Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials Strong oxidizing agents. Strong acids.

Hazardous Decomposition Products

SAFETY DATA SHEET

m-Xylene

Revision Date 12-Jun-2024

Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

Information on expected route of exposure

Inhalation Not an expected route of exposure.
Ingestion May be harmful if swallowed. Harmful if swallowed. Potential for aspiration if swallowed.
Eyes Avoid contact with eyes. Irritating to eyes.
Skin Avoid contact with skin. May cause irritation. Harmful in contact with skin.

Information on Health Hazards

(a) acute toxicity;

Oral Based on available data, the classification criteria are not met
Dermal Category 4
Inhalation Category 4

Component	CAS No	LD50 Oral	LD50 Dermal	LC50 Inhalation
m-Xylene	108-38-3	LD50 = 5 g/kg (Rat)	LD50 = 12.18 g/kg (Rabbit)	LC50 = 27124 mg/m ³ (Rat) 4 h

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;

Respiratory No data available
Skin No data available

Component	CAS No	Test method	Test species	Study result
m-Xylene	108-38-3	No data available	No data available	No data available

(e) germ cell mutagenicity; No data available

Component	CAS No	Test method	Test species	Study result
m-Xylene	108-38-3	No data available	No data available	No data available

(f) carcinogenicity; No data available

Component	CAS No	Test method	Test species / Duration	Study result
m-Xylene	108-38-3	No data available	No data available	No data available

There are no known carcinogenic chemicals in this product

Component	CAS No	IARC	NTP	ACGIH	OSHA	UK
m-Xylene	108-38-3	Not listed	Not listed	Not listed	Not listed	Not listed

(g) reproductive toxicity; No data available

Component	CAS No	Test method	Test species / Duration	Study result
-----------	--------	-------------	-------------------------	--------------

SAFETY DATA SHEET

m-Xylene

Revision Date 12-Jun-2024

m-Xylene	108-38-3	No data available	No data available	No data available
----------	----------	-------------------	-------------------	-------------------

(h) STOT-single exposure;
Results / Target organs

Category 3
Respiratory system.

(i) STOT-repeated exposure;
Target Organs

Category 1
None known.

(j) aspiration hazard;

No data available

Other Adverse Effects

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Component	CAS No	EU - Endocrine Disrupters Candidate List	EU - Endocrine Disruptors - Evaluated Substances	Japan - Endocrine Disruptor Information
m-Xylene	108-38-3	Not applicable	Not applicable	Not applicable

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity effects

The product contains following substances which are hazardous for the environment. Contains a substance which is: Toxic to aquatic organisms.

Component	CAS No	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
m-Xylene	108-38-3	LC50: = 12.9 mg/L, 96h semi-static (Poecilia reticulata) LC50: 14.3 - 18 mg/L, 96h flow-through (Pimephales promelas) LC50: = 8.4 mg/L, 96h semi-static (Oncorhynchus mykiss)	EC50: 2.81 - 5.0 mg/L, 48h Static (Daphnia magna)	EC50: = 4.9 mg/L, 72h static (Pseudokirchneriella subcapitata)	EC50 = 0.0084 mg/L 24 h

Persistence and degradability

Persistence

Degradation in sewage treatment plant

Expected to be biodegradable

Persistence is unlikely.

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
m-Xylene	3.2	No data available

Mobility in soil

The product is insoluble and floats on water The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces Spillage unlikely to penetrate soil Will likely be mobile in the environment due to its volatility. Is not likely mobile in the environment due its low water solubility.

Ozone Depletion Potential

Component	CAS No	Ozone Depletion Potential
m-Xylene	108-38-3	Not listed

Other adverse effects

No information available

ALFAAC18086

SAFETY DATA SHEET

m-Xylene

Revision Date 12-Jun-2024

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose in accordance with the Wastes Control Act (폐기물관리법).

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

Other Information

Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not let this chemical enter the environment. Do not empty into drains.

SECTION 14: TRANSPORT INFORMATION

Road and Rail Transport

UN-No UN1307
Proper Shipping Name XYLENES
Hazard Class 3
Packing Group III

IATA

UN-No UN1307
Proper Shipping Name XYLENES
Hazard Class 3
Packing Group III

IMDG/IMO

UN-No UN1307
Proper Shipping Name XYLENES
Hazard Class 3
Packing Group III
Marine Pollutant No hazards identified

Special Precautions for User

No special precautions required

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Legend: X - Listed '-' - Not Listed

International Inventories

Component	CAS No	KECL	TSCA	EINECS	IECSC	DSL	NDSL	PICCS	ENCS	ISHL	AICS
m-Xylene	108-38-3	KE-35428	X	203-576-3	X	X	-	X	X	X	X

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
m-Xylene	108-38-3	Not applicable	Not applicable	Not applicable	Not applicable

SAFETY DATA SHEET

m-Xylene

Revision Date 12-Jun-2024

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential
m-Xylene	108-38-3	Listed	Not applicable	Not applicable

Korean National Regulations

Component	CAS No	Act on Registration and Evaluation of Chemical Substances (K-REACH)	Authorised Chemicals	Existing Substances Subject to Registration
m-Xylene	108-38-3	Annex 1 - KE-35428	Not applicable	Listed

Component	CAS No	Chemical Control Act - Toxic Chemicals	Chemical Control Act - Prohibited Chemicals	Chemical Control Act - Use Restricted Chemicals
m-Xylene	108-38-3	1997-1-0275 (>85%)	Not applicable	Not applicable

Component	CAS No	Chemical Control Act - Accident Precaution Chemicals (% in mixtures)	Chemical Control Act - Accident Precaution Chemicals - Quantity limits Storage (% in mixtures)	Chemical Control Act - Accident Precaution Chemicals - Quantity limits Manufacture/Use (% in mixtures)
m-Xylene	108-38-3	Not applicable	Not applicable	Not applicable

Component	CAS No	Waste Control Law	Ministry of Environment - CMR risk	Ministry of Environment - Critically Controlled Substance
m-Xylene	108-38-3	> 85% (CCA)	Not applicable	STOT

CCA = Chemical Control Act

Component	CAS No	ISHA - Harmful Agents Subject to Work Environment Monitoring	ISHA - Prohibited substances	ISHA - Substances requiring permission
m-Xylene	108-38-3	Listed	Not applicable	Not applicable

Component	CAS No	ISHA - Substances subject to control	ISHA - Harmful Agents Requiring Health Examination	ISHA - Permissible Exposure Limits
m-Xylene	108-38-3	Listed	Listed	Not applicable

Component	CAS No	ISHA - Subject to Process Safety Reports (minimum quantity)	ISHA - Threshold Limit Values (TLVs) Chemicals	ISHA - Special management materials
m-Xylene	108-38-3	5000 kg	STEL: 150 ppm TWA: 100 ppm	Not applicable

National Fire Association - Dangerous Substances Minimum quantity requiring a permit

Component	CAS No	Class 1 - Oxidising solids	Class 2 - Flammable solid	Class 3 - Spontaneously Combustible Substances and Dangerous Substances When Wet	Class 4 - Flammable liquids	Class 5 - Self-reactive substances	Class 6 - Oxidising liquids
m-Xylene	108-38-3	Not applicable	Not applicable	Not applicable	4. Group 2 Petroleum (Insoluble) 1000 L	Not applicable	Not applicable

Control Parameters

ALFAAC18086

SAFETY DATA SHEET

m-Xylene

Revision Date 12-Jun-2024

Component	CAS No	Korea	ACGIH - Biological Exposure Indices
m-Xylene	108-38-3	STEL: 150 ppm TWA: 100 ppm	1.5 g/g creatinine Medium: urine Time: end of shift Determinant: Methylhippuric acids

US Management Information

OSHA - Occupational Safety and Health Administration

Not applicable

Component	CAS No	Specifically Regulated Chemicals	Highly Hazardous Chemicals
m-Xylene	108-38-3	Not applicable	Not applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355)

Component	CAS No	CERCLA Extremely Hazardous Substances RQs	Hazardous Substances RQs	SARA 313 - Threshold Values %
m-Xylene	108-38-3	Not applicable	1000 lb	1.0 %

GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Danger.

H226 - Flammable liquid and vapor. H304 - May be fatal if swallowed and enters airways. H315 - Causes skin irritation. H319 - Causes serious eye irritation. H312 + H332 - Harmful in contact with skin or if inhaled. H335 - May cause respiratory irritation. H412 - Harmful to aquatic life with long lasting effects.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P280 - Wear protective gloves/protective clothing/eye protection/face protection.

SECTION 16: OTHER INFORMATION

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

POW - Partition coefficient Octanol:Water

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

SAFETY DATA SHEET

m-Xylene

Revision Date 12-Jun-2024

OECD - Organisation for Economic Co-operation and Development
BCF - Bioconcentration factor

ATE - Acute Toxicity Estimate
VOC - (Volatile Organic Compound)

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Prepared By	Health, Safety and Environmental Department
Creation Date	26-Sep-2009
Revision Date	12-Jun-2024
Revision Number	2
Revision Summary	New emergency telephone response service provider.

MOEL's Public Notice No. 2023-9 (Standards for Classification and Labeling of Chemical Substances and Safety Data Sheets)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet