

Creation Date 10-Jun-2024

Revision Date 10-Jun-2024

Revision Number 1

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**1.1. Product identifier**

Product Description: **Aluminum Etch 80-15-3-2, VLSI electronic grade**
Cat No. : **S60413**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet**Company**

Thermo Fisher (Kandel) GmbH
Erlenbachweg 2, 76870 Kandel, Germany
Tel: +49 (0) 721 84007 280
Fax: +49 (0) 721 84007 300

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
<https://www.fishersci.ch/ch/en/customer-help-support/forms/email-us.html>

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

SECTION 2: HAZARDS IDENTIFICATION**2.1. Classification of the substance or mixture**

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

SAFETY DATA SHEET

Aluminum Etch 80-15-3-2, VLSI electronic grade

Revision Date 10-Jun-2024

Substances/mixtures corrosive to metal

Category 1 (H290)

Health hazards

Acute oral toxicity

Category 4 (H302)

Acute Inhalation Toxicity - Vapors

Category 4 (H332)

Skin Corrosion/Irritation

Category 1 (H314) A

Serious Eye Damage/Eye Irritation

Category 1 (H318)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H290 - May be corrosive to metals

H314 - Causes severe skin burns and eye damage

H302 + H332 - Harmful if swallowed or if inhaled

Precautionary Statements

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/physician

2.3. Other hazards

This product does not contain any known or suspected endocrine disruptors

Toxic to terrestrial vertebrates

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Phosphoric acid	7664-38-2	EEC No. 231-633-2	75	Met. Corr. 1 (H290) Acute Tox. 4 (H302) Skin Corr. 1B (H314)

SAFETY DATA SHEET

Aluminum Etch 80-15-3-2, VLSI electronic grade

Revision Date 10-Jun-2024

				Eye Dam. 1 (H318)
Water	7732-18-5	231-791-2	12	-
Acetic acid	64-19-7	200-580-7	10	Flam. Liq. 3 (H226) Skin Corr. 1A (H314) Eye Dam. 1 (H318)
Nitric acid	7697-37-2	231-714-2	3	Ox. Liq. 2 (H272) Met. Corr. 1 (H290) Acute Tox. 1 (H330) Skin Corr. 1A (H314) Eye Dam. 1 (H318) (EUH071)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Phosphoric acid	Skin Corr. 1B :: C>=25% Eye Irrit. 2 :: 10%<=C<25% Skin Irrit. 2 :: 10%<=C<25%	-	-
Acetic acid	Skin Corr. 1A (H314) :: C>=90% Skin Corr. 1B (H314) :: 25%<=C<90% Eye Irrit. 2 (H319) :: 10%<=C<25% Skin Irrit. 2 (H315) :: 10%<=C<25%	-	-
Nitric acid	Ox. Liq. 2 :: C>=99% Ox. Liq. 3 :: 65%<=C<99% Acute Tox. 1 (inhal) :: C>=70% Acute Tox. 3 (inhal) :: 70%>C>=26.5% Acute Tox. 4 (inhal) :: 26.5%>C>=13.25% Skin Corr. 1A :: C>=20% Skin Corr. 1B :: 5%<=C<20% Met. Corr. 1 :: C>=2% EUH071 :: C>=20%	-	-

Component	ECHA (RAC) ATE (Oral)	ECHA (RAC) ATE (Dermal)	ECHA (RAC) ATE (Inhalation)
Nitric acid	-	-	ATE = 2.65 mg/L (vapours)

ECHA (RAC) - Committee for Risk Assessment - European CHemicals Agency
ATE - Acute Toxicity Estimate

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately.
Ingestion	Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately.
Inhalation	If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration

SAFETY DATA SHEET

Aluminum Etch 80-15-3-2, VLSI electronic grade

Revision Date 10-Jun-2024

with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately.

Self-Protection of the First Aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes.

Hazardous Combustion Products

Oxides of phosphorus, Nitrogen oxides (NO_x), Carbon oxides.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

6.2. Environmental precautions

Should not be released into the environment.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SAFETY DATA SHEET

Aluminum Etch 80-15-3-2, VLSI electronic grade

Revision Date 10-Jun-2024

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Corrosives area. Keep containers tightly closed in a dry, cool and well-ventilated place.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Storage Class/LGK 8B

Switzerland - Storage of hazardous substances

Storage class - SC 8 (Acid)
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Phosphoric acid	TWA: 1 mg/m ³ (8h) STEL: 2 mg/m ³ (15min)	STEL: 2 mg/m ³ TWA: 1 mg/m ³	TWA / VME: 0.2 ppm (8 heures). indicative limit TWA / VME: 1 mg/m ³ (8 heures). indicative limit STEL / VLCT: 0.5 ppm. indicative limit STEL / VLCT: 2 mg/m ³ . indicative limit	TWA: 1 mg/m ³ 8 uren STEL: 2 mg/m ³ 15 minuten	STEL / VLA-EC: 2 mg/m ³ (15 minutos). TWA / VLA-ED: 1 mg/m ³ (8 horas)
Acetic acid	TWA: 25 mg/m ³ (8h) TWA: 10 ppm (8h) STEL: 50 mg/m ³ (15min) STEL: 20 ppm (15min)	STEL: 37 mg/m ³ STEL: 15 ppm TWA: 10 ppm TWA: 25 mg/m ³	TWA / VME: 10 ppm (8 heures). TWA / VME: 25 mg/m ³ (8 heures). STEL / VLCT: 20 ppm. indicative limit STEL / VLCT: 50 mg/m ³ . indicative limit	TWA: 10 ppm 8 uren TWA: 25 mg/m ³ 8 uren STEL: 15 ppm 15 minuten STEL: 38 mg/m ³ 15 minuten	STEL / VLA-EC: 20 ppm (15 minutos). STEL / VLA-EC: 50 mg/m ³ (15 minutos). TWA / VLA-ED: 10 ppm (8 horas) TWA / VLA-ED: 25 mg/m ³ (8 horas)
Nitric acid	STEL: 1 ppm (15min) STEL: 2.6 mg/m ³	STEL: 1 ppm 15 min STEL: 2.6 mg/m ³ 15 min	STEL / VLCT: 1 ppm. indicative limit	STEL: 1 ppm 15 minuten	STEL / VLA-EC: 1 ppm (15 minutos).

SAFETY DATA SHEET

Aluminum Etch 80-15-3-2, VLSI electronic grade

Revision Date 10-Jun-2024

	(15min)		STEL / VLCT: 2.6 mg/m ³ . indicative limit	STEL: 2.6 mg/m ³ 15 minuten	STEL / VLA-EC: 2.6 mg/m ³ (15 minutos).
--	---------	--	---	--	--

Component	Italy	Germany	Portugal	The Netherlands	Finland
Phosphoric acid	TWA: 1 mg/m ³ 8 ore. Time Weighted Average STEL: 2 mg/m ³ 15 minuti. Short-term	TWA: 2 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 2 mg/m ³ (8 Stunden). MAK Höhepunkt: 4 mg/m ³	STEL: 2 mg/m ³ 15 minutos TWA: 1 mg/m ³ 8 horas	STEL: 2 mg/m ³ 15 minuten TWA: 1 mg/m ³ 8 uren	TWA: 1 mg/m ³ 8 tunteina STEL: 2 mg/m ³ 15 minuutteina
Acetic acid	TWA: 25 ppm 8 ore. Time Weighted Average TWA: 10 mg/m ³ 8 ore. Time Weighted Average STEL: 50 mg/m ³ 15 minuti. Short-term STEL: 20 ppm 15 minuti. Short-term	TWA: 10 ppm (8 Stunden). AGW - exposure factor 2 TWA: 25 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 10 ppm (8 Stunden). MAK TWA: 25 mg/m ³ (8 Stunden). MAK Höhepunkt: 20 ppm Höhepunkt: 50 mg/m ³	STEL: 20 ppm 15 minutos STEL: 50 mg/m ³ 15 minutos TWA: 10 ppm 8 horas TWA: 25 mg/m ³ 8 horas	MAC-TGG 25 mg/m ³	TWA: 5 ppm 8 tunteina TWA: 13 mg/m ³ 8 tunteina STEL: 10 ppm 15 minuutteina STEL: 25 mg/m ³ 15 minuutteina
Nitric acid	STEL: 1 ppm 15 minuti. Short-term STEL: 2.6 mg/m ³ 15 minuti. Short-term	TWA: 1 ppm (8 Stunden). AGW - TWA: 2.6 mg/m ³ (8 Stunden). AGW -	STEL: 1 ppm 15 minutos STEL: 2.6 mg/m ³ 15 minutos TWA: 2 ppm 8 horas	STEL: 1.3 mg/m ³ 15 minuten	TWA: 0.5 ppm 8 tunteina TWA: 1.3 mg/m ³ 8 tunteina STEL: 1 ppm 15 minuutteina STEL: 2.6 mg/m ³ 15 minuutteina

Component	Austria	Denmark	Switzerland	Poland	Norway
Phosphoric acid	MAK-KZGW: 2 mg/m ³ 15 Minuten MAK-TMW: 1 mg/m ³ 8 Stunden	TWA: 1 mg/m ³ 8 timer STEL: 2 mg/m ³ 15 minutter	STEL: 4 mg/m ³ 15 Minuten TWA: 2 mg/m ³ 8 Stunden	STEL: 2 mg/m ³ 15 minutach TWA: 1 mg/m ³ 8 godzinach	TWA: 1 mg/m ³ 8 timer STEL: 3 mg/m ³ 15 minutter. value calculated
Acetic acid	MAK-KZGW: 20 ppm 15 Minuten MAK-KZGW: 50 mg/m ³ 15 Minuten MAK-TMW: 10 ppm 8 Stunden MAK-TMW: 25 mg/m ³ 8 Stunden	TWA: 10 ppm 8 timer TWA: 25 mg/m ³ 8 timer STEL: 50 mg/m ³ 15 minutter STEL: 20 ppm 15 minutter	STEL: 20 ppm 15 Minuten STEL: 50 mg/m ³ 15 Minuten TWA: 10 ppm 8 Stunden TWA: 25 mg/m ³ 8 Stunden	STEL: 50 mg/m ³ 15 minutach TWA: 25 mg/m ³ 8 godzinach	TWA: 10 ppm 8 timer TWA: 25 mg/m ³ 8 timer STEL: 20 ppm 15 minutter. value from the regulation STEL: 50 mg/m ³ 15 minutter. value from the regulation
Nitric acid	MAK-KZGW: 1 ppm 15 Minuten MAK-KZGW: 2.6 mg/m ³ 15 Minuten	STEL: 1 ppm 15 minutter STEL: 2.6 mg/m ³ 15 minutter	STEL: 2 ppm 15 Minuten STEL: 5 mg/m ³ 15 Minuten TWA: 2 ppm 8 Stunden TWA: 5 mg/m ³ 8 Stunden	STEL: 2.6 mg/m ³ 15 minutach TWA: 1.4 mg/m ³ 8 godzinach	TWA: 2 ppm 8 timer TWA: 5 mg/m ³ 8 timer STEL: 4 ppm 15 minutter. value calculated STEL: 10 mg/m ³ 15 minutter. value calculated

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Phosphoric acid	TWA: 1.0 mg/m ³ STEL : 2.0 mg/m ³	TWA-GVI: 1 mg/m ³ 8 satima. STEL-KGVI: 2 mg/m ³ 15 minutama.	TWA: 1 mg/m ³ 8 hr. STEL: 2 mg/m ³ 15 min	STEL: 2.0 mg/m ³ TWA: 1 mg/m ³	TWA: 1 mg/m ³ 8 hodinách. Ceiling: 2 mg/m ³
Acetic acid	TWA: 25 mg/m ³ TWA: 10 ppm STEL : 50 mg/m ³ STEL : 20 ppm	TWA-GVI: 10 ppm 8 satima. TWA-GVI: 25 mg/m ³ 8 satima. STEL-KGVI: 20 ppm 15 minutama. STEL-KGVI: 50 mg/m ³ 15 minutama.	TWA: 20 ppm 8 hr. TWA: 50 mg/m ³ 8 hr. STEL: 20 ppm 15 min STEL: 50 mg/m ³ 15 min	STEL: 50 mg/m ³ STEL: 20 ppm TWA: 10 ppm TWA: 25 mg/m ³	TWA: 25 mg/m ³ 8 hodinách. Ceiling: 50 mg/m ³
Nitric acid	STEL : 1 ppm STEL : 2.6 mg/m ³	STEL-KGVI: 1 ppm 15 minutama.	STEL: 1 ppm 15 min STEL: 2.6 mg/m ³ 15 min	STEL: 1 ppm STEL: 2.6 mg/m ³	TWA: 1 mg/m ³ 8 hodinách.

SAFETY DATA SHEET

Aluminum Etch 80-15-3-2, VLSI electronic grade

Revision Date 10-Jun-2024

		STEL-KGVI: 2.6 mg/m ³ 15 minutama.			Ceiling: 2.5 mg/m ³
--	--	--	--	--	--------------------------------

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Phosphoric acid	TWA: 1 mg/m ³ 8 tundides. vapor STEL: 2 mg/m ³ 15 minutites. vapor	TWA: 1 mg/m ³ 8 hr STEL: 2 mg/m ³ 15 min	STEL: 3 mg/m ³ TWA: 1 mg/m ³	STEL: 2 mg/m ³ 15 percekben. CK TWA: 1 mg/m ³ 8 órában. AK	STEL: 2 mg/m ³ TWA: 1 mg/m ³ 8 klukkustundum.
Acetic acid	TWA: 10 ppm 8 tundides. TWA: 25 mg/m ³ 8 tundides. STEL: 10 ppm 15 minutites. STEL: 25 mg/m ³ 15 minutites.	TWA: 25 mg/m ³ 8 hr TWA: 10 ppm 8 hr STEL: 50 mg/m ³ 15 min STEL: 20 ppm 15 min	STEL: 15 ppm STEL: 37 mg/m ³ TWA: 10 ppm TWA: 25 mg/m ³	STEL: 50 mg/m ³ 15 percekben. CK TWA: 25 mg/m ³ 8 órában. AK	STEL: 20 ppm STEL: 50 mg/m ³ TWA: 10 ppm 8 klukkustundum. TWA: 25 mg/m ³ 8 klukkustundum.
Nitric acid	STEL: 1 ppm 15 minutites. STEL: 2.6 mg/m ³ 15 minutites.	STEL: 1 ppm 15 min STEL: 2.6 mg/m ³ 15 min	STEL: 1 ppm STEL: 2.6 mg/m ³	STEL: 2.6 mg/m ³ 15 percekben. CK	STEL: 1 ppm STEL: 2.6 mg/m ³

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Phosphoric acid	STEL: 2 mg/m ³ TWA: 1 mg/m ³	TWA: 1 mg/m ³ IPRD STEL: 2 mg/m ³	TWA: 1 mg/m ³ 8 Stunden STEL: 2 mg/m ³ 15 Minuten	TWA: 1 mg/m ³ STEL: 2 mg/m ³ 15 minuti	TWA: 1 mg/m ³ 8 ore STEL: 2 mg/m ³ 15 minute
Acetic acid	STEL: 50 mg/m ³ STEL: 20 ppm TWA: 10 ppm TWA: 25 mg/m ³	TWA: 10 ppm IPRD TWA: 25 mg/m ³ IPRD STEL: 50 mg/m ³ STEL: 20 ppm	TWA: 10 ppm 8 Stunden TWA: 25 mg/m ³ 8 Stunden STEL: 50 mg/m ³ 15 Minuten STEL: 20 ppm 15 Minuten	TWA: 10 ppm TWA: 25 mg/m ³ STEL: 20 ppm 15 minuti STEL: 50 mg/m ³ 15 minuti	TWA: 10 ppm 8 ore TWA: 25 mg/m ³ 8 ore STEL: 20 ppm 15 minute STEL: 50 mg/m ³ 15 minute
Nitric acid	STEL: 1 ppm STEL: 2.6 mg/m ³ TWA: 0.78 ppm TWA: 2 mg/m ³	STEL: 1 ppm STEL: 2.6 mg/m ³	STEL: 1 ppm 15 Minuten STEL: 2.6 mg/m ³ 15 Minuten	STEL: 1 ppm 15 minuti STEL: 2.6 mg/m ³ 15 minuti	STEL: 1 ppm 15 minute STEL: 2.6 mg/m ³ 15 minute

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Phosphoric acid		Ceiling: 2 mg/m ³ TWA: 1 mg/m ³	TWA: 1 mg/m ³ 8 urah inhalable fraction STEL: 2 mg/m ³ 15 minutah inhalable fraction	Binding STEL: 2 mg/m ³ 15 minuter TLV: 1 mg/m ³ 8 timmar. NGV	TWA: 1 mg/m ³ 8 saat STEL: 2 mg/m ³ 15 dakika
Acetic acid	Skin notation MAC: 5 mg/m ³	Ceiling: 50 mg/m ³ TWA: 10 ppm TWA: 25 mg/m ³	TWA: 10 ppm 8 urah TWA: 25 mg/m ³ 8 urah STEL: 50 mg/m ³ 15 minutah STEL: 20 ppm 15 minutah	Binding STEL: 10 ppm 15 minuter Binding STEL: 25 mg/m ³ 15 minuter TLV: 5 ppm 8 timmar. NGV TLV: 13 mg/m ³ 8 timmar. NGV	TWA: 10 ppm 8 saat TWA: 25 mg/m ³ 8 saat
Nitric acid	Skin notation MAC: 2 mg/m ³	Ceiling: 2.6 mg/m ³	TWA: 1 ppm 8 urah TWA: 2.6 mg/m ³ 8 urah STEL: 1 ppm 15 minutah STEL: 2.6 mg/m ³ 15 minutah	Binding STEL: 1 ppm 15 minuter Binding STEL: 2.6 mg/m ³ 15 minuter TLV: 0.5 ppm 8 timmar. NGV TLV: 1.3 mg/m ³ 8 timmar. NGV	STEL: 1 ppm 15 dakika STEL: 2.6 mg/m ³ 15 dakika

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

SAFETY DATA SHEET

Aluminum Etch 80-15-3-2, VLSI electronic grade

Revision Date 10-Jun-2024

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Phosphoric acid 7664-38-2 (75)		DNEL = 134.5mg/kg bw/day		DNEL = 3.8mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Phosphoric acid 7664-38-2 (75)	DNEL = 1mg/m ³	DNEL = 948.6mg/m ³	DNEL = 1mg/m ³	DNEL = 13.2mg/m ³
Acetic acid 64-19-7 (10)	DNEL = 25mg/m ³		DNEL = 25mg/m ³	

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Phosphoric acid 7664-38-2 (75)	PNEC = 100µg/L	PNEC = 392µg/kg sediment dw	PNEC = 1000µg/L	PNEC = 100mg/L	PNEC = 19.7µg/kg soil dw
Acetic acid 64-19-7 (10)	PNEC = 3.058mg/L	PNEC = 11.36mg/kg sediment dw	PNEC = 30.58mg/L	PNEC = 85mg/L	PNEC = 0.47mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Phosphoric acid 7664-38-2 (75)	PNEC = 10µg/L	PNEC = 39.2µg/kg sediment dw		PNEC = 4mg/kg food	
Acetic acid 64-19-7 (10)	PNEC = 0.3058mg/L	PNEC = 1.136mg/kg sediment dw			

8.2. Exposure controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Butyl rubber	See manufacturers recommendations	-	EN 374	(minimum requirement)

Skin and body protection Long sleeved clothing.

SAFETY DATA SHEET

Aluminum Etch 80-15-3-2, VLSI electronic grade

Revision Date 10-Jun-2024

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced
Recommended Filter type: Particulates filter conforming to EN 143 Acid gases filter Type E Yellow conforming to EN14387

Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141
When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls No information available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance		
Odor	No information available	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	100 °C / 212 °F	
Flammability (liquid)	No data available	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	No information available	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	1.5	
Viscosity	No data available	
Water Solubility	No information available	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Acetic acid	-0.2	
Nitric acid	-2.3	
Vapor Pressure	No data available	
Density / Specific Gravity	1.573	
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

SAFETY DATA SHEET

Aluminum Etch 80-15-3-2, VLSI electronic grade

Revision Date 10-Jun-2024

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization
Hazardous Reactions

No information available.
None under normal processing.

10.4. Conditions to avoid

Incompatible products. Excess heat.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Oxides of phosphorus. Nitrogen oxides (NOx). Carbon oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral

Category 4

Dermal

Based on available data, the classification criteria are not met

Inhalation

Category 4

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Phosphoric acid	LD50 = 1530 mg/kg (Rat)	LD50 = 2740 mg/kg (Rabbit)	850 mg/m ³ (Rat) 1 h
Water	-	-	-
Acetic acid	3310 mg/kg (Rat)	-	> 40 mg/L (Rat) 4 h
Nitric acid	-	-	LC50 = 2500 ppm. (Rat) 1h

Component	ECHA (RAC) ATE (Oral)	ECHA (RAC) ATE (Dermal)	ECHA (RAC) ATE (Inhalation)
Nitric acid	-	-	ATE = 2.65 mg/L (vapours)

ECHA (RAC) - Committee for Risk Assessment - European CHemicals Agency
ATE - Acute Toxicity Estimate

(b) skin corrosion/irritation;

Category 1 A

(c) serious eye damage/irritation;

Category 1

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

No data available

SAFETY DATA SHEET

Aluminum Etch 80-15-3-2, VLSI electronic grade

Revision Date 10-Jun-2024

(e) germ cell mutagenicity;	No data available
(f) carcinogenicity;	No data available There are no known carcinogenic chemicals in this product
(g) reproductive toxicity;	No data available
(h) STOT-single exposure;	No data available
(i) STOT-repeated exposure;	No data available
Target Organs	None known.
(j) aspiration hazard;	No data available
Symptoms / effects, both acute and delayed	Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

Component	Freshwater Fish	Water Flea	Freshwater Algae
Phosphoric acid	98 - 106 mg/L LC50 96 h	> 100 mg/L EC50 = 48 h	> 100 mg/L EC50 = 72 h
Acetic acid	Pimephales promelas: LC50 = 88 mg/L/96h Lepomis macrochirus: LC50 = 75 mg/L/96h	EC50 = 95 mg/L/24h	-

Component	Microtox	M-Factor
Acetic acid	Photobacterium phosphoreum: EC50 = 8.8 mg/L/15 min Photobacterium phosphoreum: EC50 = 8.8 mg/L/25 min Photobacterium phosphoreum: EC50 = 8.8 mg/L/5 min	

12.2. Persistence and degradability No information available

12.3. Bioaccumulative potential No information available

Component	log Pow	Bioconcentration factor (BCF)
Acetic acid	-0.2	No data available
Nitric acid	-2.3	No data available

SAFETY DATA SHEET

Aluminum Etch 80-15-3-2, VLSI electronic grade

Revision Date 10-Jun-2024

12.4. Mobility in soil	No information available
12.5. Results of PBT and vPvB assessment	No data available for assessment.
12.6. Endocrine disrupting properties Endocrine Disruptor Information	This product does not contain any known or suspected endocrine disruptors
12.7. Other adverse effects Persistent Organic Pollutant Ozone Depletion Potential	This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products	Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.
Contaminated Packaging	Dispose of this container to hazardous or special waste collection point.
European Waste Catalogue (EWC)	According to the European Waste Catalog, Waste Codes are not product specific, but application specific.
Other Information	Waste codes should be assigned by the user based on the application for which the product was used. Do not empty into drains. Do not flush to sewer. Large amounts will affect pH and harm aquatic organisms. Solutions with low pH-value must be neutralized before discharge.
Switzerland - Waste Ordinance	Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600 https://www.fedlex.admin.ch/eli/cc/2015/891/en

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number	UN3264
14.2. UN proper shipping name Technical Shipping Name	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. Phosphoric acid/nitric acid/acetic acid
14.3. Transport hazard class(es)	8
14.4. Packing group	II

ADR

14.1. UN number	UN3264
14.2. UN proper shipping name Technical Shipping Name	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. Phosphoric acid/nitric acid/acetic acid
14.3. Transport hazard class(es)	8
14.4. Packing group	II

IATA

ALFAAS60413

SAFETY DATA SHEET

Aluminum Etch 80-15-3-2, VLSI electronic grade

Revision Date 10-Jun-2024

14.1. UN number UN3264
14.2. UN proper shipping name CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
Technical Shipping Name Phosphoric acid/nitric acid/acetic acid
14.3. Transport hazard class(es) 8
14.4. Packing group II

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

China, X = listed, Australia, U.S.A. (TSCA), Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Australia (AICS), Korea (KECL), China (IECSC), Japan (ENCS), Philippines (PICCS), Taiwan (TCSI), Japan (ISHL), New Zealand (NZIoC), Japan (ISHL). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Phosphoric acid	7664-38-2	231-633-2	-	-	X	X	KE-27427	X	X
Water	7732-18-5	231-791-2	-	-	X	X	KE-35400	X	-
Acetic acid	64-19-7	200-580-7	-	-	X	X	X	X	X
Nitric acid	7697-37-2	231-714-2	-	-	X	X	KE-25911	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Phosphoric acid	7664-38-2	X	ACTIVE	X	-	X	X	X
Water	7732-18-5	X	ACTIVE	X	-	X	X	X
Acetic acid	64-19-7	X	ACTIVE	X	-	X	X	X
Nitric acid	7697-37-2	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Phosphoric acid	7664-38-2	-	Use restricted. See item 75. (see link for restriction details)	-
Water	7732-18-5	-	-	-
Acetic acid	64-19-7	-	Use restricted. See item 75. (see link for restriction details)	-
Nitric acid	7697-37-2	-	Use restricted. See item 75. (see link for restriction details)	-

REACH links

SAFETY DATA SHEET

Aluminum Etch 80-15-3-2, VLSI electronic grade

Revision Date 10-Jun-2024

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Phosphoric acid	7664-38-2	Not applicable	Not applicable
Water	7732-18-5	Not applicable	Not applicable
Acetic acid	64-19-7	Not applicable	Not applicable
Nitric acid	7697-37-2	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 1 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Phosphoric acid	WGK1	
Acetic acid	WGK1	Class II : 0.10 g/m ³ (Massenkonzentration)
Nitric acid	WGK1	

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Phosphoric acid 7664-38-2 (75)	Prohibited and Restricted Substances		
Acetic acid 64-19-7 (10)	Prohibited and Restricted Substances	Group I	
Nitric acid 7697-37-2 (3)	Prohibited and Restricted Substances		

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

SAFETY DATA SHEET

Aluminum Etch 80-15-3-2, VLSI electronic grade

Revision Date 10-Jun-2024

Full text of H-Statements referred to under sections 2 and 3

H290 - May be corrosive to metals
H302 - Harmful if swallowed
H332 - Harmful if inhaled
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H226 - Flammable liquid and vapor
H272 - May intensify fire; oxidizer
H330 - Fatal if inhaled
EUH071 - Corrosive to the respiratory tract

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadviser - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Prepared By

Health, Safety and Environmental Department

Creation Date

10-Jun-2024

Revision Date

10-Jun-2024

Revision Summary

Initial Release.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No
1907/2006 .**

SAFETY DATA SHEET

Aluminum Etch 80-15-3-2, VLSI electronic grade

Revision Date 10-Jun-2024

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet