

SAFETY DATA SHEET

Creation Date 21-January-2009

Revision Date 20-January-2025

Revision Number 1

1. Identification

Product Name 1-Butanol, GR

Cat No. : W00403

CAS-No 71-36-3
Synonyms n-Butanol; n-Butyl alcohol, Butan-1-ol

Recommended Use Laboratory chemicals.
Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet**Company****Importer/Distributor**

Fisher Scientific
112 Colonnade Road,
Ottawa, ON K2E 7L6,
Canada
Tel: 1-800-234-7437

Emergency Telephone NumberFor information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99**CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887**2. Hazard(s) identification****Classification****WHMIS 2015 Classification**

Classified as hazardous under the Hazardous Products Regulations (SOR/2015-17)

Flammable liquids	Category 3
Acute oral toxicity	Category 4
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 1
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Respiratory system, Central nervous system (CNS).	

Label Elements**Signal Word**

Danger

Hazard Statements

Flammable liquid and vapor

Harmful if swallowed
Causes skin irritation
Causes serious eye damage
May cause respiratory irritation
May cause drowsiness and dizziness

**Precautionary Statements****Prevention**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting/equipment
Do not breathe dust/fumes/gas/mist/vapours/spray
Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product
Use only outdoors or in a well-ventilated area
Wear protective gloves/protective clothing/eye protection/face protection
Use only non-sparking tools
Take action to prevent static discharges

Response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower
IF INHALED: Remove person to fresh air and keep comfortable for breathing
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
Immediately call a POISON CENTER/doctor
Rinse mouth
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish
Take off contaminated clothing and wash it before reuse

Storage

Store in a well-ventilated place. Keep container tightly closed
Store locked up

Disposal

Dispose of contents/container to an approved waste disposal plant

3. Composition/Information on Ingredients

Component	CAS-No	Weight %
1-Butanol	71-36-3	99

4. First-aid measures

General Advice

If symptoms persist, call a physician.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.

Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.
Ingestion	Clean mouth with water and drink afterwards plenty of water.
Most important symptoms/effects	Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	Water spray, carbon dioxide (CO ₂), dry chemical, alcohol-resistant foam.
Unsuitable Extinguishing Media	No information available
Flash Point	35 °C / 95 °F
Method -	CC (closed cup)
Autoignition Temperature	340 °C / 644 °F
Explosion Limits	
Upper	11.2 vol %
Lower	1.4 vol %
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂).

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health
2

Flammability
3

Instability
0

Physical hazards
N/A

6. Accidental release measures

Personal Precautions	Use personal protective equipment as required. Ensure adequate ventilation.
Environmental Precautions	Should not be released into the environment.

Methods for Containment and Clean Up Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

7. Handling and storage

Handling	Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation.
Storage.	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area. Incompatible Materials. Strong oxidizing agents. Reducing Agent. Acid chlorides. copper. Copper alloys. Acid anhydrides.

8. Exposure controls / personal protection

Exposure Guidelines

Component	Alberta	British Columbia	Ontario TWAEV	Quebec	ACGIH TLV	OSHA PEL	NIOSH
1-Butanol	TWA: 20 ppm TWA: 60 mg/m ³	TWA: 15 ppm Ceiling: 30 ppm	TWA: 20 ppm	Ceiling: 50 ppm Ceiling: 152 mg/m ³ Skin	TWA: 20 ppm	Skin (Vacated) Ceiling: 50 ppm (Vacated) Ceiling: 150 mg/m ³ TWA: 100 ppm TWA: 300 mg/m ³	IDLH: 1400 ppm Ceiling: 50 ppm Ceiling: 150 mg/m ³

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH - NIOSH - National Institute for Occupational Safety and Health

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles

Hand Protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Glove material	Breakthrough time	Glove thickness	Glove comments
Butyl rubber	> 480 minutes	0.35 mm	As tested under EN374-3
Nitrile rubber	> 480 minutes	0.38 mm	Determination of Resistance to Permeation by Chemicals

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to EN14387

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

No information available.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

9. Physical and chemical properties

Physical State	Liquid
Appearance	Colorless
Odor	Alcohol-like
Odor Threshold	No information available
pH	No information available
Melting Point/Range	-89 °C / -128.2 °F
Boiling Point/Range	117.6 °C / 243.7 °F
Flash Point	35 °C / 95 °F
Method -	CC (closed cup)
Evaporation Rate	0.46
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	11.2 vol %
Lower	1.4 vol %
Vapor Pressure	6.7 mbar @ 20 °C
Vapor Density	2.6
Specific Gravity	0.810
Solubility	Slightly soluble in water
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	340 °C / 644 °F
Decomposition Temperature	No information available
Viscosity	2.95 mPa.s (20 °C)
Molecular Formula	C4 H10 O
Molecular Weight	74.12
Refractive index	1.390 - 1.400

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Keep away from open flames, hot surfaces and sources of ignition. Incompatible products.
Incompatible Materials	Strong oxidizing agents, Reducing Agent, Acid chlorides, copper, Copper alloys, Acid anhydrides
Hazardous Decomposition Products	Carbon monoxide (CO), Carbon dioxide (CO ₂)
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
1-Butanol	LD50 = 700 mg/kg (Rat)	LD50 = 3402 mg/kg (Rabbit)	LC50 > 8000 ppm (Rat) 4 h

Toxicologically Synergistic Products No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation	Severe eye irritant; Irritating to respiratory system and skin
Sensitization	No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
1-Butanol	71-36-3	Not listed	Not listed	Not listed	Not listed	Not listed

Mutagenic Effects No information available

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure Respiratory system Central nervous system (CNS)

STOT - repeated exposure None known

Aspiration hazard No information available

Symptoms / effects, both acute and delayed Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Do not flush into surface water or sanitary sewer system.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
1-Butanol	EC50: 225 mg/L, 96h (Pseudokirchneriella subcapitata) OECD Guideline 201 EC50: > 500 mg/L, 72h (Desmodesmus subspicatus) EC50: > 500 mg/L, 96h (Desmodesmus subspicatus)	LC50: 1376 mg/L, 96h (Pimephales promelas) OECD Guideline 203 : 100000 - 500000 µg/L, 96h static (Lepomis macrochirus) LC50: = 1740 mg/L, 96h flow-through (Pimephales promelas) LC50: = 1910000 µg/L, 96h static (Pimephales promelas) LC50: 1730 - 1910 mg/L, 96h static (Pimephales promelas)	EC50 = 2041.4 mg/L 5 min EC50 = 2186 mg/L 30 min EC50 = 3980 mg/L 24 h EC50 = 4400 mg/L 17 h	EC50: 1328 mg/L, 48h (Daphnia magna) OECD Guideline 202 EC50: 1897 - 2072 mg/L, 48h Static (Daphnia magna) EC50: = 1983 mg/L, 48h (Daphnia magna)

Persistence and Degradability Soluble in water Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility . Will likely be mobile in the environment due to its water solubility.

Component	log Pow
1-Butanol	1

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
1-Butanol - 71-36-3	U031	-

14. Transport information

DOT

UN-No UN1120
 Proper Shipping Name BUTANOLS
 Hazard Class 3
 Packing Group III

TDG

UN-No UN1120
 Proper Shipping Name BUTANOLS
 Hazard Class 3
 Packing Group III

IATA

UN-No UN1120
 Proper Shipping Name BUTANOLS
 Hazard Class 3
 Packing Group III

IMDG/IMO

UN-No UN1120
 Proper Shipping Name BUTANOLS
 Hazard Class 3
 Packing Group III

15. Regulatory information

International Inventories

Component	CAS-No	DSL	NDSL	TSCA	TSCA Inventory notification - Active-Inactive	EINECS	ELINCS	NLP
1-Butanol	71-36-3	X	-	X	ACTIVE	200-751-6	-	-

Component	CAS-No	IECSC	KECL	ENCS	ISHL	TCSI	AICS	NZIoC	PICCS
1-Butanol	71-36-3	X	KE-03867	X	X	X	X	X	X

Legend:

X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

Canada

SDS in compliance with provisions of information as set out in Canadian Standard - Part 4, Schedule 1 and 2 of the Hazardous Products Regulations (HPR) and meets the requirements of the HPR (Paragraph 13(1)(a) of the Hazardous Products Act (HPA)).

Component	Canada - National Pollutant Release Inventory (NPRI)	Canadian Environmental Protection Agency (CEPA) - List of Toxic Substances	Canada's Chemicals Management Plan (CEPA)
1-Butanol	Part 1, Group A Substance Part 4 Substance		

Other International Regulations**Authorisation/Restrictions according to EU REACH**

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
1-Butanol	-	Use restricted. See entry 75. (see link for restriction details)	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS-No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
1-Butanol	71-36-3	Listed	Not applicable	Not applicable	Not applicable

Component	CAS-No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
1-Butanol	71-36-3	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information

Prepared By

Product Safety Department
Email: chem.techinfo@thermofisher.com
www.thermofisher.com

Creation Date

21-January-2009

Revision Date

20-January-2025

Print Date

20-January-2025

Revision Summary

Initial Release.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS