

# SAFETY DATA SHEET

Creation Date 11-June-2009 Revision Date 24-December-2021 **Revision Number** 6

1. Identification

**Product Name Xylenes** 

AC200910000; AC200910010; AC200910025; AC200910250 Cat No.:

Synonyms Dimethylbenzene

**Recommended Use** Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Manufacturer Importer/Distributor

Acros Organics Fisher Scientific Company Fisher Scientific One Reagent Lane 112 Colonnade Road, One Reagent Lane Fair Lawn, NJ 07410 Fair Lawn, NJ 07410 Ottawa, ON K2E 7L6. Tel: (201) 796-7100

Canada

Tel: 1-800-234-7437

**Emergency Telephone Number** For information **US** call: 001-800-ACROS-01 / Europe call: +32 14 57 52 11

> Emergency Number US:001-201-796-7100 / Europe: +32 14 57 52 99 CHEMTREC Tel. No. US: 001-800-424-9300 / Europe: 001-703-527-3887

# 2. Hazard(s) identification

Classification

WHMIS 2015 Classification Classified as hazardous under the Hazardous Products Regulations (SOR/2015-17)

Flammable liquids Category 3 Acute dermal toxicity Category 4 Category 4 **Acute Inhalation Toxicity** Skin Corrosion/Irritation Category 2 Serious Eye Damage/Eye Irritation Category 2 Carcinogenicity Category 2 Specific target organ toxicity (single exposure) Category 3 Target Organs - Respiratory system. Specific target organ toxicity - (repeated exposure) Category 2 Target Organs - Heart, Liver, Kidney, Ears. **Aspiration Toxicity** Category 1

**Label Elements** 

Signal Word

#### Danger

#### **Hazard Statements**

Flammable liquid and vapor
Harmful in contact with skin or if inhaled
May be fatal if swallowed and enters airways
Causes skin irritation
Causes serious eye irritation
May cause respiratory irritation
Suspected of causing cancer

May cause damage to organs through prolonged or repeated exposure



### **Precautionary Statements**

#### Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use only non-sparking tools

Take precautionary measures against static discharges

Do not breathe dust/fumes/gas/mist/vapours/spray

Wash face, hands and any exposed skin thoroughly after handling

Use only outdoors or in a well-ventilated area

Wear protective gloves/protective clothing/eye protection/face protection

#### Response

IF SWALLOWED: Immediately call a POISON CENTER/doctor

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

IF INHALED: Remove person to fresh air and keep comfortable for breathing

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

IF exposed or concerned: Get medical advice/attention

Call a POISON CENTER/ doctor if you feel unwell

Do NOT induce vomiting

Wash contaminated clothing before reuse

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

## Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

### Disposal

Dispose of contents/container to an approved waste disposal plant

## Other Hazards

Harmful to aquatic life with long lasting effects

# 3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Xylenes (o-, m-, p- isomers)	1330-20-7	>75
Ethylbenzene	100-41-4	<25

## 4. First-aid measures

**General Advice** If symptoms persist, call a physician.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur. Risk of serious damage to the lungs (by aspiration).

Ingestion Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call

a physician or poison control center immediately. If vomiting occurs naturally, have victim

lean forward.

**Most important symptoms/effects** Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness,

nausea and vomiting

Notes to Physician Treat symptomatically

# 5. Fire-fighting measures

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may

be used to cool closed containers.

Unsuitable Extinguishing Media No information available

Flash Point 25 °C / 77 °F

Method - No information available

Autoignition Temperature 460 °C / 860 °F

**Explosion Limits** 

Upper No data available
Lower No data available
Sensitivity to Mechanical Impact No information available
Sensitivity to Static Discharge No information available

### **Specific Hazards Arising from the Chemical**

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

#### **Hazardous Combustion Products**

Carbon monoxide (CO). Carbon dioxide (CO2).

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

<u>NFPA</u>

Health Flammability Instability Physical hazards
3 2 0 N/A

### 6. Accidental release measures

Personal Precautions Use personal protective equipment as required. Ensure adequate ventilation. Remove all

sources of ignition. Take precautionary measures against static discharges.

**Environmental Precautions** Do not flush into surface water or sanitary sewer system.

**Methods for Containment and Clean** Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. **Up** Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage

Handling Wear personal protective equipment/face prote

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Ensure adequate ventilation. Keep away from open

flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take

precautionary measures against static discharges.

**Storage.** Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area.

Keep away from heat, sparks and flame. Incompatible Materials. Strong oxidizing agents.

Strong acids.

# 8. Exposure controls / personal protection

#### **Exposure Guidelines**

Component	Alberta	British Columbia	Ontario TWAEV	Quebec	ACGIH TLV	OSHA PEL	NIOSH IDLH
Xylenes (o-, m-, p- isomers)	TWA: 100 ppm TWA: 434 mg/m³ STEL: 150 ppm STEL: 651 mg/m³	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 434 mg/m³ STEL: 150 ppm STEL: 651 mg/m³	TWA: 100 ppm STEL: 150 ppm	(Vacated) TWA: 100 ppm (Vacated) TWA: 435 mg/m³ (Vacated) STEL: 150 ppm (Vacated) STEL: 655 mg/m³ TWA: 100 ppm TWA: 435 mg/m³	
Ethylbenzene	TWA: 100 ppm TWA: 434 mg/m³ STEL: 125 ppm STEL: 543 mg/m³	TWA: 20 ppm	TWA: 20 ppm	TWA: 20 ppm	TWA: 20 ppm	(Vacated) TWA: 100 ppm (Vacated) TWA: 435 mg/m³ (Vacated) STEL: 125 ppm (Vacated) STEL: 545 mg/m³ TWA: 100 ppm TWA: 435 mg/m³	mg/m³ STEL: 125 ppm STEL: 545

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

# **Engineering Measures**

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

#### Personal protective equipment

**Eye Protection** Goggle

**Hand Protection** Wear appropriate protective gloves and clothing to prevent skin exposure.

Glove material	Breakthrough time	Glove thickness	Glove comments
Viton (R)	> 480 minutes	-	As tested under EN374-3

Determination of Resistance to Permeation by Chemicals

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

#### **Respiratory Protection**

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly **Recommended Filter type:** Organic gases and vapours filter Type A Brown conforming to EN14387

When RPE is used a face piece Fit Test should be conducted

#### **Environmental exposure controls**

Prevent product from entering drains. Do not allow material to contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained.

## **Hygiene Measures**

When using do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

# 9. Physical and chemical properties

Physical StateLiquidAppearanceColorlessOdoraromatic

Odor Threshold No information available

H Not applicable

Melting Point/Range -34 °C / -29.2 °F

**Boiling Point/Range** 137 - 143 °C / 278.6 - 289.4 °F

Flash Point 25 °C / 77 °F
Evaporation Rate No information available

Flammability (solid,gas) Not applicable

Flammability or explosive limits

UpperNo data availableLowerNo data availableVapor Pressure8 mbar @ 20 °CVapor DensityNo information available

Specific Gravity 0.865

Solubilitypractically insolublePartition coefficient; n-octanol/waterNo data availableAutoignition Temperature460 °C / 860 °FDecomposition TemperatureNo information available

Viscosity 0.6 mPa s @ 20 °C

Molecular FormulaC8 H10Molecular Weight106.17

# 10. Stability and reactivity

Reactive Hazard None known, based on information available

**Stability** Stable under normal conditions.

Conditions to Avoid Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition.

Incompatible Materials Strong oxidizing agents, Strong acids

**Xylenes** 

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2)

**Hazardous Polymerization** Hazardous polymerization does not occur.

**Hazardous Reactions** None under normal processing.

# Toxicological information

**Acute Toxicity** 

**Product Information** 

Oral LD50 Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.

**Dermal LD50** Category 4. ATE = 1000 - 2000 mg/kg. Vapor LC50 Category 4. ATE = 10 - 20 mg/l.

Component Information

Component	Component LD50 Oral		LC50 Inhalation
Xylenes (o-, m-, p- isomers)	LD50 = 3500 mg/kg (Rat)	LD50 > 4350 mg/kg (Rabbit)	29.08 mg/L [MOE Risk Assessment
			Vol.1, 2002]
Ethylbenzene	3500 mg/kg ( Rat )	15400 mg/kg ( Rabbit )	17.2 mg/L ( Rat ) 4 h

**Toxicologically Synergistic** No information available

**Products** 

Irritation No information available

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Xylenes (o-, m-, p- isomers)	1330-20-7	Not listed				
Ethylbenzene	100-41-4	Group 2B	Not listed	A3	Х	A3

IARC (International Agency for Research on Cancer)

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans

ACGIH: (American Conference of Governmental Industrial A1 - Known Human Carcinogen

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

ACGIH: (American Conference of Governmental Industrial Hygienists)

Mexico - Occupational Exposure Limits - Carcinogens Mexico - Occupational Exposure Limits - Carcinogens

A1 - Confirmed Human Carcinogen A2 - Suspected Human Carcinogen

A3 - Confirmed Animal Carcinogen

A4 - Not Classifiable as a Human Carcinogen

A5 - Not Suspected as a Human Carcinogen

No information available **Mutagenic Effects** 

No information available. **Reproductive Effects** 

**Developmental Effects** No information available.

**Teratogenicity** No information available.

STOT - single exposure Respiratory system STOT - repeated exposure Heart Liver Kidney Ears

No information available **Aspiration hazard** 

Symptoms / effects, both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting delayed

**Endocrine Disruptor Information** No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

# 12. Ecological information

## Ecotoxicity

The product contains following substances which are hazardous for the environment. Contains a substance which is:. Very toxic to aquatic organisms.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Xylenes (o-, m-, p- isomers)	Not listed	LC50: 30.26 - 40.75 mg/L, 96h static (Poecilia reticulata) LC50: = 780 mg/L, 96h semi-static (Cyprinus carpio) LC50: 23.53 - 29.97 mg/L, 96h static (Pimephales promelas) LC50: > 780 mg/L, 96h (Cyprinus carpio) LC50: 7.711 - 9.591 mg/L, 96h static (Lepomis macrochirus) LC50: = 19 mg/L, 96h (Lepomis macrochirus) LC50: 13.1 - 16.5 mg/L, 96h flow-through (Lepomis macrochirus) LC50: 13.5 - 17.3 mg/L, 96h (Oncorhynchus mykiss) LC50: 2.661 - 4.093 mg/L, 96h static (Oncorhynchus mykiss) LC50: = 13.4 mg/L, 96h flow-through (Pimephales promelas)	EC50 = 0.0084 mg/L 24 h	LC50: = 0.6 mg/L, 48h (Gammarus lacustris) EC50: = 3.82 mg/L, 48h (water flea)
Ethylbenzene	EC50: 2.6 - 11.3 mg/L, 72h static (Pseudokirchneriella subcapitata) EC50: 1.7 - 7.6 mg/L, 96h static (Pseudokirchneriella subcapitata) EC50: > 438 mg/L, 96h (Pseudokirchneriella subcapitata) EC50: = 4.6 mg/L, 72h (Pseudokirchneriella subcapitata)	LC50: 7.55 - 11 mg/L, 96h flow-through (Pimephales promelas) LC50: 11.0 - 18.0 mg/L, 96h static (Oncorhynchus mykiss) LC50: = 4.2 mg/L, 96h semi-static (Oncorhynchus mykiss) LC50: = 32 mg/L, 96h static (Lepomis macrochirus) LC50: 9.1 - 15.6 mg/L, 96h static (Pimephales promelas) LC50: = 9.6 mg/L, 96h static (Poecilia reticulata)	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	EC50: 1.8 - 2.4 mg/L, 48h (Daphnia magna)

Persistence and Degradability Insoluble in water Persistence is unlikely based on information available.

**Bioaccumulation/ Accumulation** No information available.

Mobility Will likely be mobile in the environment due to its volatility. Is not likely mobile in the

environment due its low water solubility.

Component	log Pow
Xylenes (o-, m-, p- isomers)	3.15
Ethylbenzene	3.2

# 13. Disposal considerations

**Waste Disposal Methods** 

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Xylenes (o-, m-, p- isomers) - 1330-20-7	U239	-

# 14. Transport information

DOT

UN-No UN1307 Proper Shipping Name XYLENES

Hazard Class 3 Packing Group III

TDG

UN-No UN1307 Proper Shipping Name XYLENES

Hazard Class 3
Packing Group III

<u>IATA</u>

UN-No UN1307 Proper Shipping Name XYLENES

Hazard Class 3
Packing Group III

IMDG/IMO

UN-No UN1307 Proper Shipping Name XYLENES

Hazard Class 3
Packing Group III

# 15. Regulatory information

#### **International Inventories**

Component	CAS-No	DSL	NDSL	TSCA	TSCA Inventory notification - Active-Inactive	EINECS	ELINCS	NLP
Xylenes (o-, m-, p- isomers)	1330-20-7	X	-	Х	ACTIVE	215-535-7	-	-
Ethylbenzene	100-41-4	Х	-	Х	ACTIVE	202-849-4	-	-

Component	CAS-No	IECSC	KECL	ENCS	ISHL	TCSI	AICS	NZIoC	PICCS
Xylenes (o-, m-, p- isomers)	1330-20-7	Х	KE-35427	X	X	X	Х	X	X
Ethylbenzene	100-41-4	X	KE-13532	X	X	X	Х	X	Х

#### Legend:

X - Listed '-' - Not Listed

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**ENCS** - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

### Canada

SDS in compliance with provisions of information as set out in Canadian Standard - Part 4, Schedule 1 and 2 of the Hazardous Products Regulations (HPR) and meets the requirements of the HPR (Paragraph 13(1)(a) of the Hazardous Products Act (HPA)).

Component	Canada - National Pollutant Release Inventory (NPRI)	Canadian Environmental Protection Agency (CEPA) - List of Toxic Substances	Canada's Chemicals Management Plan (CEPA)
Xylenes (o-, m-, p- isomers)	Part 1, Group A Substance Part 5, Isomer Groups Part 4 Substance		
Ethylbenzene	Part 1, Group A Substance Part 4 Substance		

Legend

NPRI - National Pollutant Release Inventory

#### Other International Regulations

## Authorisation/Restrictions according to EU REACH

Component	_	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	
Xylenes (o-, m-, p- isomers)	-	Use restricted. See item 75. (see link for restriction details)	-

https://echa.europa.eu/substances-restricted-under-reach

#### Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS-No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Xylenes (o-, m-, p- isomers)	1330-20-7	Listed	Not applicable	Not applicable	Not applicable
Ethylbenzene	100-41-4	Listed	Not applicable	Not applicable	Not applicable

Component	CAS-No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Xylenes (o-, m-, p- isomers)	1330-20-7	Not applicable	Not applicable	Not applicable	Annex I - Y42
Ethylbenzene	100-41-4	Not applicable	Not applicable	Not applicable	Not applicable

# 16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

Creation Date11-June-2009Revision Date24-December-2021Print Date24-December-2021

**Revision Summary**This document has been updated to comply with the requirements of WHMIS 2015 to align

with the Globally Harmonised System (GHS) for the Classification and Labelling of

Chemicals.

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

## **End of SDS**