

Page 1/10 Creation Date 11-Nov-2010 Revision Date 23-Mar-2025 Version 5

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THECOMPANY/UNDERTAKING

Product Identifier

Molecular Formula

 Perihalan Produk:
 iso-Propylamine

 Product Description:
 iso-Propylamine

 Cat No.:
 P/7662/PB07

 Synonyms
 2-Aminopropane

 CAS No
 75-31-0

Relevant identified uses of the substance or mixture and uses advised against

C3 H9 N

Recommended Use Laboratory chemicals.
Uses advised against No Information available

Company Thermo Fisher Scientific Fisher Scientific (M) Sdn Bhd

Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square, No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,

Selangor Darul Ehsan, Malaysia. Main line: +60 3-5525 7888

Supplier

E-mail address Enquiry.my@thermofisher.com

Emergency Telephone Number Tel: +03-5525 7888

CHEMTREC Malaysia 1-800-815-308 (Malay)

CHEMTREC Malaysia (Kuala Lumpur) +(60)-327884561 (Malay)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

Flammable liquids	Category 1 (H224)
Substances/mixtures corrosive to metal	Category 1 (H290)
Acute oral toxicity	Category 3 (H301)
Acute dermal toxicity	Category 3 (H311)
Acute Inhalation Toxicity - Vapors	Category 3 (H331)
Skin Corrosion/Irritation	Category 1 A (H314)
Serious Eye Damage/Eye Irritation	Category 1 (H318)
Specific target organ toxicity - (single exposure)	Category 3 (H335)

Label Elements



Signal Word

Danger

Hazard Statements

H224 - Extremely flammable liquid and vapor

H290 - May be corrosive to metals

H335 - May cause respiratory irritation

H314 - Causes severe skin burns and eye damage

H301 + H311 + H331 - Toxic if swallowed, in contact with skin or if inhaled

Precautionary Statements

Prevention

P234 - Keep only in original packaging

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P241 - Use explosion-proof electrical/ ventilating/ lighting equipment

P264 - Wash face, hands and any exposed skin thoroughly after handling

P240 - Ground and bond container and receiving equipment

P242 - Use non-sparking tools

P243 - Take action to prevent static discharges

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P270 - Do not eat, drink or smoke when using this product

Response

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor

P330 - Rinse mouth

P331 - Do NOT induce vomiting

P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

P390 - Absorb spillage to prevent material damage

P362 + P364 - Take off contaminated clothing and wash it before reuse

Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P402 - Store in a dry place

P406 - Store in corrosion resistant polypropylene container with a resistant inliner

P405 - Store locked up

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other Hazards

Toxicity to Soil Dwelling Organisms

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No	Weight %	
Isopropylamine	75-31-0	>95	

SECTION 4: FIRST AID MEASURES

Description of first aid measures

General Advice Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In

the case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately.

InhalationDo not use mouth-to-mouth method if victim ingested or inhaled the substance; give

artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Remove to fresh air. Immediate medical attention is

required. If not breathing, give artificial respiration.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Causes burns by all exposure routes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting. Product is a corrosive material. Use of gastric lavage or emesis is

contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of

perforation.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

No information available.

Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Extremely flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO₂), Ammonia, nitriles, Thermal decomposition can lead to release of irritating gases and vapors.

Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental precautions

Do not flush into surface water or sanitary sewer system.

Methods and Material for Containment and Cleaning Up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Use only under a chemical fume hood. Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use spark-proof tools and explosion-proof equipment. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Conditions for Safe Storage, Including any Incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area. Keep away from heat, sparks and flame. Do not store in metal containers.

Specific End Uses

Use in laboratories.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	Malaysia	ACGIH TLV	OSHA PEL
Isopropylamine		TWA: 2 ppm	(Vacated) TWA: 5 ppm
		STEL: 5 ppm	(Vacated) TWA: 12 mg/m ³
		Skin	(Vacated) STEL: 10 ppm
			(Vacated) STEL: 24 mg/m ³
			TWA: 5 ppm
			TWA: 12 mg/m ³

Component	European Union	The United Kingdom	Germany
Isopropylamine			TWA: 5 ppm (8 Stunden). AGW -
			ceiling factor 2

	TWA: 12 mg/m3 (8 Stunden). AGW -
	ceiling factor 2
	TWA: 5 ppm (8 Stunden). MAK an
	instantaneous value of 10 ppm
	corresponding to 25 mg/m ³ should
	not be exceeded; even if the MAK
	value is adhered to,
	"odor-associated" symptoms cannot
	be ruled out in individual cases
	TWA: 12 mg/m³ (8 Stunden). MAK
	an instantaneous value of 10 ppm
	corresponding to 25 mg/m³ should
	not be exceeded; even if the MAK
	value is adhered to,
	"odor-associated" symptoms cannot
	be ruled out in individual cases
	Höhepunkt: 10 ppm
	Höhepunkt: 24 mg/m ³

Exposure Controls

iso-Propylamine

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles
Hand Protection Protective gloves
Skin and body protection Long sleeved clothing

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators

Recommended Filter type: Inorganic gases and vapours filter Type B Grey Ammonia and organic ammonia derivatives

filter Type K Green Particulates filter conforming to EN 143

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

When RPE is used a face piece Fit Test should be conducted

Handle in accordance with good industrial hygiene and safety practice

system

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance Colorless Physical State Liquid

Revision Date 23-Mar-2025

iso-Propylamine Revision Date 23-Mar-2025

Liquid

Liquid

Vapors may form explosive mixtures with air

Ammonia-like Odor **Odor Threshold** No data available

70% aq.sol pН 14

Melting Point/Range -101 °C / -149.8 °F **Softening Point** No data available

Boiling Point/Range 33 - 34 °C / 91.4 - 93.2 °F

-37 °C / -34.6 °F **Flash Point** Method - No information available

Evaporation Rate No data available Flammability (solid,gas) Not applicable **Explosion Limits** Lower 2.3

Upper 10.4

478 mmHg @ 20 °C **Vapor Pressure**

Vapor Density 2.03 (Air = 1.0)(Air = 1.0)

Specific Gravity / Density 0.690 **Bulk Density** Not applicable

Water Solubility Miscible

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Component log Pow Isopropylamine

Autoignition Temperature 400 - °C / 752 - °F **Decomposition Temperature** No data available 0.3 mPa.s at 20 °C **Viscosity**

Explosive Properties

Oxidizing Properties No information available

C3 H9 N Molecular Formula **Molecular Weight** 59.11

SECTION 10: STABILITY AND REACTIVITY

Reactivity

None known, based on information available.

Chemical Stability

Stable under normal conditions.

Possibility of Hazardous Reactions

Hazardous Polymerization Hazardous polymerization does not occur. **Hazardous Reactions** None under normal processing.

Conditions to Avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition.

Incompatible Materials

Acids. Strong oxidizing agents. Metals. copper. Aluminium. Lead. Acid anhydrides. Acid

chlorides.

Hazardous Decomposition Products

Nitrogen oxides (NOx). Carbon monoxide (CO). Carbon dioxide (CO₂). Ammonia. nitriles.

Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects

Product Information

(a) acute toxicity;

OralCategory 3DermalCategory 3InhalationCategory 3

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation		
Isopropylamine	122 mg/kg (Rat)	>400 mg/kg (Rabbit)	8.7 mg/L/4h (Rat)		
	170 mg/kg (Rat)				

(b) skin corrosion/irritation; Category 1 A

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

RespiratoryBased on available data, the classification criteria are not met **Skin**Based on available data, the classification criteria are not met

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

(f) carcinogenicity; Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; Based on available data, the classification criteria are not met

(h) STOT-single exposure; Category 3

Results / Target organs Respiratory system.

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

Target Organs None known.

(j) aspiration hazard; Based on available data, the classification criteria are not met

Revision Date 23-Mar-2025 iso-Propylamine

delayed

Symptoms / effects.both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation.

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity effects

Contains a substance which is:. The product contains following substances which are hazardous for the environment. Toxic to aquatic organisms.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Isopropylamine	LC50: = 310 mg/L, 96h	EC50: = 20.8 mg/L, 48h	EC50: = 62.5 mg/L, 96h	EC50 = 99 mg/L 17 h
	(Pimephales promelas)	(Daphnia magna)	(Pseudokirchneriella	
			subcapitata)	
			EC50: = 1.2 mg/L, 96h	
			(Desmodesmus	
			subspicatus)	
			EC50: = 4.13 mg/L, 72h	
			(Desmodesmus	
			subspicatus)	
			·	

Persistence and degradability

Persistence

Degradation in sewage treatment plant

Readily biodegradable

Persistence is unlikely, based on information available.

Contains substances known to be hazardous to the environment or not degradable in waste

water treatment plants.

Bioaccumulative potential Bioaccumulation is unlikely

Component		log Pow	Bioconcentration factor (BCF)		
Isopropylamine		-0.5	0.43 dimensionless		

The product contains volatile organic compounds (VOC) which will evaporate easily from all **Mobility in soil**

surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in

air.

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

No information available Other adverse effects

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from Residues/Unused

Products

Waste is classified as hazardous Dispose of in accordance with the European Directives on waste and hazardous waste Dispose of in accordance with local regulations

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous Keep product and

empty container away from heat and sources of ignition

iso-Propylamine Revision Date 23-Mar-2025

Other Information

Do not flush to sewer Waste codes should be assigned by the user based on the application for which the product was used Can be landfilled or incinerated, when in compliance with local regulations Do not empty into drains Large amounts will affect pH and harm aquatic organisms Solutions with high pH-value must be neutralized before discharge

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

UN-No UN1221
Hazard Class 3
Subsidiary Hazard Class 8
Packing Group |

Proper Shipping Name ISOPROPYLAMINE

Road and Rail Transport

UN-No UN1221
Hazard Class 3
Subsidiary Hazard Class 8
Packing Group |

Proper Shipping Name ISOPROPYLAMINE

<u>IATA</u>

UN-No UN1221
Hazard Class 3
Subsidiary Hazard Class 8
Packing Group |

Proper Shipping Name ISOPROPYLAMINE

Special Precautions for User No special precautions required

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories X = listed

Component	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	IECSC	AICS	KECL
Isopropylamine	200-860-9	X	X	Х	X	X	X	X	KE-29257

National Regulations

Persistent Organic Pollutant Ozone Depletion Potential This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 16: OTHER INFORMATION

Legend

iso-Propylamine Revision Date 23-Mar-2025

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances Substances List

ENCS - Japanese Existing and New Chemical Substances AICS - Australian Inventory of Chemical Substances

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50% POW - Partition coefficient Octanol:Water TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

NZIoC - New Zealand Inventory of Chemicals

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Dangerous Goods Code

ICAO/IATA - International Civil Aviation Organization/International Air **Transport Association**

MARPOL - International Convention for the Prevention of Pollution from

Ships

ATE - Acute Toxicity Estimate VOC - (Volatile Organic Compound)

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Revision Date 23-Mar-2025 **Revision Summary** Not applicable.

In accordance with local and national regulations: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet