# Thermo Fisher SCIENTIFIC

# SAFETY DATA SHEET

Page 1/9 Revision Date 09-May-2024 Version 4

AI FAA39170

# Tungsten(VI) ethoxide, 5% w/v in ethanol

## SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

产品说明: 乙醇钨(VI)

Product Description: Tungsten(VI) ethoxide, 5% w/v in ethanol

Cat No.: 39170

Molecular Formula C12 H30 O6 W

**Supplier** Avocado Research Chemicals Ltd.

(Part of Thermo Fisher Scientific)

Shore Road, Heysham Lancashire, LA3 2XY, United Kingdom

Office Tel: +44 (0) 1524 850506 Office Fax: +44 (0) 1524 850608

Emergency Telephone Number For information US call: 001-800-227-6701 / Europe call: +32 14 57 52 11

Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

**E-mail address** begel.sdsdesk@thermofisher.com

Recommended Use Laboratory chemicals.
Uses advised against No Information available

## **SECTION 2. HAZARD IDENTIFICATION**

Physical StateAppearanceOdorLiquidLight yellow - BrownAlcohol

**Emergency Overview** 

Highly flammable liquid and vapor. Causes mild skin irritation. Causes serious eye irritation. May cause respiratory irritation. Moisture sensitive.

#### Classification of the substance or mixture

Flammable liquids.	Category 2
Skin Corrosion/Irritation	Category 3
Serious Eye Damage/Eye Irritation	Category 2

## **Label Elements**



Signal Word Danger

Page 2/9 Revision Date 09-May-2024

## Tungsten(VI) ethoxide, 5% w/v in ethanol

#### **Hazard Statements**

H225 - Highly flammable liquid and vapor

H316 - Causes mild skin irritation

H319 - Causes serious eve irritation

H335 - May cause respiratory irritation

## **Precautionary Statements**

#### Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P233 - Keep container tightly closed

P240 - Ground and bond container and receiving equipment

P242 - Use non-sparking tools

P243 - Take action to prevent static discharges

P264 - Wash face, hands and any exposed skin thoroughly after handling

P280 - Wear protective gloves/protective clothing/eye protection/face protection

#### Response

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P337 + P313 - If eye irritation persists: Get medical advice/attention

P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

#### Storage

P403 + P235 - Store in a well-ventilated place. Keep cool

#### **Disposal**

P501 - Dispose of contents/ container to an approved waste disposal plant

#### **Physical and Chemical Hazards**

Vapors may cause flash fire or explosion. Highly flammable.

#### **Health Hazards**

Causes mild skin irritation. Causes serious eye irritation. May cause respiratory irritation.

#### **Environmental hazards**

Contains no substances known to be hazardous to the environment or not degradable in waste water treatment plants. Is not likely mobile in the environment due its low water solubility. Spillage unlikely to penetrate soil.

This product does not contain any known or suspected endocrine disruptors.

## **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS No	Weight %
Ethyl alcohol	64-17-5	95
Tungsten(VI) ethoxide	62571-53-3	5

## **SECTION 4. FIRST AID MEASURES**

## **General Advice**

If symptoms persist, call a physician.

## **Eve Contact**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

#### Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.

#### Inhalation

If not breathing, give artificial respiration. Remove to fresh air. Get medical attention if symptoms occur.

#### Ingestion

Clean mouth with water and drink afterwards plenty of water.

## Most important symptoms and effects

Page 3/9 Revision Date 09-May-2024

## Tungsten(VI) ethoxide, 5% w/v in ethanol

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation

#### Self-Protection of the First Aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

## **Notes to Physician**

Treat symptomatically. Symptoms may be delayed.

## **SECTION 5. FIRE-FIGHTING MEASURES**

## **Suitable Extinguishing Media**

Dry sand. Carbon dioxide (CO<sub>2</sub>). Powder. Do not use water or foam. CO<sub>2</sub>, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

# Extinguishing media which must not be used for safety reasons

No information available.

#### **Specific Hazards Arising from the Chemical**

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

## **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

## **Personal Precautions**

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.

## **Environmental Precautions**

Do not flush into surface water or sanitary sewer system. Should not be released into the environment. Do not allow material to contaminate ground water system.

#### Methods for Containment and Clean Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Refer to protective measures listed in Sections 8 and 13.

## **SECTION 7. HANDLING AND STORAGE**

#### Handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Ensure adequate ventilation. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

## **Storage**

Corrosives area. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame.

Page 4/9 Revision Date 09-May-2024

Tungsten(VI) ethoxide, 5% w/v in ethanol

Specific Use(s)

Use in laboratories

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Control Parameters**

Component	China	Taiwan	Thailand	Hong Kong
Ethyl alcohol	-	TWA: 1000 ppm	TWA: 1000 ppm	TWA: 1000 ppm
		TWA: 1880 mg/m <sup>3</sup>		TWA: 1880 mg/m <sup>3</sup>

Component	ACGIH TLV	OSHA PEL	NIOSH	The United Kingdom	European Union
Ethyl alcohol	STEL: 1000 ppm	(Vacated) TWA: 1000	IDLH: 3300 ppm	TWA: 1000 ppm TWA;	
		ppm	TWA: 1000 ppm	1920 mg/m <sup>3</sup> TWA	
		(Vacated) TWA: 1900	TWA: 1900 mg/m <sup>3</sup>	WEL - STEL: 3000	
		mg/m³		ppm STEL; 5760	
		TWA: 1000 ppm		mg/m³ STEL	
		TWA: 1900 mg/m <sup>3</sup>			

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

## Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. MDHS70 General methods for sampling airborne gases and vapours MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography MDHS 91 Metals and metalloids in workplace air by X-ray fluorescence spectrometry MDHS 99 Metals in air by ICP-AES

## **Exposure Controls**

#### **Engineering Measures**

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source.

## Personal protective equipment

**Eye Protection** Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Viton (R)	See manufacturers	-	EN 374	(minimum requirement)
	recommendations			

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection Long sleeved clothing

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Page 5/9 Revision Date 09-May-2024

Tungsten(VI) ethoxide, 5% w/v in ethanol

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: Organic gases and vapours filter low boiling organic solvent

Type AX Brown conforming to EN371 or Type A Brown conforming to EN14387

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure Small scale/Laboratory use

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

Liquid

Liquid

Vapors may form explosive mixtures with air

141

When RPE is used a face piece Fit Test should be conducted

**Hygiene Measures** Handle in accordance with good industrial hygiene and safety practice.

Prevent product from entering drains. Do not allow material to contaminate ground water **Environmental exposure controls** 

system.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Light yellow - Brown **Appearance** 

**Physical State** Liquid

Alcohol Odor

No data available **Odor Threshold** 

No information available pН

Melting Point/Range No data available No data available **Softening Point** No information available **Boiling Point/Range** 

17 °C / 62.6 °F **Flash Point** Method - No information available

**Evaporation Rate** No data available Flammability (solid,gas) Not applicable

No data available **Explosion Limits** 

**Vapor Pressure** 

23 hPa @ 20 °C **Vapor Density** No data available (Air = 1.0)

Specific Gravity / Density

No data available **Bulk Density** Not applicable

Water Solubility **Immiscible** 

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Component log Pow Ethyl alcohol -0.32

**Autoignition Temperature** No data available

**Decomposition Temperature** No data available No data available **Viscosity** 

**Explosive Properties** 

**Oxidizing Properties** No information available

C12 H30 O6 W Molecular Formula

454.21 **Molecular Weight** 

## **SECTION 10. STABILITY AND REACTIVITY**

Stability Moisture sensitive.

**Hazardous Reactions** None under normal processing. **Hazardous Polymerization** No information available.

Page 6 / 9 Revision Date 09-May-2024

Tungsten(VI) ethoxide, 5% w/v in ethanol

**Conditions to Avoid** Keep away from open flames, hot surfaces and sources of ignition.

Materials to avoid Oxidizing agent.

Hazardous Decomposition Products Carbon monoxide (CO<sub>2</sub>). Tungsten oxides.

# **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Product Information**

(a) acute toxicity;

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl alcohol	LD50 = 10470 mg/kg		LC50 = 117-125 mg/l (4h)
	OECD 401 (Rat)		OECD 403 (rat)
	3450 mg/kg ( Mouse )		20000 ppm/10H (rat)

(b) skin corrosion/irritation; No data available

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;

Respiratory No data available Skin No data available

Component	Test method	Test species	Study result
Ethyl alcohol	Mouse Ear Swelling Test (MEST)	mouse	non-sensitising
64-17-5 ( 95 )		mouse	non-sensitising
	OECD Test Guideline 429 Local Lymph Node Assay		· ·

(e) germ cell mutagenicity; No data available

Component	Test method	Test species	Study result
Ethyl alcohol	AMES test	in vitro	negative
64-17-5 ( 95 )	OECD Test Guideline 471 Bacteria		_
	Gene cell mutation		
	OECD Test Guideline 476	in vitro	negative
		Mammalian	_

(f) carcinogenicity; No data available

The table below indicates whether each agency has listed any ingredient as a carcinogen

(g) reproductive toxicity; No data available

Component	Test method	Test species / Duration	Study result
Ethyl alcohol 64-17-5 ( 95 )	OECD Test Guideline 416	Oral / mouse 2 Generation	NOAEL = 13.8 g/kg/day
04-17-3 ( 93 )	OECD Test Guideline 414	Inhalation / Rat	NOAEC = 16000 ppm

(h) STOT-single exposure; No data available

(i) STOT-repeated exposure; No data available

Page 7/9 Revision Date 09-May-2024

Tungsten(VI) ethoxide, 5% w/v in ethanol

**Target Organs** 

No information available.

(j) aspiration hazard;

Based on available data, the classification criteria are not met

delaved

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric layage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation

## **SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity effects** 

Contains a substance which is:. Toxic to aquatic organisms. The product contains following substances which are hazardous for the environment. May cause long-term adverse effects in the environment. Do not allow material to contaminate ground water system.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Ethyl alcohol	Fathead minnow	EC50 = 9268 mg/L/48h	EC50 (72h) = 275 mg/l	Photobacterium
	(Pimephales promelas)	EC50 = 10800 mg/L/24h	(Chlorella vulgaris)	phosphoreum:EC50 =
	LC50 = 14200 mg/l/96h			34634 mg/L/30 min
				Photobacterium
				phosphoreum:EC50 =
				35470 mg/l /5 min

Persistence and Degradability

Product contains heavy metals. Discharge into the environment must be avoided. Special

pre-treatment is necessary

**Persistence** 

Component	Degradability
Ethyl alcohol	OECD 301E = 94%
64-17-5 ( 95 )	

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

**Bioaccumulative Potential** 

May have some potential to bioaccumulate

May persist, based on information available.

Component	log Pow	Bioconcentration factor (BCF)
Ethyl alcohol	-0.32	No data available

Mobility in soil

Spillage unlikely to penetrate soil Is not likely mobile in the environment due its low water

solubility

64-17-5

**Endocrine Disruptor Information Persistent Organic Pollutant Ozone Depletion Potential** 

This product does not contain any known or suspected endocrine disruptors

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

## **SECTION 13. DISPOSAL CONSIDERATIONS**

Waste from Residues/Unused **Products** 

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

**Contaminated Packaging** 

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

Other Information

Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in

compliance with local regulations.

Page 8 / 9 Revision Date 09-May-2024

Tungsten(VI) ethoxide, 5% w/v in ethanol

## **SECTION 14. TRANSPORT INFORMATION**

#### **Road and Rail Transport**

**UN-No** UN1170

Proper Shipping Name Ethanol solution

Hazard Class 3
Packing Group ||

IMDG/IMO

**UN-No** UN1170

Proper Shipping Name Ethanol solution

Hazard Class 3
Packing Group II

<u>IATA</u>

**UN-No** UN1170

Proper Shipping Name Ethanol solution

Hazard Class 3 Packing Group II

Special Precautions for User No special precautions required

## **SECTION 15. REGULATORY INFORMATION**

## **International Inventories**

X = listed, China (IECSC), Europe (EINECS/ELINCS/NLP), U.S.A. (TSCA), Canada (DSL/NDSL), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), Korea (KECL).

Component	The Inventory of Hazardous Chemicals (2015		TCSI	IECSC	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	AICS	KECL
	Edition)	2012										
Ethyl alcohol	X	X	X	Х	200-578-6	Х	Х	Х	Х	Х	Х	KE-13217

## **National Regulations**

## **SECTION 16. OTHER INFORMATION**

Prepared By Health, Safety and Environmental Department

Revision Date 09-May-2024

**Revision Summary** New emergency telephone response service provider.

**Training Advice** 

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Page 9/9 Revision Date 09-May-2024

## Tungsten(VI) ethoxide, 5% w/v in ethanol

#### Legend

**CAS** - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b)

Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances **IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances AICS - Australian Inventory of Chemical Substances NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

PNEC - Predicted No Effect Concentration

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50% POW - Partition coefficient Octanol:Water vPvB - very Persistent, very Bioaccumulative

ICAO/IATA - International Civil Aviation Organization/International Air **Transport Association** 

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

OECD - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate VOC - (Volatile Organic Compound)

## Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

On basis of test data **Physical hazards** Calculation method **Health Hazards Environmental hazards** Calculation method

## **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**