

SAFETY DATA SHEET

Creation Date 01-Apr-2014 Revision Date 01-Apr-2014 Revision Number 2

1. Identification

Product Name Papanicolaou Stain EA-36

Cat No.: 22050314

Synonyms No information available

Recommended Use Laboratory chemicals.

Uses advised against No Information available

Details of the supplier of the safety data sheet

Company Emergency Telephone Number

Richard Állan Scientific Chemtrec ÚS: (800) 424-9300
A Subsidiary of Thermo Fisher Scientific Chemtrec EU: 001 (202) 483-7616

4481 Campus Drive Kalamazoo, MI 49008 Tel: (800) 522-7270

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Category 1
Specific target organ toxicity (single exposure) Category 1

Target Organs - Central nervous system (CNS), Optic nerve.

Specific target organ toxicity - (repeated exposure) Category 1

Target Organs - Kidney, Liver.

Label Elements

Signal Word

Danger

Hazard Statements

Extremely flammable liquid and vapor
May cause drowsiness or dizziness
Causes damage to organs
Causes damage to organs through prolonged or repeated exposure



Precautionary Statements

Prevention

Do not breathe dust/fume/gas/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Keep cool

Response

IF exposed: Call a POISON CENTER or doctor/physician

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

rire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other hazards

Poison, may be fatal or cause blindness if swallowed. Vapor harmful. Cannot be made non-poisonous. WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

Unknown Acute Toxicity

 $.?\ \%$ of the mixture consists of ingredients of unknown toxicity.

3. Composition / information on ingredients

Component	CAS-No	Weight %
Ethyl alcohol	64-17-5	80-85
Water	7732-18-5	10-15
Methyl alcohol	67-56-1	4-5
Isopropyl alcohol	67-63-0	4-5
Phosphotungstic acid	12067-99-1	<1
Eosin-Y Dye	17372-87-1	<1
Bismarck Brown Y	10114-58-6	<1
Fast green fcf	2353-45-9	<1

4. First-aid measures

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Obtain medical attention.

Inhalation Move to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth

resuscitation if victim ingested or inhaled the substance; induce artificial respiration with a

respiratory medical device. Immediate medical attention is required.

Ingestion Do not induce vomiting. Call a physician or Poison Control Center immediately.

Most important symptoms/effects Breathing difficulties. Inhalation of high vapor concentrations may cause symptoms like

headache, dizziness, tiredness, nausea and vomiting

Notes to Physician Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media CO 2, dry chemical, dry sand, alcohol-resistant foam. Cool closed containers exposed to fire

with water spray.

Unsuitable Extinguishing Media Water may be ineffective

Flash Point 20 °C / 68 °F

Method - No information available

Autoignition Temperature

Explosion Limits

No information available

Upper No data available
Lower No data available
Sensitivity to Mechanical Impact No information available
Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Keep product and empty container away from heat and sources of ignition.

Hazardous Combustion Products

Carbon monoxide (CO) Carbon dioxide (CO2) formaldehyde peroxides

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health	Flammability	Instability	Physical hazards
3	4	0	N/A

6. Accidental release measures

Personal Precautions Use personal protective equipment. Remove all sources of ignition. Take precautionary

measures against static discharges. Do not get in eyes, on skin, or on clothing.

Environmental Precautions Should not be released into the environment. See Section 12 for additional ecological

information.

Methods for Containment and Clean Remove all sources of ignition. Soak up with inert absorbent material. Take precautionary **Up** measures against static discharges. Keep in suitable, closed containers for disposal.

	7. Handling and storage
Handling	Use only under a chemical fume hood. Wear personal protective equipment. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not breathe vapors or spray mist. Do not get in eyes, on skin, or on clothing. Do not ingest.

StorageKeep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Flammables area.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethyl alcohol	STEL: 1000 ppm	(Vacated) TWA: 1000 ppm (Vacated) TWA: 1900 mg/m³ TWA: 1000 ppm TWA: 1900 mg/m³	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m³
Methyl alcohol	TWA: 200 ppm STEL: 250 ppm Skin	(Vacated) TWA: 200 ppm (Vacated) TWA: 260 mg/m³ (Vacated) STEL: 250 ppm (Vacated) STEL: 325 mg/m³ Skin TWA: 200 ppm TWA: 260 mg/m³	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m³ STEL: 250 ppm STEL: 325 mg/m³
Isopropyl alcohol	TWA: 200 ppm STEL: 400 ppm	(Vacated) TWA: 400 ppm (Vacated) TWA: 980 mg/m³ (Vacated) STEL: 500 ppm (Vacated) STEL: 1225 mg/m³ TWA: 400 ppm TWA: 980 mg/m³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m³ STEL: 500 ppm STEL: 1225 mg/m³

Component	Quebec	Mexico OEL (TWA)	Ontario TWAEV
Ethyl alcohol	TWA: 1000 ppm TWA: 1880 mg/m ³	TWA: 1000 ppm TWA: 1900 mg/m ³	STEL: 1000 ppm
Methyl alcohol	TWA: 200 ppm TWA: 262 mg/m³ STEL: 250 ppm STEL: 328 mg/m³ Skin	TWA: 200 ppm TWA: 260 mg/m³ STEL: 250 ppm STEL: 310 mg/m³	TWA: 200 ppm STEL: 250 ppm Skin
Isopropyl alcohol	TWA: 400 ppm TWA: 985 mg/m³ STEL: 500 ppm STEL: 1230 mg/m³	TWA: 400 ppm TWA: 980 mg/m³ STEL: 500 ppm STEL: 1225 mg/m³	TWA: 200 ppm STEL: 400 ppm

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Engineering MeasuresUse only under a chemical fume hood. Use explosion-proof

electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers

are close to the workstation location.

Personal Protective Equipment

Eye/face Protection Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State Liquid
Appearance Green to red
Odor Alcohol-like

Odor Threshold
pHNo information available
No information available

Melting Point/Range No data available

Boiling Point/Range Not applicable 20 °C / 68 °F **Flash Point**

Evaporation Rate No information available Flammability (solid,gas) No information available

Flammability or explosive limits

No data available Upper Lower No data available **Vapor Pressure** No information available

Vapor Density No information available **Relative Density** No information available Solubility Soluble in water

Partition coefficient; n-octanol/water No data available

Autoignition Temperature No information available **Decomposition Temperature** No information available **Viscosity** No information available

10. Stability and reactivity

Reactive Hazard None known, based on information available

Stable under normal conditions. Stability

Conditions to Avoid Incompatible products. Heat, flames and sparks.

Incompatible Materials Strong oxidizing agents, Acids, Acid anhydrides, Acid chlorides, Peroxides, Metals

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2), formaldehyde, peroxides

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information No acute toxicity information is available for this product

Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg. Oral LD50 Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg. **Dermal LD50** Based on ATE data, the classification criteria are not met. ATE > 20 mg/l. Vapor LC50

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl alcohol	7060 mg/kg (Rat)	Not listed	20000 ppm/10H (Rat)
Methyl alcohol	6200 mg/kg (Rat)	15800 mg/kg (Rabbit)	64000 ppm (Rat) 4 h
			22500 ppm (Rat) 8 h
Isopropyl alcohol	5840 mg/kg (Rat)	13900 mg/kg (Rat)	72.6 mg/L (Rat) 4 h
		12870 mg/kg (Rabbit)	
Phosphotungstic acid	3300 mg/kg (Rat)	Not listed	Not listed
Fast green fcf	2 g/kg (Rat)	Not listed	Not listed

Toxicologically Synergistic

No information available

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Irritating to eyes and skin Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Ethyl alcohol	64-17-5	Group 1	Not listed	A3	Х	Not listed

Hygienists)

| Water | 7732-18-5 | Not listed |
|----------------------|------------|------------|------------|------------|------------|------------|
| Methyl alcohol | 67-56-1 | Not listed |
| Isopropyl alcohol | 67-63-0 | Not listed |
| Phosphotungstic acid | 12067-99-1 | Not listed |
| Eosin-Y Dye | 17372-87-1 | Not listed |
| Bismarck Brown Y | 10114-58-6 | Not listed |
| Fast green fcf | 2353-45-9 | Not listed |

IARC: (International Agency for Research on Cancer)

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans

A1 - Known Human Carcinogen
A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

ACGIH: (American Conference of Governmental Industrial Hygienists)

Mutagenic Effects No information available

ACGIH: (American Conference of Governmental Industrial

Reproductive Effects Adverse reproductive effects have occurred in humans.

Developmental EffectsSubstances known to cause developmental toxicity in humans.

Teratogenicity Teratogenic effects have occurred in humans.

STOT - single exposure Central nervous system (CNS) Optic nerve

STOT - repeated exposure Kidney Liver

Aspiration hazard No information available

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

delayed tiredness, nausea and vomiting

Endocrine Disruptor Information No information available

Other Adverse Effects Tumorigenic effects have been reported in experimental animals. See actual entry in

RTECS for complete information.

12. Ecological information

Ecotoxicity

Do not empty into drains.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Ethyl alcohol	lcohol EC50 (72h) = 275 mg/l Fathead minnow		Photobacterium	EC50 = 9268 mg/L/48h
	(Chlorella vulgaris)	(Pimephales promelas)	phosphoreum:EC50 = 34634	EC50 = 10800 mg/L/24h
		LC50 = 14200 mg/l/96h	mg/L/30 min	
			Photobacterium	
			phosphoreum:EC50 = 35470	
			mg/L/5 min	
Methyl alcohol	Not listed	Pimephales promelas: LC50	EC50 = 39000 mg/L 25 min	EC50 > 10000 mg/L 24h
		> 10000 mg/L 96h	EC50 = 40000 mg/L 15 min	
			EC50 = 43000 mg/L 5 min	
Isopropyl alcohol	1000 mg/L EC50 > 96 h	1400000 µg/L LC50 96 h	= 35390 mg/L EC50	13299 mg/L EC50 = 48 h
	1000 mg/L EC50 > 72 h	11130 mg/L LC50 96 h 9640	Photobacterium	9714 mg/L EC50 = 24 h
		mg/L LC50 96 h	phosphoreum 5 min	

Persistence and Degradability Bioaccumulation/ Accumulation

No information available No information available.

Mobility

Component	log Pow
Ethyl alcohol	-0.32
Methyl alcohol	-0.74
Isopropyl alcohol	0.05

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes		
Methyl alcohol - 67-56-1	U154	-		

14. Transport information

DOT

UN-No UN1170

Proper Shipping Name ETHANOL SOLUTION

Hazard Class 3 Packing Group II

TDG

UN-No UN1170

Proper Shipping Name ETHANOL SOLUTION

Hazard Class 3
Packing Group ||

IATA

UN-No UN1170

Proper Shipping Name ETHANOL SOLUTION

Hazard Class 3
Packing Group ||

IMDG/IMO

UN-No UN1170

Proper Shipping Name ETHANOL SOLUTION

Hazard Class 3 Packing Group II

15. Regulatory information

International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Ethyl alcohol	Х	Х	-	200-578-6	-		Χ	Χ	Χ	Χ	Χ
Water	Х	X	-	231-791-2	-		Χ	-	Χ	Х	Χ
Methyl alcohol	Х	Х	-	200-659-6	-		Х	Χ	Х	Х	Χ
Isopropyl alcohol	Х	Х	-	200-661-7	-		Χ	Χ	Χ	Χ	Χ
Phosphotungstic acid	Х	X	-	235-087-6	-		Χ	Χ	Х	-	Χ
Eosin-Y Dye	Х	Χ	-	241-409-6	-		Χ	Χ	Χ	Χ	Χ
Bismarck Brown Y	Х	X	-	233-314-3	-		-	Χ	Х	-	Χ
Fast green fcf	Х	Х	-	219-091-5	-		Х	Χ	Χ	Х	Χ

Legend:

- X Listed
- E Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.
- F Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.
- N Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.
- P Indicates a commenced PMN substance
- R Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.
- S Indicates a substance that is identified in a proposed or final Significant New Use Rule
- T Indicates a substance that is the subject of a Section 4 test rule under TSCA.
- XU Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).
- Y1 Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.
- Y2 Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b)

Not applicable

SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Methyl alcohol	67-56-1	4-5	1.0
Isopropyl alcohol	67-63-0	4-5	1.0

SARA 311/312 Hazardous Categorization

Acute Health HazardYesChronic Health HazardYesFire HazardYesSudden Release of Pressure HazardNoReactive HazardNo

Clean Water Act Not applicable

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Methyl alcohol	X		-

OSHA Occupational Safety and Health Administration

Not applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Methyl alcohol	5000 lb	-

California Proposition 65

This product contains the following Proposition 65 chemicals: Ethyl alcohol is only a considered a Proposition 65 developmental hazard when it is ingested as an alcoholic beverage

Component	CAS-No	California Prop. 65	Prop 65 NSRL	Category
Ethyl alcohol	64-17-5	Developmental	-	Developmental Carcinogen
Methyl alcohol	67-56-1	Developmental	-	Developmental

State Right-to-Know

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Ethyl alcohol	X	X	X	X	Х
Water	-	-	X	-	-
Methyl alcohol	X	X	X	X	X
Isopropyl alcohol	X	X	X	-	X

U.S. Department of Transportation

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade No information available

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

WHMIS Hazard Class

B2 Flammable liquid D1B Toxic materials D2A Very toxic materials



16. Other information

Prepared By Regulatory Affairs

Richard Allan Scientific

A Subsidiary of Thermo Fisher Scientific

Tel: (800) 522-7270

 Creation Date
 01-Apr-2014

 Revision Date
 01-Apr-2014

 Print Date
 01-Apr-2014

Revision Summary

This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Harmonized System of Classification and Labeling of Chemicals (GHS)

Disclaimer

The information provided on this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of SDS