

SAFETY DATA SHEET

Creation Date 13-April-2009 Revision Date 28-December-2021 **Revision Number** 7

1. Identification

Product Name 2-Butanone

AC444170000: AC444170050 Cat No.:

CAS-No

Synonyms Methyl ethyl ketone; MEK; Ethyl methyl ketone

Recommended Use Laboratory chemicals.

Food, drug, pesticide or biocidal product use. Uses advised against

Details of the supplier of the safety data sheet

Company

Manufacturer Importer/Distributor

Acros Organics Fisher Scientific Company Fisher Scientific One Reagent Lane 112 Colonnade Road. One Reagent Lane Fair Lawn, NJ 07410 Fair Lawn, NJ 07410 Ottawa, ON K2E 7L6, Tel: (201) 796-7100

Canada

Tel: 1-800-234-7437

Emergency Telephone Number For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11

Emergency Number US:001-201-796-7100 / Europe: +32 14 57 52 99 CHEMTREC Tel. No.US:001-800-424-9300 / Europe:001-703-527-3887

2. Hazard(s) identification

Classification

WHMIS 2015 Classification Classified as hazardous under the Hazardous Products Regulations (SOR/2015-17)

Flammable liquids Category 2 Serious Eye Damage/Eye Irritation Category 2 Specific target organ toxicity (single exposure) Category 3 Target Organs - Central nervous system (CNS).

Specific target organ toxicity - (repeated exposure) Category 2

Target Organs - Kidney, Liver.

Health Hazards Not Otherwise Classified Category 1 Prolonged or repeated contact may dry skin and cause irritation or cracking

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor
Causes serious eye irritation
May cause drowsiness and dizziness
May cause damage to organs through prolonged or repeated exposure
Prolonged or repeated contact may dry skin and cause irritation or cracking



Precautionary Statements

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharges

Do not breathe dust/fumes/gas/mist/vapours/spray

Wash face, hands and any exposed skin thoroughly after handling

Use only outdoors or in a well-ventilated area

Wear protective gloves/protective clothing/eye protection/face protection

Response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

IF INHALED: Remove person to fresh air and keep comfortable for breathing

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Call a POISON CENTER/ doctor if you feel unwell

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Disposal

Dispose of contents/container to an approved waste disposal plant

Other Hazards

Contains a known or suspected endocrine disruptor

3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Methyl ethyl ketone	78-93-3	>95

4. First-aid measures	4. First-aid measures	
-----------------------	-----------------------	--

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Get medical attention if

symptoms occur.

Inhalation Remove to fresh air. Get medical attention if symptoms occur. If not breathing, give artificial

respiration.

Ingestion Do NOT induce vomiting. Get medical attention.

Most important symptoms/effects Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness,

nausea and vomiting: Inhalation of high vapor concentrations may cause symptoms like

headache, dizziness, tiredness, nausea and vomiting

Notes to Physician Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool

closed containers.

Unsuitable Extinguishing Media Water may be ineffective

Flash Point -7 °C / 19.4 °F

Method - CC (closed cup)

Autoignition Temperature 404 °C / 759.2 °F

Explosion Limits

Upper 11.4 vol %
Lower 1.4 vol %
Oxidizing Properties Not oxidising

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO2).

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

HealthFlammabilityInstabilityPhysical hazards231N/A

6. Accidental release measures

Personal Precautions Use personal protective equipment as required. Remove all sources of ignition. Take

precautionary measures against static discharges. Avoid contact with skin, eyes or clothing.

Ensure adequate ventilation.

Environmental Precautions Avoid release to the environment. See Section 12 for additional Ecological Information.

Methods for Containment and Clean Remove all sources of ignition. Soak up with inert absorbent material. Keep in suitable, **Up** closed containers for disposal. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage

Handling Wear personal protective equipment/face protection. Ensure adequate ventilation. Use

spark-proof tools and explosion-proof equipment. Avoid contact with skin, eyes or clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of

ignition. Take precautionary measures against static discharges. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Storage.

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area. Incompatible Materials. Strong oxidizing agents. Strong acids. Strong bases. Strong reducing agents. Ammonia. copper. Amines.

8. Exposure controls / personal protection

Exposure Guidelines

Component	Alberta	British	Ontario TWAEV	Quebec	ACGIH TLV	OSHA PEL	NIOSH IDLH
		Columbia					
Methyl ethyl ketone	TWA: 200 ppm	TWA: 50 ppm	TWA: 200 ppm	TWA: 50 ppm	TWA: 200 ppm	(Vacated) TWA:	IDLH: 3000 ppm
	TWA: 590	STEL: 100 ppm	STEL: 300 ppm	TWA: 150	STEL: 300 ppm	200 ppm	TWA: 200 ppm
	mg/m³			mg/m³		(Vacated) TWA:	TWA: 590
	STEL: 300 ppm			STEL: 100 ppm		590 mg/m ³	mg/m³
	STEL: 885			STEL: 300		(Vacated) STEL:	STEL: 300 ppm
	mg/m³			mg/m³		300 ppm	STEL: 885
						(Vacated) STEL:	mg/m³
						885 mg/m ³	
						TWA: 200 ppm	
						TWA: 590	
						mg/m³	

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles

Hand Protection Wear appropriate protective gloves and clothing to prevent skin exposure.

Glove material	Breakthrough time	Glove thickness	Glove comments
Butyl rubber	< 60 minutes	0.5 mm	Permeation rate 36 µg/cm2/min
			As tested under EN374-3
			Determination of Resistance to
			Permeation by Chemicals

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Recommended Filter type: Type A Organic gases and vapours filter Brown conforming to EN14387

Environmental exposure controls

No information available.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

9. Physical and chemical properties

Physical State Liquid
Appearance Colorless

Odor Characteristic - sweet
Odor Threshold No information available

pH No information available

Melting Point/Range -87 °C / -124.6 °F

Boiling Point/Range 80 °C / 176 °F

Flash Point -7 °C / 19.4 °F

Method - CC (closed cup)
Evaporation Rate 3.7

Flammability (solid,gas)

Not applicable

Flammability or explosive limits

 Upper
 11.4 vol %

 Lower
 1.4 vol %

Vapor Pressure105 mbar @ 20 °CVapor Density2.41

Vapor Density 2.41 Specific Gravity 0.806

Solubility

Partition coefficient; n-octanol/water

Autoignition Temperature

Pecomposition Temperature

Viscosity

Soluble in water

No data available

404 °C / 759.2 °F

No information available

0.42 mPa.s @ 15°C

Molecular FormulaC4 H8 OMolecular Weight72.11

10. Stability and reactivity

Reactive Hazard None known, based on information available

Stability Hygroscopic.

Conditions to Avoid Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition. Exposure to moist air or water.

Incompatible Materials Strong oxidizing agents, Strong acids, Strong bases, Strong reducing agents, Ammonia,

copper, Amines

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2)

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information Component Information

2-Butanone

Methyl ethyl ketone	LD50 = 2483 mg/kg (Rat)	LD50 = 5000 mg/kg (Rabbit)	LC50 = 11700 ppm (Rat) 4 h

Toxicologically Synergistic

No information available

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Irritating to eyes

Sensitization No information available

The table below indicates whether each agency has listed any ingredient as a carcinogen. Carcinogenicity

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Methyl ethyl ketone	78-93-3	Not listed				

Mutagenic Effects Not mutagenic in AMES Test

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure Central nervous system (CNS)

STOT - repeated exposure Kidney Liver

Aspiration hazard No information available

delayed

Symptoms / effects,both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Methyl ethyl ketone	Not listed	Lepomis macrochirus: LC50=3,22 g/L 96 h	EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min	EC50: = 5091 mg/L, 48h (Daphnia magna) EC50: 4025 - 6440 mg/L, 48h Static (Daphnia magna) EC50: > 520 mg/L, 48h (Daphnia magna)

Persistence and Degradability Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility Will likely be mobile in the environment due to its volatility.

Component	log Pow
Methyl ethyl ketone	0.29

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

2-Butanone

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Methyl ethyl ketone - 78-93-3	U159	=

14. Transport information

DOT

UN-No UN1193

Proper Shipping Name Ethyl methyl ketone

Hazard Class 3
Packing Group ||

_TDG

UN-No UN1193

Proper Shipping Name ETHYL METHYL KETONE

Hazard Class 3
Packing Group ||

<u>IATA</u>

UN-No UN1193

Proper Shipping Name Methyl ethyl ketone

Hazard Class 3 Packing Group II

IMDG/IMO

UN-No UN1193

Proper Shipping Name Ethyl methyl ketone (Methyl ethyl ketone)

Hazard Class 3 Packing Group II

15. Regulatory information

International Inventories

Component	CAS-No	DSL	NDSL	TSCA	TSCA Inventory notification - Active-Inactive	EINECS	ELINCS	NLP
Methyl ethyl ketone	78-93-3	X	-	Х	ACTIVE	201-159-0	-	-
	•	•				•		

	Component	CAS-No	IECSC	KECL	ENCS	ISHL	TCSI	AICS	NZIoC	PICCS
Г	Methyl ethyl ketone	78-93-3	Х	KE-24094	Х	X	X	Х	X	Х

Legend:

X - Listed '-' - Not Listed

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

Canada

SDS in compliance with provisions of information as set out in Canadian Standard - Part 4, Schedule 1 and 2 of the Hazardous Products Regulations (HPR) and meets the requirements of the HPR (Paragraph 13(1)(a) of the Hazardous Products Act (HPA)).

Component	Canada - National Pollutant Release Inventory (NPRI)	Canadian Environmental Protection Agency (CEPA) - List of Toxic Substances	Canada's Chemicals Management Plan (CEPA)
Methyl ethyl ketone	Part 1, Group A Substance		
	Part 5, Individual Substances Part 4		
	Substance		

Other International Regulations

Authorisation/Restrictions according to EU REACH

Component	. ,	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	• • • • • • • • • • • • • • • • • • • •
Methyl ethyl ketone	-	Use restricted. See item 75. (see link for restriction details)	-

https://echa.europa.eu/substances-restricted-under-reach

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS-No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Methyl ethyl ketone	78-93-3	Listed	Not applicable	Not applicable	Not applicable
Component	CAS-No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Methyl ethyl ketone	78-93-3	Not applicable	Not applicable	Not applicable	Annex I - Y42

16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

Creation Date13-April-2009Revision Date28-December-2021Print Date28-December-2021

Revision Summary This document has been updated to comply with the requirements of WHMIS 2015 to align

with the Globally Harmonised System (GHS) for the Classification and Labelling of

Chemicals.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS