

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Copper based medium temperature water gas shift catalyst, HiFUEL® W230
Cat No. : 45470

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

Thermo Fisher (Kandel) GmbH
Erlenbachweg 2, 76870 Kandel, Germany
Tel: +49 (0) 721 84007 280
Fax: +49 (0) 721 84007 300

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
<https://www.fishersci.ch/ch/en/customer-help-support/forms/email-us.html>

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

SAFETY DATA SHEET

Copper based medium temperature water gas shift catalyst, HiFUEL® W230

Revision Date 17-Mar-2024

Based on available data, the classification criteria are not met

Health hazards

Based on available data, the classification criteria are not met

Environmental hazards

Acute aquatic toxicity
Chronic aquatic toxicity

Category 1 (H400)
Category 1 (H410)

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Warning

Hazard Statements

H410 - Very toxic to aquatic life with long lasting effects

Precautionary Statements

P273 - Avoid release to the environment

P391 - Collect spillage

P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other hazards

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Copper oxide (CuO)	1317-38-0	EEC No. 215-269-1	64.2	Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)
Zinc oxide (ZnO)	1314-13-2	215-222-5	24.5	Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)
Aluminum oxide (Al ₂ O ₃)	1344-28-1	215-691-6	9.8	-
Magnesium oxide (MgO)	1309-48-4	EEC No. 215-171-9	1.5	-

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Copper oxide (CuO)	-	100 (acute) 10 (chronic)	-
Zinc oxide (ZnO)	-	10	-

SAFETY DATA SHEET

Copper based medium temperature water gas shift catalyst, HiFUEL® W230

Revision Date 17-Mar-2024

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	If symptoms persist, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Get medical attention if symptoms occur.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.
Self-Protection of the First Aider	No special precautions required.

4.2. Most important symptoms and effects, both acute and delayed

None reasonably foreseeable.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media
Not combustible.

Extinguishing media which must not be used for safety reasons
No information available.

5.2. Special hazards arising from the substance or mixture

Do not allow run-off from fire-fighting to enter drains or water courses.

Hazardous Combustion Products
Metal oxides.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Avoid dust formation.

6.2. Environmental precautions

SAFETY DATA SHEET

Copper based medium temperature water gas shift catalyst, HiFUEL® W230

Revision Date 17-Mar-2024

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained. Should not be released into the environment.

6.3. Methods and material for containment and cleaning up

Sweep up and shovel into suitable containers for disposal. Keep in suitable, closed containers for disposal.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Avoid ingestion and inhalation. Avoid dust formation. Do not get in eyes, on skin, or on clothing.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Storage Class/LGK 13

Switzerland - Storage of hazardous substances

Storage class - SC 11/13
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Copper oxide (CuO)		STEL: 2 mg/m ³ 15 min TWA: 1 mg/m ³ 8 hr			TWA / VLA-ED: 0.01 mg/m ³ (8 horas)
Zinc oxide (ZnO)			TWA / VME: 5 mg/m ³ (8 heures). TWA / VME: 10 mg/m ³ (8 heures).	TWA: 2 mg/m ³ 8 uren STEL: 10 mg/m ³ 15 minuten	STEL / VLA-EC: 10 mg/m ³ (15 minutos). TWA / VLA-ED: 2 mg/m ³ (8 horas)
Aluminum oxide (Al ₂ O ₃)		STEL: 30 mg/m ³ 15 min STEL: 12 mg/m ³ 15 min TWA: 10 mg/m ³ 8 hr TWA: 4 mg/m ³ 8 hr	TWA / VME: 10 mg/m ³ (8 heures).	TWA: 1 mg/m ³ 8 uren	TWA / VLA-ED: 10 mg/m ³ (8 horas) TWA / VLA-ED: 1 mg/m ³ (8 horas)

SAFETY DATA SHEET

Copper based medium temperature water gas shift catalyst, HiFUEL® W230

Revision Date 17-Mar-2024

Magnesium oxide (MgO)		STEL: 30 mg/m ³ 15 min STEL: 12 mg/m ³ 15 min TWA: 10 mg/m ³ 8 hr TWA: 4 mg/m ³ 8 hr	TWA / VME: 10 mg/m ³ (8 heures).	TWA: 10 mg/m ³ 8 uren	TWA / VLA-ED: 10 mg/m ³ (8 horas)
-----------------------	--	---	---	----------------------------------	--

Component	Italy	Germany	Portugal	The Netherlands	Finland
Copper oxide (CuO)		TWA: 0.01 mg/m ³ (8 Stunden). MAK Höhepunkt: 0.02 mg/m ³			TWA: 0.02 mg/m ³ 8 tunteina
Zinc oxide (ZnO)		TWA: 0.1 mg/m ³ (8 Stunden). MAK TWA: 2 mg/m ³ (8 Stunden). MAK Höhepunkt: 0.4 mg/m ³ Höhepunkt: 4 mg/m ³	STEL: 10 mg/m ³ 15 minutos TWA: 2 mg/m ³ 8 horas		TWA: 2 mg/m ³ 8 tunteina STEL: 10 mg/m ³ 15 minuutteina
Aluminum oxide (Al ₂ O ₃)		TWA: 1.25 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 10 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 4 mg/m ³ (8 Stunden). MAK TWA: 1.5 mg/m ³ (8 Stunden). MAK	TWA: 1 mg/m ³ 8 horas		
Magnesium oxide (MgO)		TWA: 1.25 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 10 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 0.3 mg/m ³ (8 Stunden). MAK multiplied by the material density TWA: 4 mg/m ³ (8 Stunden). MAK Höhepunkt: 2.4 mg/m ³	TWA: 10 mg/m ³ 8 horas		

Component	Austria	Denmark	Switzerland	Poland	Norway
Copper oxide (CuO)	MAK-KZGW: 4 mg/m ³ 15 Minuten MAK-KZGW: 0.4 mg/m ³ 15 Minuten MAK-TMW: 1 mg/m ³ 8 Stunden MAK-TMW: 0.1 mg/m ³ 8 Stunden		STEL: 0.2 mg/m ³ 15 Minuten TWA: 0.1 mg/m ³ 8 Stunden		
Zinc oxide (ZnO)	MAK-TMW: 5 mg/m ³ 8 Stunden	TWA: 4 mg/m ³ 8 timer STEL: 8 mg/m ³ 15 minutter	STEL: 3 mg/m ³ 15 Minuten TWA: 3 mg/m ³ 8 Stunden	STEL: 10 mg/m ³ 15 minutach TWA: 5 mg/m ³ 8 godzinach	TWA: 5 mg/m ³ 8 timer STEL: 10 mg/m ³ 15 minutter. value calculated
Aluminum oxide (Al ₂ O ₃)	MAK-KZGW: 10 mg/m ³ 15 Minuten MAK-TMW: 5 mg/m ³ 8 Stunden	TWA: 5 mg/m ³ 8 timer TWA: 2 mg/m ³ 8 timer STEL: 10 mg/m ³ 15 minutter STEL: 4 mg/m ³ 15 minutter	STEL: 24 mg/m ³ 15 Minuten TWA: 3 mg/m ³ 8 Stunden TWA: 10 mg/m ³ 8 Stunden	TWA: 2.5 mg/m ³ 8 godzinach TWA: 1.2 mg/m ³ 8 godzinach	TWA: 10 mg/m ³ 8 timer STEL: 20 mg/m ³ 15 minutter. set equal to the limit value for Nuisance dust;value calculated
Magnesium oxide (MgO)	MAK-KZGW: 20 mg/m ³ 15 Minuten MAK-KZGW: 10 mg/m ³ 15 Minuten MAK-TMW: 5 mg/m ³ 8 Stunden MAK-TMW: 10 mg/m ³ 8 Stunden	TWA: 6 mg/m ³ 8 timer STEL: 12 mg/m ³ 15 minutter	TWA: 3 mg/m ³ 8 Stunden TWA: 10 mg/m ³ 8 Stunden	TWA: 10 mg/m ³ 8 godzinach	TWA: 10 mg/m ³ 8 timer STEL: 20 mg/m ³ 15 minutter. set equal to the limit value for Nuisance dust;value calculated

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Zinc oxide (ZnO)	TWA: 5.0 mg/m ³ STEL : 10.0 mg/m ³	TWA-GVI: 2 mg/m ³ 8 satima. respirable dust STEL-KGVI: 10 mg/m ³ 15 minutama.	TWA: 2 mg/m ³ 8 hr. fume; respirable fraction STEL: 10 mg/m ³ 15 min		TWA: 2 mg/m ³ 8 hodinách. Zn Ceiling: 5 mg/m ³ Zn

SAFETY DATA SHEET

Copper based medium temperature water gas shift catalyst, HiFUEL® W230

Revision Date 17-Mar-2024

Aluminum oxide (Al ₂ O ₃)		TWA-GVI: 10 mg/m ³ 8 satima. total dust, inhalable particles TWA-GVI: 4 mg/m ³ 8 satima. respirable dust			
Magnesium oxide (MgO)	TWA: 10.0 mg/m ³	TWA-GVI: 4 mg/m ³ 8 satima. fume; respirable dust TWA-GVI: 10 mg/m ³ 8 satima. fume; total dust, inhalable particles	TWA: 4 mg/m ³ 8 hr. respirable dust TWA: 5 mg/m ³ 8 hr. fume TWA: 10 mg/m ³ 8 hr. total inhalable dust STEL: 10 mg/m ³ 15 min STEL: 12 mg/m ³ 15 min STEL: 30 mg/m ³ 15 min		TWA: 5 mg/m ³ 8 hodinách. fume Ceiling: 10 mg/m ³ fume

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Zinc oxide (ZnO)	TWA: 5 mg/m ³ 8 tundides.		STEL: 10 mg/m ³ TWA: 5 mg/m ³	TWA: 5 mg/m ³ 8 óraban. AK	TWA: 4 mg/m ³ 8 klukkustundum. Zn including fume Ceiling: 8 mg/m ³ Zn including fume
Aluminum oxide (Al ₂ O ₃)	TWA: 10 mg/m ³ 8 tundides. total dust TWA: 4 mg/m ³ 8 tundides. respirable dust		TWA: 10 mg/m ³ TWA: 5 mg/m ³	TWA: 5 mg/m ³ 8 óraban. AK Al TWA: 2 mg/m ³ 8 óraban. AK Al	TWA: 10 mg/m ³ 8 klukkustundum. Al Ceiling: 20 mg/m ³ Al
Magnesium oxide (MgO)			TWA: 10 mg/m ³ TWA: 5 mg/m ³	TWA: 6 mg/m ³ 8 óraban. AK	TWA: 6 mg/m ³ 8 klukkustundum. Mg Ceiling: 12 mg/m ³ Mg

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Zinc oxide (ZnO)	TWA: 0.5 mg/m ³	TWA: 5 mg/m ³ IPRD			TWA: 5 mg/m ³ 8 ore STEL: 10 mg/m ³ 15 minute
Aluminum oxide (Al ₂ O ₃)	TWA: 6 mg/m ³	TWA: 5 mg/m ³ inhalable fraction IPRD Al TWA: 2 mg/m ³ respirable fraction IPRD Al			TWA: 2 mg/m ³ 8 ore TWA: 3 mg/m ³ 8 ore TWA: 1 mg/m ³ 8 ore STEL: 5 mg/m ³ 15 minute STEL: 10 mg/m ³ 15 minute STEL: 3 mg/m ³ 15 minute
Magnesium oxide (MgO)		TWA: 4 mg/m ³ IPRD			TWA: 5 mg/m ³ 8 ore STEL: 15 mg/m ³ 15 minute

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Zinc oxide (ZnO)	TWA: 0.5 mg/m ³ 2345 MAC: 1.5 mg/m ³	Ceiling: 1 mg/m ³ TWA: 1 mg/m ³ fume		TLV: 5 mg/m ³ 8 timmar. NGV	
Aluminum oxide (Al ₂ O ₃)	TWA: 6 mg/m ³ 0043 in the form of disintegration aerosol TWA: 1 mg/m ³ 0045 containing up to 20% Cr ₂ O ₃ ; catalyst IM-2201 MAC: 3 mg/m ³	TWA: 4 mg/m ³ inhalable dust TWA: 1.5 mg/m ³ respirable dust		TLV: 5 mg/m ³ 8 timmar. AI NGV TLV: 2 mg/m ³ 8 timmar. AI NGV	
Magnesium oxide (MgO)	MAC: 4 mg/m ³	TWA: 10 mg/m ³ respirable fraction, dust TWA: 4 mg/m ³ inhalable fraction, fume			

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Monitoring methods

SAFETY DATA SHEET

Copper based medium temperature water gas shift catalyst, HiFUEL® W230

Revision Date 17-Mar-2024

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust

MDHS 91 Metals and metalloids in workplace air by X-ray fluorescence spectrometry

MDHS 99 Metals in air by ICP-AES

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Zinc oxide (ZnO) 1314-13-2 (24.5)				DNEL = 83mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Zinc oxide (ZnO) 1314-13-2 (24.5)			DNEL = 0.5mg/m ³	DNEL = 5mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Zinc oxide (ZnO) 1314-13-2 (24.5)	PNEC = 20.6µg/L	PNEC = 117.8mg/kg sediment dw		PNEC = 100µg/L	PNEC = 35.6mg/kg soil dw
Aluminum oxide (Al ₂ O ₃) 1344-28-1 (9.8)	PNEC = 0.3136µg/L		PNEC = 3.136µg/L	PNEC = 20mg/L	

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Zinc oxide (ZnO) 1314-13-2 (24.5)	PNEC = 6.1µg/L	PNEC = 56.5mg/kg sediment dw			

8.2. Exposure controls

Engineering Measures

None under normal use conditions.

Personal protective equipment

Eye Protection

Wear safety glasses with side shields (or goggles) (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Natural rubber Nitrile rubber Neoprene PVC	See manufacturers recommendations	-	EN 374	(minimum requirement)

Skin and body protection

Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

No protective equipment is needed under normal use conditions.

SAFETY DATA SHEET

Copper based medium temperature water gas shift catalyst, HiFUEL® W230

Revision Date 17-Mar-2024

Large scale/emergency use	Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced Recommended Filter type: Particle filter
Small scale/Laboratory use	Maintain adequate ventilation
Environmental exposure controls	Prevent product from entering drains. Do not allow material to contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Solid Pellets	
Appearance		
Odor	No information available	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flammability (liquid)	Not applicable	Solid
Flammability (solid,gas)	No information available	
Explosion Limits	No data available	
Flash Point	No information available	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	Not applicable	Solid
Water Solubility	Insoluble in water	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Vapor Pressure	No data available	
Density / Specific Gravity	No data available	
Bulk Density	No data available	
Vapor Density	Not applicable	Solid
Particle characteristics	No data available	

9.2. Other information

Evaporation Rate	Not applicable - Solid
------------------	------------------------

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization	No information available.
Hazardous Reactions	None under normal processing.

10.4. Conditions to avoid

Incompatible products. Excess heat.

SAFETY DATA SHEET

Copper based medium temperature water gas shift catalyst, HiFUEL® W230

Revision Date 17-Mar-2024

10.5. Incompatible materials

Oxidizing agent.

10.6. Hazardous decomposition products

Metal oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

No data available

Inhalation

No data available

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Copper oxide (CuO)	-	LD50 > 2000 mg/kg (Rat)	-
Zinc oxide (ZnO)	LD50 > 5000 mg/kg (Rat)	LD50 > 2000 mg/kg, 24h (Rat)	LC50 > 5.7 mg/L, 4h (Rat)
Aluminum oxide (Al2O3)	> 5000 mg/kg (Rat) (OECD Guideline 401)	-	> 2.3 mg/l 4 h (OECD Guideline 403)
Magnesium oxide (MgO)	LD50 = 3990 mg/kg (Rat) LD50 = 3870 mg/kg (Rat)	-	-

(b) skin corrosion/irritation;

No data available

(c) serious eye damage/irritation;

No data available

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

No data available

Component	Test method	Test species	Study result
Zinc oxide (ZnO) 1314-13-2 (24.5)	in vivo OECD Test Guideline 406 Test method B.6	guinea pig	non-sensitising

(e) germ cell mutagenicity;

No data available

Component	Test method	Test species	Study result
Zinc oxide (ZnO) 1314-13-2 (24.5)	in vitro OECD Test Guideline 471 Bacterial Reverse Mutation Test	in vitro: Bacteria	negative
	in vivo OECD Test Guideline 474 Mammalian	in vivo Mammalian	negative

(f) carcinogenicity;

No data available

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Aluminum oxide (Al2O3)			Cat. 2 (Fibre dust)	

SAFETY DATA SHEET

Copper based medium temperature water gas shift catalyst, HiFUEL® W230

Revision Date 17-Mar-2024

- (g) reproductive toxicity; No data available
- (h) STOT-single exposure; No data available
- (i) STOT-repeated exposure; No data available
- Target Organs No information available.
- (j) aspiration hazard; Not applicable
Solid

Symptoms / effects, both acute and delayed No information available.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

The product contains following substances which are hazardous for the environment. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. May cause long-term adverse effects in the environment. Do not allow material to contaminate ground water system.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Copper oxide (CuO)	Onchorhynchus mykiss: LC50: 25 mg/L/48h	Daphnia: EC50: 0.04 mg/L/48h	
Zinc oxide (ZnO)	LC50: = 1.55 mg/L, 96h static (Danio rerio)		

Component	Microtox	M-Factor
Copper oxide (CuO)		100 (acute) 10 (chronic)
Zinc oxide (ZnO)		10

12.2. Persistence and degradability

Persistence
Degradability
Degradation in sewage treatment plant

Product contains heavy metals. Discharge into the environment must be avoided. Special pre-treatment is necessary
Insoluble in water, May persist.
Not relevant for inorganic substances.
Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential

May have some potential to bioaccumulate; Product has a high potential to bioconcentrate

12.4. Mobility in soil

Spillage unlikely to penetrate soil Is not likely mobile in the environment due its low water solubility.

12.5. Results of PBT and vPvB assessment

No data available for assessment.

SAFETY DATA SHEET

Copper based medium temperature water gas shift catalyst, HiFUEL® W230

Revision Date 17-Mar-2024

12.6. Endocrine disrupting properties

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant This product does not contain any known or suspected substance
Ozone Depletion Potential This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products Should not be released into the environment. Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Do not empty into drains. Do not let this chemical enter the environment.

Switzerland - Waste Ordinance Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number UN3077
14.2. UN proper shipping name Environmentally hazardous substances, solid, n.o.s.
14.3. Transport hazard class(es) 9
14.4. Packing group III

ADR

14.1. UN number UN3077
14.2. UN proper shipping name Environmentally hazardous substances, solid, n.o.s.
14.3. Transport hazard class(es) 9
14.4. Packing group III

IATA

14.1. UN number UN3077
14.2. UN proper shipping name Environmentally hazardous substances, solid, n.o.s.
14.3. Transport hazard class(es) 9
14.4. Packing group III

14.5. Environmental hazards Dangerous for the environment
Product is a marine pollutant according to the criteria set by IMDG/IMO

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk Not applicable, packaged goods

SAFETY DATA SHEET

Copper based medium temperature water gas shift catalyst, HiFUEL® W230

Revision Date 17-Mar-2024

according to IMO instruments

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Copper oxide (CuO)	1317-38-0	215-269-1	-	-	X	X	KE-08942	X	X
Zinc oxide (ZnO)	1314-13-2	215-222-5	-	-	X	X	KE-35565	X	X
Aluminum oxide (Al ₂ O ₃)	1344-28-1	215-691-6	-	-	X	X	KE-01012	X	X
Magnesium oxide (MgO)	1309-48-4	215-171-9	-	-	X	X	KE-22728	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Copper oxide (CuO)	1317-38-0	X	ACTIVE	X	-	X	X	X
Zinc oxide (ZnO)	1314-13-2	X	ACTIVE	X	-	X	X	X
Aluminum oxide (Al ₂ O ₃)	1344-28-1	X	ACTIVE	X	-	X	X	X
Magnesium oxide (MgO)	1309-48-4	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Copper oxide (CuO)	1317-38-0	-	-	-
Zinc oxide (ZnO)	1314-13-2	-	Use restricted. See item 75. (see link for restriction details)	-
Aluminum oxide (Al ₂ O ₃)	1344-28-1	-	-	-
Magnesium oxide (MgO)	1309-48-4	-	-	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Copper oxide (CuO)	1317-38-0	Not applicable	Not applicable
Zinc oxide (ZnO)	1314-13-2	Not applicable	Not applicable
Aluminum oxide (Al ₂ O ₃)	1344-28-1	Not applicable	Not applicable
Magnesium oxide (MgO)	1309-48-4	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

SAFETY DATA SHEET

Copper based medium temperature water gas shift catalyst, HiFUEL® W230

Revision Date 17-Mar-2024

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 3 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Copper oxide (CuO)	WGK 3	
Zinc oxide (ZnO)	WGK2	
Aluminum oxide (Al ₂ O ₃)	nwg	
Magnesium oxide (MgO)	WGK1	

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Magnesium oxide (MgO) 1309-48-4 (1.5)	Prohibited and Restricted Substances		

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

SAFETY DATA SHEET

Copper based medium temperature water gas shift catalyst, HiFUEL® W230

Revision Date 17-Mar-2024

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health Hazards	Calculation method
Environmental hazards	Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Chemical incident response training.

Prepared By	Health, Safety and Environmental Department
Revision Date	17-Mar-2024
Revision Summary	New emergency telephone response service provider.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No
1907/2006 .**

**For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2,
Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and
Preparations).**

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet