

SAFETY DATA SHEET

Creation Date 16-Sep-2011 Revision Date 25-Mar-2024 Revision Number 5

1. Identification

Product Name Methylamine, 2M in methanol

Cat No.: H26889

Synonyms No information available

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Thermo Fisher Scientific Chemicals, Inc. 30 Bond Street Ward Hill, MA 01835-8099

Tel: 800-343-0660 Fax: 800-322-4757

Emergency Telephone Number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Category 2 Acute oral toxicity Category 3 Acute dermal toxicity Category 3 Acute Inhalation Toxicity - Vapors Category 3 Skin Corrosion/Irritation Category 1 B Serious Eye Damage/Eye Irritation Category 1 Specific target organ toxicity (single exposure) Category 1 Target Organs - Respiratory system, Central nervous system (CNS), Optic nerve. Specific target organ toxicity - (repeated exposure) Category 1

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor Causes severe skin burns and eye damage May cause respiratory irritation May cause drowsiness or dizziness Causes damage to organs

Causes damage to organs through prolonged or repeated exposure

Toxic if swallowed, in contact with skin or if inhaled



Precautionary Statements

Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Wear protective gloves/protective clothing/eye protection/face protection

Use only outdoors or in a well-ventilated area

Do not breathe dust/fume/gas/mist/vapors/spray

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Response

Immediately call a POISON CENTER or doctor/physician

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Skir

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

⊏yes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Ingestion

Rinse mouth

Do NOT induce vomiting

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other hazards

Poison, may be fatal or cause blindness if swallowed. Vapor harmful. CANNOT BE MADE NON-POISONOUS. WARNING. Reproductive Harm - https://www.p65warnings.ca.gov/.

3. Composition/Information on Ingredients

| Component | CAS No | Weight % |
|-----------|--------|----------|

| Methyl alcohol | 67-56-1 | 92-93 |
|----------------|---------|-------|
| Methylamine% | 74-89-5 | 7-8 |

4. First-aid measures

General Advice Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance.

Eye ContactRinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In

the case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

Inhalation If breathing is difficult, give oxygen. Do not use mouth-to-mouth method if victim ingested or

inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Remove to fresh air. Immediate

medical attention is required.

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately.

Most important symptoms and

effects

Causes burns by all exposure routes. . Difficulty in breathing. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting

Notes to Physician Treat symptomatically

Fire-fighting measures

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may

be used to cool closed containers.

Unsuitable Extinguishing Media No information available

Flash Point 7 °C / 44.6 °F

Method - No information available

Autoignition Temperature

Explosion Limits

No information available

Upper No data available
Lower No data available

Sensitivity to Mechanical Impact No information available
Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Nitrogen oxides (NOx). Carbon monoxide (CO). Carbon dioxide (CO₂). Thermal decomposition can lead to release of irritating gases and vapors.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health **Flammability** Instability Physical hazards N/A

Accidental release measures

Personal Precautions

Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges. Should not be released into the environment. See Section 12 for additional Ecological

Environmental Precautions

Information.

Methods for Containment and Clean Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage

Handling

Do not breathe mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not ingest. If swallowed then seek immediate medical assistance. Use only under a chemical fume hood. Wear personal protective equipment/face protection. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Storage.

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, sparks and flame. Flammables area. Incompatible Materials. Acids. Acid anhydrides. Acid chlorides. Metals. Reducing Agent.

8. Exposure controls / personal protection

Exposure Guidelines

| Component | ACGIH TLV | OSHA PEL | NIOSH | Mexico OEL (TWA) |
|----------------|---------------|---------------------------------------|-----------------------------|------------------|
| Methyl alcohol | TWA: 200 ppm | (Vacated) TWA: 200 ppm | IDLH: 6000 ppm | TWA: 200 ppm |
| | STEL: 250 ppm | (Vacated) TWA: 260 mg/m ³ | TWA: 200 ppm | STEL: 250 ppm |
| | Skin | (Vacated) STEL: 250 ppm | TWA: 260 mg/m ³ | |
| | | (Vacated) STEL: 325 mg/m ³ | STEL: 250 ppm | |
| | | Skin | STEL: 325 mg/m ³ | |
| | | TWA: 200 ppm | | |
| | | TWA: 260 mg/m ³ | | |
| Methylamine% | TWA: 5 ppm | (Vacated) TWA: 10 ppm | IDLH: 100 ppm | TWA: 5 ppm |
| | STEL: 15 ppm | (Vacated) TWA: 12 mg/m ³ | TWA: 10 ppm | STEL: 15 ppm |
| | | TWA: 10 ppm | TWA: 12 mg/m ³ | |
| | | TWA: 12 mg/m ³ | | |

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations **Engineering Measures**

and safety showers are close to the workstation location. Ensure adequate ventilation,

especially in confined areas.

Personal Protective Equipment

Eye/face Protection Tight sealing safety goggles. Face protection shield.

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

> EN 149, Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Recommended Filter type: Particulates filter conforming to EN 143. Ammonia and organic ammonia derivatives filter.

Type K. Green.

Handle in accordance with good industrial hygiene and safety practice. **Hygiene Measures**

9. Physical and chemical properties

Physical State Liquid **Appearance** Clear

Odor No information available **Odor Threshold** No information available

Hq

No information available **Melting Point/Range** No data available **Boiling Point/Range** 40 °C / 104 °F Flash Point 7 °C / 44.6 °F **Evaporation Rate** No information available

Not applicable Flammability (solid, gas)

Flammability or explosive limits

No data available Upper Lower No data available **Vapor Pressure** 2.07 Psi @ 20 °C **Vapor Density** No information available **Specific Gravity** 0.785

Solubility No information available

Partition coefficient; n-octanol/water No data available

Autoignition Temperature No information available No information available **Decomposition Temperature** No information available **Viscosity**

Molecular Formula C H₅ N **Molecular Weight** 31.06

10. Stability and reactivity

Reactive Hazard None known, based on information available

Stability Stable under normal conditions.

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and **Conditions to Avoid**

sources of ignition.

Incompatible Materials Acids, Acid anhydrides, Acid chlorides, Metals, Reducing Agent

Hazardous Decomposition Products Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO₂), Thermal

decomposition can lead to release of irritating gases and vapors

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information

Oral LD50 Category 3. ATE = 50 - 300 mg/kg. Category 3. ATE = 200 - 1000 mg/kg. **Dermal LD50** Category 3. ATE = 2 - 10 mg/l. Vapor LC50

Component Information

| Component | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|----------------|--------------------------------|-------------------------------|-----------------------------|
| Methyl alcohol | LD50 = 1187 – 2769 mg/kg (Rat) | LD50 = 17100 mg/kg (Rabbit) | LC50 = 128.2 mg/L (Rat) 4 h |
| Methylamine% | 698 mg/kg (Rat) | Not listed | 2.9 mg/L/4h (Rat) |

Toxicologically Synergistic

No information available

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

No information available Irritation

Sensitization No information available

The table below indicates whether each agency has listed any ingredient as a carcinogen. Carcinogenicity

| Component | CAS No | IARC | NTP | ACGIH | OSHA | Mexico |
|----------------|---------|------------|------------|------------|------------|------------|
| Methyl alcohol | 67-56-1 | Not listed |
| Methylamine% | 74-89-5 | Not listed |

Mutagenic Effects

No information available

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure

Respiratory system Central nervous system (CNS) Optic nerve

STOT - repeated exposure

None known

Aspiration hazard

No information available

delayed

Symptoms / effects,both acute and Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness,

nausea and vomiting

Endocrine Disruptor Information

No information available

Other Adverse Effects

The toxicological properties have not been fully investigated. See actual entry in RTECS for complete information.

12. Ecological information

Ecotoxicity

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Do not empty into drains.

| Component | Freshwater Algae | Freshwater Fish | Microtox | Water Flea |
|----------------|------------------|---------------------------|--------------------------|---------------------------|
| Methyl alcohol | Not listed | Pimephales promelas: LC50 | EC50 = 39000 mg/L 25 min | EC50 > 10000 mg/L 24h |
| | | > 10000 mg/L 96h | EC50 = 40000 mg/L 15 min | _ |
| | | | EC50 = 43000 mg/L 5 min | |
| Methylamine% | Not listed | Not listed | Not listed | EC50: 147 - 180 mg/L, 48h |
| | | | | Static (Daphnia magna) |
| | | | | EC50: = 163 mg/L, 48h |
| | | | | (Daphnia magna) |
| | | | | |

Persistence and Degradability Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility Will likely be mobile in the environment due to its volatility.

| Component | log Pow |
|----------------|---------|
| Methyl alcohol | -0.74 |
| Methylamine% | -0.713 |

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

| Component | RCRA - U Series Wastes | RCRA - P Series Wastes |
|--------------------------|------------------------|------------------------|
| Methyl alcohol - 67-56-1 | U154 | - |

14. Transport information

DOT

UN-No UN3286

Proper Shipping Name Technical NameFlammable liquid, toxic, corrosive, n.o.s.

Methyl alcohol, Methylamine ...%

Hazard Class 3
Subsidiary Hazard Class 6.1, 8

Packing Group

TDG

UN-No UN3286

Proper Shipping Name Flammable liquid, toxic, corrosive, n.o.s.

Ш

Hazard Class 3
Subsidiary Hazard Class 6.1, 8
Packing Group |

<u>IATA</u>

UN-No UN3286

Proper Shipping Name Flammable liquid, toxic, corrosive, n.o.s.

Hazard Class 3
Subsidiary Hazard Class 6.1, 8
Packing Group

IMDG/IMO

UN-No UN3286

Proper Shipping Name Flammable liquid, toxic, corrosive, n.o.s.

Hazard Class 3
Subsidiary Hazard Class 6.1, 8
Packing Group |

15. Regulatory information

United States of America Inventory

| Component | CAS No | TSCA | TSCA Inventory notification - Active-Inactive | TSCA - EPA Regulatory Flags |
|----------------|---------|------|--|-----------------------------|
| Methyl alcohol | 67-56-1 | X | ACTIVE | - |
| Methylamine% | 74-89-5 | Χ | ACTIVE | - |

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed '-' - Not Listed

TSCA - Per 40 CFR 751, Regulation of Certain Chemical Substances & Mixtures, Under TSCA Section 6(h) (PBT)

Not applicable

TSCA 12(b) - Notices of Export

Not applicable

International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

| Component | CAS No | DSL | NDSL | EINECS | PICCS | ENCS | ISHL | AICS | IECSC | KECL |
|----------------|---------|-----|------|-----------|-------|------|------|------|-------|----------|
| Methyl alcohol | 67-56-1 | Χ | - | 200-659-6 | Χ | Χ | Χ | Х | Χ | KE-23193 |
| Methylamine% | 74-89-5 | Х | 1 | 200-820-0 | Χ | Х | Χ | Χ | Х | KE-23421 |

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

| Component | CAS No | Weight % | SARA 313 - Threshold Values % | SARA 313 - Reporting threasholds | |
|----------------|---------|----------|----------------------------------|----------------------------------|--|
| Methyl alcohol | 67-56-1 | 92-93 | 1.0 % | - | |

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

| Component | CWA - Hazardous Substances | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants |
|--------------|-------------------------------|--------------------------------|------------------------|---------------------------|
| Methylamine% | X | 100 lb | - | - |

Clean Air Act

| Component | HAPS Data | Class 1 Ozone Depletors | Class 2 Ozone Depletors |
|----------------|-----------|-------------------------|-------------------------|
| Methyl alcohol | X | | - |

OSHA - Occupational Safety and Health Administration

OSHA - United States Occupational Safety and Health Administration

| Component | Specifically Regulated Chemicals | Highly Hazardous Chemicals | |
|--------------|----------------------------------|----------------------------|--|
| Methylamine% | - | TQ: 1000 lb | |

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

| Component | Hazardous Substances RQs | CERCLA Extremely Hazardous Substances RQs | SARA Reportable Quantity (RQ) |
|----------------|-----------------------------|---|-------------------------------|
| Methyl alcohol | 5000 lb | - | 5000 lb 2270 kg |
| Methylamine% | 100 lb | - | 100 lb 45.4 kg |

California Proposition 65

This product contains the following Proposition 65 chemicals.

| Component CAS No | | California Prop. 65 | Prop 65 NSRL | Category | |
|------------------|---------|---------------------|--------------|---------------|--|
| Methyl alcohol | 67-56-1 | Developmental | - | Developmental | |

U.S. State Right-to-Know Regulations

| Component | Massachusetts | New Jersey | Pennsylvania | Illinois | Rhode Island |
|----------------|---------------|------------|--------------|----------|--------------|
| Methyl alcohol | X | X | X | X | X |
| Methylamine% | X | X | X | - - | X |

U.S. Department of Transportation

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland

This product contains the following DHS chemicals:

Security

Legend - STQs = Screening Threshold Quantities, APA = A placarded amount

| Component | DHS Chemical Facility Anti-Terrorism Standard | | |
|--------------|---|--|--|
| Methylamine% | Release STQs - 10000lb | | |

Other International Regulations

Mexico - Grade Serious risk, Grade 3

Authorisation/Restrictions according to EU REACH

| Component | CAS No | REACH (1907/2006) - Annex XIV - Substances Subject to Authorization | REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances | REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC) |
|----------------|---------|---|---|---|
| Methyl alcohol | 67-56-1 | - | Use restricted. See item 69. (see link for restriction details) Use restricted. See item 75. (see link for restriction details) | |
| Methylamine% | 74-89-5 | - | Use restricted. See item 75. (see link for restriction details) | - |

REACH links

https://echa.europa.eu/substances-restricted-under-reach

Safety, health and environmental regulations/legislation specific for the substance or mixture

| Component | CAS No | OECD HPV | Persistent Organic Pollutant | Ozone Depletion Potential | Restriction of Hazardous Substances (RoHS) |
|----------------|---------|----------|---------------------------------|------------------------------|--|
| Methyl alcohol | 67-56-1 | Listed | Not applicable | Not applicable | Not applicable |
| Methylamine% | 74-89-5 | Listed | Not applicable | Not applicable | Not applicable |

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Other International Regulations

| Component | CAS No | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification | (2012/18/EC) - | Rotterdam Convention (PIC) | Basel Convention (Hazardous Waste) |
|----------------|---------|---|----------------|-------------------------------|---------------------------------------|
| Methyl alcohol | 67-56-1 | 500 tonne | 5000 tonne | Not applicable | Not applicable |
| Methylamine% | 74-89-5 | Not applicable | Not applicable | Not applicable | Not applicable |

16. Other information

Prepared By Health, Safety and Environmental Department

Email: chem.techinfo@thermofisher.com

www.thermofisher.com

 Creation Date
 16-Sep-2011

 Revision Date
 25-Mar-2024

 Print Date
 25-Mar-2024

Revision Summary New emergency telephone response service provider.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS