

Creation Date 28-Apr-2011

Revision Date 04-Oct-2023

Revision Number 8

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description:	<u>Isohexane</u>
Cat No. :	383810000; 383810010; 383810025
CAS No	73513-42-5
EC No	931-254-9
Molecular Formula	C6 H14
REACH registration number	01-2119484651-34

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use	Laboratory chemicals.
Sector of use	SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites
Product category	PC21 - Laboratory chemicals
Process categories	PROC15 - Use as a laboratory reagent
Environmental release category	ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)
Uses advised against	No Information available

1.3. Details of the supplier of the safety data sheet

Company

EU entity/business name

Thermo Fisher Scientific
Janssen Pharmaceuticaaan 3a, 2440 Geel, Belgium

UK entity/business name

Fisher Scientific UK
Bishop Meadow Road,
Loughborough, Leicestershire LE11 5RG, United Kingdom

Swiss distributor - Fisher Scientific AG

Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
e-mail - infoch@thermofisher.com

E-mail address

begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:

Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

SAFETY DATA SHEET

Isohexane

Revision Date 04-Oct-2023

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Flammable liquids

Category 2 (H225)

Health hazards

Aspiration Toxicity

Category 1 (H304)

Skin Corrosion/Irritation

Category 2 (H315)

Specific target organ toxicity - (single exposure)

Category 3 (H336)

Environmental hazards

Chronic aquatic toxicity

Category 2 (H411)

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness
H411 - Toxic to aquatic life with long lasting effects

Precautionary Statements

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P331 - Do NOT induce vomiting
P280 - Wear protective gloves/protective clothing
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

SAFETY DATA SHEET

Isohexane

Revision Date 04-Oct-2023

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Naphtha, petroleum, hydrotreated light	64742-49-0	931-254-9	> 95	Flam. Liq. 2 (H225) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 (H336) Aquatic Chronic 2 (H411)
Hexanes, branched isomers	73513-42-5		-	Flam. Liq. 2 (H225) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 (H336) Aquatic Chronic 2 (H411)

Note

REACH

UVCB Hydrocarbons

C6, isoalkanes, < 5% n-Hexane

Contains

CAS 73513-42-5 (Iso-Hexane)

REACH registration number	01-2119484651-34
---------------------------	------------------

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	If symptoms persist, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
Inhalation	Remove to fresh air. If breathing is difficult, give oxygen. Get medical attention if symptoms occur. Risk of serious damage to the lungs (by aspiration).
Self-Protection of the First Aider	Use personal protective equipment as required.

4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. . Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

SAFETY DATA SHEET

Isohexane

Revision Date 04-Oct-2023

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Water may be ineffective. Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition. Extremely flammable.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂).

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information. Avoid release to the environment. Collect spillage.

6.3. Methods and material for containment and cleaning up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures

SAFETY DATA SHEET

Isohexane

Revision Date 04-Oct-2023

against static discharges. Use spark-proof tools and explosion-proof equipment.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a dry, cool and well-ventilated place. Keep container tightly closed. Keep away from heat, sparks and flame. Flammables area. Keep containers tightly closed in a cool, well-ventilated place. Keep in properly labeled containers. Keep container tightly closed in a dry and well-ventilated place.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Class 3

Switzerland - Storage of hazardous substances

Storage class - SC 3
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Naphtha, petroleum, hydrotreated light		RCP Isohexanes, TWA (8 h) 250 ppm, 1000 mg/m ³			
Hexanes, branched isomers			TWA / VME: 1000 mg/m ³ (8 heures). STEL / VLCT: 1500 mg/m ³ .	TWA: 500 ppm 8 uren TWA: 1786 mg/m ³ 8 uren STEL: 1000 ppm 15 minuten STEL: 3551 mg/m ³ 15 minuten	STEL / VLA-EC: 1000 ppm (15 minutos). STEL / VLA-EC: 3580 mg/m ³ (15 minutos).

Component	Italy	Germany	Portugal	The Netherlands	Finland
Hexanes, branched isomers		TWA: 500 ppm (8 Stunden). MAK except n-Hexane TWA: 1800 mg/m ³ (8 Stunden). MAK except n-Hexane	STEL: 1000 ppm 15 minutos		TWA: 500 ppm 8 tunteina TWA: 1800 mg/m ³ 8 tunteina STEL: 630 ppm 15 minuutteina STEL: 2300 mg/m ³ 15 minuutteina

Component	Austria	Denmark	Switzerland	Poland	Norway
Naphtha, petroleum, hydrotreated light				STEL: 1500 mg/m ³ 15 minutach TWA: 500 mg/m ³ 8 godzinach	
Hexanes, branched isomers	MAK-KZGW: 800 ppm 15 Minuten	TWA: 200 ppm 8 timer TWA: 700 mg/m ³ 8 timer	STEL: 1000 ppm 15 Minuten	TWA: 400 mg/m ³ 8 godzinach	TWA: 250 ppm 8 timer TWA: 1050 mg/m ³ 8

SAFETY DATA SHEET

Isohexane

Revision Date 04-Oct-2023

	MAK-KZGW: 2860 mg/m ³ 15 Minuten MAK-TMW: 200 ppm 8 Stunden MAK-TMW: 715 mg/m ³ 8 Stunden	STEL: 400 ppm 15 minutter STEL: 1400 mg/m ³ 15 minutter	STEL: 3600 mg/m ³ 15 Minuten TWA: 500 ppm 8 Stunden TWA: 1800 mg/m ³ 8 Stunden		timer TWA: 40 ppm 8 timer TWA: 275 mg/m ³ 8 timer STEL: 312.5 ppm 15 minutter. value calculated STEL: 1312.5 mg/m ³ 15 minutter. value calculated
--	-----------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------	--	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Hexanes, branched isomers			TWA: 500 ppm 8 hr. except n-Hexane TWA: 1800 mg/m ³ 8 hr. except n-Hexane STEL: 1000 ppm 15 min STEL: 3600 mg/m ³ 15 min		TWA: 1000 mg/m ³ 8 hodinách. Ceiling: 2000 mg/m ³ other than n-Hexane

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Hexanes, branched isomers	TWA: 200 ppm 8 tundides. TWA: 700 mg/m ³ 8 tundides. STEL: 300 ppm 15 minutites. STEL: 1100 mg/m ³ 15 minutites.		STEL: 1000 ppm STEL: 3600 mg/m ³ TWA: 500 ppm TWA: 1800 mg/m ³		TWA: 200 ppm 8 klukkustundum. TWA: 700 mg/m ³ 8 klukkustundum. Ceiling: 400 ppm Ceiling: 1400 mg/m ³

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Hexanes, branched isomers		TWA: 200 ppm IPRD TWA: 700 mg/m ³ IPRD STEL: 300 ppm STEL: 1100 mg/m ³			

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Hexanes, branched isomers			TWA: 1800 mg/m ³ 8 urah TWA: 500 ppm 8 urah STEL: 1000 ppm 15 minutah STEL: 3600 mg/m ³ 15 minutah	Indicative STEL: 300 ppm 15 minuter Indicative STEL: 1100 mg/m ³ 15 minuter TLV: 200 ppm 8 timmar. NGV TLV: 700 mg/m ³ 8 timmar. NGV	

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

SAFETY DATA SHEET

Isohexane

Revision Date 04-Oct-2023

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Naphtha, petroleum, hydrotreated light 64742-49-0 (> 95)	DNEL = 1066.67mg/m ³	DNEL = 1286.4mg/m ³	DNEL = 837.5mg/m ³	

Predicted No Effect Concentration (PNEC)

Not applicable. Substance is complex UVCB.

8.2. Exposure controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure adequate ventilation, especially in confined areas. Use spark-proof tools and explosion-proof equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Wear safety glasses with side shields (or goggles) (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber	> 480 minutes	0.38 mm	Level 6	As tested under EN374-3 Determination of
Viton (R)	> 480 minutes	0.35 mm	EN 374	Resistance to Permeation by Chemicals
Neoprene gloves	< 45 minutes	0.45 mm		

Skin and body protection

Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

No protective equipment is needed under normal use conditions.

Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371

Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141

Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

SAFETY DATA SHEET

Isohexane

Revision Date 04-Oct-2023

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Colorless	
Odor	Slight	
Odor Threshold	No data available	
Melting Point/Range	-154 °C / -245.2 °F	
Softening Point	No data available	
Boiling Point/Range	48 - 70 °C / 118.4 - 158 °F	
Flammability (liquid)	Highly flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	Lower 1.0 vol% Upper 7.4 vol%	
Flash Point	-33 °C / -27.4 °F	Method - No information available
Autoignition Temperature	265 - °C / 509 - °F	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	No data available	
Water Solubility	Insoluble	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Vapor Pressure	250 hPa @ 250 °C	
Density / Specific Gravity	0.660	
Bulk Density	Not applicable	Liquid
Vapor Density	> 1	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

Molecular Formula	C6 H14
Molecular Weight	86.18
Explosive Properties	Vapors may form explosive mixtures with air
Evaporation Rate	13 (Butyl acetate = 1.0)

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition. Incompatible products.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

SAFETY DATA SHEET

Isohexane

Revision Date 04-Oct-2023

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Naphtha, petroleum, hydrotreated light	LD50 > 5000 mg/kg (Rat)	LD50 > 3160 mg/kg (Rabbit)	LC50 = 73680 ppm (Rat) 4 h

(b) skin corrosion/irritation;

Category 2

(c) serious eye damage/irritation;

Based on available data, the classification criteria are not met

(d) respiratory or skin sensitization;

Respiratory

Based on available data, the classification criteria are not met

Skin

Based on available data, the classification criteria are not met

(e) germ cell mutagenicity;

Based on available data, the classification criteria are not met

(f) carcinogenicity;

Based on available data, the classification criteria are not met

The table below indicates whether each agency has listed any ingredient as a carcinogen
The classification as a carcinogen need not apply if the full refining history is known and it can be shown that the substance from which it is produced is not a carcinogen. This note applies only to certain complex oil derived substances in Annex I

Component	EU	UK	Germany	IARC
Naphtha, petroleum, hydrotreated light	Carc Cat. 1B			

(g) reproductive toxicity;

Based on available data, the classification criteria are not met

(h) STOT-single exposure;

Category 3

Results / Target organs

Central nervous system (CNS).

(i) STOT-repeated exposure;

Based on available data, the classification criteria are not met

Target Organs

None known.

(j) aspiration hazard;

Category 1

Other Adverse Effects

See actual entry in RTECS for complete information

Symptoms / effects, both acute and delayed

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

11.2. Information on other hazards

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any

SAFETY DATA SHEET

Isohexane

Revision Date 04-Oct-2023

known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Naphtha, petroleum, hydrotreated light	LC50: = 8.41 mg/L, 96h semi-static, closed (Oncorhynchus mykiss)		

12.2. Persistence and degradability

Persistence

Persistence is unlikely, based on information available.

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential

Bioaccumulation is unlikely

12.4. Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air.

12.5. Results of PBT and vPvB assessment

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB).

12.6. Endocrine disrupting properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance
This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information

Do not flush to sewer. Waste codes should be assigned by the user based on the

SAFETY DATA SHEET

Isohexane

Revision Date 04-Oct-2023

application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not let this chemical enter the environment. Do not empty into drains.

Switzerland - Waste Ordinance

Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number UN1208
14.2. UN proper shipping name HEXANES
14.3. Transport hazard class(es) 3
14.4. Packing group II

ADR

14.1. UN number UN1208
14.2. UN proper shipping name HEXANES
14.3. Transport hazard class(es) 3
14.4. Packing group II

IATA

14.1. UN number UN1208
14.2. UN proper shipping name HEXANES
14.3. Transport hazard class(es) 3
14.4. Packing group II

14.5. Environmental hazards Dangerous for the environment
Product is a marine pollutant according to the criteria set by IMDG/IMO

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Naphtha, petroleum, hydrotreated light	64742-49-0	265-151-9	-	-	X	X	KE-25623	-	-
Hexanes, branched isomers	73513-42-5	-	438-390-3	-	X	X	-	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Naphtha, petroleum, hydrotreated	64742-49-0	X	ACTIVE	X	-	X	X	X

SAFETY DATA SHEET

Isohexane

Revision Date 04-Oct-2023

light								
Hexanes, branched isomers	73513-42-5	-	-	-	-	-	X	-

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Naphtha, petroleum, hydrotreated light	64742-49-0	-	Use restricted. See item 28. (see link for restriction details) Use restricted. See item 29. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-
Hexanes, branched isomers	73513-42-5	-	-	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Naphtha, petroleum, hydrotreated light	64742-49-0	Not applicable	Not applicable
Hexanes, branched isomers	73513-42-5	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

See table for values

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Naphtha, petroleum, hydrotreated light	WGK2	

Component	France - INRS (Tables of occupational diseases)
-----------	-------------------------------------------------

SAFETY DATA SHEET

Isohexane

Revision Date 04-Oct-2023

Naphtha, petroleum, hydrotreated light	Tableaux des maladies professionnelles (TMP) - RG 84
Hexanes, branched isomers	Tableaux des maladies professionnelles (TMP) - RG 84

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Hexanes, branched isomers 73513-42-5 (-)	Prohibited and Restricted Substances		

15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has been conducted by the manufacturer/importer

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness
H411 - Toxic to aquatic life with long lasting effects

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

First aid for chemical exposure, including the use of eye wash and safety showers.

SAFETY DATA SHEET

Isohexane

Revision Date 04-Oct-2023

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Chemical incident response training.

Creation Date 28-Apr-2011
Revision Date 04-Oct-2023
Revision Summary Not applicable.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No
1907/2006 .**

**For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2,
Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and
Preparations).**

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet