

SAFETY DATA SHEET

Revision Date 01-Apr-2024 Revision Number 3

1. Identification

Product Name Barium titanium(IV) 2-ethylhexanoate pentaisopropoxide in

isopropanol

Cat No.: 43893

Synonyms No information available

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Thermo Fisher Scientific Chemicals, Inc. 30 Bond Street

Ward Hill, MA 01835-8099

Tel: 800-343-0660 Fax: 800-322-4757

Emergency Telephone Number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids
Category 2
Acute oral toxicity
Category 2
Acute dermal toxicity
Category 1
Acute Inhalation Toxicity - Vapors
Serious Eye Damage/Eye Irritation
Category 2
Specific target organ toxicity (single exposure)
Category 3
Target Organs - Central nervous system (CNS).

Specific target organ toxicity - (repeated exposure) Category 2

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor
Causes serious eye irritation
May cause drowsiness or dizziness
May cause damage to organs through prolonged or repeated exposure
Fatal if swallowed, in contact with skin or if inhaled



Precautionary Statements

Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Do not get in eyes, on skin, or on clothing

Wear protective gloves/protective clothing/eye protection/face protection

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Wear respiratory protection

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Response

Get medical attention/advice if you feel unwell

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Immediately call a POISON CENTER or doctor/physician

Call a POISON CENTER or doctor/physician if you feel unwell

Skin

Immediately call a POISON CENTER or doctor/physician

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Rinse mouth

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Toxic to aquatic life with long lasting effects

3. Composition/Information on Ingredients

Component	CAS No	Weight %
Isopropyl alcohol	67-63-0	86.60
Barium titanium(IV) 2-ethylhexanoate	N/A	13.4
pentaisopropoxide		

4. First-aid measures

General Advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In

the case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Do not use mouth-to-mouth

method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Immediate medical attention is required.

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately.

Most important symptoms and

effects

Notes to Physician

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like

headache, dizziness, tiredness, nausea and vomiting

Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media Water mist may be used to cool closed containers.

Unsuitable Extinguishing Media No information available

Flash Point No information available Method - No information available

Autoignition Temperature

Explosion Limits

No information available

UpperNo data availableLowerNo data available

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO2). Barium oxides. Titanium oxides.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Flammability Instability Health Physical hazards 4 3 0

Accidental release measures

Personal Precautions

Environmental Precautions

Ensure adequate ventilation. Use personal protective equipment as required. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Remove all sources

of ignition. Take precautionary measures against static discharges. Do not flush into surface water or sanitary sewer system. Should not be released into the

environment. Do not allow material to contaminate ground water system.

Up

Methods for Containment and Clean Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage

Handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Take precautionary measures against static discharges.

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, Storage.

sparks and flame.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH	Mexico OEL (TWA)
Isopropyl alcohol	TWA: 200 ppm	(Vacated) TWA: 400 ppm	IDLH: 2000 ppm	TWA: 200 ppm
	STEL: 400 ppm	(Vacated) TWA: 980 mg/m ³	TWA: 400 ppm	STEL: 400 ppm
		(Vacated) STEL: 500 ppm	TWA: 980 mg/m ³	
		(Vacated) STEL: 1225	STEL: 500 ppm	
		mg/m³	STEL: 1225 mg/m ³	
		TWA: 400 ppm	_	
		TWA: 980 mg/m ³		

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures Ensure that evewash stations and safety showers are close to the workstation location.

Ensure adequate ventilation, especially in confined areas. Use explosion-proof

electrical/ventilating/lighting equipment.

Personal Protective Equipment

Wear appropriate protective eyeglasses or chemical safety goggles as described by **Eye/face Protection**

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

Wear appropriate protective gloves and clothing to prevent skin exposure. Skin and body protection

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard **Respiratory Protection**

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Recommended Filter type: Multi-purpose/ABEK. conforming to EN14387. low boiling organic solvent. Type AX. Brown.

conforming to EN371. or. Organic gases and vapours filter. Type A. Brown.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State Liquid

Appearance
Odor
No information available
No data available

Melting Point/RangeNo data availableBoiling Point/RangeNo information availableFlash PointNo information availableEvaporation RateNo information available

Flammability (solid,gas)
Not applicable
Flammability or explosive limits

Upper No data available

Lower No data available
Vapor Pressure 23 hPa @ 20 °C
Vapor Density No information available

Vapor DensityNo information availableSpecific GravityNo information availableSolubilityNo information availablePartition coefficient; n-octanol/waterNo data available

Autoignition TemperatureNo information availableDecomposition TemperatureNo information availableViscosityNo information available

Molecular Formula C23 H50 BaO7 Ti

Molecular Weight 623.89

10. Stability and reactivity

Reactive Hazard None known, based on information available

Stability Moisture sensitive.

Conditions to Avoid Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials Strong oxidizing agents

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2), Barium oxides, Titanium oxides

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information

Oral LD50 Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg. Category 2.

ATE = 5 - 50 mg/kg.

Dermal LD50 Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg. Category 1.

ATE < 50 mg/kg.

Vapor LC50 Based on ATE data, the classification criteria are not met. ATE > 20 mg/l. Category 2. ATE

= 0.5 - 2 mg/l.

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Isopropyl alcohol	5045 mg/kg (Rat)	12800 mg/kg (Rat)	72.6 mg/L (Rat)4 h
	3600 mg/kg (Mouse)		

Toxicologically Synergistic

No information available

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation No information available

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Isopropyl alcohol	67-63-0	Not listed				
Barium titanium(IV) 2-ethylhexanoate	N/A	Not listed				
pentaisopropoxide						

Mutagenic Effects No information available

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure Central nervous system (CNS)

STOT - repeated exposure None known

No information available **Aspiration hazard**

delayed

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment. May cause long-term adverse effects in the environment. Do not allow material to contaminate ground water system.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Isopropyl alcohol	EC50: > 1000 mg/L, 72h	LC50: = 9640 mg/L, 96h	= 35390 mg/L EC50	13299 mg/L EC50 = 48 h
	(Desmodesmus	flow-through (Pimephales	Photobacterium	9714 mg/L EC50 = 24 h
	subspicatus)	promelas)	phosphoreum 5 min	
	EC50: > 1000 mg/L, 96h	LC50: > 1400000 µg/L, 96h		
	(Desmodesmus	(Lepomis macrochirus)		
	subspicatus)	LC50: = 11130 mg/L, 96h		
		static (Pimephales		
		promelas)		
		LC50: = 10000000 µg/L, 96h		
		(Daphnia)		

Persistence and Degradability May persist based on information available.

Bioaccumulation/ Accumulation No information available.

Is not likely mobile in the environment due its low water solubility. Mobility

Component	log Pow
Isopropyl alcohol	0.05

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

UN-No UN1219

Proper Shipping Name ISOPROPANOL

Hazard Class 3 Packing Group II

TDG

UN-No UN1219

Proper Shipping Name ISOPROPANOL

Hazard Class 3
Packing Group

<u>IATA</u>

UN-No UN1219

Proper Shipping Name ISOPROPANOL

Hazard Class 3 Packing Group II

IMDG/IMO

UN-No UN1219

Proper Shipping Name ISOPROPANOL

Hazard Class 3 Packing Group II

15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Isopropyl alcohol	67-63-0	X	ACTIVE	-
Barium titanium(IV) 2-ethylhexanoate pentaisopropoxide	N/A	-	-	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA - Per 40 CFR 751, Regulation of Certain Chemical Substances & Mixtures, Under TSCA Section 6(h) (PBT)

Not applicable

TSCA 12(b) - Notices of Export

Not applicable

International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Isopropyl alcohol	67-63-0	Х	-	200-661-7	Х	Х	Х	Х	Х	KE-29363

Barium titanium(IV) 2-ethylhexanoate pentaisopropoxide in isopropanol

Barium titanium(IV)	N/A	-	-	-	-	-	-	-	-
2-ethylhexanoate									
pentaisopropoxide									

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS No	Weight %	SARA 313 - Threshold Values %	SARA 313 - Reporting threasholds
Isopropyl alcohol	67-63-0	86.60	1.0 %	-

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act) Not applicable

Clean Air Act Not applicable

OSHA - Occupational Safety and

Health Administration

Not applicable

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Isopropyl alcohol	X	X	X	-	X

U.S. Department of Transportation

Reportable Quantity (RQ): N
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland

Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade No information available

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) -	REACH (1907/2006) -	REACH Regulation (EC
-		Annex XIV - Substances	Annex XVII - Restrictions	1907/2006) article 59 -
		Subject to Authorization	on Certain Dangerous	Candidate List of

			Substances	Substances of Very High Concern (SVHC)
Isopropyl alcohol	67-63-0	-	Use restricted. See item	-
			75.	
			(see link for restriction	
			details)	
Barium titanium(IV)	N/A	-	-	-
2-ethylhexanoate pentaisopropoxide				

REACH links

https://echa.europa.eu/substances-restricted-under-reach

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Isopropyl alcohol	67-63-0	Listed	Not applicable	Not applicable	Not applicable
Barium titanium(IV) 2-ethylhexanoate pentaisopropoxide	N/A	Not applicable	Not applicable	Not applicable	Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Other International Regulations

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Isopropyl alcohol	67-63-0	Not applicable	Not applicable	Not applicable	Annex I - Y42
Barium titanium(IV) 2-ethylhexanoate pentaisopropoxide	N/A	Not applicable	Not applicable	Not applicable	Not applicable

- 1		\sim 1			•		
	^	/ NT	her i	пот	\sim r \sim	\mathbf{r}	-
		. , .	1101			1/1	
	\circ	\sim $^{\circ}$			\sim 111		

Prepared By Health, Safety and Environmental Department

Email: chem.techinfo@thermofisher.com

www.thermofisher.com

 Revision Date
 01-Apr-2024

 Print Date
 01-Apr-2024

Revision Summary New emergency telephone response service provider.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS