

Page 1/9 Creation Date 01-Nov-2011 Revision Date 28-Mar-2023 Version 1

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product Identifier

Perihalan Produk: 95% Ethanol
Product Description: 95% Ethanol
Cat No.: R40132

Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

Details of the supplier of the safety data sheet

Company Thermo Scientific Microbiology Sdn Bhd

No.6, Jalan TTC 6, Taman Teknologi Cheng,

Cheng, 75250 Melaka, Malaysia

+606 334 0975 .

Supplier Oxoid Ltd.

Wade Road

Basingstoke, Hants, UK

RG24 8PW

Telephone: +44 (0) 1256 841144

E-mail address mbd-sds@thermofisher.com

Emergency Telephone Number

(603) 5122 8888

CHEMTREC Malaysia 1-800-815-308 (Malay)

CHEMTREC Malaysia (Kuala Lumpur) +(60)-327884561 (Malay)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

Flammable liquids	Category 2 (H225)
Acute oral toxicity	Category 4 (H302)
Acute Inhalation Toxicity - Vapors	Category 4 (H332)
Specific target organ toxicity - (single exposure)	Category 1 (H370)

Label Elements



Signal Word Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H302 - Harmful if swallowed H332 - Harmful if inhaled

H370 - Causes damage to organs

Precautionary Statements

P301 + P330 + P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting

P312 - Call a POISON CENTER or doctor if you feel unwell

P264 - Wash face, hands and any exposed skin thoroughly after handling

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P260 - Do not breathe dust/fume/gas/mist/vapors/spray

P308 + P311 - IF exposed or concerned: Call a POISON CENTER or doctor

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Other Hazards

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No	Weight %
Ethyl alcohol	64-17-5	95
Methyl alcohol	67-56-1	5

SECTION 4: FIRST AID MEASURES

Description of first aid measures

General Advice If symptoms persist, call a physician.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

Ingestion Clean mouth with water and drink afterwards plenty of water.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like

headache, dizziness, tiredness, nausea and vomiting.

95% Ethanol Revision Date 28-Mar-2023

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptom

Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture

Flammable. Keep product and empty container away from heat and sources of ignition. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Combustible material.

Hazardous Combustion Products

Carbon oxides.

Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental precautions

Should not be released into the environment. See Section 12 for additional Ecological Information.

Methods and Material for Containment and Cleaning Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Ensure adequate ventilation. Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Conditions for Safe Storage, Including any Incompatibilities

Keep away from heat, sparks and flame. Keep containers tightly closed in a cool, well-ventilated place. Keep containers tightly closed in a dry, cool and well-ventilated place.

Specific End Uses

Use in laboratories.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	Malaysia	ACGIH TLV	OSHA PEL
Ethyl alcohol		STEL: 1000 ppm	(Vacated) TWA: 1000 ppm
			(Vacated) TWA: 1900 mg/m ³
			TWA: 1000 ppm
			TWA: 1900 mg/m ³
Methyl alcohol		TWA: 200 ppm	(Vacated) TWA: 200 ppm
		STEL: 250 ppm	(Vacated) TWA: 260 mg/m ³
		Skin	(Vacated) STEL: 250 ppm
			(Vacated) STEL: 325 mg/m ³
			Skin
			TWA: 200 ppm
			TWA: 260 mg/m ³

Component	European Union	The United Kingdom	Germany
Ethyl alcohol		TWA: 1000 ppm TWA; 1920 mg/m ³	200 ppm TWA MAK; 380 mg/m ³
		TWA	TWA MAK
		WEL - STEL: 3000 ppm STEL;	
		5760 mg/m ³ STEL	
Methyl alcohol	TWA: 200 ppm 8 hr	WEL - TWA: 200 ppm TWA; 266	100 ppm TWA MAK; 130 mg/m ³
	TWA: 260 mg/m ³ 8 hr	mg/m³ TWA	TWA MAKSkin absorber
	Skin	WEL - STEL: 250 ppm STEL; 333	
		mg/m³ STEL	

Exposure Controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Wear safety glasses with side shields (or goggles)

Hand Protection Protective gloves
Skin and body protection Long sleeved clothing

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators

Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and

vapours filter Type A Brown conforming to EN14387

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

When RPE is used a face piece Fit Test should be conducted

<u>Hygiene Measures</u> When using do not eat, drink or smoke Provide regular cleaning of equipment, work area

and clothing

Environmental exposure controls No information available

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance Clear Colourless

Physical State Liquid Odor aromatic

Odor Threshold No data available

pH No information available

Melting Point/RangeNo data availableSoftening PointNo data available

Boiling Point/Range No information available

Flash Point 65 °C / 149 °F Method - CC (closed cup)

Evaporation Rate No data available

Flammability (solid,gas) Not applicable Liquid

Explosion Limits No data available Lower 3.3%

Upper 19.0%

Vapor Pressure No data available

Vapor Density No data available (Air = 1.0)

Specific Gravity / Density No data available
Bulk Density Not applicable

Water Solubility
Solubility in other solvents
No information available
No information available

Partition Coefficient (n-octanol/water)

Componentlog PowEthyl alcohol-0.32Methyl alcohol-0.74

Autoignition Temperature 363 °C / 685.4 °F **Decomposition Temperature** No data available

Viscosity No data available

Explosive PropertiesVapors may form explosive mixtures with air

explosive air/vapour mixtures possible

Liquid

Oxidizing Properties No information available

SECTION 10: STABILITY AND REACTIVITY

Reactivity

None known, based on information available.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

Conditions to Avoid

Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of

ignition.

Incompatible Materials

None known.

Hazardous Decomposition Products

Carbon oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects

Acute Toxicity

Toxicology data for the components

Component	Component LD50 Oral LD50 Dermal		LC50 Inhalation
Ethyl alcohol	LD50 = 7060 mg/kg (Rat)		20000 ppm/10H (Rat)
Methyl alcohol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg (Rabbit)	LC50 = 128.2 mg/L (Rat) 4 h

Chronic Toxicity

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen

SensitizationNo information availableMutagenic EffectsNo information availableReproductive EffectsNo information availableDevelopmental EffectsNo information availableTarget OrgansNo information available

Symptoms Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity effects

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Ethyl alcohol	Fathead minnow	EC50 = 9268 mg/L/48h	EC50 (72h) = 275 mg/l	Photobacterium
	(Pimephales promelas)	EC50 = 10800 mg/L/24h	(Chlorella vulgaris)	phosphoreum:EC50 =
	LC50 = 14200 mg/l/96h			34634 mg/L/30 min
				Photobacterium
				phosphoreum:EC50 =
				35470 mg/L/5 min
Methyl alcohol	Pimephales promelas:	EC50 > 10000 mg/L 24h		EC50 = 39000 mg/L 25
	LC50 > 10000 mg/L 96h			min
				EC50 = 40000 mg/L 15
				min
				EC50 = 43000 mg/L 5
				min

Component	Degradability
Methyl alcohol	DT50 ~ 17.2d
67-56-1 (5)	>94% after 20d

Bioaccumulative potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Ethyl alcohol	-0.32	No data available
Methyl alcohol	-0.74	<10 dimensionless

Mobility in soil No information available. .

Other adverse effects No information available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Contaminated Packaging

Waste from Residues/Unused

Products

Waste is classified as hazardous Dispose of in accordance with the European Directives on waste and hazardous waste Dispose of in accordance with local regulations

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous Keep product and

empty container away from heat and sources of ignition

Other Information Waste codes should be assigned by the user based on the application for which the product

was used Do not flush to sewer Can be landfilled or incinerated, when in compliance with

local regulations

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

UN-No UN1170
Hazard Class 3
Packing Group ||

Proper Shipping Name ETHANOL

Road and Rail Transport

UN-No UN1170

95% Ethanol Revision Date 28-Mar-2023

Hazard Class Packing Group

ETHANOL Proper Shipping Name

IATA

UN1170 **UN-No Hazard Class** 3 **Packing Group** Ш

Proper Shipping Name ETHANOL

Special Precautions for User No special precautions required

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

X = listed**International Inventories**

Component	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	IECSC	AICS	KECL
Ethyl alcohol	-	Х	X	Х	X	Х	Х	Х	KE-13217
Methyl alcohol	=	Х	Х	Х	Х	Х	Х	Χ	KE-23193

Component	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Ethyl alcohol				Annex I - Y42
Methyl alcohol	500 tonne	5000 tonne		

National Regulations

Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 16: OTHER INFORMATION

Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

Substances List **ENCS** - Japanese Existing and New Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances **IECSC** - Chinese Inventory of Existing Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances

AICS - Australian Inventory of Chemical Substances NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

TWA - Time Weighted Average

ACGIH - American Conference of Governmental Industrial Hygienists

IARC - International Agency for Research on Cancer

RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50%

LD50 - Lethal Dose 50%

POW - Partition coefficient Octanol:Water

EC50 - Effective Concentration 50%

95% Ethanol Revision Date 28-Mar-2023

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Revision Date 28-Mar-2023

Revision Summary Update to CLP Format.

In accordance with local and national regulations: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet