

Australian statement of hazardous nature: Classified as hazardous according to criteria of Safe Work Australia

Section 1 - Identification

Product Name IsobutyImagnesium bromide, 2M solution in diethyl ether

Product Code 427390000; 427391000; 427398000

Address ThermoFisher Scientific Australia Pty Ltd

> 5 Caribbean Drive, Scoresby VICTORIA 3179, Australia

Emergency Tel. **CHEMTREC®**

03 9757 4559 or +613 9757 4559

Telephone / Fax Numbers Tel: 1300 735 292

Fax: 1800 067 639

E-mail address ANZinfo@thermofisher.com

Recommended Use Laboratory chemicals.

Uses advised against This product contains one or more substance(s) on the Illicit Drug Precursors/Reagents list.

> Verify requirements related to using, handling and storing these substances. This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction. This product does not contain any substance(s) listed on the voluntary National Code of Practice

for Chemicals of Security Concern.

Section 2 - Hazard(s) Identification

Classification under Safe Work Australia

Classified as hazardous according to criteria of Safe Work Australia

Physical hazards

Flammable liquids Category 1

Health hazards

Acute Oral Toxicity Category 4 Skin Corrosion/Irritation Category 1 B Serious Eye Damage/Eye Irritation Category 1 Specific target organ toxicity - (single exposure) Category 3

Environmental hazards

No hazards identified

Label Elements

ACR42739 Version 2 17-Nov-2022 Page 1/11







Signal Word

Danger

Hazard Statements

H224 - Extremely flammable liquid and vapor

H302 - Harmful if swallowed

H314 - Causes severe skin burns and eye damage

H336 - May cause drowsiness or dizziness

AUH014 - Reacts violently with water

AUH019 - May form explosive peroxides

AUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P233 - Keep container tightly closed

P240 - Ground and bond container and receiving equipment

P241 - Use explosion-proof electrical/ ventilating/ lighting equipment

P242 - Use non-sparking tools

P243 - Take action to prevent static discharges

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P264 - Wash face, hands and any exposed skin thoroughly after handling

P270 - Do not eat, drink or smoke when using this product

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor

P330 - Rinse mouth

P331 - Do NOT induce vomiting

P363 - Wash contaminated clothing before reuse

P372 - Explosion risk

P374 - Fight fire with normal precautions from a reasonable distance

P380 - Evacuate area

P403 + P235 - Store in a well-ventilated place. Keep cool

P404 - Store in a closed container

P501 - Dispose of contents/ container to an approved waste disposal plant

Other information

Toxic to terrestrial vertebrates

Section 3 - Composition and Information on Ingredients

Component	CAS No	Weight %		
Ethyl ether	60-29-7	66		
Isobutylmagnesium bromide	926-62-5	34		

ACR42739 Version 2 17-Nov-2022 Page 2 / 11

Section 4 - First Aid Measures

Inhalation Remove to fresh air. Do not use mouth-to-mouth method if victim ingested or inhaled the

substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required. If

not breathing, give artificial respiration.

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

First Aid Facilities Eyewash, safety shower and washroom.

Most important symptoms and

effects

Difficulty in breathing. Causes burns by all exposure routes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and promiting. Product is a correction material. Here of protein layout a promiting to the correction of the correcti

vomiting: Product is a corrosive material. Use of gastric lavage or emesis is

contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of

perforation

Notes to Physician Treat symptomatically. Symptoms may be delayed.

Section 5 - Fire Fighting Measures

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Water.

Hazardous Decomposition Products

Carbon monoxide (CO), Carbon dioxide (CO2).

Specific Hazards Arising from the Chemical

Extremely flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Reacts violently with water. Contact with water liberates extremely flammable gases.

Special protective equipment and precautions for fire fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

Section 6 - Accidental Release Measures

Emergency procedures

Use personal protective equipment as required. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

Should not be released into the environment. See Section 12 for additional Ecological Information.

Methods for Containment and Clean Up

ACR42739 Version 2 17-Nov-2022 Page 3 / 11

Clean-up methods - small spillage

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Do not expose spill to water.

Clean-up methods - large spillage

Typically only supplied is small quantiites as packaged goods.

If extremely toxic or used in larger quantities ensure a spillage action plan is in place. Evacuate area. Control the source and/or contain the spill if safe and able to do so. Use temporary diking, sand bags, dry sand, earth or proprietary booms/absorbent pads if available. Obtain advice on containment, neutralisation and clean-up from local emergency responders.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

Section 7 - Handling and Storage

Precautions for Safe Handling

Use only under a chemical fume hood. Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Use spark-proof tools and explosion-proof equipment. Do not breathe (dust, vapor, mist, gas). Do not ingest. If swallowed then seek immediate medical assistance. Take precautionary measures against static discharges. Do not allow contact with water. If peroxide formation is suspected, do not open or move container. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Conditions for Safe Storage, Including any Incompatibilities

Corrosives area. Flammables area. Keep away from heat, sparks and flame. Store under an inert atmosphere. Keep away from water or moist air. Store indoors. Keep containers tightly closed in a dry, cool and well-ventilated place. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals.

AS/NZS 2243.10:2004, Safety in laboratories - Storage of chemicals AS 1940-2004 - The storage and handling of flammable and combustible liquids

Section 8 - Exposure Controls and Personal Protection

Exposure limits

AUS - Exposure Standards for Atmospheric Contaminants in the Occupational Environment - Guidance Note on the Interpretation of Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:3008(1995)] Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)] updated in August, 2005. Safe Work Australia ACGIH - Threshold Limit Values - Ceiling (TLV-C) guidelines by the American Conference of Governmental Industrial Hygienists (ACGIH) for controlling worker exposure to airborne chemical concentrations in the workplace. UK - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. DE - MAK and BAT values of Hazardous Chemical Compounds in the Work Area. Published by German Research Foundation on July 1, 2011

Component	Australia	New Zealand WEL	ACGIH TLV	The United Kingdom	Germany
Ethyl ether	STEL: 500 ppm	TWA: 400 ppm	TWA: 400 ppm	STEL: 200 ppm 15 min	TWA: 400 ppm (8
	STEL: 1520 mg/m ³	TWA: 1210 mg/m ³	STEL: 500 ppm	STEL: 620 mg/m ³ 15	Stunden). AGW -
	TWA: 400 ppm	STEL: 500 ppm		min	exposure factor 1
	TWA: 1210 mg/m ³	STEL: 1520 mg/m ³		TWA: 100 ppm 8 hr	TWA: 1200 mg/m ³ (8
				TWA: 310 mg/m ³ 8 hr	Stunden). AGW -
					exposure factor 1
					TWA: 400 ppm (8
					Stunden). MAK
					TWA: 1200 mg/m ³ (8
					Stunden). MAK
					Höhepunkt: 400 ppm
					Höhepunkt: 1200 mg/m ³

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

ACR42739 Version 2 17-Nov-2022 Page 4 / 11

Exposure Controls Engineering Measures

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles (Australian/New Zealand Standard AS/NZS 1337 - Eye protectors for Industrial

applications)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	AUS/NZ Standard	Glove comments
Nitrile rubber	See manufacturers	-	AS/NZS 2161	(minimum requirement)
Viton (R)	recommendations			

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure

Use an AS/NZS 1716 approved respirator if exposure limits are exceeded or if irritation or **Repiratory Protection**

other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained in line with AS/NZS 1715 on the use

and maintenance of repiratory protective devices

low boiling organic solvent Type AX Brown conforming to EN371 (or AUS/NZ equivalent) Recommended Filter type:

Recommended half mask:-Valve filtering: EN405 or Half mask: EN140 plus filter, EN 141 (or AUS/NZ equivalent)

When RPE is used a face piece Fit Test should be conducted

Handle in accordance with good industrial hygiene and safety practice. **Hygiene Measures**

Environmental exposure controls No information available.

Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance

Physical State Liquid

No information available Odor

No data available **Odor Threshold** No information available

No data available

Melting Point/Range **Softening Point** No data available **Boiling Point/Range** 34.6 °C / 94.3 °F

-34 °C / -29.2 °F **Flash Point** Method - No information available

Evaporation Rate No data available Flammability (solid,gas) Not applicable Liquid

Explosion Limits No data available

Vapor Pressure No data available

Vapor Density No data available (Air = 1.0)

ACR42739 Version 2 17-Nov-2022 Page 5/11

Isobutylmagnesium bromide, 2M solution in diethyl ether

SAFETY DATA SHEET

Specific Gravity / Density 0.941

Bulk Density Not applicable Liquid

Water Solubility
Solubility in other solvents

No information available
No information available

Partition Coefficient (n-octanol/water)

Componentlog PowEthyl ether0.82

Autoignition Temperature

Decomposition Temperature

Viscosity

No data available
No data available
No data available

Explosive Properties

Oxidizing Properties No information available

Vapors may form explosive mixtures with air

Other information

Molecular Formula C4 H9 Br Mg Molecular Weight 161.32

Section 10 - Stability and Reactivity

Reactivity Yes

Stability Moisture sensitive. Reacts violently with water.

Conditions to Avoid Incompatible products, Excess heat, Keep away from open flames, hot surfaces and

sources of ignition.

Incompatible Materials Water, Oxidizing agent.

Hazardous Decomposition Products Carbon monoxide (CO). Carbon dioxide (CO2).

Hazardous Polymerization Hazardous polymerization does not occur.

Section 11 - Toxicological Information

Information on Toxicological Effects

Product Information

(a) acute toxicity;

Oral Category 4

DermalBased on available data, the classification criteria are not met
Inhalation
Based on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation		
Ethyl ether	Ethyl ether 1215 mg/kg (Rat)		32000 ppm (Rat) 4 h		

(b) skin corrosion/irritation; Category 1 B

(c) serious eye damage/irritation; No data available

(d) respiratory or skin sensitization;

Respiratory SkinNo data available
No data available

(e) germ cell mutagenicity; No data available

ACR42739 Version 2 17-Nov-2022 Page 6/11

(f) carcinogenicity; No data available

There are no known carcinogenic chemicals in this product

No data available (g) reproductive toxicity;

(h) STOT-single exposure; Category 3

Results / Target organs Central nervous system (CNS)

(i) STOT-repeated exposure; No data available

No information available. **Target Organs**

(j) aspiration hazard; No data available

Other Adverse Effects The toxicological properties have not been fully investigated.

delayed

Symptoms / effects, both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and

danger of perforation

Section 12 - Ecological Information

Do not empty into drains. . **Ecotoxicity effects**

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Ethyl ether	LC50: > 10000 mg/L, 96h static (Lepomis	EC50 = 165 mg/L/24h		EC50 = 5600 mg/L 15 min
	macrochirus) LC50: = 2560 mg/L, 96h flow-through (Pimephales promelas)			

Persistence and Degradability

Persistence

No information available

Persistence is unlikely, based on information available.

Bioaccumulation is unlikely **Bioaccumulative Potential**

Component	log Pow	Bioconcentration factor (BCF)				
Ethyl ether	Ethyl ether 0.82 No data a					
Mobility	The product contains volatile organic compounds (VOC) which will evaporate easily from all					
-	surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in					
Endocrine Disruptor Information	This product does not contain any known or so	uspected endocrine disruptors				
Persistent Organic Pollutant	This product does not contain any known or suspected substance					
Ozone Depletion Potential	This product does not contain any known or su	uspected substance				

Section 13 - Disposal Considerations

Waste from Residues/Unused **Products**

Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with all federal, E.P.A., state and local regulations. Assure conformity with all applicable regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

ACR42739 Version 2 17-Nov-2022 Page 7/11

Other Information Chemical wastes should be disposed through a licensed commercial waste collection

service. Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH

and harm aquatic organisms.

Section 14 - Transport Information

IMDG/IMO

UN-No UN3399

Proper Shipping Name Organometallic substance, liquid, water-reactive, flammable (Mixture)

Hazard Class 4.3 Subsidiary Hazard Class 3 Packing Group 1

<u>ADG</u>

UN-No UN3399

Proper Shipping Name Organometallic substance, liquid, water-reactive, flammable (Mixture)

Hazard Class 4.3
Subsidiary Hazard Class 3
Packing Group

racking Group	<u> </u>	
	Component	Hazchem Code
	Ethyl ether	3YE
	60-29-7 (66)	

IATA

UN-No UN3399

Proper Shipping Name Organometalic substance, liquid, water-reactive, flammable (Mixture)

Hazard Class 4.3 Subsidiary Hazard Class 3 Packing Group 1

Environmental hazards No hazards identified

Special Precautions No special precautions required

Additional information None known

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National Regulations Australia

See section 8 for national exposure control parameters.

Standard for the Uniform Scheduling of Medicines and Poisons

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons.

Component	Standard for the Uniform Scheduling of Medicines and Poisons
Ethyl ether - 60-29-7	Schedule 2 listed
·	Schedule 4 listed - for use in anaesthesia
	Schedule 5 listed - in preparations for use in internal combustion engines

ACR42739 Version 2 17-Nov-2022 Page 8 / 11

Schedule 6 listed - except when included in Schedule 2, 4 or 5, or in preparations containing <=10% of
Ether

Australian Industrial Chemicals Introduction Scheme (AICIS)

Component	Australian Industrial Chemicals Introduction Scheme (AICIS)	Additional information
Ethyl ether - 60-29-7	Present	-

Australian - Illicit Drug Precursors/Reagents Substance List

This product contains one or more substance(s) on the Illicit Drug Precursors/Reagents list. Verify requirements related to using, handling and storing these substances.

Chemicals of Security Concern

This product does not contain any substance(s) listed on the voluntary National Code of Practice for Chemicals of Security Concern

	Component	Australian - Illicit Drug Precursors/Reagents Substance List	Chemicals of Security Concern
-	Ethyl ether - 60-29-7	Category 3	

Legend

Category 3 - Chemicals and apparatus that may be used in the illicit production of drugs. Purchases from this list should alert companies or organizations to seek further indicators of any suspicious orders or enquiries. No official reporting is required for items on this list unless considered warranted

National pollutant inventory Not applicable

Prohibition or notification/licensing requirements

Shown below are details of specific prohibition/notifications or licencing requirements when they apply.

This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction.

International Inventories

Com	ponent	AICS	NZIoC	EINECS	ELINCS	TSCA	DSL	NDSL	PICCS	ENCS	ISHL	IECSC	KECL
Ethy	yl ether	X	X	200-467-2	-	X	X	-	Χ	Х	Χ	Х	KE-27690

Legend: X - Listed. '-' - Not Listed. KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

International Regulations

Ozone Depletion Potential This product does not contain any known or suspected substance

Persistent Organic Pollutant This product does not contain any known or suspected substance

Rotterdam Convention (PIC) Not applicable

Basel convention on the control of transboundary movements of hazardous wastes and their dispoal

Take note that wastes may be subject to export, import, or transit controls pursuant to the Basel convention and/or local regulations implementing the Basel convention.

ACR42739 Version 2 17-Nov-2022 Page 9 / 11

Component	Basel Convention (Hazardous Waste)	Australian Hazardous Waste Act - Categories	
		of Wastes to Be Controlled	
Ethyl ether - 60-29-7	Annex I - Y40 Annex I - Y42	Y40 Y42 except Halogenated solvents	

Component	CAS No	OECD HPV	Restriction of Hazardous Substances (RoHS)	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Ethyl ether	60-29-7	Listed	Not applicable	Not applicable	Not applicable
IsobutyImagnesium bromide	926-62-5	Not applicable	Not applicable	Not applicable	Not applicable

Authorisation/Restrictions according to EU REACH

Not applicable

Section 16 - Other Information

Legend

AICS - Australian Inventory of Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

IECSC - Chinese Inventory of Existing Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from

NZS 5433:2012 - Transport of Dangerous Goods on Land

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%
WEL - Workplace Exposure Limit
DNEL - Derived No Effect Level

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

VOC - (Volatile Organic Compound)

NZIoC - New Zealand Inventory of Chemicals

EINECS/ELINCS - European Inventory of Existing Commercial Chemical

Substances/EU List of Notified Chemical Substances
ENCS - Japanese Existing and New Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

CAS - Chemical Abstracts Service

ACGIH - American Conference of Governmental Industrial Hygienists

Predicted No Effect Concentration (PNEC)

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

ADG Australian Code for the Transport of Dangerous Goods by Road and Rail

OECD - Organisation for Economic Co-operation and Development

LC50 - Lethal Concentration 50% **ATE** - Acute Toxicity Estimate

RPE - Respiratory Protective Equipment **NOEC** - No Observed Effect Concentration

BCF - Bioconcentration factor

PBT - Persistent, Bioaccumulative, Toxic

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazardsOn basis of test dataHealth HazardsCalculation methodEnvironmental hazardsCalculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts. Chemical incident response training.

Revision Date 17-Nov-2022 Revision Summary Not applicable.

ACR42739 Version 2 17-Nov-2022 Page 10 / 11

This Safety Data Sheet (SDS) is prepared in accordance to and complies with the requirements of Safe Work Australia - Work Health and Safety Regulations (WHS Regulations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

ACR42739 Version 2 17-Nov-2022 Page 11 / 11