

according to Regulation (EC) No. 1907/2006

Creation Date 25-Oct-2010 Revision Date 08-Feb-2024 Revision Number 4

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product Description: <u>Aluminum powder</u>

Cat No.: 41000

 Index No
 013-001-00-6

 CAS No
 7429-90-5

 EC No
 231-072-3

Molecular Formula Al REACH registration number -

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

# 1.3. Details of the supplier of the safety data sheet

Company

Thermo Fisher (Kandel) GmbH

Erlenbachweg 2, 76870 Kandel, Germany

Tel: +49 (0) 721 84007 280 Fax: +49 (0) 721 84007 300

**Swiss distributor -** Fisher Scientific AG Neuhofstrasse 11, CH 4153 Reinach

Tel: +41 (0) 56 618 41 11

https://www.fishersci.ch/ch/en/customer-help-

support/forms/email-us.html

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:

Tox Info Suisse Emergency Number: 145 (24hr)

Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)

Chemtrec (24h) Toll-Free: 0800 564 402 Chemtrec Local: +41-43 508 20 11 (Zurich)

# **SECTION 2: HAZARDS IDENTIFICATION**

### 2.1. Classification of the substance or mixture

\_\_\_\_\_

### Aluminum powder Revision Date 08-Feb-2024

# CLP Classification - Regulation (EC) No 1272/2008

# **Physical hazards**

Substances/mixtures which, in contact with water, emit flammable gases Pyrophoric solids

Category 2 (H261) Category 1 (H250)

### **Health hazards**

Based on available data, the classification criteria are not met

### **Environmental hazards**

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

### 2.2. Label elements



**Signal Word** 

Danger

### **Hazard Statements**

H250 - Catches fire spontaneously if exposed to air

H261 - In contact with water releases flammable gases

May form combustible dust concentrations in air

### **Precautionary Statements**

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P231 + P232 - Handle and store contents under inert gas. Protect from moisture

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P302 + P335 + P334 - IF ON SKIN: Brush off loose particles from skin. Immerse in cool water

### 2.3. Other hazards

In accordance with Annex XIII of the REACH Regulation, inorganic substances do not require assessment

May form explosible dust-air mixture if dispersed

This product does not contain any known or suspected endocrine disruptors

# **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

### 3.1. Substances

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Aluminum	7429-90-5	EEC No. 231-072-3	<=100	Pyr. Sol. 1 (H250) Water-react. 2 (H261)

Aluminum powder Revision Date 08-Feb-2024

REACH registration number -

Full text of Hazard Statements: see section 16

# **SECTION 4: FIRST AID MEASURES**

### 4.1. Description of first aid measures

General Advice If symptoms persist, call a physician.

**Eye Contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

**Ingestion** Clean mouth with water and drink afterwards plenty of water. Get medical attention if

symptoms occur.

**Inhalation** Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

None reasonably foreseeable.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

# **SECTION 5: FIREFIGHTING MEASURES**

# 5.1. Extinguishing media

### **Suitable Extinguishing Media**

Dry sand; dry clay; Limestone powder; approved class D extinguishers.

# Extinguishing media which must not be used for safety reasons

Water.

### 5.2. Special hazards arising from the substance or mixture

Water reactive. Contact with water liberates extremely flammable gases. Spontaneously flammable in air. Fine dust dispersed in air may ignite. Dust can form an explosive mixture with air. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

### **Hazardous Combustion Products**

Hydrogen, Fumes of aluminum or aluminum oxide.

# 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# **SECTION 6: ACCIDENTAL RELEASE MEASURES**

Aluminum powder Revision Date 08-Feb-2024

### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Avoid dust formation. Ensure adequate ventilation.

### 6.2. Environmental precautions

Should not be released into the environment.

# 6.3. Methods and material for containment and cleaning up

Sweep up and shovel into suitable containers for disposal. Keep in suitable, closed containers for disposal.

### 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

# **SECTION 7: HANDLING AND STORAGE**

### 7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Avoid dust formation. Avoid ingestion and inhalation. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing.

### **Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area. Store under an inert atmosphere. Keep away from water or moist air.

Technical Rules for Hazardous Substances (TRGS) 510

Storage Class (LGK) (Germany)

Storage Class/LGK 4.2

Switzerland - Storage of hazardous substances

Storage class - SC 4.2 https://www.kvu.ch/de/themen/stoffe-und-produkte https://www.kvu.ch/fr/themes/substances-et-produits https://www.kvu.ch/it/temi/sostanze-e-prodotti

### 7.3. Specific end use(s)

Use in laboratories

# **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

# 8.1. Control parameters

### **Exposure limits**

List source(s): **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Aluminum		STEL: 30 mg/m <sup>3</sup> 15 min	TWA / VME: 10 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup> 8 uren	TWA / VLA-ED: 1 mg/m <sup>3</sup>
		STEL: 12 mg/m <sup>3</sup> 15 min	(8 heures). metal		(8 horas)
		TWA: 10 mg/m <sup>3</sup> 8 hr	TWA / VME: 5 mg/m³ (8		, ,
		TWA: 4 mg/m <sup>3</sup> 8 hr	heures).		

### Aluminum powder

Revision Date 08-Feb-2024

Component	Italy	Germany	Portugal	The Netherlands	Finland
Aluminum		TWA: 1.25 mg/m <sup>3</sup> (8	TWA: 1 mg/m <sup>3</sup> 8 horas		
		Stunden). AGW -	_		
		exposure factor 2			
		TWA: 10 mg/m <sup>3</sup> (8			
		Stunden). AGW -			
		exposure factor 2			
		TWA: 4 mg/m³ (8			
		Stunden). MAK			
		TWA: 1.5 mg/m³ (8			
		Stunden). MAK			
0	Acceptate	D	0	Dalam I	N
Component Aluminum	Austria MAK-KZGW: 20 mg/m³	Denmark TWA: 5 mg/m <sup>3</sup> 8 timer	Switzerland TWA: 3 mg/m <sup>3</sup> 8	Poland TWA: 2.5 mg/m <sup>3</sup> 8	Norway TWA: 5 mg/m <sup>3</sup> 8 time
Aluminum	15 Minuten	TWA: 2 mg/m³ 8 timer	Stunden	godzinach	STEL: 10 mg/m <sup>3</sup> 15
	MAK-TMW: 10 mg/m <sup>3</sup> 8	STEL: 10 mg/m <sup>3</sup> 15	TWA: 10 mg/m <sup>3</sup> 8	TWA: 1.2 mg/m <sup>3</sup> 8	minutter.
	Stunden	minutter	Stunden	godzinach	pyrotechnical;value
	Standen	STEL: 4 mg/m <sup>3</sup> 15	Stariaeri	godzinach	calculated powder
		minutter			odiodiated powder
	•				
Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Aluminum	TWA: 10.0 mg/m <sup>3</sup>	TWA-GVI: 10 mg/m³ 8	TWA: 1 mg/m³ 8 hr.		TWA: 10.0 mg/m³ 8 hodinách, dust
	TWA: 1.5 mg/m <sup>3</sup>	satima. total dust,	respirable fraction		nodinach, dust
		inhalable particles	STEL: 3 mg/m <sup>3</sup> 15 min		
		TWA-GVI: 4 mg/m <sup>3</sup> 8 satima. respirable dust			
		Satima. Tespirable dust			<u> </u>
Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Aluminum	TWA: 10 mg/m <sup>3</sup> 8		TWA: 10 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup> 8	STEL: 10 mg/m <sup>3</sup> dus
	tundides. total dust		TWA: 5 mg/m <sup>3</sup>	órában. AK	and powder
	TWA: 4 mg/m <sup>3</sup> 8				TWA: 5 mg/m <sup>3</sup> 8
	tundides. respirable				klukkustundum. dus
	dust				and powder
Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Aluminum	TWA: 2 mg/m <sup>3</sup>	TWA: 5 mg/m³ inhalable			TWA: 3 mg/m <sup>3</sup> 8 ore
		fraction IPRD			TWA: 1 mg/m <sup>3</sup> 8 ore
		TWA: 2 mg/m <sup>3</sup>			STEL: 10 mg/m <sup>3</sup> 15
		respirable fraction IPRD			minute
		TWA: 1 mg/m <sup>3</sup> IPRD			STEL: 3 mg/m <sup>3</sup> 15
		<u> </u>			minute
Component	Durasia	Clavek Benublis	Clavenia	Cwadan	Tuelcase
Component Aluminum	Russia TWA: 2 mg/m³ 0036	Slovak Republic TWA: 4 mg/m <sup>3</sup>	Slovenia	Sweden TLV: 5 mg/m³ 8 timmar.	Turkey
Alullillulli	MAC: 6 mg/m <sup>3</sup>	inhalable dust		NGV	
	WAC. 6 mg/m²	TWA: 1.5 mg/m <sup>3</sup>		TLV: 2 mg/m <sup>3</sup> 8 timmar.	
		respirable dust		NGV	
ological limit v	alues				
st source(s):					
Component	European Union	United Kingdom	France	Spain	Germany
Aluminum					Aluminum: 50 μg/g
					Creatinine urine (for
					long-term exposures:
					the end of the shift aft
					several shifts)

		Finland	Denmark	Bulgaria	Romania
Aluminu	n				Aluminum: 200 μg/L
					urine end of shift

	Component	Gibraltar	Latvia	Slovak Republic	Luxembourg	Turkey
Γ	Aluminum			Aluminum: 60 μg/g		
1				creatinine urine not		
1				critical		

**Monitoring methods**BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of

Aluminum powder Revision Date 08-Feb-2024

exposure to chemical and biological agents.

MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust

### Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

# **Predicted No Effect Concentration (PNEC)**

See values below.

Component	Fresh water		Water Intermittent	•	Soil (Agriculture)
		sediment		sewage treatment	
Aluminum				PNEC = 20mg/L	
7429-90-5 ( <=100 )					

# 8.2. Exposure controls

### **Engineering Measures**

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

# Personal protective equipment

**Eye Protection** Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material Natural rubber Nitrile rubber	Breakthrough time See manufacturers recommendations	Glove thickness	EU standard EN 374	Glove comments (minimum requirement)
Neoprene PVC	recommendations			

**Skin and body protection** Wear appropriate protective gloves and clothing to prevent skin exposure.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

**Respiratory Protection** When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced **Recommended Filter type:** Particulates filter conforming to EN 143

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

**Recommended half mask:-** Particle filtering: EN149:2001 When RPE is used a face piece Fit Test should be conducted

**Environmental exposure controls** No information available.

Aluminum powder Revision Date 08-Feb-2024

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

# 9.1. Information on basic physical and chemical properties

Physical State Powder Solid

Appearance Grey Odor Odorless

Odor ThresholdNo data availableMelting Point/Range660 °C / 1220 °FSoftening PointNo data available

Boiling Point/Range 2327 °C / 4220.6 °F @ 760 mmHg

Flammability (liquid) Not applicable

Flammability (solid,gas) No information available

**Explosion Limits** No data available

Flash Point No information available Method - No information available

Autoignition Temperature 400 °C / 752 °F Decomposition Temperature PH No data available Not applicable

Viscosity Not applicable

Water Solubility Insoluble

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Vapor Pressure No data available

Density / Specific Gravity 2.7020

Bulk Density

No data available

Vapor Density Not applicable Solid

Particle characteristics No data available

# 9.2. Other information

Molecular Formula Al Molecular Weight 26.98

**Substances/mixtures which, in** Emitted gas ignites spontaneously

contact with water, emit flammable

gases

Evaporation Rate Not applicable - Solid

# **SECTION 10: STABILITY AND REACTIVITY**

10.1. Reactivity Yes

10.2. Chemical stability

Water reactive. Moisture sensitive. Air sensitive. Pyrophoric: Spontaneously flammable in

Solid

Solid

air.

10.3. Possibility of hazardous reactions

**Hazardous Polymerization** Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

10.4. Conditions to avoid

Avoid dust formation. Incompatible products. Exposure to air. Exposure to moist air or

water. Excess heat.

10.5. Incompatible materials

Water. Strong acids. Strong bases. Alcohols. Halogens. Halogenated compounds. Carbon

dioxide (CO2).

Aluminum powder Revision Date 08-Feb-2024

10.6. Hazardous decomposition products

Hydrogen. Fumes of aluminum or aluminum oxide.

# **SECTION 11: TOXICOLOGICAL INFORMATION**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Product Information**No acute toxicity information is available for this product

(a) acute toxicity;

OralNo data availableDermalNo data availableInhalationNo data available

Component	Component LD50 Oral		LC50 Inhalation	
Aluminum	-	-	LC50 > 0.888 mg/L (Rat) 4 h	

(b) skin corrosion/irritation; No data available

(c) serious eye damage/irritation; No data available

(d) respiratory or skin sensitization;

**Respiratory Skin**No data available
No data available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; No data available

(h) STOT-single exposure; No data available

(i) STOT-repeated exposure; No data available

Target Organs None known.

(j) aspiration hazard; Not applicable

Solid

Symptoms / effects,both acute and No information available. delayed

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any

known or suspected endocrine disruptors.

# **SECTION 12: ECOLOGICAL INFORMATION**

Aluminum powder Revision Date 08-Feb-2024

12.1. Toxicity

Ecotoxicity effects

12.2. Persistence and degradability

Persistence Insoluble in water.

**Degradability** Not relevant for inorganic substances.

**12.3. Bioaccumulative potential** May have some potential to bioaccumulate

12.4. Mobility in soil Spillage unlikely to penetrate soil Is not likely mobile in the environment due its low water

solubility.

12.5. Results of PBT and vPvB

assessment

In accordance with Annex XIII of the REACH Regulation, inorganic substances do not

require assessment.

12.6. Endocrine disrupting

properties

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects
Persistent Organic Pollutant

Persistent Organic Pollutant Ozone Depletion Potential This product does not contain any known or suspected substance This product does not contain any known or suspected substance

# **SECTION 13: DISPOSAL CONSIDERATIONS**

13.1. Waste treatment methods

Waste from Residues/Unused

**Products** 

Waste is classified as hazardous. Dispose of in accordance with the European Directives

on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but

application specific.

Other Information Waste codes should be assigned by the user based on the application for which the product

was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with

local regulations.

Switzerland - Waste Ordinance Disposal should be in accordance with applicable regional, national and local laws and

regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance,

ADWO) SR 814.600

https://www.fedlex.admin.ch/eli/cc/2015/891/en

# **SECTION 14: TRANSPORT INFORMATION**

### IMDG/IMO

**14.1. UN number** UN1396

14.2. UN proper shipping name ALUMINIUM POWDER, UNCOATED

14.3. Transport hazard class(es) 4.3 14.4. Packing group II

Aluminum powder Revision Date 08-Feb-2024

### ADR

**14.1. UN number** UN1396

14.2. UN proper shipping name ALUMINIUM POWDER, UNCOATED

14.3. Transport hazard class(es) 4.3. 14.4. Packing group

# **IATA**

<u>14.1. UN number</u> UN1396

14.2. UN proper shipping name ALUMINIUM POWDER, UNCOATED

**14.3. Transport hazard class(es)** 4.3 **14.4. Packing group** II

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable, packaged goods

# **SECTION 15: REGULATORY INFORMATION**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **International Inventories**

Aluminum

China, X = listed, Australia, U.S.A. (TSCA), Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Australia (AICS), Korea (KECL), China (IECSC), Japan (ENCS), Philippines (PICCS), Taiwan (TCSI), Japan (ISHL), New Zealand (NZIoC), Japan (ISHL). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Aluminum	7429-90-5	231-072-3	ı	-	X	Χ	KE-00881	Χ	ı
Component	CAS No	TSCA		ventory ation - Inactive	DSL	NDSL	AICS	NZIoC	PICCS

**ACTIVE** 

Legend: X - Listed '-' - Not Listed KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

7429-90-5

# Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization		REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Aluminum	7429-90-5	-	Use restricted. See item 75. (see link for restriction details)	•

# **REACH links**

https://echa.europa.eu/substances-restricted-under-reach

# Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) -	Seveso III Directive (2012/18/EC) -
-		Qualifying Quantities for Major Accident	Qualifying Quantities for Safety Report
		Notification	Requirements

### Aluminum powder

Aluminum

Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

7429-90-5

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

# **National Regulations**

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

**WGK Classification** See table for values

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Aluminum	nwg	

Component	France - INRS (Tables of occupational diseases)
Aluminum	Tableaux des maladies professionnelles (TMP) - RG 32
	Tableaux des maladies professionnelles (TMP) - RG 16,RG 16bis

### **Swiss Regulations**

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

### 15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has not been conducted

# **SECTION 16: OTHER INFORMATION**

# Full text of H-Statements referred to under sections 2 and 3

H250 - Catches fire spontaneously if exposed to air

H261 - In contact with water releases flammable gases

### Legend

**CAS** - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

Revision Date 08-Feb-2024

Not applicable

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

Substances List

PICCS - Philippines Inventory of Chemicals and Chemical Substances

**ENCS** - Japanese Existing and New Chemical Substances **AICS** - Australian Inventory of Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

Aluminum powder Revision Date 08-Feb-2024

ADR - European Agreement Concerning the International Carriage of

Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime

Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air **Transport Association** 

MARPOL - International Convention for the Prevention of Pollution from

Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

### Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

### **Training Advice**

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

**Prepared By** Health, Safety and Environmental Department

**Creation Date** 25-Oct-2010 **Revision Date** 08-Feb-2024

**Revision Summary** New emergency telephone response service provider.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2. Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**