

Creation Date 22-Oct-2009

Revision Date 06-Dec-2024

Revision Number 10

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: **Sodium trimethylsilanolate, 1M solution in THF**
Cat No. : **428830000; 428831000; 428838000**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

EU entity/business name
Thermo Fisher Scientific
Janssen Pharmaceuticaaan 3a, 2440 Geel, Belgium

UK entity/business name
Fisher Scientific UK
Bishop Meadow Road,
Loughborough, Leicestershire LE11 5RG, United Kingdom

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
e-mail - infoch@thermofisher.com

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

SAFETY DATA SHEET

Sodium trimethylsilanolate, 1M solution in THF

Revision Date 06-Dec-2024

Physical hazards

Flammable liquids

Category 2 (H225)

Health hazards

Acute oral toxicity
Skin Corrosion/Irritation
Serious Eye Damage/Eye Irritation
Carcinogenicity
Specific target organ toxicity - (single exposure)

Category 4 (H302)
Category 1 B (H314)
Category 1 (H318)
Category 2 (H351)
Category 3 (H335) (H336)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor
H302 - Harmful if swallowed
H314 - Causes severe skin burns and eye damage
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H351 - Suspected of causing cancer
EUH019 - May form explosive peroxides

Precautionary Statements

P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor/physician
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

2.3. Other hazards

Toxic to terrestrial vertebrates
This product does not contain any known or suspected endocrine disruptors

Section 3: Composition/information on ingredients

SAFETY DATA SHEET

Sodium trimethylsilanolate, 1M solution in THF

Revision Date 06-Dec-2024

3.2. Mixtures

| Component | CAS No | EC No | Weight % | CLP Classification - Regulation (EC) No 1272/2008 |
|----------------------------------|------------|-------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Silanol, trimethyl-, sodium salt | 18027-10-6 | EEC No. 241-939-8 | 13 | Skin Corr. 1B (H314) Eye Dam. 1 (H318) |
| Tetrahydrofuran | 109-99-9 | 203-726-8 | 87 | Flam. Liq. 2 (H225) Acute Tox. 4 (H302) Eye Irrit. 2 (H319) STOT SE 3 (H335) STOT SE 3 (H336) Carc. 2 (H351) (EUH019) |

| Component | Specific concentration limits (SCL's) | M-Factor | Component notes |
|-----------------|--------------------------------------------------------------------------|----------|-----------------|
| Tetrahydrofuran | Acute Tox. 4 :: C>82.5% Eye Irrit. 2 :: C>=25% STOT SE 3 :: C>=25% | - | - |

Full text of Hazard Statements: see section 16

Section 4: First aid measures

4.1. Description of first aid measures

| | |
|-------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General Advice | Show this safety data sheet to the doctor in attendance. Immediate medical attention is required. |
| Eye Contact | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required. |
| Skin Contact | Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately. |
| Ingestion | Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately. |
| Inhalation | If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately. |
| Self-Protection of the First Aider | Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. |

4.2. Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Causes central nervous system depression

SAFETY DATA SHEET

Sodium trimethylsilanolate, 1M solution in THF

Revision Date 06-Dec-2024

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

Section 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂), Silicon dioxide, Sodium oxides.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Should not be released into the environment.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

Section 7: Handling and storage

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. If peroxide formation is suspected, do not open or move container. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

SAFETY DATA SHEET

Sodium trimethylsilanolate, 1M solution in THF

Revision Date 06-Dec-2024

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area. Flammables area. Keep away from heat, sparks and flame. Shelf life 12 months. May form explosive peroxides on prolonged storage. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Class 3

Switzerland - Storage of hazardous substances

SC 3 Storage class -
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

Section 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

| Component | European Union | The United Kingdom | France | Belgium | Spain |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Tetrahydrofuran | TWA: 50 ppm (8h) TWA: 150 mg/m ³ (8h) STEL: 100 ppm (15min) STEL: 300 mg/m ³ (15min) Skin | STEL: 100 ppm 15 min STEL: 300 mg/m ³ 15 min TWA: 50 ppm 8 hr TWA: 150 mg/m ³ 8 hr Skin | TWA / VME: 50 ppm (8 heures). restrictive limit TWA / VME: 150 mg/m ³ (8 heures). restrictive limit STEL / VLCT: 100 ppm. restrictive limit STEL / VLCT: 300 mg/m ³ . restrictive limit Peau | TWA: 50 ppm 8 uren TWA: 150 mg/m ³ 8 uren STEL: 100 ppm 15 minuten STEL: 300 mg/m ³ 15 minuten Huid | STEL / VLA-EC: 100 ppm (15 minutos). STEL / VLA-EC: 300 mg/m ³ (15 minutos). TWA / VLA-ED: 50 ppm (8 horas) TWA / VLA-ED: 150 mg/m ³ (8 horas) Piel |

| Component | Italy | Germany | Portugal | The Netherlands | Finland |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Tetrahydrofuran | TWA: 50 ppm 8 ore. Time Weighted Average TWA: 150 mg/m ³ 8 ore. Time Weighted Average STEL: 100 ppm 15 minuti. Short-term STEL: 300 mg/m ³ 15 minuti. Short-term Pelle | TWA: 50 ppm (8 Stunden). AGW - exposure factor 2 TWA: 150 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 20 ppm (8 Stunden). MAK TWA: 60 mg/m ³ (8 Stunden). MAK Höhepunkt: 40 ppm | STEL: 100 ppm 15 minutos STEL: 300 mg/m ³ 15 minutos TWA: 50 ppm 8 horas TWA: 150 mg/m ³ 8 horas Pele | huid STEL: 200 ppm 15 minuten STEL: 600 mg/m ³ 15 minuten TWA: 100 ppm 8 uren TWA: 300 mg/m ³ 8 uren | TWA: 50 ppm 8 tunteina TWA: 150 mg/m ³ 8 tunteina STEL: 100 ppm 15 minuutteina STEL: 300 mg/m ³ 15 minuutteina Iho |

SAFETY DATA SHEET

Sodium trimethylsilanolate, 1M solution in THF

Revision Date 06-Dec-2024

| | | | | | |
|--|--|------------------------------------------|--|--|--|
| | | Höhepunkt: 120 mg/m ³ Haut | | | |
|--|--|------------------------------------------|--|--|--|

| Component | Austria | Denmark | Switzerland | Poland | Norway |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Tetrahydrofuran | Haut MAK-KZGW: 100 ppm 15 Minuten MAK-KZGW: 300 mg/m ³ 15 Minuten MAK-TMW: 50 ppm 8 Stunden MAK-TMW: 150 mg/m ³ 8 Stunden | TWA: 50 ppm 8 timer TWA: 150 mg/m ³ 8 timer STEL: 300 mg/m ³ 15 minutter STEL: 100 ppm 15 minutter Hud | Haut/Peau STEL: 100 ppm 15 Minuten STEL: 300 mg/m ³ 15 Minuten TWA: 50 ppm 8 Stunden TWA: 150 mg/m ³ 8 Stunden | STEL: 300 mg/m ³ 15 minutach TWA: 150 mg/m ³ 8 godzinach | TWA: 50 ppm 8 timer TWA: 150 mg/m ³ 8 timer STEL: 75 ppm 15 minutter. value calculated STEL: 187.5 mg/m ³ 15 minutter. value calculated Hud |

| Component | Bulgaria | Croatia | Ireland | Cyprus | Czech Republic |
|-----------------|--------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Tetrahydrofuran | TWA: 50.0 ppm TWA: 150.0 mg/m ³ STEL : 100 ppm STEL : 300.0 mg/m ³ Skin notation | kože TWA-GVI: 50 ppm 8 satima. TWA-GVI: 150 mg/m ³ 8 satima. STEL-KGVI: 100 ppm 15 minutama. STEL-KGVI: 300 mg/m ³ 15 minutama. | TWA: 50 ppm 8 hr. TWA: 150 mg/m ³ 8 hr. STEL: 100 ppm 15 min STEL: 300 mg/m ³ 15 min Skin | Skin-potential for cutaneous absorption STEL: 100 ppm STEL: 300 mg/m ³ TWA: 50 ppm TWA: 150 mg/m ³ | TWA: 150 mg/m ³ 8 hodinách. Potential for cutaneous absorption Ceiling: 300 mg/m ³ |

| Component | Estonia | Gibraltar | Greece | Hungary | Iceland |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| Tetrahydrofuran | Nahk TWA: 50 ppm 8 tundides. TWA: 150 mg/m ³ 8 tundides. STEL: 100 ppm 15 minutites. STEL: 300 mg/m ³ 15 minutites. | Skin notation TWA: 50 ppm 8 hr TWA: 150 mg/m ³ 8 hr STEL: 100 ppm 15 min STEL: 300 mg/m ³ 15 min | STEL: 250 ppm STEL: 735 mg/m ³ TWA: 200 ppm TWA: 590 mg/m ³ | STEL: 300 mg/m ³ 15 percekben. CK STEL: 100 ppm 15 percekben. CK TWA: 150 mg/m ³ 8 óraban. AK TWA: 50 ppm 8 óraban. AK lehetséges borön keresztüli felszívódás | STEL: 100 ppm STEL: 300 mg/m ³ TWA: 50 ppm 8 klukkustundum. TWA: 150 mg/m ³ 8 klukkustundum. Skin notation |

| Component | Latvia | Lithuania | Luxembourg | Malta | Romania |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| Tetrahydrofuran | skin - potential for cutaneous exposure STEL: 100 ppm STEL: 300 mg/m ³ TWA: 50 ppm TWA: 150 mg/m ³ | TWA: 50 ppm IPRD TWA: 150 mg/m ³ IPRD Oda STEL: 100 ppm STEL: 300 mg/m ³ | Possibility of significant uptake through the skin TWA: 50 ppm 8 Stunden TWA: 150 mg/m ³ 8 Stunden STEL: 100 ppm 15 Minuten STEL: 300 mg/m ³ 15 Minuten | possibility of significant uptake through the skin TWA: 50 ppm TWA: 150 mg/m ³ STEL: 100 ppm 15 minuti STEL: 300 mg/m ³ 15 minuti | Skin notation TWA: 50 ppm 8 ore TWA: 150 mg/m ³ 8 ore STEL: 100 ppm 15 minute STEL: 300 mg/m ³ 15 minute |

| Component | Russia | Slovak Republic | Slovenia | Sweden | Turkey |
|-----------------|----------------------------|----------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| Tetrahydrofuran | MAC: 100 mg/m ³ | Ceiling: 300 mg/m ³ Potential for cutaneous absorption TWA: 50 ppm TWA: 150 mg/m ³ | TWA: 50 ppm 8 urah TWA: 150 mg/m ³ 8 urah Koža STEL: 100 ppm 15 minutah STEL: 300 mg/m ³ 15 minutah | Binding STEL: 100 ppm 15 minuter Binding STEL: 300 mg/m ³ 15 minuter TLV: 50 ppm 8 timmar. NGV TLV: 150 mg/m ³ 8 timmar. NGV | Deri TWA: 50 ppm 8 saat TWA: 150 mg/m ³ 8 saat STEL: 100 ppm 15 dakika STEL: 300 mg/m ³ 15 dakika |

Biological limit values

List source(s):

| Component | European Union | United Kingdom | France | Spain | Germany |
|-----------------|----------------|----------------|--------|-----------------------------------------------|--------------------------------------------------|
| Tetrahydrofuran | | | | Tetrahydrofuran: 2 mg/L urine end of shift | Tetrahydrofuran: 2 mg/L urine (end of shift) |

SAFETY DATA SHEET

Sodium trimethylsilanolate, 1M solution in THF

Revision Date 06-Dec-2024

| Component | Gibraltar | Latvia | Slovak Republic | Luxembourg | Turkey |
|-----------------|-----------|--------|-------------------------------------------------------------------|------------|--------|
| Tetrahydrofuran | | | Tetrahydrofuran: 2 mg/L urine end of exposure or work shift | | |

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

| Component | Acute effects local (Dermal) | Acute effects systemic (Dermal) | Chronic effects local (Dermal) | Chronic effects systemic (Dermal) |
|------------------------------------|---------------------------------|------------------------------------|-----------------------------------|--------------------------------------|
| Tetrahydrofuran 109-99-9 (87) | | | | DNEL = 12.6mg/kg bw/day |

| Component | Acute effects local (Inhalation) | Acute effects systemic (Inhalation) | Chronic effects local (Inhalation) | Chronic effects systemic (Inhalation) |
|------------------------------------|-------------------------------------|----------------------------------------|---------------------------------------|------------------------------------------|
| Tetrahydrofuran 109-99-9 (87) | DNEL = 300mg/m ³ | DNEL = 96mg/m ³ | DNEL = 150mg/m ³ | DNEL = 72.4mg/m ³ |

Predicted No Effect Concentration (PNEC)

See values below.

| Component | Fresh water | Fresh water sediment | Water Intermittent | Microorganisms in sewage treatment | Soil (Agriculture) |
|------------------------------------|-----------------|---------------------------------|--------------------|---------------------------------------|-----------------------------|
| Tetrahydrofuran 109-99-9 (87) | PNEC = 4.32mg/L | PNEC = 23.3mg/kg sediment dw | PNEC = 21.6mg/L | PNEC = 4.6mg/L | PNEC = 2.13mg/kg soil dw |

| Component | Marine water | Marine water sediment | Marine water Intermittent | Food chain | Air |
|------------------------------------|------------------|---------------------------------|------------------------------|------------------------|-----|
| Tetrahydrofuran 109-99-9 (87) | PNEC = 0.432mg/L | PNEC = 2.33mg/kg sediment dw | | PNEC = 67mg/kg food | |

8.2. Exposure controls

Engineering Measures

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles (European standard - EN 166)

Hand Protection

Protective gloves

| Glove material | Breakthrough time | Glove thickness | EU standard | Glove comments |
|----------------|-------------------|-----------------|-------------|-----------------------|
| Butyl rubber | See manufacturers | - | | (minimum requirement) |

SAFETY DATA SHEET

Sodium trimethylsilanolate, 1M solution in THF

Revision Date 06-Dec-2024

| | | |
|-----------------|-----------------|--------|
| Neoprene gloves | recommendations | EN 374 |
|-----------------|-----------------|--------|

Skin and body protection Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced
Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141
When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls No information available.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | | |
|------------------------------------------------|--------------------------|------------------------------------------|
| Physical State | Liquid | |
| Appearance | | |
| Odor | No information available | |
| Odor Threshold | No data available | |
| Melting Point/Range | No data available | |
| Softening Point | No data available | |
| Boiling Point/Range | No information available | |
| Flammability (liquid) | Highly flammable | On basis of test data |
| Flammability (solid,gas) | Not applicable | Liquid |
| Explosion Limits | No data available | |
| Flash Point | -17 °C / 1.4 °F | Method - No information available |
| Autoignition Temperature | No data available | |
| Decomposition Temperature | No data available | |
| pH | No information available | |
| Viscosity | No data available | |
| Water Solubility | Miscible | |
| Solubility in other solvents | No information available | |
| Partition Coefficient (n-octanol/water) | | |
| Component | log Pow | |
| Tetrahydrofuran | 0.45 | |
| Vapor Pressure | No data available | |
| Density / Specific Gravity | No data available | |
| Bulk Density | Not applicable | Liquid |
| Vapor Density | No data available | (Air = 1.0) |
| Particle characteristics | Not applicable (liquid) | |

SAFETY DATA SHEET

Sodium trimethylsilanolate, 1M solution in THF

Revision Date 06-Dec-2024

9.2. Other information

Explosive Properties

Vapors may form explosive mixtures with air

Section 10: Stability and reactivity

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Moisture sensitive. May form explosive peroxides.

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous Reactions

Hazardous polymerization does not occur.
None under normal processing.

10.4. Conditions to avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition. Exposure to moist air or water.

10.5. Incompatible materials

Water. Strong oxidizing agents.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂). Silicon dioxide. Sodium oxides.

Section 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral

Category 4

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

Toxicology data for the components

| Component | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|-----------------|--------------------|-----------------------|-----------------------------------------------|
| Tetrahydrofuran | 1650 mg/kg (Rat) | > 2000 mg/kg (Rabbit) | 180 mg/L (Rat) 1 h 53.9 mg/L (Rat) 4 h |

(b) skin corrosion/irritation;

Category 1 B

(c) serious eye damage/irritation;

Category 1

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

No data available

| Component | Test method | Test species | Study result |
|------------------------------------|---------------------------------------------------|--------------|-----------------|
| Tetrahydrofuran 109-99-9 (87) | Local Lymph Node Assay OECD Test Guideline 429 | mouse | non-sensitising |

SAFETY DATA SHEET

Sodium trimethylsilanolate, 1M solution in THF

Revision Date 06-Dec-2024

(e) germ cell mutagenicity; No data available

| Component | Test method | Test species | Study result |
|------------------------------------|---------------------------------------------------------|-----------------------|--------------|
| Tetrahydrofuran 109-99-9 (87) | OECD Test Guideline 476 Gene cell mutation | in vivo Mammalian | negative |
| | OECD Test Guideline 473 Chromosomal aberration assay | in vitro Mammalian | negative |

(f) carcinogenicity; Category 2

The table below indicates whether each agency has listed any ingredient as a carcinogen
Limited evidence of a carcinogenic effect

| Component | EU | UK | Germany | IARC |
|-----------------|----|----|---------|----------|
| Tetrahydrofuran | | | | Group 2B |

(g) reproductive toxicity; No data available

| Component | Test method | Test species / Duration | Study result |
|------------------------------------|-------------------------|-------------------------|-------------------|
| Tetrahydrofuran 109-99-9 (87) | OECD Test Guideline 416 | Rat 2 Generation | NOAEL = 3,000 ppm |

(h) STOT-single exposure; Category 3

Results / Target organs Respiratory system, Central nervous system (CNS).

(i) STOT-repeated exposure; No data available

Target Organs No information available.

(j) aspiration hazard; No data available

Other Adverse Effects The toxicological properties have not been fully investigated.

Symptoms / effects, both acute and delayed Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Causes central nervous system depression.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

Section 12: Ecological information

12.1. Toxicity Ecotoxicity effects

| Component | Freshwater Fish | Water Flea | Freshwater Algae |
|-----------------|----------------------------------------------------------------------------|----------------------------------------------|------------------|
| Tetrahydrofuran | 2160 mg/l LC50 = 96 h Pimephales promelas Leuciscus idus: LC50: 2820 | EC50 48 h 3485 mg/l EC50: >10000 mg/L/24h | |

SAFETY DATA SHEET

Sodium trimethylsilanolate, 1M solution in THF

Revision Date 06-Dec-2024

| | | | |
|--|----------|--|--|
| | mg/L/48h | | |
|--|----------|--|--|

12.2. Persistence and degradability

Persistence

Persistence is unlikely, Miscible with water, based on information available.

12.3. Bioaccumulative potential

Bioaccumulation is unlikely

| Component | log Pow | Bioconcentration factor (BCF) |
|-----------------|---------|-------------------------------|
| Tetrahydrofuran | 0.45 | No data available |

12.4. Mobility in soil

The product is water soluble, and may spread in water systems . Will likely be mobile in the environment due to its water solubility. Highly mobile in soils

12.5. Results of PBT and vPvB assessment

No data available for assessment.

12.6. Endocrine disrupting properties

Endocrine Disruptor Information

| Component | EU - Endocrine Disruptors Candidate List | EU - Endocrine Disruptors - Evaluated Substances |
|-----------------|------------------------------------------|--------------------------------------------------|
| Tetrahydrofuran | Group III Chemical | |

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance
This product does not contain any known or suspected substance

Section 13: Disposal considerations

13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information

Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms.

Switzerland - Waste Ordinance

Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

Section 14: Transport information

SAFETY DATA SHEET

Sodium trimethylsilanolate, 1M solution in THF

Revision Date 06-Dec-2024

IMDG/IMO

| | |
|-----------------------------------------|---------------------------------------------------|
| 14.1. UN number | UN2924 |
| 14.2. UN proper shipping name | Flammable liquid, corrosive, n.o.s. |
| Technical Shipping Name | Tetrahydrofuran, Silanol, trimethyl-, sodium salt |
| 14.3. Transport hazard class(es) | 3 |
| Subsidiary Hazard Class | 8 |
| 14.4. Packing group | II |

ADR

| | |
|-----------------------------------------|---------------------------------------------------|
| 14.1. UN number | UN2924 |
| 14.2. UN proper shipping name | Flammable liquid, corrosive, n.o.s. |
| Technical Shipping Name | Tetrahydrofuran, Silanol, trimethyl-, sodium salt |
| 14.3. Transport hazard class(es) | 3 |
| Subsidiary Hazard Class | 8 |
| 14.4. Packing group | II |

IATA

| | |
|-----------------------------------------|---------------------------------------------------|
| 14.1. UN number | UN2924 |
| 14.2. UN proper shipping name | Flammable liquid, corrosive, n.o.s. |
| Technical Shipping Name | Tetrahydrofuran, Silanol, trimethyl-, sodium salt |
| 14.3. Transport hazard class(es) | 3 |
| Subsidiary Hazard Class | 8 |
| 14.4. Packing group | II |

| | |
|----------------------------------------------------------------------|----------------------------------|
| 14.5. Environmental hazards | No hazards identified |
| 14.6. Special precautions for user | No special precautions required. |
| 14.7. Maritime transport in bulk according to IMO instruments | Not applicable, packaged goods |

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

| Component | CAS No | EINECS | ELINCS | NLP | IECSC | TCSI | KECL | ENCS | ISHL |
|----------------------------------|------------|-----------|--------|-----|-------|------|----------|------|------|
| Silanol, trimethyl-, sodium salt | 18027-10-6 | 241-939-8 | - | - | - | X | - | - | X |
| Tetrahydrofuran | 109-99-9 | 203-726-8 | - | - | X | X | KE-33454 | X | X |

| Component | CAS No | TSCA | TSCA Inventory notification - Active-Inactive | DSL | NDSL | AICS | NZIoC | PICCS |
|----------------------------------|------------|------|-----------------------------------------------|-----|------|------|-------|-------|
| Silanol, trimethyl-, sodium salt | 18027-10-6 | X | ACTIVE | - | X | - | X | X |
| Tetrahydrofuran | 109-99-9 | X | ACTIVE | X | - | X | X | X |

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

| Component | CAS No | REACH (1907/2006) - Annex XIV - Substances | REACH (1907/2006) - Annex XVII - Restrictions | REACH Regulation (EC 1907/2006) article 59 - |
|-----------|--------|--------------------------------------------|-----------------------------------------------|----------------------------------------------|
|-----------|--------|--------------------------------------------|-----------------------------------------------|----------------------------------------------|

SAFETY DATA SHEET

Sodium trimethylsilanolate, 1M solution in THF

Revision Date 06-Dec-2024

| | | Subject to Authorization | on Certain Dangerous Substances | Candidate List of Substances of Very High Concern (SVHC) |
|----------------------------------|------------|--------------------------|---------------------------------------------------------------------|----------------------------------------------------------|
| Silanol, trimethyl-, sodium salt | 18027-10-6 | - | - | - |
| Tetrahydrofuran | 109-99-9 | - | Use restricted. See entry 75. (see link for restriction details) | - |

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

| Component | CAS No | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements |
|----------------------------------|------------|-------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|
| Silanol, trimethyl-, sodium salt | 18027-10-6 | Not applicable | Not applicable |
| Tetrahydrofuran | 109-99-9 | Not applicable | Not applicable |

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 1 (self classification)

| Component | Germany - Water Classification (AwSV) | Germany - TA-Luft Class |
|-----------------|---------------------------------------|-------------------------|
| Tetrahydrofuran | WGK1 | |

| Component | France - INRS (Tables of occupational diseases) |
|-----------------|------------------------------------------------------|
| Tetrahydrofuran | Tableaux des maladies professionnelles (TMP) - RG 84 |

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

| Component | Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81) | Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC) | Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure |
|------------------------------------|----------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|
| Tetrahydrofuran 109-99-9 (87) | | Group I | |

15.2. Chemical safety assessment

SAFETY DATA SHEET

Sodium trimethylsilanolate, 1M solution in THF

Revision Date 06-Dec-2024

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

Section 16: Other information

Full text of H-Statements referred to under sections 2 and 3

H302 - Harmful if swallowed
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H351 - Suspected of causing cancer
EUH019 - May form explosive peroxides
H225 - Highly flammable liquid and vapor
H319 - Causes serious eye irritation

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadviser - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Chemical incident response training.

Creation Date 22-Oct-2009

Revision Date 06-Dec-2024

Revision Summary Not applicable.

SAFETY DATA SHEET

Sodium trimethylsilanolate, 1M solution in THF

Revision Date 06-Dec-2024

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No
1907/2006 .**

**For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2,
Number 3, Chemo (SR 813.11 - Ordinance on Protection against Dangerous Substances and
Preparations).**

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet