

Page 1 / 10 Revision Date 30-Mar-2025 Version 4

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THECOMPANY/UNDERTAKING

Product Identifier

Perihalan Produk:

Beryllium, plasma standard solution, Specpure®, Be 1000µg/ml

Beryllium, plasma standard solution, Specpure®, Be 1000µg/ml

Cat No.: 1384

Molecular Formula Be4 O(C2 H3 O2)6 in 5% HN O3

Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

Company Thermo Fisher Scientific (M) Sdn Bhd

Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square, No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,

Selangor Darul Ehsan, Malaysia. Main line: +60 3-5525 7888

**Supplier** 

E-mail address Enquiry.my@thermofisher.com

Emergency Telephone Number Tel: +03-5525 7888

CHEMTREC Malaysia 1-800-815-308 (Malay)

CHEMTREC Malaysia (Kuala Lumpur) +(60)-327884561 (Malay)

# **SECTION 2: HAZARDS IDENTIFICATION**

#### Classification of the substance or mixture

Substances/mixtures corrosive to metal	Category 1 (H290)
Acute Inhalation Toxicity - Vapors	Category 4 (H332)
Skin Corrosion/Irritation	Category 1 (H314) B
Serious Eye Damage/Eye Irritation	Category 1 (H318)
Skin Sensitization	Category 1 (H317)
Carcinogenicity	Category 1B (H350i)
Specific target organ toxicity - (repeated exposure)	Category 2 (H373)

# Label Elements



Beryllium, plasma standard solution, Specpure®, Be 1000µg/ml

# **Signal Word**

#### Danger

# **Hazard Statements**

H290 - May be corrosive to metals

H332 - Harmful if inhaled

H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction

H350i - May cause cancer by inhalation

H373 - May cause damage to organs through prolonged or repeated exposure

#### **Precautionary Statements**

#### Prevention

P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood

P234 - Keep only in original packaging

P260 - Do not breathe dust/fume/gas/mist/vapors/spray

P264 - Wash face, hands and any exposed skin thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area

P272 - Contaminated work clothing should not be allowed out of the workplace

P280 - Wear protective gloves

#### Response

P301 + P330 + P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor

P390 - Absorb spillage to prevent material damage

P362 + P364 - Take off contaminated clothing and wash it before reuse

#### Storage

P402 - Store in a dry place

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P406 - Store in corrosion resistant polypropylene container with a resistant inliner

#### Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

## Other Hazards

This product does not contain any known or suspected endocrine disruptors

# **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS No	Weight %
Water	7732-18-5	93.87
Nitric acid% [C ≤ 70 %]	7697-37-2	5.00
Hexakis[.mu(acetato-O:O')]mu.4-oxotetraberyllium	19049-40-2	1.13

# **SECTION 4: FIRST AID MEASURES**

## Description of first aid measures

General Advice

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

#### Beryllium, plasma standard solution, Specpure®, Be 1000µg/ml

Revision Date 30-Mar-2025

Immediate medical attention is required.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. Remove and wash

contaminated clothing and gloves, including the inside, before re-use. Call a physician

immediately.

**Ingestion** Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an

unconscious person. Call a physician immediately.

**Inhalation** If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use

mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory

medical device. Call a physician immediately.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. May cause allergic skin reaction. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing.

lightheadedness, chest pain, muscle pain of hushing

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

# **SECTION 5: FIREFIGHTING MEASURES**

#### Extinguishing media

#### **Suitable Extinguishing Media**

Not combustible. CO<sub>2</sub>, dry chemical, dry sand, alcohol-resistant foam.

#### Extinguishing media which must not be used for safety reasons

No information available.

# Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes.

# **Hazardous Combustion Products**

Nitrogen oxides (NOx), Heavy metal oxides.

#### Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

# **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### Personal Precautions, Protective Equipment and Emergency Procedures

Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

#### Beryllium, plasma standard solution, Specpure®, Be 1000µg/ml

\_\_\_\_

#### **Environmental precautions**

Should not be released into the environment. See Section 12 for additional Ecological Information. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system.

#### Methods and Material for Containment and Cleaning Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

#### Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

# **SECTION 7: HANDLING AND STORAGE**

#### Precautions for Safe Handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance.

## Conditions for Safe Storage, Including any Incompatibilities

Corrosives area. Keep containers tightly closed in a dry, cool and well-ventilated place.

#### Specific End Uses

Use in laboratories.

# **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### **Control Parameters**

Component	Malaysia	ACGIH TLV	OSHA PEL
Nitric acid% [C ≤ 70 %]		TWA: 2 ppm	(Vacated) TWA: 2 ppm
		STEL: 4 ppm	(Vacated) TWA: 5 mg/m <sup>3</sup>
			(Vacated) STEL: 4 ppm
			(Vacated) STEL: 10 mg/m <sup>3</sup>
			TWA: 2 ppm
			TWA: 5 mg/m <sup>3</sup>
Hexakis[.mu(acetato-O:O')]mu.4-		TWA: 0.00005 mg/m <sup>3</sup>	(Vacated) TWA: 2 μg/m <sup>3</sup>
oxotetraberyllium			(Vacated) STEL: 25 μg/m <sup>3</sup>
			(Vacated) Ceiling: 5 µg/m <sup>3</sup>
			Ceiling: 2 µg/m <sup>3</sup>

Component	European Union	The United Kingdom	Germany
Nitric acid% [C ≤ 70 %]	STEL: 1 ppm (15min)	STEL: 1 ppm 15 min	TWA: 1 ppm (8 Stunden). AGW -
	STEL: 2.6 mg/m <sup>3</sup> (15min)	STEL: 2.6 mg/m <sup>3</sup> 15 min	TWA: 2.6 mg/m³ (8 Stunden). AGW
		_	
Hexakis[.mu(acetato-O:O')]mu.4-		STEL: 0.006 mg/m <sup>3</sup> 15 min	
oxotetraberyllium		TWA: 0.002 mg/m <sup>3</sup> 8 hr	
		Carc.	

# **Exposure Controls**

# **Engineering Measures**

Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

#### Personal protective equipment

Eye Protection Goggles

Beryllium, plasma standard solution, Specpure®, Be 1000µg/ml

Hand Protection Protective gloves
Skin and body protection Long sleeved clothing

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

**Respiratory Protection** When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators

Recommended Filter type: Acid gases filter

To protect the wearer, respiratory protective equipment must be the correct fit and be used

(Air = 1.0)

Liquid

Revision Date 30-Mar-2025

and maintained properly

When RPE is used a face piece Fit Test should be conducted

<u>Hygiene Measures</u> Handle in accordance with good industrial hygiene and safety practice

**Environmental exposure controls** No information available

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Information on basic physical and chemical properties

Appearance Clear Physical State Liquid

Odor No information available
Odor Threshold No data available

pH

Melting Point/RangeNo data availableSoftening PointNo data availableBoiling Point/RangeNo information available

Flash Point No information available Method - No information available

Evaporation Rate No data available

Flammability (solid,gas) Not applicable Liquid

Explosion Limits No data available

Vapor PressureNo data availableVapor DensityNo data available

Specific Gravity / Density No data available

No data available

Bulk Density
Not applicable
Water Solubility
Not applicable
Miscible

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Component  $\log Pow$ Nitric acid ...% [C  $\leq$  70 %] -2.3

Beryllium, plasma standard solution, Specpure®, Be 1000µg/ml

Autoignition Temperature No data available

Decomposition Temperature

Viscosity Explosive Properties Oxidizing Properties No data available
No data available
No information available
No information available

Molecular Formula Be4 O(C2 H3 O2)6 in 5% HN O3

# **SECTION 10: STABILITY AND REACTIVITY**

Reactivity

None known, based on information available.

**Chemical Stability** 

Stable under normal conditions.

Possibility of Hazardous Reactions

Hazardous Polymerization Nazardous Reactions N

No information available. None under normal processing.

**Conditions to Avoid** 

None known.

Incompatible Materials

Strong bases.

**Hazardous Decomposition Products** 

Nitrogen oxides (NOx). Heavy metal oxides.

# **SECTION 11: TOXICOLOGICAL INFORMATION**

# Information on Toxicological Effects

#### **Product Information**

(a) acute toxicity;

Oral Based on available data, the classification criteria are not met

DermalNo data availableInhalationCategory 4

## Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Water	-	-	-
Nitric acid% [C ≤ 70 %]	-	-	LC50 = 2500 ppm. (Rat) 1h

Beryllium, plasma standard solution, Specpure®, Be 1000µg/ml

Nitric acid ...% [C ≤ 70 %] ATE = 2.65 mg/L (vapours)

(b) skin corrosion/irritation; Category 1 B

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

Respiratory No data available

Skin Category 1

No information available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; No data available

No data available (h) STOT-single exposure;

Category 2 (i) STOT-repeated exposure;

Route of exposure Inhalation **Target Organs** Lungs.

No data available (j) aspiration hazard;

delayed

Symptoms / effects,both acute and Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation, Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing.

**Endocrine Disrupting Properties** Assess endocrine disrupting properties for human health. This product does not contain any

known or suspected endocrine disruptors.

## **SECTION 12: ECOLOGICAL INFORMATION**

**Ecotoxicity effects** May cause long-term adverse effects in the environment. Do not allow material to

contaminate ground water system.

Persistence and degradability Product contains heavy metals. Discharge into the environment must be avoided. Special

pre-treatment is necessary

based on information available, May persist. **Persistence** 

Degradation in sewage Contains substances known to be hazardous to the environment or not degradable in waste

treatment plant water treatment plants.

Bioaccumulative potential May have some potential to bioaccumulate

	many many common protection to the control of the c	
Component	log Pow	Bioconcentration factor (BCF)
Nitric acid% [C ≤ 70 %]	-2.3	No data available

**ALFAA13848** 

Beryllium, plasma standard solution, Specpure®, Be 1000µg/ml

Mobility in soil The product is water soluble, and may spread in water systems. Will likely be mobile in the

environment due to its water solubility. Highly mobile in soils.

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

Other adverse effects No information available

# **SECTION 13: DISPOSAL CONSIDERATIONS**

Waste treatment methods

Waste from Residues/Unused

**Products** 

Waste is classified as hazardous Dispose of in accordance with the European Directives on

Revision Date 30-Mar-2025

waste and hazardous waste Dispose of in accordance with local regulations

**Contaminated Packaging** Dispose of this container to hazardous or special waste collection point.

Other Information Waste codes should be assigned by the user based on the application for which the product

was used Do not empty into drains Do not flush to sewer Large amounts will affect pH and

harm aquatic organisms

# **SECTION 14: TRANSPORT INFORMATION**

IMDG/IMO

UN-No UN3264
Hazard Class 8
Packing Group III

Proper Shipping Name Corrosive liquid, acidic, inorganic, n.o.s. (NITRIC ACID)

Road and Rail Transport

UN-No UN3264
Hazard Class 8
Packing Group III

Proper Shipping Name Corrosive liquid, acidic, inorganic, n.o.s. (NITRIC ACID)

<u>IATA</u>

UN-No UN3264
Hazard Class 8
Packing Group III

Proper Shipping Name Corrosive liquid, acidic, inorganic, n.o.s. (NITRIC ACID)

Special Precautions for User No special precautions required

# **SECTION 15: REGULATORY INFORMATION**

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories X = listed

Component EINECS TSCA DSL PICCS ENCS ISHL IECSC AICS	KECL
--	------

#### Beryllium, plasma standard solution, Specpure®, Be 1000µg/ml

Water	231-791-2	Х	Х	Х	Х		Х	Х	KE-35400
Nitric acid% [C ≤ 70 %]	231-714-2	Х	X	Х	Х	X	Χ	Х	KE-25911
Hexakis[.mu(acetato-O:O')]mu.	242-785-4	-	-	-	-		-	-	-
4-oxotetraberyllium									

Component	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Nitric acid% [C ≤ 70 %]				Annex I - Y34
Hexakis[.mu(acetato-O:O')]mu.4- oxotetraberyllium				Annex I - Y20

## **National Regulations**

**Persistent Organic Pollutant Ozone Depletion Potential** 

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

# **SECTION 16: OTHER INFORMATION**

#### Legend

**CAS** - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

Revision Date 30-Mar-2025

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

Substances List

PICCS - Philippines Inventory of Chemicals and Chemical Substances **IECSC** - Chinese Inventory of Existing Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances

**ENCS** - Japanese Existing and New Chemical Substances **AICS** - Australian Inventory of Chemical Substances NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

POW - Partition coefficient Octanol:Water

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air **Transport Association** 

MARPOL - International Convention for the Prevention of Pollution from Shins

Page 9/10

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

# Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

**Prepared By** Health, Safety and Environmental Department

**Revision Date** 30-Mar-2025 **Revision Summary** Not applicable.

In accordance with local and national regulations: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

Beryllium, plasma standard solution, Specpure®, Be 1000µg/ml

Revision Date 30-Mar-2025

## **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**