

according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended

Creation Date 16-Sep-2011 Revision Date 30-Nov-2024 Revision Number 4

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THECOMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Methylamine, 2M in methanol

Cat No. : H26889 Molecular Formula C H5 N

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

Avocado Research Chemicals Ltd. (Part of Thermo Fisher Scientific)

Shore Road, Heysham Lancashire, LA3 2XY, United Kingdom

Office Tel: +44 (0) 1524 850506 Office Fax: +44 (0) 1524 850608

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

Poison Centre - Emergency information services

Ireland: National Poisons Information Centre (NPIC) -

01 809 2166 (8am-10pm, 7 days a week)

Malta: +356 2395 2000 Cyprus: +357 2240 5611

## **SECTION 2: HAZARDS IDENTIFICATION**

## 2.1. Classification of the substance or mixture

GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

**Physical hazards** 

Flammable liquids Category 2 (H225)

**Health hazards** 

#### Methylamine, 2M in methanol

Revision Date 30-Nov-2024

Acute oral toxicity

Category 3 (H301)

Acute dermal toxicity Category 3 (H311)

Acute Inhalation Toxicity - Vapors

Skin Corrosion/Irritation

Category 3 (H331)

Category 1 B (H314)

Serious Eye Damage/Eye Irritation Category 1 (H318)
Specific target organ toxicity - (single exposure) Category 1 (H370)

Category 3 (H335)

#### **Environmental hazards**

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

#### 2.2. Label elements



Signal Word

Danger

#### **Hazard Statements**

H225 - Highly flammable liquid and vapor

H335 - May cause respiratory irritation

H370 - Causes damage to organs

H314 - Causes severe skin burns and eye damage

H301 + H311 + H331 - Toxic if swallowed, in contact with skin or if inhaled

## **Precautionary Statements**

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/physician

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

## 2.3. Other hazards

Lachrymator (substance which increases the flow of tears)

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

## **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.2. Mixtures

Component	CAS No	EC No	Weight %	GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Methyl alcohol	67-56-1	200-659-6	92-93	Flam. Liq. 2 (H225)

#### Methylamine, 2M in methanol

				Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370)
Methylamine%	74-89-5	EEC No. 200-820-0	7-8	Flam. liq. 1 (H224) Acute Tox. 4 (H302) Acute Tox; 4 (H332) Skin Corr. 1B (H314) Eye Dam. 1 (H318) STOT SE 3 (H335)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Methyl alcohol	STOT Single Exp. 1 :: >= 10	-	-
	STOT Single Exp. 2 :: 3 - < 10		
Methylamine%	STOT SE 3 :: C>=5%	-	-

Full text of Hazard Statements: see section 16

## **SECTION 4: FIRST AID MEASURES**

#### 4.1. Description of first aid measures

General Advice Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance.

**Eye Contact**Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In

the case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

**Ingestion** Do NOT induce vomiting. Call a physician or poison control center immediately.

**Inhalation** If breathing is difficult, give oxygen. Do not use mouth-to-mouth method if victim ingested or

inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Remove to fresh air. Immediate

medical attention is required.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

## 4.2. Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. . Difficulty in breathing. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

## 4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

## **SECTION 5: FIREFIGHTING MEASURES**

ALFAAH26889

Revision Date 30-Nov-2024

#### Methylamine, 2M in methanol

Revision Date 30-Nov-2024

#### 5.1. Extinguishing media

#### **Suitable Extinguishing Media**

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

## Extinguishing media which must not be used for safety reasons

No information available.

#### 5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

## **Hazardous Combustion Products**

Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), Thermal decomposition can lead to release of irritating gases and vapors.

## 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

## 6.2. Environmental precautions

Should not be released into the environment. See Section 12 for additional Ecological Information.

#### 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

## 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

## **SECTION 7: HANDLING AND STORAGE**

#### 7.1. Precautions for safe handling

Do not breathe mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not ingest. If swallowed then seek immediate medical assistance. Use only under a chemical fume hood. Wear personal protective equipment/face protection. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

#### **Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice.

## 7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

Methylamine, 2M in methanol

Technical Rules for Hazardous Substances (TRGS) 510 Storage Class (LGK) (Germany)

Class 3

## 7.3. Specific end use(s)

Use in laboratories

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### 8.1. Control parameters

#### **Exposure limits**

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Methyl alcohol	WEL - TWA: 200 ppm TWA;	TWA: 200 ppm 8 hr	TWA: 200 ppm 8 hr.
	266 mg/m³ TWA	TWA: 260 mg/m <sup>3</sup> 8 hr	TWA: 260 mg/m <sup>3</sup> 8 hr.
	WEL - STEL: 250 ppm	Skin	STEL: 600 ppm 15 min
	STEL; 333 mg/m <sup>3</sup> STEL		STEL: 780 mg/m <sup>3</sup> 15 min
			Skin
Methylamine%			TWA: 5 ppm 8 hr.
			TWA: 6 mg/m <sup>3</sup> 8 hr.
			STEL: 15 ppm 15 min
			STEL: 19 mg/m <sup>3</sup> 15 min

## **Biological limit values**

List source(s):

## Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Methyl alcohol		DNEL = 20mg/kg		DNEL = 20mg/kg
67-56-1 ( 92-93 )		bw/day		bw/day
Methylamine%				DNEL = 0.1mg/kg
74-89-5 ( 7-8 )				bw/day

Component		Acute effects local	Acute effects	Chronic effects local	Chronic effects
		(Inhalation)	systemic (Inhalation)	(Inhalation)	systemic (Inhalation)
Methyl alcohol 67-56-1 ( 92-93		DNEL = 130mg/m <sup>3</sup>	DNEL = 130mg/m <sup>3</sup>	DNEL = 130mg/m <sup>3</sup>	DNEL = 130mg/m <sup>3</sup>
Methylamine9 74-89-5 ( 7-8 )	I			DNEL = 0.427mg/m <sup>3</sup>	DNEL = 0.72mg/m <sup>3</sup>

## **Predicted No Effect Concentration (PNEC)**

See values below.

Component	Fresh water	Fresh water	Water Intermittent	Microorganisms in	Soil (Agriculture)
		sediment		sewage treatment	
Methyl alcohol	PNEC = 20.8mg/L	PNEC = 77mg/kg	PNEC = 1540mg/L	PNEC = 100mg/L	PNEC = 100mg/kg

ALFAAH26889

Revision Date 30-Nov-2024

#### Methylamine, 2M in methanol

67-56-1 ( 92-93 )		sediment dw			soil dw
Methylamine%	PNEC = 0.016mg/L	PNEC =	PNEC = 0.016mg/L	PNEC =	PNEC =
74-89-5 ( 7-8 )		0.776mg/kg		0.1263mg/L	0.126mg/kg soil dw
		sediment dw			

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
Methyl alcohol	PNEC = 2.08mg/L	PNEC = 7.7mg/kg			
67-56-1 ( 92-93 )		sediment dw			
Methylamine%	PNEC =	PNEC =			
74-89-5 ( 7-8 )	0.0016mg/L	0.0776mg/kg			
	-	sediment dw			

#### 8.2. Exposure controls

#### **Engineering Measures**

Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

**Eye Protection** Goggles (European standard - EN 166)

Hand Protection Protective gloves

	Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
	Natural rubber	See manufacturers	-	EN 374	(minimum requirement)
	Nitrile rubber	recommendations			
	Neoprene				
L	PVC				

Skin and body protection Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

**Respiratory Protection** When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: Particulates filter conforming to EN 143 Ammonia and organic

ammonia derivatives filter Type K Green

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

141

When RPE is used a face piece Fit Test should be conducted

No information available.

**Environmental exposure controls** 

Revision Date 30-Nov-2024

Revision Date 30-Nov-2024

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

## 9.1. Information on basic physical and chemical properties

Physical State Liquid

**Appearance** Clear

Odor
Odor No information available
No data available

Flammability (liquid) Highly flammable On basis of test data

Flammability (solid,gas) Not applicable Liquid

Explosion Limits No data available

Flash Point 7 °C / 44.6 °F Method - No information available

Autoignition TemperatureNo data availableDecomposition TemperatureNo data availablepHNo information availableViscosityNo data available

Water Solubility Soluble

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Componentlog PowMethyl alcohol-0.74Methylamine ...%-0.713

Vapor Pressure 2.07 Psi @ 20 °C

Density / Specific Gravity 0.785

Bulk DensityNot applicableLiquidVapor DensityNo data available(Air = 1.0)

Particle characteristics (liquid) Not applicable

9.2. Other information

Molecular Formula C H5 N Molecular Weight 31.06

**Explosive Properties** Vapors may form explosive mixtures with air

## **SECTION 10: STABILITY AND REACTIVITY**

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

**Hazardous Polymerization** Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

10.4. Conditions to avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition.

10.5. Incompatible materials

Acids. Acid anhydrides. Acid chlorides. Metals. Reducing Agent.

#### 10.6. Hazardous decomposition products

Nitrogen oxides (NOx). Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Thermal decomposition can lead to release of irritating gases and vapors.

Revision Date 30-Nov-2024

## **SECTION 11: TOXICOLOGICAL INFORMATION**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Product Information**

(a) acute toxicity;

Oral Category 3
Dermal Category 3
Inhalation Category 3

## Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl alcohol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg ( Rabbit )	LC50 = 128.2 mg/L (Rat) 4 h
Methylamine%	698 mg/kg ( Rat )	-	2.9 mg/L/4h ( Rat )

(b) skin corrosion/irritation; Category 1 B

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

**Respiratory**Skin
No data available
No data available

Component	Test method	Test species	Study result
Methyl alcohol	OECD Test Guideline 406	guinea pig	non-sensitising
67-56-1 ( 92-93 )	Guinea Pig Maximisation Test		
	(GPMT)		

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; No data available

Component	Test method	Test species / Duration	Study result
Methyl alcohol	OECD Test Guideline 416	Rat / Inhalation	NOAEC =
67-56-1 ( 92-93 )		2 Generation	1.3 mg/l (air)

(h) STOT-single exposure; Category 1 Category 3

Results / Target organs Respiratory system, Optic nerve, Central nervous system (CNS).

(i) STOT-repeated exposure; No data available

Target Organs No information available.

Methylamine, 2M in methanol Revision Date 30-Nov-2024

(j) aspiration hazard; No data available

The toxicological properties have not been fully investigated. See actual entry in RTECS for **Other Adverse Effects** 

complete information

delayed

Symptoms / effects,both acute and Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness,

nausea and vomiting.

#### 11.2. Information on other hazards

**Endocrine Disrupting Properties** 

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

## **SECTION 12: ECOLOGICAL INFORMATION**

12.1. Toxicity **Ecotoxicity effects** 

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Do not empty into drains.

	Component	Freshwater Fish	Water Flea	Freshwater Algae
ı	Methyl alcohol	Pimephales promelas: LC50 >	EC50 > 10000 mg/L 24h	
		10000 mg/L 96h		
	Methylamine%		EC50: = 163 mg/L, 48h (Daphnia magna) EC50: 147 - 180 mg/L, 48h Static (Daphnia magna)	

Component	Microtox	M-Factor
Methyl alcohol	EC50 = 39000 mg/L 25 min	
	EC50 = 40000 mg/L 15 min	
	EC50 = 43000 mg/L 5 min	

## 12.2. Persistence and degradability

**Persistence** Persistence is unlikely, based on information available.

Component	Degradability
Methyl alcohol	DT50 ~ 17.2d
67-56-1 ( 92-93 )	>94% after 20d

#### 12.3. Bioaccumulative potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Methyl alcohol	-0.74	<10 dimensionless
Methylamine%	-0.713	2860 - 6910 dimensionless

The product contains volatile organic compounds (VOC) which will evaporate easily from all 12.4. Mobility in soil

surfaces Will likely be mobile in the environment due to its volatility. Disperses rapidly in

air

12.5. Results of PBT and vPvB

assessment

No data available for assessment.

## 12.6. Endocrine disrupting

Revision Date 30-Nov-2024 Methylamine, 2M in methanol

properties

**Endocrine Disruptor Information** This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects Persistent Organic Pollutant **Ozone Depletion Potential** 

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

## **SECTION 13: DISPOSAL CONSIDERATIONS**

13.1. Waste treatment methods

Waste from Residues/Unused

**Products** 

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

**Contaminated Packaging** Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

According to the European Waste Catalog, Waste Codes are not product specific, but **European Waste Catalogue (EWC)** 

application specific.

Other Information Waste codes should be assigned by the user based on the application for which the product

was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic

organisms.

## SECTION 14: TRANSPORT INFORMATION

## IMDG/IMO

UN3286 14.1. UN number

Flammable liquid, toxic, corrosive, n.o.s. 14.2. UN proper shipping name

**Technical Shipping Name** Methyl alcohol, Methylamine

14.3. Transport hazard class(es) **Subsidiary Hazard Class** 6.1, 8 14.4. Packing group II

ADR

14.1. UN number

14.2. UN proper shipping name Flammable liquid, toxic, corrosive, n.o.s.

**Technical Shipping Name** Methyl alcohol, Methylamine

14.3. Transport hazard class(es) 3 **Subsidiary Hazard Class** 6.1, 8 14.4. Packing group П

IATA

UN3286 14.1. UN number

14.2. UN proper shipping name Flammable liquid, toxic, corrosive, n.o.s.

**Technical Shipping Name** Methyl alcohol, Methylamine

14.3. Transport hazard class(es) 3 **Subsidiary Hazard Class** 

6.1, 8 II 14.4. Packing group

Revision Date 30-Nov-2024

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk Not applicable, packaged goods

according to IMO instruments

## **SECTION 15: REGULATORY INFORMATION**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **International Inventories**

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Methyl alcohol	67-56-1	200-659-6	-	-	Х	X	KE-23193	X	X
Methylamine%	74-89-5	200-820-0	-	-	Х	Х	KE-23421	X	Х

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Methyl alcohol	67-56-1	X	ACTIVE	X	Ī	X	Χ	X
Methylamine%	74-89-5	Х	ACTIVE	X	-	X	Х	Х

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do) Legend: X - Listed '-' - Not Listed

#### Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Methyl alcohol	67-56-1	-	Use restricted. See entry 69. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details)	-
Methylamine%	74-89-5	-	Use restricted. See entry 75. (see link for restriction details)	-

#### **REACH links**

https://echa.europa.eu/substances-restricted-under-reach

#### Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) -	Seveso III Directive (2012/18/EC) -
		Qualifying Quantities for Major Accident	Qualifying Quantities for Safety Report
		Notification	Requirements
Methyl alcohol	67-56-1	500 tonne	5000 tonne
Methylamine%	74-89-5	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and

#### Methylamine, 2M in methanol

Revision Date 30-Nov-2024

### import of dangerous chemicals

Not applicable

## Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

## **National Regulations**

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

#### **WGK Classification**

Water endangering class = 2 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Methyl alcohol	WGK 2	Class I: 20 mg/m³ (Massenkonzentration)
Methylamine%	WGK1	Class I: 20 mg/m³ (Massenkonzentration)

Component	France - INRS (Tables of occupational diseases)
Methyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84
Methylamine%	Tableaux des maladies professionnelles (TMP) - RG 49,RG 49bis

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Methyl alcohol	Prohibited and Restricted	Group I	
67-56-1 ( 92-93 )	Substances		

## 15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

## **SECTION 16: OTHER INFORMATION**

#### Full text of H-Statements referred to under sections 2 and 3

H224 - Extremely flammable liquid and vapor

H225 - Highly flammable liquid and vapor

H301 - Toxic if swallowed

H311 - Toxic in contact with skin

H331 - Toxic if inhaled

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H370 - Causes damage to organs

H302 - Harmful if swallowed

H332 - Harmful if inhaled

H335 - May cause respiratory irritation

Legend

#### Methylamine, 2M in methanol

Revision Date 30-Nov-2024

CAS - Chemical Abstracts Service TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic

Substances/EU List of Notified Chemical Substances Substances List

PICCS - Philippines Inventory of Chemicals and Chemical Substances **ENCS** - Japanese Existing and New Chemical Substances IECSC - Chinese Inventory of Existing Chemical Substances AICS - Australian Inventory of Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit TWA - Time Weighted Average

**ACGIH** - American Conference of Governmental Industrial Hygienists IARC - International Agency for Research on Cancer

**DNEL** - Derived No Effect Level Predicted No Effect Concentration (PNEC)

**RPE** - Respiratory Protective Equipment LD50 - Lethal Dose 50% LC50 - Lethal Concentration 50% EC50 - Effective Concentration 50%

NOEC - No Observed Effect Concentration POW - Partition coefficient Octanol:Water PBT - Persistent. Bioaccumulative. Toxic vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of ICAO/IATA - International Civil Aviation Organization/International Air Dangerous Goods by Road Transport Association

IMO/IMDG - International Maritime Organization/International Maritime MARPOL - International Convention for the Prevention of Pollution from

Dangerous Goods Code Ships **OECD** - Organisation for Economic Co-operation and Development ATE - Acute Toxicity Estimate VOC - (Volatile Organic Compound)

**BCF** - Bioconcentration factor Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

## Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data **Health Hazards** Calculation method **Environmental hazards** Calculation method

**Training Advice** 

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

**Prepared By** Health, Safety and Environmental Department

Creation Date 16-Sep-2011 **Revision Date** 30-Nov-2024 **Revision Summary** Not applicable.

## This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

## **End of Safety Data Sheet**