

Creation Date 03-May-2010

Revision Date 12-Mar-2019

Revision Number 5

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identification

<b>Product Description:</b>	<b>1-Hexene (Duty Paid)</b>
<b>Cat No. :</b>	<b>PS/738</b>
<b>Synonyms</b>	Butyl ethylene
<b>CAS-No</b>	592-41-6
<b>EC-No.</b>	209-753-1
<b>Molecular Formula</b>	C6 H12
<b>Reach Registration Number</b>	01-2119475505-34

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

<b>Recommended Use</b>	Laboratory chemicals.
<b>Sector of use</b>	SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites
<b>Product category</b>	PC21 - Laboratory chemicals
<b>Process categories</b>	PROC15 - Use as a laboratory reagent
<b>Environmental release category</b>	ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)
<b>Uses advised against</b>	No Information available

### 1.3. Details of the supplier of the safety data sheet

<b>Company</b>	<b>EU entity/business name</b> Acros Organics BVBA Janssen Pharmaceuticaaan 3a 2440 Geel, Belgium
	<b>UK entity/business name</b> Fisher Scientific UK Bishop Meadow Road, Loughborough, Leicestershire LE11 5RG, United Kingdom
<b>E-mail address</b>	begel.sdsdesk@thermofisher.com

### 1.4. Emergency telephone number

Tel: 01509 231166  
Chemtrec US: (800) 424-9300  
Chemtrec EU: 001 (202) 483-7616

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

#### CLP Classification - Regulation (EC) No 1272/2008

#### Physical hazards

Flammable liquids

Category 2 (H225)

# SAFETY DATA SHEET

1-Hexene (Duty Paid)

Revision Date 12-Mar-2019

## Health hazards

Aspiration Toxicity

Category 1 (H304)

## Environmental hazards

Based on available data, the classification criteria are not met

## 2.2. Label elements



Signal Word

Danger

## Hazard Statements

H225 - Highly flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

EUH066 - Repeated exposure may cause skin dryness or cracking

## Precautionary Statements

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking

P243 - Take precautionary measures against static discharge

P280 - Wear protective gloves/ protective clothing/ eye protection/ face protection

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician

P331 - Do NOT induce vomiting

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

## 2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substances

Component	CAS-No	EC-No.	Weight %	CLP Classification - Regulation (EC) No 1272/2008
1-Hexene	592-41-6	EEC No. 209-753-1	>95	Flam. Liq. 2 (H225) Asp. Tox. 1 (H304) (EUH066)

Reach Registration Number	01-2119475505-34
---------------------------	------------------

Full text of Hazard Statements: see section 16

# SAFETY DATA SHEET

1-Hexene (Duty Paid)

Revision Date 12-Mar-2019

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
<b>Skin Contact</b>	Wash off immediately with plenty of water for at least 15 minutes. Get medical attention if symptoms occur.
<b>Ingestion</b>	Aspiration hazard. Do not induce vomiting. Call a physician or Poison Control Center immediately. If vomiting occurs naturally, have victim lean forward.
<b>Inhalation</b>	Move to fresh air. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Obtain medical attention. If not breathing, give artificial respiration. Risk of serious damage to the lungs.
<b>Self-Protection of the First Aider</b>	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

### 4.2. Most important symptoms and effects, both acute and delayed

Breathing difficulties. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes to Physician** Treat symptomatically. Symptoms may be delayed.

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

#### Suitable Extinguishing Media

CO<sub>2</sub>, dry chemical, dry sand, alcohol-resistant foam. Cool closed containers exposed to fire with water spray.

#### Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

### 5.2. Special hazards arising from the substance or mixture

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

#### Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>).

### 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

# SAFETY DATA SHEET

1-Hexene (Duty Paid)

Revision Date 12-Mar-2019

Use personal protective equipment. Remove all sources of ignition. Take precautionary measures against static discharges. Ensure adequate ventilation. Avoid contact with skin, eyes and clothing.

## 6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

## 6.3. Methods and material for containment and cleaning up

Remove all sources of ignition. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Use spark-proof tools and explosion-proof equipment.

## 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Wear personal protective equipment. Ensure adequate ventilation. Use spark-proof tools and explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Avoid contact with skin, eyes and clothing. Avoid ingestion and inhalation. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

### Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing before re-use. Wash hands before breaks and at the end of workday.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Keep under nitrogen. Flammables area.

### 7.3. Specific end use(s)

Use in laboratories

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Exposure limits

List source(s):

Component	European Union	The United Kingdom	France	Belgium	Spain
1-Hexene			TWA / VME: 1000 mg/m <sup>3</sup> (8 heures). STEL / VLCT: 1500 mg/m <sup>3</sup> .	TWA: 50 ppm 8 uren TWA: 175 mg/m <sup>3</sup> 8 uren	TWA / VLA-ED: 50 ppm (8 horas)
Component	Italy	Germany	Portugal	The Netherlands	Finland
1-Hexene			TWA: 50 ppm 8 horas		
Component	Austria	Denmark	Switzerland	Poland	Norway
1-Hexene					TWA: 40 ppm 8 timer TWA: 275 mg/m <sup>3</sup> 8 timer

# SAFETY DATA SHEET

1-Hexene (Duty Paid)

Revision Date 12-Mar-2019

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
1-Hexene			TWA: 50 ppm 8 hr. STEL: 150 mg/m <sup>3</sup> 15 min Skin		

## Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

## Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

**Derived No Effect Level (DNEL)** No information available

<u>Route of exposure</u>	Acute effects (local)	Acute effects (systemic)	Chronic effects (local)	Chronic effects (systemic)
Oral Dermal Inhalation				

**Predicted No Effect Concentration (PNEC)** See values below.

Fresh water	0.111 mg/l
Fresh water sediment	19.25 mg/kg
Marine water	0.111 mg/l
Marine water sediment	19.25 mg/kg
Soil (Agriculture)	4.01 mg/kg

## 8.2. Exposure controls

### Engineering Measures

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

### Personal protective equipment

**Eye Protection** Safety glasses with side-shields (European standard - EN 166)

**Hand Protection** Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber	> 480 minutes	0.38 mm	Level 6	As tested under EN374-3 Determination of
Viton (R)	> 480 minutes	0.35 mm	EN 374	Resistance to Permeation by Chemicals
Neoprene gloves	< 45 minutes	0.45 mm		

# SAFETY DATA SHEET

1-Hexene (Duty Paid)

Revision Date 12-Mar-2019

## Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

## Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.  
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

## Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

**Recommended Filter type:** low boiling organic solvent Type AX Brown conforming to EN371

## Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

**Recommended half mask:-** Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141

When RPE is used a face piece Fit Test should be conducted

## Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance	Colorless	
Physical State	Liquid	
Odor	Characteristic	
Odor Threshold	No data available	
pH	No information available	
Melting Point/Range	-140 °C / -220 °F	
Softening Point	No data available	
Boiling Point/Range	62 - 65 °C / 143.6 - 149 °F	@ 760 mmHg
Flash Point	-26 °C / -14.8 °F	<b>Method -</b> Closed cup
Evaporation Rate	No data available	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	<b>Lower</b> 1.2 Vol% <b>Upper</b> 6.9 Vol%	
Vapor Pressure	186 mmHg @ 25 °C	
Vapor Density	3.0	(Air = 1.0)
Specific Gravity / Density	0.678	
Bulk Density	Not applicable	Liquid
Water Solubility	50 mg/L (20°C)	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	<b>log Pow</b>	
1-Hexene	3.39	
Autoignition Temperature	265 °C / 509 °F	
Decomposition Temperature	No data available	
Viscosity	0.34 cSt at 40 °C	
Explosive Properties	No information available	Vapors may form explosive mixtures with air
Oxidizing Properties	No information available	

### 9.2. Other information

# SAFETY DATA SHEET

1-Hexene (Duty Paid)

Revision Date 12-Mar-2019

Molecular Formula C<sub>6</sub> H<sub>12</sub>  
Molecular Weight 84.15

## SECTION 10: STABILITY AND REACTIVITY

**10.1. Reactivity**  
None known, based on information available

**10.2. Chemical stability**  
Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

Hazardous Polymerization Hazardous Reactions  
Hazardous polymerization may occur.  
None under normal processing.

**10.4. Conditions to avoid**  
Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition.

**10.5. Incompatible materials**  
Strong oxidizing agents. Acids. Peroxides.

**10.6. Hazardous decomposition products**  
Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## SECTION 11: TOXICOLOGICAL INFORMATION

**11.1. Information on toxicological effects**

**Product Information**

(a) acute toxicity;  
Oral Based on available data, the classification criteria are not met  
Dermal Based on available data, the classification criteria are not met  
Inhalation Based on available data, the classification criteria are not met

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
1-Hexene	LD50 > 5600 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	LC50 = 32000 ppm ( Rat ) 4 h

(b) skin corrosion/irritation; Based on available data, the classification criteria are not met

(c) serious eye damage/irritation; Based on available data, the classification criteria are not met

(d) respiratory or skin sensitization;  
Respiratory Based on available data, the classification criteria are not met  
Skin Based on available data, the classification criteria are not met

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met  
Not mutagenic in AMES Test

(f) carcinogenicity; Based on available data, the classification criteria are not met

# SAFETY DATA SHEET

1-Hexene (Duty Paid)

Revision Date 12-Mar-2019

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; Based on available data, the classification criteria are not met

(h) STOT-single exposure; Based on available data, the classification criteria are not met

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

Test method OECD Test Guideline 407  
Test species / Duration rat / 28 days  
Study result NOAEL = 101 mg/kg  
Route of exposure Oral  
Target Organs None known.

(j) aspiration hazard; Category 1

Other Adverse Effects The toxicological properties have not been fully investigated.

Symptoms / effects, both acute and delayed Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

#### Ecotoxicity effects

The product contains following substances which are hazardous for the environment. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
1-Hexene	LC50 96 h 5.6 mg/L (Rainbow trout)	EC50: = 30 mg/L, 48h Static (Daphnia magna) EC50: = 230 mg/L, 48h (Daphnia magna)	EC50: > 1000 mg/L, 96h (Pseudokirchneriella subcapitata)	

### 12.2. Persistence and degradability

#### Persistence

Readily biodegradable  
Persistence is unlikely, based on information available.

Component	Degradability
1-Hexene 592-41-6 ( >95 )	67 - 98 % (28d)

#### Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

### 12.3. Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
1-Hexene	3.39	No data available

### 12.4. Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air

### 12.5. Results of PBT and vPvB assessment

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB).



# SAFETY DATA SHEET

1-Hexene (Duty Paid)

Revision Date 12-Mar-2019

## 12.6. Other adverse effects

**Endocrine Disruptor Information**  
**Persistent Organic Pollutant**  
**Ozone Depletion Potential**

This product does not contain any known or suspected endocrine disruptors  
This product does not contain any known or suspected substance  
This product does not contain any known or suspected substance

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Waste from Residues / Unused Products**

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

**Contaminated Packaging**

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

**European Waste Catalogue (EWC)**

According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.

**Other Information**

Do not dispose of waste into sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be incinerated, when in compliance with local regulations.

## SECTION 14: TRANSPORT INFORMATION

### IMDG/IMO

<b>14.1. UN number</b>	UN2370
<b>14.2. UN proper shipping name</b>	1-HEXENE
<b>14.3. Transport hazard class(es)</b>	3
<b>14.4. Packing group</b>	II

### ADR

<b>14.1. UN number</b>	UN2370
<b>14.2. UN proper shipping name</b>	1-HEXENE
<b>14.3. Transport hazard class(es)</b>	3
<b>14.4. Packing group</b>	II

### IATA

<b>14.1. UN number</b>	UN2370
<b>14.2. UN proper shipping name</b>	1-HEXENE
<b>14.3. Transport hazard class(es)</b>	3
<b>14.4. Packing group</b>	II

**14.5. Environmental hazards** No hazards identified

**14.6. Special precautions for user** No special precautions required

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable, packaged goods

## SECTION 15: REGULATORY INFORMATION

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

# SAFETY DATA SHEET

1-Hexene (Duty Paid)

Revision Date 12-Mar-2019

## International Inventories X = listed.

Component	EINECS	ELINCS	NLP	TSCA	DSL	NDSL	PICCS	ENCS	IECSC	AICS	KECL
1-Hexene	209-753-1	-		X	X	-	X	X	X	X	KE-1984 5

## National Regulations

Component	Germany - Water Classification (VwVwS)	Germany - TA-Luft Class
1-Hexene	WGK 2	

Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment.

## 15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has been conducted by the manufacturer/importer

## SECTION 16: OTHER INFORMATION

### Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H304 - Repeated exposure may cause skin dryness or cracking

### Legend

**CAS** - Chemical Abstracts Service

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

**WEL** - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

**RPE** - Respiratory Protective Equipment

**LC50** - Lethal Concentration 50%

**NOEC** - No Observed Effect Concentration

**PBT** - Persistent, Bioaccumulative, Toxic

**TWA** - Time Weighted Average

**IARC** - International Agency for Research on Cancer

**PNEC** - Predicted No Effect Concentration

**LD50** - Lethal Dose 50%

**EC50** - Effective Concentration 50%

**POW** - Partition coefficient Octanol:Water

**vPvB** - very Persistent, very Bioaccumulative

**ADR** - European Agreement Concerning the International Carriage of Dangerous Goods by Road

**IMO/IMDG** - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

### Key literature references and sources for data

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

**ICAO/IATA** - International Civil Aviation Organization/International Air Transport Association

**MARPOL** - International Convention for the Prevention of Pollution from Ships

**ATE** - Acute Toxicity Estimate

**VOC** - Volatile Organic Compounds

## Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

# SAFETY DATA SHEET

1-Hexene (Duty Paid)

Revision Date 12-Mar-2019

---

Creation Date	03-May-2010
Revision Date	12-Mar-2019
Revision Summary	SDS sections updated, 15.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006**

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**