

according to Regulation (EC) No. 1907/2006

Creation Date 11-Nov-2011 Revision Date 16-Jul-2025 Revision Number 3

# Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product Description: Lead wire, .187" dia., x 25 lb. spool, 99.99% (metals basis)

 Cat No. :
 97115

 Synonyms
 Lead metal

 Index No
 082-014-00-7

 CAS No
 7439-92-1

 EC No
 231-100-4

 Molecular Formula
 Pb

 REACH registration number

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

#### 1.3. Details of the supplier of the safety data sheet

Company

Thermo Fisher (Kandel) GmbH

Erlenbachweg 2, 76870 Kandel, Germany

Tel: +49 (0) 721 84007 280 Fax: +49 (0) 721 84007 300

**Swiss distributor -** Fisher Scientific AG Neuhofstrasse 11, CH 4153 Reinach

Tel: +41 (0) 56 618 41 11

https://www.fishersci.ch/ch/en/customer-help-

support/forms/email-us.html

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:

Tox Info Suisse Emergency Number: 145 (24hr)

Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)

Chemtrec (24h) Toll-Free: 0800 564 402 Chemtrec Local: +41-43 508 20 11 (Zurich)

### **Section 2: HAZARDS IDENTIFICATION**

#### 2.1. Classification of the substance or mixture

Lead wire, .187" dia., x 25 lb. spool, 99.99% (metals basis)

Revision Date 16-Jul-2025

#### CLP Classification - Regulation (EC) No 1272/2008

### **Physical hazards**

Based on available data, the classification criteria are not met

### **Health hazards**

Reproductive Toxicity
Effects on or via lactation
Specific target organ toxicity - (repeated exposure)

Category 1A (H360FD)
/ Effects on or via lactation (H362)
Category 1 (H372)

#### **Environmental hazards**

Chronic aquatic toxicity Category 1 (H410)

Full text of Hazard Statements: see section 16

### 2.2. Label elements



### Signal Word

### Danger

#### **Hazard Statements**

H360FD - May damage fertility. May damage the unborn child

H362 - May cause harm to breast-fed children

H372 - Causes damage to organs through prolonged or repeated exposure

H410 - Very toxic to aquatic life with long lasting effects

### **Precautionary Statements**

P201 - Obtain special instructions before use

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P308 + P313 - IF exposed or concerned: Get medical advice/attention

#### Additional EU labelling

Restricted to professional users

### 2.3. Other hazards

In accordance with Annex XIII of the REACH Regulation, inorganic substances do not require assessment

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

### **Section 3: Composition/information on ingredients**

### 3.1. Substances

Lead wire, .187" dia., x 25 lb. spool, 99.99% (metals basis)

Revision Date 16-Jul-2025

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Lead	7439-92-1	EEC No. 231-100-4	<=100	Repr. 1A (H360FD) STOT RE 1 (H372)
				Lact. (H362) Aquatic Chronic 1 (H410)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Lead	-	M = 10'	-

REACH registration number	-

Full text of Hazard Statements: see section 16

### **Section 4: First aid measures**

### 4.1. Description of first aid measures

**General Advice** Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

**Eye Contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

Do NOT induce vomiting. Call a physician or poison control center immediately. Ingestion

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Do not use mouth-to-mouth

method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Immediate medical attention is required.

Ensure that medical personnel are aware of the material(s) involved, take precautions to Self-Protection of the First Aider

protect themselves and prevent spread of contamination.

### 4.2. Most important symptoms and effects, both acute and delayed

None reasonably foreseeable.

#### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes to Physician** Treat symptomatically.

### **Section 5: Firefighting measures**

### 5.1. Extinguishing media

### **Suitable Extinguishing Media**

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

### Extinguishing media which must not be used for safety reasons

No information available.

### 5.2. Special hazards arising from the substance or mixture

Lead wire, .187" dia., x 25 lb. spool, 99.99% (metals basis)

Revision Date 16-Jul-2025

Non-combustible. Do not allow run-off from fire-fighting to enter drains or water courses.

#### **Hazardous Combustion Products**

Lead, lead oxides.

### 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

### **Section 6: ACCIDENTAL RELEASE MEASURES**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Avoid dust formation. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas.

#### 6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained. Should not be released into the environment.

### 6.3. Methods and material for containment and cleaning up

Sweep up and shovel into suitable containers for disposal. Avoid dust formation.

#### 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

### Section 7: Handling and storage

### 7.1. Precautions for safe handling

Do not get in eyes, on skin, or on clothing. Wear personal protective equipment/face protection. Avoid dust formation. Use only under a chemical fume hood. Do not breathe (dust, vapor, mist, gas). Do not ingest. If swallowed then seek immediate medical assistance.

### **Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

#### 7.2. Conditions for safe storage, including any incompatibilities

Keep in a dry, cool and well-ventilated place. Keep container tightly closed.

Technical Rules for Hazardous Substances (TRGS) 510 Storage Class (LGK) (Germany)

Storage Class/LGK 6.1D

Switzerland - Storage of hazardous substances

Storage class - SC 6.1

https://www.kvu.ch/de/themen/stoffe-und-produkte https://www.kvu.ch/fr/themes/substances-et-produits https://www.kvu.ch/it/temi/sostanze-e-prodotti

### 7.3. Specific end use(s)

\_\_\_\_\_

Use in laboratories

### Section 8: Exposure controls/personal protection

### 8.1. Control parameters

#### **Exposure limits**

List source(s): **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is

based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund). **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC

Component	European Union	The United Kingdom	France	Belgium	Spain
Lead	TWA: 0.15 mg/m <sup>3</sup> (8h)	STEL: 0.45 mg/m <sup>3</sup> 15	TWA / VME: 0.1 mg/m <sup>3</sup>		TWA / VLA-ED: 0.15
		min	(8 heures). restrictive		mg/m <sup>3</sup> (8 horas)
		TWA: 0.15 mg/m <sup>3</sup> 8 hr	limit		
•	1 1	_		<b>-</b>	
Component	Italy	Germany	Portugal	The Netherlands	Finland
Lead	TWA: 0.15 mg/m <sup>3</sup> 8 ore. Time Weighted Average	TWA: 0.004 mg/m³ (8 Stunden). MAK	TWA: 0.05 mg/m <sup>3</sup> 8 horas	TWA: 0.15 mg/m <sup>3</sup> 8	TWA: 0.1 mg/m <sup>3</sup> 8 tunteina
	Time Weighted Average	Höhepunkt: 0.032	noras	uren	turiteiria
		mg/m <sup>3</sup>			
	L	I ilig/ili•			
Component	Austria	Denmark	Switzerland	Poland	Norway
Lead	MAK-KZGW: 0.4 mg/m <sup>3</sup>	TWA: 0.05 mg/m <sup>3</sup> 8	STEL: 0.8 mg/m <sup>3</sup> 15	TWA: 0.05 mg/m <sup>3</sup> 8	TWA: 0.05 mg/m <sup>3</sup> 8
	15 Minuten	timer	Minuten	godzinach	timer
	MAK-TMW: 0.1 mg/m <sup>3</sup> 8	STEL: 0.1 mg/m <sup>3</sup> 15	TWA: 0.1 mg/m <sup>3</sup> 8		STEL: 0.15 mg/m <sup>3</sup> 15
	Stunden	minutter	Stunden		minutter. value
					calculated dust and
					fume
0	Deliverie	0	111	0	O
Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Lead	TWA: 0.05 mg/m <sup>3</sup>	TWA-GVI: 0.15 mg/m <sup>3</sup> 8 satima.	TWA: 0.15 mg/m <sup>3</sup> 8 hr. STEL: 0.45 mg/m <sup>3</sup> 15	TWA: 0.15 mg/m <sup>3</sup>	TWA: 0.05 mg/m <sup>3</sup> 8 hodinách.
		Satima.	min		Ceiling: 0.2 mg/m <sup>3</sup>
			111111		biological test, toxic for
					reproduction
					. op.oddonon
Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Lead	TWA: 0.1 mg/m <sup>3</sup> 8	TWA: 0.15 mg/m <sup>3</sup> 8 hr	TWA: 0.15 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup> 8	TWA: 0.05 mg/m <sup>3</sup> 8
	tundides. total dust			órában. AK	klukkustundum. dust,
	TWA: 0.05 mg/m <sup>3</sup> 8			TWA: 0.05 mg/m <sup>3</sup> 8	fume, and powder
	tundides. respirable			órában. AK	Ceiling: 0.1 mg/m <sup>3</sup>
	dust				dust, fume, and powder
Component	Latvia	Lithuania	Luxombourg	Malta	Romania
Component Lead	STEL: 0.1 mg/m <sup>3</sup>	TWA: 0.15 mg/m <sup>3</sup>	Luxembourg TWA: 0.15 mg/m <sup>3</sup> 8	IVIAILA	TWA: 0.15 mg/m <sup>3</sup> 8 ore
Leau	TWA: 0.05 mg/m <sup>3</sup>	inhalable fraction IPRD	Stunden		I I VVA. 0. 13 mg/m² 6 0le
	TVVA. 0.05 mg/m	TWA: 0.07 mg/m <sup>3</sup>	Glanden		
		respirable fraction IPRD			
		proophiable hadden in the			1
Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Lead	TWA: 0.05 mg/m <sup>3</sup> 1826	TWA: 0.15 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup> 8 urah	TLV: 0.1 mg/m <sup>3</sup> 8	TWA: 0.15 mg/m <sup>3</sup> 8 saat
		inhalable fraction	inhalable fraction	timmar. NGV	
	1	TWA: 0.5 mg/m <sup>3</sup>	STEL: 0.4 mg/m <sup>3</sup> 15	TLV: 0.05 mg/m <sup>3</sup> 8	
			j –		
		respirable fraction	minutah inhalable fraction	timmar. NGV	

### **Biological limit values**

List source(s):

Lead wire, .187" dia., x 25 lb. spool, 99.99% (metals basis)

Revision Date 16-Jul-2025

Component	European Union	United Kingdom	France	Spain	Germany
Lead			Lead: 400 µg/L blood	Lead: 70 µg/dL blood	Lead: 150 µg/L whole
			Lead: 180 µg/L blood	not critical	blood (no restriction)
			indifferent sampling time		
			Lead: 300 µg/L blood		
			Lead: 200 µg/L blood		
			Lead: 100 µg/L blood		

Component	Italy	Finland	Denmark	Bulgaria	Romania
Lead	60 Pb μg/100 mL blood	Lead: 1.4 µmol/L blood	Lead: 20 µg/100 mL	Lead: 300 µg/L blood	Lead: 150 µg/L urine
	end of workweek	time of day does not	blood	not fixed for women	end of shift
		matter.		under 45 years old	Lead: 70 µg/100 mL
		Lead: 50 µg/dL blood . if		Lead: 400 µg/L blood	blood end of shift
		the medical examination		not fixed	Lead: 3 mg/cm hair end
		shows that the Lead			of shift
		concentration in the			.deltaAminolevulinic
		employee's blood is			acid: 10 mg/L urine end
		higher than 50 µg/dL, he			of shift
		must not be used for			Coproporphyrin: 300
		work that involves			μg/L urine end of shift
		exposure to Lead			free Erythrocytes
		Lead: 40 µg/dL blood . if			protoporphyrin: 100
		the blood's Lead			μg/100 mL Erythrocyte
		concentration of even			blood end of shift
		one employee in the			
		workplace is 40 µg/dL or			
		more, the employer			
		must especially monitor			
		the Lead concentration			
		in the air of the			
		workplace, the Lead			
		concentration in the			
		employees' blood and			
		the possible health			
		hazards caused by Lead			

### **Monitoring methods**

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust

MDHS6/3 Lead and inorganic compounds of lead in air Laboratory method using flame or electrothermal atomic absorption spectrometry

Lead wire, .187" dia., x 25 lb. spool, 99.99% (metals basis)

Revision Date 16-Jul-2025

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

No information available

#### **Predicted No Effect Concentration (PNEC)**

See values below.

Component	Fresh water	Fresh water	Water Intermittent	Microorganisms in	Soil (Agriculture)
		sediment		sewage treatment	
Lead	$PNEC = 2.4 \mu g/L$	PNEC = 186mg/kg		PNEC = 100µg/L	PNEC = 212mg/kg
7439-92-1 ( <=100 )		sediment dw			soil dw

	Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Γ	Lead	PNEC = $3.3\mu g/L$	PNEC = 168mg/kg	kg PNEC = 10.9mg/kg		
1	7439-92-1 ( <=100 )		sediment dw		food	

#### 8.2. Exposure controls

### **Engineering Measures**

Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

**Eye Protection** Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Natural rubber	See manufacturers	-	EN 374	(minimum requirement)
Nitrile rubber	recommendations			
Neoprene				
PVC				

Skin and body protection Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, gloves with care avoiding skin contamination.

**Respiratory Protection** When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced.

Recommended Filter type: Particulates filter conforming to EN 143

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

**Recommended half mask:-** Particle filtering: EN149:2001 When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls Prevent product from entering drains. Do not allow material to contaminate ground water

\_\_\_\_\_

Lead wire, .187" dia., x 25 lb. spool, 99.99% (metals basis)

system. Local authorities should be advised if significant spillages cannot be contained.

Solid

### **Section 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical State Solid

Appearance Grey Odor Odorless

Odor Threshold
Melting Point/Range
Softening Point
No data available
No data available
No data available

Boiling Point/Range 1740 °C / 3164 °F @ 760 mmHg

Flammability (liquid) Not applicable Solid

Flammability (solid,gas) No information available

**Explosion Limits** No data available

Flash Point No information available Method - No information available

Autoignition TemperatureNo data availableDecomposition TemperatureNo data available

pH No data available
No information available

Viscosity Not applicable

Water Solubility Insoluble

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Vapor Pressure 1.77 mmHg @ 1000 °C

Density / Specific Gravity

Bulk Density No data available

Vapor Density Not applicable Solid

Particle characteristics No data available

9.2. Other information

Molecular Formula Pb Molecular Weight 207.19

Evaporation Rate Not applicable - Solid

### Section 10: Stability and reactivity

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

10.4. Conditions to avoid

Exposure to air. Incompatible products.

10.5. Incompatible materials

Strong acids. Ammonium nitrate: fertilizers capable of self-sustaining decomposition.

Peroxides.

Lead wire, .187" dia., x 25 lb. spool, 99.99% (metals basis)

#### 10.6. Hazardous decomposition products

Lead. lead oxides.

### **Section 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Product Information** 

(a) acute toxicity;

OralNo data availableDermalNo data availableInhalationNo data available

(b) skin corrosion/irritation; No data available

(c) serious eye damage/irritation; No data available

(d) respiratory or skin sensitization;

Respiratory No data available Skin No data available

No information available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Lead				Group 2A

(g) reproductive toxicity; Category 1A

Reproductive Effects May cause harm to the unborn child. Possible risk of impaired fertility.

(h) STOT-single exposure; No data available

(i) STOT-repeated exposure; Category 1

Target Organs Kidney, Central nervous system (CNS), Blood.

(j) aspiration hazard; Not applicable

Solid

Symptoms / effects,both acute and No information available.

delayed

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any

known or suspected endocrine disruptors.

Revision Date 16-Jul-2025

### **Section 12: Ecological information**

#### 12.1. Toxicity **Ecotoxicity effects**

The product contains following substances which are hazardous for the environment. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. May cause long-term adverse effects in the environment. Do not allow material to contaminate ground water system.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Lead	LC50: = 1.32 mg/L, 96h static	EC50: = 600 µg/L, 48h (water	
	(Oncorhynchus mykiss)	flea)	
	LC50: = 1.17 mg/L, 96h		
	flow-through (Oncorhynchus		
	mykiss)		
	LC50: = 0.44 mg/L, 96h		
	semi-static (Cyprinus carpio)		

Component	Microtox	M-Factor
Lead		M = 10'

12.2. Persistence and degradability Product contains heavy metals. Discharge into the environment must be avoided. Special

pre-treatment is necessary

**Persistence** Degradability Insoluble in water, May persist.

Not relevant for inorganic substances.

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential

May have some potential to bioaccumulate; Product has a high potential to bioconcentrate

12.4. Mobility in soil

Spillage unlikely to penetrate soil Is not likely mobile in the environment due its low water

solubility.

12.5. Results of PBT and vPvB

assessment

In accordance with Annex XIII of the REACH Regulation, inorganic substances do not

require assessment.

12.6. Endocrine disrupting

properties

**Endocrine Disruptor Information** 

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

**Persistent Organic Pollutant Ozone Depletion Potential** 

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

### Section 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste from Residues/Unused **Products** 

Should not be released into the environment. Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Lead wire, .187" dia., x 25 lb. spool, 99.99% (metals basis)

Revision Date 16-Jul-2025

Contaminated Packaging Dispose of this container to hazardous or special waste collection point.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but

application specific.

Other Information Do not flush to sewer. Waste codes should be assigned by the user based on the

application for which the product was used. Do not empty into drains. Do not let this

chemical enter the environment.

Switzerland - Waste Ordinance Disposal should be in accordance with applicable regional, national and local laws and

regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance,

ADWO) SR 814.600

https://www.fedlex.admin.ch/eli/cc/2015/891/en

### **Section 14: Transport information**

#### IMDG/IMO

**14.1. UN number** UN3077

**14.2. UN** proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

Technical Shipping Name
Lead
14.3. Transport hazard class(es)
9
14.4. Packing group

#### ADR

**14.1. UN number** UN3077

**14.2. UN** proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

Technical Shipping Name

14.3. Transport hazard class(es)

14.4. Packing group

Lea

9

III

### IATA

**14.1. UN number** UN3077

**14.2. UN proper shipping name** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

Technical Shipping Name

14.3. Transport hazard class(es)

14.4. Packing group

III

**14.5. Environmental hazards** Dangerous for the environment

Product is a marine pollutant according to the criteria set by IMDG/IMO

**14.6. Special precautions for user** No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable, packaged goods

### **Section 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

	Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL	
--	-----------	--------	--------	--------	-----	-------	------	------	------	------	--

Lead wire, .187" dia., x 25 lb. spool, 99.99% (metals basis)

Revision Date 16-Jul-2025

Lead	7439-92-1	231-100-4	-	-	Χ	Χ	KE-21887	Χ	-
Component	CAS No	TSCA	notific	iventory ation - Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Lead	7439-92-1	X	ACT	IVE	X	Ī	X	X	X

Legend: X - Listed '-' - Not listed

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

### Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Lead	7439-92-1	-	Use restricted. See entry 72. (see link for restriction details) Use restricted. See entry 30. (see link for restriction details) Use restricted. See entry 63. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details)	SVHC Candidate list - 231-100-4 - Toxic for reproduction (Article 57c)

### **REACH links**

https://echa.europa.eu/authorisation-list

https://echa.europa.eu/substances-restricted-under-reach

https://echa.europa.eu/candidate-list-table

After the sunset date the use of this substance requires either an authorization or can only be used for exempted uses, e.g. use in scientific research and development which includes routine analytics or use as intermediate.

### Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) -	Seveso III Directive (2012/18/EC) -
-		Qualifying Quantities for Major Accident	Qualifying Quantities for Safety Report
		Notification	Requirements
Lead	7439-92-1	Not applicable	Not applicable

## Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Component	ANNEX I - PART 1 List of chemicals subject to export notification procedure (referred to in Article 8)	ANNEX I - PART 2 List of chemicals qualifying for PIC notification (referred to in Article 11)	ANNEX I - PART 3 List of chemicals subject to the PIC procedure (referred to in Articles 13 and 14)
Lead 7439-92-1 ( <=100 )	sr — severe restriction	-	-
	i(2) — industrial chemical for public		

https://eur-lex.europa.eu/legal-content/EN/TXT/?uri=CELEX%3A32012R0649&qid=1604065742303.

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Lead wire, .187" dia., x 25 lb. spool, 99.99% (metals basis)

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

Take note of Directive 94/33/EC on the protection of young people at work

Take note of Dir 92/85/EC on the protection of pregnant and breastfeeding women at work

#### **National Regulations**

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

**WGK Classification** 

See table for values

	Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
[	Lead	nwg	Class II: 0.5 mg/m³ (Massenkonzentration)

Component	France - INRS (Tables of occupational diseases)
Lead	Tableaux des maladies professionnelles (TMP) - RG 1

#### **Swiss Regulations**

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Lead	Prohibited and Restricted		
7439-92-1 ( <=100 )	Substances		

#### 15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has not been conducted

### **Section 16: Other information**

### Full text of H-Statements referred to under sections 2 and 3

H360Df - May damage the unborn child. Suspected of damaging fertility

H362 - May cause harm to breast-fed children

H372 - Causes damage to organs through prolonged or repeated exposure

H410 - Very toxic to aquatic life with long lasting effects

H360FD - May damage fertility. May damage the unborn child

H360Fd - May damage fertility. Suspected of damaging the unborn child

#### Legend

**CAS** - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances Substances List **ENCS** - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

**ALFAA97115** 

Revision Date 16-Jul-2025

Transport Association

ATE - Acute Toxicity Estimate

**VOC** - (volatile organic compound)

Lead wire, .187" dia., x 25 lb. spool, 99.99% (metals basis)

Revision Date 16-Jul-2025

ICAO/IATA - International Civil Aviation Organization/International Air

MARPOL - International Convention for the Prevention of Pollution from

NOEC - No Observed Effect Concentration POW - Partition coefficient Octanol:Water PBT - Persistent, Bioaccumulative, Toxic vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

**Training Advice** 

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hvaiene.

Ships

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

**Prepared By** Health, Safety and Environmental Department

**Creation Date** 11-Nov-2011 **Revision Date** 16-Jul-2025

**Revision Summary** SDS sections updated.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

## **End of Safety Data Sheet**