

Australian statement of hazardous nature: Classified as hazardous according to criteria of Safe Work Australia

Section 1 - Identification

Product Name <u>Isobutanol</u>

CAS No 78-83-1

Synonyms Isobutanol; Isobutyl alcohol

Product Code 36643

Address ThermoFisher Scientific Australia Pty Ltd

5 Caribbean Drive, Scoresby VICTORIA 3179, Australia

Emergency Tel. CHEMTREC®

03 9757 4559 or +613 9757 4559

Telephone / Fax Numbers Tel: 1300 735 292

Fax: 1800 067 639

E-mail address ANZinfo@thermofisher.com

Recommended Use Laboratory chemicals.

Uses advised against This product does not contain any substance(s) on the Illicit Drug Precursors/Reagents list.

This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction. This product does not contain any substance(s) listed on the voluntary National

Code of Practice for Chemicals of Security Concern.

Section 2 - Hazard(s) Identification

Classification under Safe Work Australia

Classified as hazardous according to criteria of Safe Work Australia

Physical hazards

Flammable liquids Category 3

Health hazards

Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 1
Specific target organ toxicity - (single exposure) Category 3

Environmental hazards
No hazards identified

Label Elements

ALFAA36643 Version 2 18-Nov-2022 Page 1/10







Signal Word

Danger

Hazard Statements

H226 - Flammable liquid and vapor

H315 - Causes skin irritation

H318 - Causes serious eve damage

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P233 - Keep container tightly closed

P240 - Ground and bond container and receiving equipment

P241 - Use explosion-proof electrical/ ventilating/ lighting equipment

P242 - Use non-sparking tools

P243 - Take action to prevent static discharges

P264 - Wash face, hands and any exposed skin thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor

P363 - Wash contaminated clothing before reuse

P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P501 - Dispose of contents/ container to an approved waste disposal plant

Other information

Section 3 - Composition and Information on Ingredients

Component	CAS No	Weight %		
Isobutyl alcohol	78-83-1	99		

Section 4 - First Aid Measures

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

Ingestion Clean mouth with water and drink afterwards plenty of water.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

ALFAA36643 Version 2 18-Nov-2022 Page 2/10

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required.

General Advice If symptoms persist, call a physician.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

First Aid Facilities Eyewash, safety shower and washroom.

Most important symptoms and

effects

None reasonably foreseeable. Causes severe eye damage. Symptoms of overexposure

may be headache, dizziness, tiredness, nausea and vomiting

Notes to Physician Treat symptomatically. Symptoms may be delayed.

Section 5 - Fire Fighting Measures

Suitable Extinguishing Media

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

Hazardous Decomposition Products

Carbon monoxide (CO), Carbon dioxide (CO2).

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.

Special protective equipment and precautions for fire fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6 - Accidental Release Measures

Emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

Should not be released into the environment.

Methods for Containment and Clean Up

Clean-up methods - small spillage

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Clean-up methods - large spillage

Typically only supplied is small quantiites as packaged goods.

If extremely toxic or used in larger quantities ensure a spillage action plan is in place. Evacuate area. Control the source and/or contain the spill if safe and able to do so. Use temporary diking, sand bags, dry sand, earth or proprietary booms/absorbent pads if available. Obtain advice on containment, neutralisation and clean-up from local emergency responders.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

ALFAA36643 Version 2 18-Nov-2022 Page 3/10

Section 7 - Handling and Storage

Precautions for Safe Handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges.

Conditions for Safe Storage, Including any Incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

AS/NZS 2243.10:2004, Safety in laboratories - Storage of chemicals AS 1940-2004 - The storage and handling of flammable and combustible liquids

Section 8 - Exposure Controls and Personal Protection

Exposure limits

AUS - Exposure Standards for Atmospheric Contaminants in the Occupational Environment - Guidance Note on the Interpretation of Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:3008(1995)] Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)] updated in August, 2005. Safe Work Australia ACGIH - Threshold Limit Values - Ceiling (TLV-C) guidelines by the American Conference of Governmental Industrial Hygienists (ACGIH) for controlling worker exposure to airborne chemical concentrations in the workplace. UK - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. DE - MAK and BAT values of Hazardous Chemical Compounds in the Work Area. Published by German Research Foundation on July 1, 2011

Component	Australia	New Zealand WEL	ACGIH TLV	The United Kingdom	Germany
Isobutyl alcohol	TWA: 50 ppm	TWA: 50 ppm	TWA: 50 ppm	STEL: 75 ppm 15 min	TWA: 100 ppm (8
	TWA: 152 mg/m ³	TWA: 152 mg/m ³		STEL: 231 mg/m ³ 15	Stunden). AGW -
				min	exposure factor 1
				TWA: 50 ppm 8 hr	TWA: 310 mg/m ³ (8
				TWA: 154 mg/m ³ 8 hr	Stunden). AGW -
					exposure factor 1
					TWA: 100 ppm (8
					Stunden). MAK
					TWA: 310 mg/m ³ (8
					Stunden). MAK
					Höhepunkt: 100 ppm
					Höhepunkt: 310 mg/m ³

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Exposure Controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles (Australian/New Zealand Standard AS/NZS 1337 - Eye protectors for Industrial

applications)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	AUS/NZ Standard	Glove comments
Nitrile rubber	> 480 minutes	0.38 mm	AS/NZS 2161	As tested under EN374-3 Determination of
Butyl rubber	> 480 minutes	0.35 mm		Resistance to Permeation by Chemicals
Neoprene gloves	> 480 minutes	0.45 mm		-

ALFAA36643 Version 2 18-Nov-2022 Page 4/10

Viton (R) > 480 minutes 0.70 mm

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection Long sleeved clothing

Repiratory Protection Use an AS/NZS 1716 approved respirator if exposure limits are exceeded or if irritation or

> other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained in line with AS/NZS 1715 on the use

> > Liquid

and maintenance of repiratory protective devices

Organic gases and vapours filter Type A Brown conforming to EN14387 (or AUS/NZ Recommended Filter type:

equivalent)

Recommended half mask:-Valve filtering: EN405 or Half mask: EN140 plus filter, EN 141 (or AUS/NZ equivalent)

When RPE is used a face piece Fit Test should be conducted

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls No information available.

Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance Colorless **Physical State** Liquid

Odor aromatic

Odor Threshold No data available рH No information available Melting Point/Range -108 °C / -162.4 °F **Softening Point** No data available **Boiling Point/Range** 108 °C / 226.4 °F

Flash Point 28 °C / 82.4 °F Method - No information available

(Butyl Acetate = 1.0) **Evaporation Rate** 0.6

Not applicable Flammability (solid,gas) Liquid

Explosion Limits Lower 1.6 Vol% Upper 10.9 Vol%

11.7 mbar @ 20°C **Vapor Pressure**

Vapor Density 2.6 (Air = 1.0)

Specific Gravity / Density 0.800 **Bulk Density** Not applicable

Water Solubility Soluble

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Component log Pow

Isobutyl alcohol

430 °C / 806 °F **Autoignition Temperature** No data available **Decomposition Temperature** Viscosity No data available

Explosive Properties Not explosive explosive air/vapour mixtures possible

Oxidizing Properties (based on the chemical structure of the substance Not oxidising and oxidation states of the constituent elements)

Other information

C4 H10 O Molecular Formula 74.12 **Molecular Weight**

ALFAA36643 Version 2 18-Nov-2022 Page 5/10 VOC Content(%) 100 %

Section 10 - Stability and Reactivity

Reactivity None known, based on information available

Stability Stable under normal conditions.

Conditions to Avoid Incompatible products, Excess heat, Keep away from open flames, hot surfaces and

sources of ignition.

Incompatible Materials Strong oxidizing agents, Acid anhydrides, Acid chlorides.

Hazardous Decomposition Products Carbon monoxide (CO). Carbon dioxide (CO₂).

Hazardous Polymerization Hazardous polymerization does not occur.

Section 11 - Toxicological Information

Information on Toxicological Effects

Product Information See actual entry in RTECS for complete information.

(a) acute toxicity;

Oral Based on available data, the classification criteria are not met
Dermal Based on available data, the classification criteria are not met
Inhalation Based on available data, the classification criteria are not met

0 Oral LD50 Dermal	l LC50 Inhalation
0 mg/kg (Rat) LD50 = 3400 mg/kg ((Rabbit) LC50 > 18.18 mg/L (Rat) 6 h
-	

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

RespiratoryBased on available data, the classification criteria are not met
Skin
Based on available data, the classification criteria are not met

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

(f) carcinogenicity; Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; Based on available data, the classification criteria are not met

(h) STOT-single exposure; Category 3

Results / Target organs Respiratory system

Central nervous system (CNS)

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

Target Organs None known.

ALFAA36643 Version 2 18-Nov-2022 Page 6 / 10

(j) aspiration hazard;

Based on available data, the classification criteria are not met

Symptoms / effects,both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting delayed

Section 12 - Ecological Information

Ecotoxicity effects Do not empty into drains. .

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Isobutyl alcohol	LC50: 1370 - 1670	EC50: = 1300 mg/L, 48h	1799 mg/l EC50 = 72 h	EC50 = 1224.6 mg/L 15
	mg/L, 96h flow-through	(Daphnia magna)	230 mg/L EC50 = 48 h	min
	(Pimephales promelas)	EC50: 1070 - 1933		
	LC50: = 375 mg/L, 96h	mg/L, 48h Static		
	static (Pimephales	(Daphnia magna)		
	promelas)			
	LC50: 1120 - 1520			
	mg/L, 96h flow-through			
	(Oncorhynchus mykiss)			
	LC50: 1480 - 1730			
	mg/L, 96h flow-through			
	(Lepomis macrochirus)			

Persistence and Degradability

Readily biodegradable

Persistence

Soluble in water, Persistence is unlikely, based on information available.

Component	Degradability
Isobutyl alcohol	90% (14d)
78-83-1 (99)	

Degradation in sewage treatment plant Bioaccumulative Potential

Contains no substances known to be hazardous to the environment or not degradable in

waste water treatment plants.

ve Potential Product has a low potential to bioconcentrate Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)		
Isobutyl alcohol	1	< 100		
Mobility	The product is water soluble, and may spread	in water systems. Will likely be mobile in the		
	ses rapidly in air: Highly mobile in soils			
Endocrine Disruptor Information This product does not contain any known or suspected endocrine disrupto				
Persistent Organic Pollutant This product does not contain any known or suspected substance				
Ozone Depletion Potential This product does not contain any known or suspected substance				

Section 13 - Disposal Considerations

Waste from Residues/Unused Products

Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with all federal, E.P.A., state and local regulations. Assure

conformity with all applicable regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

Other Information Chemical wastes should be disposed through a licensed commercial waste collection

service. Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in

compliance with local regulations. Do not empty into drains.

Section 14 - Transport Information

IMDG/IMO

UN-No UN1212

ALFAA36643 Version 2 18-Nov-2022 Page 7/10

Proper Shipping Name ISOBUTANOL

Hazard Class 3
Packing Group III

<u>ADG</u>

UN-No UN1212
Proper Shipping Name UN1211

Hazard Class 3
Packing Group III

Component	Hazchem Code
Isobutyl alcohol	3Y
78-83-1 (99)	

<u>IATA</u>

UN-No UN1212
Proper Shipping Name UN1211

Hazard Class 3 Packing Group III

Environmental hazards No hazards identified

Special Precautions No special precautions required

Additional information None known

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National Regulations Australia

See section 8 for national exposure control parameters.

Standard for the Uniform Scheduling of Medicines and Poisons

No poison schedule number allocated.

Australian Industrial Chemicals Introduction Scheme (AICIS)

Component	Australian Industrial Chemicals Introduction Scheme (AICIS)	Additional information
Isobutyl alcohol - 78-83-1	Present	-

Australian - Illicit Drug Precursors/Reagents Substance List

This product does not contain any substance(s) on the Illicit Drug Precursors/Reagents list.

Chemicals of Security Concern

This product does not contain any substance(s) listed on the voluntary National Code of Practice for Chemicals of Security Concern

National pollutant inventory Not applicable

ALFAA36643 Version 2 18-Nov-2022 Page 8/10

Prohibition or notification/licensing requirements

Shown below are details of specific prohibition/notifications or licencing requirements when they apply.

This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction.

International Inventories

Component	AICS	NZIoC	EINECS	ELINCS	TSCA	DSL	NDSL	PICCS	ENCS	ISHL	IECSC	KECL
Isobutyl alcohol	X	Χ	201-148-0	-	X	Х	-	Х	Х	X	X	KE-24894

Legend: X - Listed. '-' - Not Listed. KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

International Regulations

Ozone Depletion Potential This product does not contain any known or suspected substance

Persistent Organic Pollutant This product does not contain any known or suspected substance

Rotterdam Convention (PIC) Not applicable

Basel convention on the control of transboundary movements of hazardous wastes and their dispoal Not applicable.

Component	CAS No	OECD HPV	Restriction of Hazardous Substances (RoHS)	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Isobutyl alcohol	78-83-1	Listed	Not applicable	Not applicable	Not applicable

Authorisation/Restrictions according to EU REACH

ſ	Component	REACH (1907/2006) - Annex XIV -	REACH (1907/2006) - Annex XVII -	REACH Regulation (EC
		Substances Subject to	Restrictions on Certain Dangerous	1907/2006) article 59 - Candidate
		Authorization	Substances	List of Substances of Very High
L				Concern (SVHC)
Ī	Isobutyl alcohol	-	Use restricted. See item 75.	-
			(see link for restriction details)	

https://echa.europa.eu/substances-restricted-under-reach

Section 16 - Other Information

Legend

AICS - Australian Inventory of Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

IECSC - Chinese Inventory of Existing Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

TWA - Time Weighted Average

NZIoC - New Zealand Inventory of Chemicals

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japanese Existing and New Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

CAS - Chemical Abstracts Service

ACGIH - American Conference of Governmental Industrial Hygienists

ALFAA36643 Version 2 18-Nov-2022 Page 9/10

IARC - International Agency for Research on Cancer

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

NZS 5433:2012 - Transport of Dangerous Goods on Land

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50% WEL - Workplace Exposure Limit DNEL - Derived No Effect Level

POW - Partition coefficient Octanol:Water **vPvB** - very Persistent, very Bioaccumulative

VOC - (Volatile Organic Compound)

Predicted No Effect Concentration (PNEC)

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

ADG Australian Code for the Transport of Dangerous Goods by Road and Rail

OECD - Organisation for Economic Co-operation and Development

LC50 - Lethal Concentration 50%
ATE - Acute Toxicity Estimate

RPE - Respiratory Protective Equipment NOEC - No Observed Effect Concentration

BCF - Bioconcentration factor

PBT - Persistent, Bioaccumulative, Toxic

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts. Chemical incident response training.

First aid for chemical exposure, including the use of eye wash and safety showers.

Revision Date 18-Nov-2022 Revision Summary Not applicable.

This Safety Data Sheet (SDS) is prepared in accordance to and complies with the requirements of Safe Work Australia - Work Health and Safety Regulations (WHS Regulations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

ALFAA36643 Version 2 18-Nov-2022 Page 10 / 10