

according to Regulation (EC) No. 1907/2006

Creation Date 10-Nov-2023 Revision Date 06-Jun-2024 Revision Number 3

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description:

Oxidising Solution, 0.05M

Cat No.: TS/0031/08; TS/0031/27; TS/0031/27SS; TS/0031/17

Unique Formula Identifier (UFI) 4KFX-H6KY-XX02-KE28

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

EU entity/business name
Thermo Fisher Scientific
Janssen Pharmaceuticalaan 3a

2440 Geel, Belgium

UK entity/business name

Fisher Scientific UK

Bishop Meadow Road, Loughborough, Leicestershire LE11 5RG, United Kingdom

Swiss distributor - Fisher Scientific AG Neuhofstrasse 11, CH 4153 Reinach

Tel: +41 (0) 56 618 41 11 e-mail - infoch@thermofisher.com

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

Tel: 01509 231166

Chemtrec US: (800) 424-9300 Chemtrec EU: 001-703-527-3887

For customers in Switzerland:

Tox Info Suisse Emergency Number: 145 (24hr)

Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)

Chemtrec (24h) Toll-Free: 0800 564 402 Chemtrec Local: +41-43 508 20 11 (Zurich)

Poison Centre - Emergency information services

Ireland: National Poisons Information Centre (NPIC) -

01 809 2166 (8am-10pm, 7 days a week)

Malta: +356 2395 2000 Cyprus: +357 2240 5611

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Flammable liquids Category 2 (H225)

Health hazards

Acute oral toxicity	Category 4 (H302)
Acute dermal toxicity	Category 4 (H312)
Acute Inhalation Toxicity - Vapors	Category 4 (H332)
Skin Corrosion/Irritation	Category 2 (H315)
Serious Eye Damage/Eye Irritation	Category 2 (H319)
Specific target organ toxicity - (repeated exposure)	Category 2 (H373)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H302 + H312 + H332 - Harmful if swallowed, in contact with skin or if inhaled

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P312 - Call a POISON CENTER or doctor if you feel unwell

2.3. Other hazards

This product does not contain any known or suspected endocrine disruptors

Section 3: Composition/information on ingredients

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Pyridine	110-86-1	203-809-9	85 - 90	Flam. Liq. 2 (H225) Acute Tox. 4 (H302) Acute Tox. 4 (H312) Acute Tox. 4 (H332) Skin Irrit. 2 (H315)
				Eye Irrit. 2 (H319)
lodine	7553-56-2	231-442-4	1 - 2.5	Acute Tox. 4 (H302) Acute Tox. 4 (H312) Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) STOT SE 3 (H335) STOT RE 1 (H372) Aquatic Acute 1 (H400)
Water	7732-18-5	231-791-2	5 - 10	-

Compone	nt Specific concentration limits (SCL's)	M-Factor	Component notes
lodine	-	1	-

Components	Reach Registration Number	
Pyridine	01-2119493105-40	
Iodine	01-2119485285-30	

Full text of Hazard Statements: see section 16

Section 4: First aid measures

4.1. Description of first aid measures

General Advice If symptoms persist, call a physician.

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get **Eye Contact**

medical attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

Ingestion Clean mouth with water and drink afterwards plenty of water.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

Ensure that medical personnel are aware of the material(s) involved, take precautions to Self-Protection of the First Aider

protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like

headache, dizziness, tiredness, nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

Section 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO2), Hydrogen cyanide (hydrocyanic acid), Nitrogen oxides (NOx).

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

Section 7: Handling and storage

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures

Oxidising Solution, 0.05M

Revision Date 06-Jun-2024

against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, sparks and flame.

Technical Rules for Hazardous Substances (TRGS) 510

Storage Class (LGK) (Germany)

Class 3

Switzerland - Storage of hazardous substances

Storage class - SC 3 https://www.kvu.ch/de/themen/stoffe-und-produkte https://www.kvu.ch/fr/themes/substances-et-produits https://www.kvu.ch/it/temi/sostanze-e-prodotti

Page 5/15

7.3. Specific end use(s)

Use in laboratories

Section 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits

List source(s): UK - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. IRE - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Pyridine		STEL: 10 ppm 15 min	TWA / VME: 5 ppm (8	TWA: 1 ppm 8 uren	TWA / VLA-ED: 1 ppm
		STEL: 33 mg/m ³ 15 min	heures).	TWA: 3.3 mg/m ³ 8 uren	(8 horas)
		TWA: 5 ppm 8 hr	TWA / VME: 15 mg/m ³	_	TWA / VLA-ED: 3 mg/m ³
		TWA: 16 mg/m ³ 8 hr	(8 heures).		(8 horas)
			STEL / VLCT: 10 ppm.		
			STEL / VLCT: 30		
			mg/m³.		
lodine		STEL: 0.1 ppm 15 min	STEL / VLCT: 0.1 ppm.	TWA: 0.01 ppm 8 uren	STEL / VLA-EC: 0.1
		STEL: 1.1 mg/m ³ 15 min	STEL / VLCT: 1 mg/m ³ .	TWA: 0.1 mg/m ³ 8 uren	ppm (15 minutos).
				STEL: 0.1 ppm 15	STEL / VLA-EC: 1
				minuten	mg/m³ (15 minutos).
				STEL: 1 mg/m ³ 15	TWA / VLA-ED: 0.01
				minuten	ppm (8 horas)
					TWA / VLA-ED: 0.1
					mg/m³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
Pyridine		Haut	TWA: 5 ppm 8 horas	TWA: 0.3 ppm 8 uren	TWA: 1 ppm 8 tunteina
			TWA: 15 mg/m ³ 8 horas	TWA: 0.9 mg/m ³ 8 uren	TWA: 3 mg/m ³ 8
					tunteina
					STEL: 5 ppm 15
					minuutteina
					STEL: 16 mg/m ³ 15
					minuutteina
					lho
lodine		Haut	STEL: 0.1 ppm 15		STEL: 0.1 ppm 15
			minutos		minuutteina
			TWA: 0.01 ppm 8 horas		STEL: 1.1 mg/m ³ 15

Oxidising Solution, 0.05M

Revision Date 06-Jun-2024

						minuutteina Iho
--	--	--	--	--	--	--------------------

Component	Austria	Denmark	Switzerland	Poland	Norway
Pyridine	Haut MAK-KZGW: 20 ppm 15 Minuten MAK-KZGW: 60 mg/m³ 15 Minuten MAK-TMW: 5 ppm 8 Stunden MAK-TMW: 15 mg/m³ 8 Stunden	STEL: 10 ppm 15 minutter STEL: 30 mg/m³ 15 minutter	STEL: 10 ppm 15 Minuten STEL: 30 mg/m³ 15 Minuten TWA: 5 ppm 8 Stunden TWA: 15 mg/m³ 8 Stunden	TWA: 5 mg/m³ 8 godzinach	TWA: 5 ppm 8 timer TWA: 15 mg/m³ 8 timer STEL: 10 ppm 15 minutter. value calculated STEL: 22.5 mg/m³ 15 minutter. value calculated
lodine	Haut MAK-KZGW: 0.1 ppm 15 Minuten MAK-KZGW: 1 mg/m³ 15 Minuten MAK-TMW: 0.1 ppm 8 Stunden MAK-TMW: 1 mg/m³ 8 Stunden Ceiling: 0.1 ppm Ceiling: 1 mg/m³	Ceiling: 0.1 ppm Ceiling: 1 mg/m³	Haut/Peau STEL: 0.1 ppm 15 Minuten STEL: 1 mg/m³ 15 Minuten TWA: 0.1 ppm 8 Stunden TWA: 1 mg/m³ 8 Stunden	STEL: 1 mg/m³ 15 minutach TWA: 0.5 mg/m³ 8 godzinach	Ceiling: 0.1 ppm Ceiling: 1 mg/m³

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Pyridine	TWA: 15.0 mg/m ³	TWA-GVI: 5 ppm 8	TWA: 5 ppm 8 hr.	TWA: 5 ppm	TWA: 5 mg/m ³ 8
·		satima.	TWA: 15 mg/m ³ 8 hr.	TWA: 15 mg/m ³	hodinách.
		TWA-GVI: 15 mg/m ³ 8	STEL: 10 ppm 15 min	_	Potential for cutaneous
		satima.	STEL: 30 mg/m ³ 15 min		absorption
			_		Ceiling: 10 mg/m ³
lodine	TWA: 3.0 mg/m ³	STEL-KGVI: 0.1 ppm 15	TWA: 0.01 ppm 8 hr.		TWA: 0.1 mg/m ³ 8
		minutama.	inhalable fraction and		hodinách.
		STEL-KGVI: 1.1 mg/m ³	vapour		Ceiling: 1 mg/m ³
		15 minutama.	TWA: 0.01 mg/m ³ 8 hr.		
			STEL: 0.1 ppm 15 min		

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Pyridine	TWA: 5 ppm 8 tundides. TWA: 15 mg/m ³ 8 tundides.	TWA: 5 ppm 8 hr existing scientific data on health effects appear to be particularly limited TWA: 15 mg/m³ 8 hr existing scientific data on health effects appear to be particularly limited	STEL: 10 ppm STEL: 30 mg/m³ TWA: 5 ppm TWA: 15 mg/m³	STEL: 30 mg/m³ 15 percekben. CK STEL: 10 ppm 15 percekben. CK TWA: 15 mg/m³ 8 órában. AK TWA: 5 ppm 8 órában. AK lehetséges borön keresztüli felszívódás	TWA: 5 ppm 8 klukkustundum. TWA: 15 mg/m³ 8 klukkustundum. Ceiling: 10 ppm Ceiling: 30 mg/m³
lodine	STEL: 0.1 ppm 15 minutites. STEL: 1 mg/m³ 15 minutites.		STEL: 0.1 ppm STEL: 1 mg/m³ TWA: 0.1 ppm TWA: 1 mg/m³	STEL: 1 mg/m³ 15 percekben. CK STEL: 0.1 ppm 15 percekben. CK TWA: 1 mg/m³ 8 órában. AK TWA: 0.1 ppm 8 órában. AK lehetséges borön keresztüli felszívódás	STEL: 0.1 ppm STEL: 1 mg/m³

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Pyridine	TWA: 5 ppm TWA: 15 mg/m ³	TWA: 5 ppm IPRD TWA: 15 mg/m³ IPRD	TWA: 5 ppm 8 Stunden TWA: 15 mg/m³ 8 Stunden	TWA: 5 ppm TWA: 15 mg/m ³	TWA: 5 ppm 8 ore TWA: 15 mg/m ³ 8 ore
lodine	TWA: 1 mg/m³	Ceiling: 0.1 ppm Ceiling: 1 mg/m³			TWA: 0.09 ppm 8 ore TWA: 0.5 mg/m³ 8 ore STEL: 0.2 ppm 15 minute STEL: 1 mg/m³ 15

Oxidising Solution, 0.05M

Revision Date 06-Jun-2024

					minute
Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Pyridine	MAC: 5 mg/m ³	TWA: 5 ppm	TWA: 5 ppm 8 urah	Indicative STEL: 3 ppm	
		TWA: 15 mg/m ³	TWA: 15 mg/m ³ 8 urah	15 minuter	TWA: 15 mg/m ³ 8 saat
				Indicative STEL: 10	
				mg/m³ 15 minuter	
				TLV: 2 ppm 8 timmar.	
				NGV	
				TLV: 7 mg/m ³ 8 timmar.	
				ŇGV	
Iodine	Skin notation	Ceiling: 1.1 mg/m ³		Binding STEL: 0.1 ppm	
	MAC: 1 mg/m ³	TWA: 0.1 ppm		15 minuter	
	1	TWA: 1.1 mg/m ³		Binding STEL: 1 mg/m ³	
				15 minuter	

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Pyridine		DNEL = 0.42mg/kg		DNEL = 0.14mg/kg
110-86-1 (85 - 90)		bw/day		bw/day
lodine				DNEL = 0.01mg/kg
7553-56-2 (1 - 2.5)				bw/day

Component	Acute effects local	Acute effects	Chronic effects local	Chronic effects
	(Inhalation)	systemic (Inhalation)	(Inhalation)	systemic (Inhalation)
Pyridine		DNEL = 7.5 mg/m ³		DNEL = 2.5 mg/m ³
110-86-1 (85 - 90)				
lodine				$DNEL = 0.07 mg/m^3$
7553-56-2 (1 - 2.5)				

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water			er Intermittent Microorganisms in Soil (Agric	
		sediment		sewage treatment	
Pyridine	PNEC = 0.3mg/L	PNEC = 3.2mg/kg	PNEC = 3mg/L	PNEC = 2mg/L	PNEC = 0.46mg/kg
110-86-1 (85 - 90)	-	sediment dw			soil dw
Iodine	PNEC = 18.13µg/L	PNEC = 3.99mg/kg		PNEC = 11mg/L	PNEC = 5.95mg/kg
7553-56-2 (1 - 2.5)		sediment dw		-	soil dw

Oxidising Solution, 0.05M Revision Date 06-Jun-2024

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Pyridine	PNEC = 0.03mg/L	PNEC = 0.32mg/kg			
110-86-1 (85 - 90)		sediment dw			
Iodine	PNEC = 60.01µg/L	PNEC =			
7553-56-2 (1 - 2.5)		20.22mg/kg			
		sediment dw			

8.2. Exposure controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

Γ	Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
1	Viton (R)	< 120 minutes	0.7 mm	Level 4 EN 374	Permeation rate 14 µg/cm2/min
					As tested under EN374-3 Determination of
					Resistance to Permeation by Chemicals
L	Butyl rubber	< 50 minutes	0.6 mm		•

Skin and body protection Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced.

Recommended Filter type: Particulates filter conforming to EN 143 Ammonia and organic

ammonia derivatives filter Type K Green conforming to EN14387

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

141

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls Prevent product from entering drains. Do not allow material to contaminate ground water

system.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Oxidising Solution, 0.05M Revision Date 06-Jun-2024

Estimated

Physical State Liquid

Appearance Light brown Odor Fishy

Odor Threshold No data available

Melting Point/Range -46 °C / -50.8 °F
Softening Point No data available

Boiling Point/Range 115 °C / 239 °F Estimated

Flammability (liquid) Highly flammable On basis of test data

Flammability (solid,gas) Not applicable Liquid

Explosion Limits No data available

Flash Point 20 °C / 68 °F Method - (based on components)

Autoignition Temperature No data available

Decomposition Temperature No data available

pH 8.8

Viscosity No data available

Water Solubility Miscible

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Component log Pow

Pyridine 0.65

Iodine 2.49

Vapor Pressure No data available

Density / Specific Gravity <1

Bulk DensityNot applicableLiquidVapor DensityNo data available(Air = 1.0)

Particle characteristics Not applicable (liquid)

9.2. Other information

Explosive Properties Vapors may form explosive mixtures with air

Section 10: Stability and reactivity

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization No information available.
Hazardous Reactions None under normal processing.

10.4. Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight. Keep away from

open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Strong acids. Strong oxidizing agents.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂). Hydrogen cyanide (hydrocyanic acid).

Nitrogen oxides (NOx).

Section 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Category 4 Oral

ATE = 952 mg/kg

Dermal Category 4

ATE = 1116 mg/kg

Category 4 Inhalation

ATE = 14.2 mg/l

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation		
Pyridine	LD50 = 866 mg/kg (Rat)	LD50 1000 - 2000 mg/kg(Rabbit)	LC50 = 12.898 mg/L (Rat) 4		
lodine	315 mg/kg (Rat)	1425 mg/kg (Rabbit)	4.588 mg/L 4h (Rat)		
Water	-	-	-		

(b) skin corrosion/irritation; Category 2

Category 2 (c) serious eye damage/irritation;

(d) respiratory or skin sensitization;

Respiratory Based on available data, the classification criteria are not met Skin Based on available data, the classification criteria are not met

Component	Test method	Test species	Study result
Iodine	OECD Test Guideline 429	mouse	non-sensitising
7553-56-2 (1 - 2.5)	Local Lymph Node Assay		

Based on available data, the classification criteria are not met (e) germ cell mutagenicity;

(f) carcinogenicity; Based on available data, the classification criteria are not met

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Pyridine				Group 2B

Based on available data, the classification criteria are not met (g) reproductive toxicity;

(h) STOT-single exposure; Based on available data, the classification criteria are not met

(i) STOT-repeated exposure; Category 2

Target Organs Thyroid.

(j) aspiration hazard; Based on available data, the classification criteria are not met

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

delayed tiredness, nausea and vomiting.

11.2. Information on other hazards

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

Section 12: Ecological information

12.1. Toxicity Ecotoxicity effects

The product contains following substances which are hazardous for the environment. However, at the concentration present, this preparation is not expected to present significant adverse environmental effects.

Component	Freshwater Fish Water Flea Freshwater Alg		
Pyridine	LC50: = 4.6 mg/L, 96h static (Oncorhynchus mykiss) LC50: = 26 mg/L, 96h semi-static (Cyprinus carpio) LC50: 63.4 - 73.6 mg/L, 96h flow-through (Pimephales promelas)		
lodine	LC50 = 1.67 mg/L 96h	EC50 = 0.55 mg/L 48h	EC50 = 0.13 mg/L 72h

Component	Microtox	M-Factor		
lodine	EC50 = 280 mg/L 3h	1		

12.2. Persistence and degradability

Persistence Persistence is unlikely.

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste

water treatment plants.

12.3. Bioaccumulative potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Pyridine	0.65	No data available
lodine	2.49	No data available

12.4. Mobility in soilThe product is water soluble, and may spread in water systems. Will likely be mobile in the

environment due to its water solubility. Highly mobile in soils

12.5. Results of PBT and vPvB

assessment

No data available for assessment.

12.6. Endocrine disrupting

properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential This product does not contain any known or suspected substance This product does not contain any known or suspected substance

Section 13: Disposal considerations

Oxidising Solution, 0.05M Revision Date 06-Jun-2024

13.1. Waste treatment methods

Waste from Residues/Unused

Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives

on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but

application specific.

Other Information Do not flush to sewer. Waste codes should be assigned by the user based on the

application for which the product was used. Can be landfilled or incinerated, when in

compliance with local regulations.

Switzerland - Waste Ordinance Disposal should be in accordance with applicable regional, national and local laws and

regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance,

ADWO) SR 814.600

https://www.fedlex.admin.ch/eli/cc/2015/891/en

Section 14: Transport information

IMDG/IMO

14.1. UN number UN1282

14.2. UN proper shipping name PYRIDINE SOLUTION

14.3. Transport hazard class(es) 3 14.4. Packing group II

<u>ADR</u>

14.1. UN number UN1282 14.2. UN proper shipping name PYRIDINE

14.3. Transport hazard class(es) 3
14.4. Packing group II

IATA

14.1. UN number UN1282

14.2. UN proper shipping name PYRIDINE SOLUTION

14.3. Transport hazard class(es) 3 14.4. Packing group II

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable, packaged goods

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Oxidising Solution, 0.05M

Revision Date 06-Jun-2024

China, X = listed, Australia, U.S.A. (TSCA), Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Australia (AICS), Korea (KECL), China (IECSC), Japan (ENCS), Philippines (PICCS), Taiwan (TCSI), Japan (ISHL), New Zealand (NZIoC), Japan (ISHL). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Pyridine	110-86-1	203-809-9	-	-	X	X	KE-29929	X	X
lodine	7553-56-2	231-442-4	-	-	Х	X	KE-21023	X	-
Water	7732-18-5	231-791-2	-	-	Х	Х	KE-35400	X	-

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Pyridine	110-86-1	Х	ACTIVE	Х	-	Х	Х	Х
lodine	7553-56-2	X	ACTIVE	Х	-	Х	Х	X
Water	7732-18-5	X	ACTIVE	Х	-	Х	Х	Х

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Pyridine	110-86-1	-	-	-
lodine	7553-56-2	-	Use restricted. See entry	-
			75.	
			(see link for restriction	
			details)	
Water	7732-18-5	-	-	-

REACH links

https://echa.europa.eu/substances-restricted-under-reach

Seveso III Directive (2012/18/EC)

	Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Г	Pyridine	110-86-1	Not applicable	Not applicable
Г	Iodine	7553-56-2	Not applicable	Not applicable
Г	Water	7732-18-5	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification Water endangering class = 2 (self classification)

_			
	Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class

Oxidising Solution, 0.05M

Revision Date 06-Jun-2024

Pyridine	WGK2	Class I: 20 mg/m³ (Massenkonzentration)
lodine	WGK2	

Component	France - INRS (Tables of occupational diseases)
Pyridine	Tableaux des maladies professionnelles (TMP) - RG 84

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure	
Iodine	Prohibited and Restricted			
7553-56-2 (1 - 2.5) Substances				

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

Section 16: Other information

Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor

H302 - Harmful if swallowed

H312 - Harmful in contact with skin

H332 - Harmful if inhaled

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H335 - May cause respiratory irritation

H372 - Causes damage to organs through prolonged or repeated exposure

H373 - May cause damage to organs through prolonged or repeated exposure

H400 - Very toxic to aquatic life

Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

ENCS - Japanese Existing and New Chemical Substances AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level RPE - Respiratory Protective Equipment

WEL - Workplace Exposure Limit

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

ADR - European Agreement Concerning the International Carriage of

Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime

Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

Substances List

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from

Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Oxidising Solution, 0.05M Revision Date 06-Jun-2024

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data
Health Hazards Calculation method
Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Creation Date 10-Nov-2023 Revision Date 10-Nov-2024

Revision Summary SDS sections updated, 2, 3, 9, 11, 12, 15.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No. 1907/2006

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet