

SAFETY DATA SHEET

Australian statement of hazardous nature: Classified as hazardous according to criteria of Safe Work Australia

Section 1 - Identification

Product Name n-Butyl acetate

CAS No 123-86-4

Synonyms Butyl acetate; Acetic acid, butyl ester; 1-Butyl acetate

Product Code TSPACR011

B/4951/08, B/4951/15, B/4951/17, B/4951/24, B/4951/25, B/4951/27, B/4951/21RSS,

B/4951/24RSS, B/4951/25RSS, B/4951/34RSS, B/4951/27RSS

Address ThermoFisher Scientific Australia Pty Ltd

5 Caribbean Drive, Scoresby VICTORIA 3179, Australia

Emergency Tel. CHEMTREC®

03 9757 4559 or +613 9757 4559

Telephone / Fax Numbers Tel: 1300 735 292

Fax: 1800 067 639

E-mail address ANZinfo@thermofisher.com

Recommended Use Laboratory chemicals.

Uses advised against This product does not contain any substance(s) on the Illicit Drug Precursors/Reagents list.

This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction. This product does not contain any substance(s) listed on the voluntary National

Code of Practice for Chemicals of Security Concern.

Section 2 - Hazard(s) Identification

Classification under Safe Work Australia

Classified as hazardous according to criteria of Safe Work Australia

Physical hazards

Flammable liquids Category 3

Health hazards

Specific target organ toxicity - (single exposure)

Category 3

Environmental hazards
No hazards identified

Label Elements

FSUB4951 Version 2 18-Nov-2022 Page 1/10





Signal Word Warning

Hazard Statements

H226 - Flammable liquid and vapor

H336 - May cause drowsiness or dizziness

AUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P233 - Keep container tightly closed

P240 - Ground and bond container and receiving equipment

P242 - Use non-sparking tools

P243 - Take action to prevent static discharges

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P312 - Call a POISON CENTER or doctor if you feel unwell

P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P501 - Dispose of contents/ container to an approved waste disposal plant

Other information

Section 3 - Composition and Information on Ingredients

Component	CAS No	Weight %
n-Butyl acetate	123-86-4	<=100

Section 4 - First Aid Measures

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

Ingestion Clean mouth with water and drink afterwards plenty of water.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

General Advice If symptoms persist, call a physician.

Self-Protection of the First Aider No special precautions required.

FSUB4951 Version 2 18-Nov-2022 Page 2/10

First Aid Facilities Eyewash, safety shower and washroom.

Most important symptoms and

effects

Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness,

nausea and vomiting

Notes to Physician Treat symptomatically. Symptoms may be delayed.

Section 5 - Fire Fighting Measures

Suitable Extinguishing Media

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

Hazardous Decomposition Products

Carbon monoxide (CO), Carbon dioxide (CO2).

Specific Hazards Arising from the Chemical

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Special protective equipment and precautions for fire fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6 - Accidental Release Measures

Emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

Should not be released into the environment. Do not flush into surface water or sanitary sewer system.

Methods for Containment and Clean Up

Clean-up methods - small spillage

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment.

Clean-up methods - large spillage

Typically only supplied is small quantiites as packaged goods.

If extremely toxic or used in larger quantities ensure a spillage action plan is in place. Evacuate area. Control the source and/or contain the spill if safe and able to do so. Use temporary diking, sand bags, dry sand, earth or proprietary booms/absorbent pads if available. Obtain advice on containment, neutralisation and clean-up from local emergency responders.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

Section 7 - Handling and Storage

Precautions for Safe Handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Avoid ingestion and inhalation. Do not get in eyes, on skin, or on clothing. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges.

FSUB4951 Version 2 18-Nov-2022 Page 3 / 10

Conditions for Safe Storage, Including any Incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

AS/NZS 2243.10:2004, Safety in laboratories - Storage of chemicals AS 1940-2004 - The storage and handling of flammable and combustible liquids

Section 8 - Exposure Controls and Personal Protection

Exposure limits

AUS - Exposure Standards for Atmospheric Contaminants in the Occupational Environment - Guidance Note on the Interpretation of Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:3008(1995)] Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)] updated in August, 2005. Safe Work Australia ACGIH - Threshold Limit Values - Ceiling (TLV-C) guidelines by the American Conference of Governmental Industrial Hygienists (ACGIH) for controlling worker exposure to airborne chemical concentrations in the workplace. UK - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. DE - MAK and BAT values of Hazardous Chemical Compounds in the Work Area. Published by German Research Foundation on July 1, 2011

Component	Australia	New Zealand WEL	ACGIH TLV	The United Kingdom	Germany
n-Butyl acetate	STEL: 200 ppm	TWA: 150 ppm	TWA: 50 ppm	STEL: 200 ppm 15 min	TWA: 62 ppm (8
	STEL: 950 mg/m ³	TWA: 713 mg/m ³	STEL: 150 ppm	STEL: 966 mg/m ³ 15	Stunden). AGW -
	TWA: 150 ppm	STEL: 200 ppm		min	exposure factor 2
	TWA: 713 mg/m ³	STEL: 950 mg/m ³		TWA: 150 ppm 8 hr	TWA: 300 mg/m ³ (8
	_	_		TWA: 724 mg/m ³ 8 hr	Stunden). AGW -
					exposure factor 2
					TWA: 100 ppm (8
					Stunden). MAK
					TWA: 480 mg/m³ (8
					Stunden). MAK
					Höhepunkt: 200 ppm
					Höhepunkt: 960 mg/m ³

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Exposure Controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Wear safety glasses with side shields (or goggles) (Australian/New Zealand Standard

AS/NZS 1337 - Eye protectors for Industrial applications)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	AUS/NZ Standard	Glove comments
Butyl rubber	< 125 minutes	0.63 mm	AS/NZS 2161	Permeation rate 83 µg/cm2/min
Nitrile rubber	< 78 minutes	0.38 mm		Permeation rate 135 µg/cm2/min As tested
				under EN374-3 Determination of
				Resistance to Permeation by Chemicals

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

FSUB4951 Version 2 18-Nov-2022 Page 4/10

SAFETY DATA SHEET

Skin and body protectionWear appropriate protective gloves and clothing to prevent skin exposure

Repiratory ProtectionUse an AS/NZS 1716 approved respirator if exposure limits are exceeded or if irritation or

other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained in line with AS/NZS 1715 on the use

and maintenance of repiratory protective devices

Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to EN14387 (or AUS/NZ

equivalent)

Recommended half mask:- Valve filtering: EN405 or Half mask: EN140 plus filter, EN 141 (or AUS/NZ equivalent)

Hygiene MeasuresHandle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls Prevent product from entering drains.

Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance Colorless
Physical State Liquid

 Odor
 sweet

 Odor Threshold
 7 - 20 ppm

 pH
 6.2 @ 20°C

 Melting Point/Range
 -90 °C / -130 °F

 Softening Point
 No data available

 Boiling Point/Range
 126 °C / 258.8 °F

 Flash Point
 27 °C / 80.6 °F

Evaporation Rate 1.0 (ether = 1) Flammability (solid,gas) Not applicable

Explosion Limits Lower 1.2

Upper 7.5
Vapor Pressure No data available

Vapor Density 4

Specific Gravity / Density 0.881 @ 20C Bulk Density Not applicable

Water Solubility Insoluble

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Componentlog Pown-Butyl acetate2.3

Autoignition Temperature 415 °C / 779 °F Decomposition Temperature No data available 0.83 mPas @ 20°C

Explosive Properties Not explosive

Oxidizing Properties Not oxidising

(no chemical groups associated with explosive properties) explosive air/vapour mixtures possible (based on the chemical structure of the substance and oxidation states of the constituent elements)

Method - No information available

Liquid

(Air = 1.0)

Liquid

Other information

Molecular FormulaC6H12O2Molecular Weight116.16Refractive index1.393

Section 10 - Stability and Reactivity

Reactivity None known, based on information available

FSUB4951 Version 2 18-Nov-2022 Page 5 / 10

SAFETY DATA SHEET

Stability Stable under normal conditions.

Conditions to Avoid Incompatible products, Excess heat, Keep away from open flames, hot surfaces and

sources of ignition.

Incompatible Materials Strong oxidizing agents, Strong acids, Strong bases.

Hazardous Decomposition Products Carbon monoxide (CO). Carbon dioxide (CO2).

Hazardous Polymerization Hazardous polymerization does not occur.

Section 11 - Toxicological Information

Information on Toxicological Effects

Product Information

(a) acute toxicity;

OralBased on available data, the classification criteria are not metDermalBased on available data, the classification criteria are not metInhalationBased on available data, the classification criteria are not met

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation		
n-Butyl acetate	LD50 = 10768 mg/kg (Rat)	LD50 > 17600 mg/kg (Rabbit)	LC50 = 0.74 mg/L (Rat) 4 h		

(b) skin corrosion/irritation; Based on available data, the classification criteria are not met

(c) serious eye damage/irritation; Based on available data, the classification criteria are not met

(d) respiratory or skin sensitization;

RespiratorySkin
Based on available data, the classification criteria are not met
Based on available data, the classification criteria are not met

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

(f) carcinogenicity; Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; Based on available data, the classification criteria are not met

(h) STOT-single exposure; Category 3

Results / Target organs Central nervous system (CNS)

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

Target Organs None known.

(j) aspiration hazard; Based on available data, the classification criteria are not met

Symptoms / effects,both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting delayed

Section 12 - Ecological Information

FSUB4951 Version 2 18-Nov-2022 Page 6 / 10

Ecotoxicity effects	Contains no substances known to be hazardous to the environment or that are not
	degradable in waste water treatment plants.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
n-Butyl acetate	Lepomis macrochirus:		EC50: = 674.7 mg/L,	EC50 = 70.0 mg/L 5 min
	LC50: 100 mg/L/96H		72h (Desmodesmus	EC50 = 82.2 mg/L 15
	Pimephales promelas:		subspicatus)	min
	LC50:17-19 mg/L/96h			EC50 = 959 mg/L 18 h
				EC50 = 98.9 mg/L 30
				min

Persistence and Degradability

Persistence

Readily biodegradable

Persistence is unlikely, based on information available.

Degradation in sewage treatment plant Bioaccumulative Potential

Contains no substances known to be hazardous to the environment or not degradable in waste water treatment plants

waste water treatment plants. Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)					
n-Butyl acetate	2.3	No data available					
Mobility	The product contains volatile organic compounds (VOC) which will evaporate easily from all						
	surfaces. Spillage unlikely to penetrate soil. Will likely be mobile in the environment due to						
	its volatility Highly mobile in soils						
Endocrine Disruptor Information	This product does not contain any known or suspected endocrine disruptors						
Persistent Organic Pollutant	This product does not contain any known or suspected substance						
Ozone Depletion Potential	This product does not contain any known or so	uspected substance					

Section 13 - Disposal Considerations

Waste from Residues/Unused

Products

Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with all federal, E.P.A., state and local regulations. Assure conformity with all applicable regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

Other Information

Chemical wastes should be disposed through a licensed commercial waste collection service. Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations.

Section 14 - Transport Information

IMDG/IMO

UN-No UN1123

Proper Shipping Name BUTYL ACETATES

Hazard Class 3
Packing Group III

<u>ADG</u>

UN-No UN1123

Proper Shipping Name BUTYL ACETATES

Hazard Class 3
Packing Group III

IATA

UN-No UN1123

Proper Shipping Name BUTYL ACETATES

FSUB4951 Version 2 18-Nov-2022 Page 7/10

Hazard Class 3
Packing Group III

Environmental hazards No hazards identified

Special Precautions No special precautions required

Additional information None known

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National Regulations Australia

See section 8 for national exposure control parameters.

Standard for the Uniform Scheduling of Medicines and Poisons

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons.

Australian Industrial Chemicals Introduction Scheme (AICIS)

Component	Australian Industrial Chemicals Introduction Scheme (AICIS)	Additional information
n-Butyl acetate - 123-86-	4 Present	-

Australian - Illicit Drug Precursors/Reagents Substance List

This product does not contain any substance(s) on the Illicit Drug Precursors/Reagents list.

Chemicals of Security Concern

This product does not contain any substance(s) listed on the voluntary National Code of Practice for Chemicals of Security Concern

National pollutant inventory Not applicable

Prohibition or notification/licensing requirements

Shown below are details of specific prohibition/notifications or licencing requirements when they apply.

This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction.

International Inventories

Component	AICS	NZIoC	EINECS	ELINCS	TSCA	DSL	NDSL	PICCS	ENCS	ISHL	IECSC	KECL
n-Butyl acetate	X	X	204-658-1	-	X	Х	-	Х	Х	Х	Χ	KE-04179

Legend: X - Listed. '-' - Not Listed. KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

International Regulations

Ozone Depletion Potential This product does not contain any known or suspected substance

FSUB4951 Version 2 18-Nov-2022 Page 8 / 10

Persistent Organic Pollutant This product does not contain any known or suspected substance

Rotterdam Convention (PIC) Not applicable

Basel convention on the control of transboundary movements of hazardous wastes and their dispoal Not applicable.

Component	CAS No	OECD HPV	Restriction of	Seveso III Directive	Seveso III Directive
			Hazardous	(2012/18/EC) -	(2012/18/EC) -
			Substances (RoHS)	Qualifying Quantities	Qualifying Quantities
				for Major Accident	for Safety Report
				Notification	Requirements
n-Butyl acetate	123-86-4	Listed	Not applicable	Not applicable	Not applicable

Authorisation/Restrictions according to EU REACH

Not applicable

Section 16 - Other Information

Legend

AICS - Australian Inventory of Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

IECSC - Chinese Inventory of Existing Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

ICAO/IATA - International Civil Aviation Organization/International Air **Transport Association**

MARPOL - International Convention for the Prevention of Pollution from Ships

NZS 5433:2012 - Transport of Dangerous Goods on Land

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50% WEL - Workplace Exposure Limit **DNEL** - Derived No Effect Level

POW - Partition coefficient Octanol:Water vPvB - very Persistent, very Bioaccumulative

VOC - (Volatile Organic Compound)

NZIoC - New Zealand Inventory of Chemicals

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japanese Existing and New Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

CAS - Chemical Abstracts Service

ACGIH - American Conference of Governmental Industrial Hygienists

Predicted No Effect Concentration (PNEC)

IMO/IMDG - International Maritime Organization/International Maritime

Dangerous Goods Code

ADG Australian Code for the Transport of Dangerous Goods by Road and Rail

OECD - Organisation for Economic Co-operation and Development

LC50 - Lethal Concentration 50%

ATE - Acute Toxicity Estimate

RPE - Respiratory Protective Equipment NOEC - No Observed Effect Concentration

BCF - Bioconcentration factor

PBT - Persistent, Bioaccumulative, Toxic

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts. Chemical incident response training.

FSUB4951 Version 2 18-Nov-2022 Page 9/10 Revision Date 18-Nov-2022 Revision Summary Not applicable.

This Safety Data Sheet (SDS) is prepared in accordance to and complies with the requirements of Safe Work Australia - Work Health and Safety Regulations (WHS Regulations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

FSUB4951 Version 2 18-Nov-2022 Page 10 / 10