

## SAFETY DATA SHEET

Creation Date 21-September-2009

Revision Date 31-January-2025

Revision Number 8

### 1. Identification

**Product Name** Vinyl acetate, stabilized

**Cat No. :** AC140840000; AC140840010; AC140840025; AC140840100; AC140840250

**CAS-No** 108-05-4  
**Synonyms** Ethenyl ethanoate; Vinyl A monomer; Ethenyl acetate

**Recommended Use** Laboratory chemicals.  
**Uses advised against** Food, drug, pesticide or biocidal product use.

#### Details of the supplier of the safety data sheet

##### Company

##### **Importer/Distributor**

Fisher Scientific  
112 Colonnade Road,  
Ottawa, ON K2E 7L6,  
Canada  
Tel: 1-800-234-7437

Acros Organics  
One Reagent Lane  
Fair Lawn, NJ 07410

##### **Manufacturer**

Fisher Scientific Company  
One Reagent Lane  
Fair Lawn, NJ 07410  
Tel: (201) 796-7100

##### **Emergency Telephone Number**

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11

Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99

**CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

### 2. Hazard(s) identification

#### Classification

##### **WHMIS 2015 Classification**

Classified as hazardous under the Hazardous Products Regulations (SOR/2015-17)

<b>Flammable liquids</b>	Category 2
<b>Acute Inhalation Toxicity</b>	Category 4
<b>Carcinogenicity</b>	Category 2
<b>Specific target organ toxicity (single exposure)</b>	Category 3
Target Organs - Respiratory system.	
<b>Physical Hazards Not Otherwise Classified</b>	Category 1
Hazardous polymerization may occur	

#### Label Elements

##### **Signal Word**

Danger

**Hazard Statements**

Highly flammable liquid and vapor  
Harmful if inhaled  
May cause respiratory irritation  
Suspected of causing cancer  
Hazardous polymerization may occur

**Precautionary Statements****Prevention**

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Wear protective gloves/protective clothing/eye protection/face protection  
Keep cool. Protect from sunlight  
Keep container tightly closed  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
Use explosion-proof electrical/ventilating/lighting/equipment  
Ground/bond container and receiving equipment  
Avoid breathing dust/fume/gas/mist/vapors/spray  
Use only outdoors or in a well-ventilated area  
Use only non-sparking tools  
Take action to prevent static discharges

**Response**

IF exposed or concerned: Get medical advice/attention  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower  
IF INHALED: Remove person to fresh air and keep comfortable for breathing  
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

**Storage**

Store locked up  
Store in a well-ventilated place. Keep container tightly closed

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Other Hazards**

Light sensitive  
Contains a known or suspected endocrine disruptor

### 3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Vinyl acetate	108-05-4	> 99
1,4-Benzenediol	123-31-9	< 0.01

### 4. First-aid measures

**General Advice**

If symptoms persist, call a physician.

**Eye Contact**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

<b>Skin Contact</b>	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
<b>Inhalation</b>	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.
<b>Ingestion</b>	Clean mouth with water and drink afterwards plenty of water.
<b>Most important symptoms/effects</b>	Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
<b>Notes to Physician</b>	Treat symptomatically

## 5. Fire-fighting measures

<b>Suitable Extinguishing Media</b>	Carbon dioxide (CO <sub>2</sub> ). Dry chemical. Water mist may be used to cool closed containers. Water mist may be used to cool closed containers.
<b>Unsuitable Extinguishing Media</b>	No information available
<b>Flash Point</b>	-8 °C / 17.6 °F
<b>Method -</b>	No information available
<b>Autoignition Temperature</b>	385 °C / 725 °F
<b>Explosion Limits</b>	
<b>Upper</b>	14.0%
<b>Lower</b>	2.6%
<b>Sensitivity to Mechanical Impact</b>	No information available
<b>Sensitivity to Static Discharge</b>	No information available

### Specific Hazards Arising from the Chemical

Flammable. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air.

### Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

### Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

### NFPA

<b>Health</b>	<b>Flammability</b>	<b>Instability</b>	<b>Physical hazards</b>
2	3	2	N/A

## 6. Accidental release measures

<b>Personal Precautions</b>	Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.
<b>Environmental Precautions</b>	Should not be released into the environment. See Section 12 for additional Ecological Information. Do not flush into surface water or sanitary sewer system.
<b>Methods for Containment and Clean Up</b>	Keep in suitable, closed containers for disposal. Soak up with inert absorbent material. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

## 7. Handling and storage

<b>Handling</b>	Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition
-----------------	--

of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

**Storage.**

Keep in a dry place. Keep container tightly closed. Keep away from heat, sparks and flame. Protect from direct sunlight. Refrigerator/flammables. May form explosive peroxides on prolonged storage. Keep container tightly closed in a dry and well-ventilated place. Incompatible Materials. Acids. Bases. oxygen. Peroxides. Acid anhydrides. Metals.

## 8. Exposure controls / personal protection

**Exposure Guidelines**

Component	Alberta	British Columbia	Ontario TWAEV	Quebec	ACGIH TLV	OSHA PEL	NIOSH
Vinyl acetate	TWA: 10 ppm TWA: 35 mg/m <sup>3</sup> STEL: 15 ppm STEL: 53 mg/m <sup>3</sup>	TWA: 10 ppm STEL: 15 ppm	TWA: 10 ppm STEL: 15 ppm	TWA: 10 ppm TWA: 35 mg/m <sup>3</sup> STEL: 15 ppm STEL: 53 mg/m <sup>3</sup>	TWA: 10 ppm STEL: 15 ppm	(Vacated) TWA: 10 ppm (Vacated) TWA: 30 mg/m <sup>3</sup> (Vacated) STEL: 20 ppm (Vacated) STEL: 60 mg/m <sup>3</sup>	Ceiling: 4 ppm Ceiling: 15 mg/m <sup>3</sup>
1,4-Benzenediol	TWA: 2 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>	(Vacated) TWA: 2 mg/m <sup>3</sup> TWA: 2 mg/m <sup>3</sup>	IDLH: 50 mg/m <sup>3</sup> Ceiling: 2 mg/m <sup>3</sup>

**Legend**

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

**Engineering Measures**

Use explosion-proof electrical/ventilating/lighting/equipment. Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

**Personal protective equipment****Eye Protection**

Goggles

**Hand Protection**

Protective gloves

Glove material	Breakthrough time	Glove thickness	Glove comments
Butyl rubber	< 160 minutes	0.635 mm	Permeation rate 6 µg/cm <sup>2</sup> /min As tested under EN374-3 Determination of Resistance to Permeation by Chemicals

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

**Respiratory Protection**

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

**Recommended Filter type:** Organic gases and vapours filter Type A Brown conforming to EN14387

When RPE is used a face piece Fit Test should be conducted

**Environmental exposure controls**

Prevent product from entering drains.

**Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

## 9. Physical and chemical properties

<b>Physical State</b>	Liquid
<b>Appearance</b>	Clear
<b>Odor</b>	sweet
<b>Odor Threshold</b>	No information available
<b>pH</b>	7
<b>Melting Point/Range</b>	-93 °C / -135.4 °F
<b>Boiling Point/Range</b>	72 - 73 °C / 161.6 - 163.4 °F
<b>Flash Point</b>	-8 °C / 17.6 °F
<b>Evaporation Rate</b>	No information available
<b>Flammability (solid,gas)</b>	Not applicable
<b>Flammability or explosive limits</b>	
Upper	14.0%
Lower	2.6%
<b>Vapor Pressure</b>	No information available
<b>Vapor Density</b>	No information available
<b>Specific Gravity</b>	0.930
<b>Solubility</b>	23 g/L @ 20 °C
<b>Partition coefficient; n-octanol/water</b>	No data available
<b>Autoignition Temperature</b>	385 °C / 725 °F
<b>Decomposition Temperature</b>	No information available
<b>Viscosity</b>	No information available
<b>Molecular Formula</b>	C4 H6 O2
<b>Molecular Weight</b>	86.09

## 10. Stability and reactivity

<b>Reactive Hazard</b>	None known, based on information available
<b>Stability</b>	May form explosive peroxides. Stable under normal conditions. Light sensitive.
<b>Conditions to Avoid</b>	Keep away from open flames, hot surfaces and sources of ignition. Excess heat. Exposure to light. Incompatible products.
<b>Incompatible Materials</b>	Acids, Bases, oxygen, Peroxides, Acid anhydrides, Metals
<b>Hazardous Decomposition Products</b>	Carbon monoxide (CO), Carbon dioxide (CO <sub>2</sub> )
<b>Hazardous Polymerization</b>	Hazardous polymerization may occur.
<b>Hazardous Reactions</b>	None under normal processing.

## 11. Toxicological information

**Acute Toxicity****Product Information****Component Information**

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Vinyl acetate	LD50 = 2900 mg/kg ( Rat )	LD50 = 2335 mg/kg ( Rabbit )	LC50 = 3680 ppm ( Rat ) 4 h

1,4-Benzenediol	LD50 = 298 mg/kg ( Rat )	LD50 = 74800 mg/kg ( Rabbit )	Not listed
-----------------	--------------------------	-------------------------------	------------

**Toxicologically Synergistic Products** No information available

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Irritation** No information available

**Sensitization** No information available

**Carcinogenicity** Possible cancer hazard. May cause cancer based on animal data. The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Vinyl acetate	108-05-4	Group 2B	Not listed	A3	X	A3
1,4-Benzenediol	123-31-9	Not listed	Not listed	A3	Not listed	A3

*IARC (International Agency for Research on Cancer)*

*IARC (International Agency for Research on Cancer)*

*Group 1 - Carcinogenic to Humans*

*Group 2A - Probably Carcinogenic to Humans*

*Group 2B - Possibly Carcinogenic to Humans*

*A1 - Known Human Carcinogen*

*A2 - Suspected Human Carcinogen*

*A3 - Animal Carcinogen*

*ACGIH: (American Conference of Governmental Industrial Hygienists)*

*ACGIH: (American Conference of Governmental Industrial Hygienists)*

*Mexico - Occupational Exposure Limits - Carcinogens*

*Mexico - Occupational Exposure Limits - Carcinogens*

*A2 - Suspected Human Carcinogen*

*A3 - Confirmed Animal Carcinogen*

*A1 - Confirmed Human Carcinogen*

*A4 - Not Classifiable as a Human Carcinogen*

*A5 - Not Suspected as a Human Carcinogen*

**Mutagenic Effects** Not mutagenic in AMES Test

**Reproductive Effects** No information available.

**Developmental Effects** No information available.

**Teratogenicity** No information available.

**STOT - single exposure** Respiratory system

**STOT - repeated exposure** None known

**Aspiration hazard** No information available

**Symptoms / effects, both acute and delayed** Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

**Endocrine Disruptor Information**

Component	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances	Japan - Endocrine Disruptor Information
Vinyl acetate	Group III Chemical	Not applicable	Not applicable

**Other Adverse Effects** The toxicological properties have not been fully investigated.

## 12. Ecological information

**Ecotoxicity**

This product contains the following substance(s) which are hazardous for the environment. Contains a substance which is: Harmful to aquatic organisms. The product contains following substances which are hazardous for the environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Vinyl acetate	Not listed	LC50: = 14 mg/L, 96h static (Pimephales promelas)	EC50 = 2080 mg/L 5 min	Not listed

		LC50: 26.1 - 36.63 mg/L, 96h static (Poecilia reticulata) LC50: 15.04 - 21.54 mg/L, 96h static (Lepomis macrochirus)		
1,4-Benzenediol	EC50: = 0.335 mg/L, 72h (Pseudokirchneriella subcapitata)	LC50: 0.1 - 0.18 mg/L, 96h static (Pimephales promelas) LC50: = 0.17 mg/L, 96h (Brachydanio rerio) LC50: = 0.044 mg/L, 96h flow-through (Pimephales promelas) LC50: = 0.044 mg/L, 96h flow-through (Oncorhynchus mykiss)	EC50 = 0.038 mg/L 15 min EC50 = 0.0382 mg/L 30 min EC50 = 0.042 mg/L 5 min EC50 = 23.75 mg/L 60 min	EC50: = 0.29 mg/L, 48h (Daphnia magna)

**Persistence and Degradability** Persistence is unlikely based on information available.

**Bioaccumulation/ Accumulation** No information available.

**Mobility** Will likely be mobile in the environment due to its volatility.

Component	log Pow
Vinyl acetate	0.73
1,4-Benzenediol	0.59

### 13. Disposal considerations

**Waste Disposal Methods** Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

### 14. Transport information

#### DOT

UN-No UN1301  
 Proper Shipping Name VINYL ACETATE, STABILIZED  
 Hazard Class 3  
 Packing Group II

#### TDG

UN-No UN1301  
 Proper Shipping Name VINYL ACETATE, STABILIZED  
 Hazard Class 3  
 Packing Group II

#### IATA

UN-No UN1301  
 Proper Shipping Name VINYL ACETATE, STABILIZED  
 Hazard Class 3  
 Packing Group II

#### IMDG/IMO

UN-No UN1301  
 Proper Shipping Name VINYL ACETATE, STABILIZED  
 Hazard Class 3  
 Packing Group II

### 15. Regulatory information

#### International Inventories

Component	CAS-No	DSL	NDSL	TSCA	TSCA Inventory notification -	EINECS	ELINCS	NLP
-----------	--------	-----	------	------	-------------------------------	--------	--------	-----

					Active-Inactive			
Vinyl acetate	108-05-4	X	-	X	ACTIVE	203-545-4	-	-
1,4-Benzenediol	123-31-9	X	-	X	ACTIVE	204-617-8	-	-

Component	CAS-No	IECSC	KECL	ENCS	ISHL	TCSI	AICS	NZIoC	PICCS
Vinyl acetate	108-05-4	X	KE-35324	X	X	X	X	X	X
1,4-Benzenediol	123-31-9	X	KE-35112	X	X	X	X	X	X

**Legend:**

X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

**Canada**

SDS in compliance with provisions of information as set out in Canadian Standard - Part 4, Schedule 1 and 2 of the Hazardous Products Regulations (HPR) and meets the requirements of the HPR (Paragraph 13(1)(a) of the Hazardous Products Act (HPA)).

Component	Canada - National Pollutant Release Inventory (NPRI)	Canadian Environmental Protection Agency (CEPA) - List of Toxic Substances	Canada's Chemicals Management Plan (CEPA)
Vinyl acetate	Part 1, Group A Substance Part 5, Individual Substances Part 4 Substance		Subject to Monitoring and Surveillance Activities
1,4-Benzenediol	Part 1, Group A Substance Part 4 Substance	Schedule I	Subject to Monitoring and Surveillance Activities

**Legend**

NPRI - National Pollutant Release Inventory

**Other International Regulations****Authorisation/Restrictions according to EU REACH**

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Vinyl acetate	-	Use restricted. See entry 75. (see link for restriction details)	-
1,4-Benzenediol	-	Use restricted. See entry 75. (see link for restriction details)	-

**REACH links**<https://echa.europa.eu/substances-restricted-under-reach>**Safety, health and environmental regulations/legislation specific for the substance or mixture**

Component	CAS-No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Vinyl acetate	108-05-4	Listed	Not applicable	Not applicable	Not applicable
1,4-Benzenediol	123-31-9	Listed	Not applicable	Not applicable	Not applicable

Component	CAS-No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)



		Notification	Requirements		
Vinyl acetate	108-05-4	Not applicable	Not applicable	Not applicable	Not applicable
1,4-Benzenediol	123-31-9	Not applicable	Not applicable	Not applicable	Annex I - Y39

## 16. Other information

**Prepared By**

Regulatory Affairs  
Thermo Fisher Scientific  
Email: EMSDS.RA@thermofisher.com

**Creation Date**

21-September-2009

**Revision Date**

31-January-2025

**Print Date**

31-January-2025

**Revision Summary**

This document has been updated to comply with the requirements of WHMIS 2015 to align with the Globally Harmonised System (GHS) for the Classification and Labelling of Chemicals.

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**