

# SAFETY DATA SHEET

Revision Date 01-Apr-2024 **Revision Number 4** 

# 1. Identification

**Product Name** tert-Butyllithium, nominally 1.5M in n-pentane

41251 Cat No.:

Synonyms No information available

**Recommended Use** Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

### Details of the supplier of the safety data sheet

### Company

Thermo Fisher Scientific Chemicals, Inc. 30 Bond Street Ward Hill, MA 01835-8099

Tel: 800-343-0660 Fax: 800-322-4757

# **Emergency Telephone Number**

For information **US** call: 001-800-227-6701 / Europe call: +32 14 57 52 11 Emergency Number US:001-201-796-7100 / Europe: +32 14 57 52 99 CHEMTREC Tel. No. US:001-800-424-9300 / Europe:001-703-527-3887

# Hazard(s) identification

### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Category 1 Substances/mixtures which, in contact with water, emit Category 1

flammable gases

Pyrophoric liquids Category 1 Skin Corrosion/Irritation Category 1 B Serious Eye Damage/Eye Irritation Category 1 Specific target organ toxicity (single exposure) Category 3

Target Organs - Respiratory system, Central nervous system (CNS).

Aspiration Toxicity Category 1

# Label Elements

# Signal Word

Danger

#### **Hazard Statements**

Extremely flammable liquid and vapor

In contact with water releases flammable gases which may ignite spontaneously

Catches fire spontaneously if exposed to air

May be fatal if swallowed and enters airways

Causes severe skin burns and eye damage

May cause respiratory irritation

May cause drowsiness or dizziness



### **Precautionary Statements**

### Prevention

Do not breathe dust/fume/gas/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Do not allow contact with air

Keep away from any possible contact with water, because of violent reaction and possible flash fire

Handle under inert gas. Protect from moisture

Keep cool

### Response

Immediately call a POISON CENTER or doctor/physician

### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

#### Skir

Wash contaminated clothing before reuse

IF ON SKIN: Immerse in cool water/wrap with wet bandages

Brush off loose particles from skin. Immerse in cool water/wrap with wet bandages

# Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing **Ingestion** 

Do NOT induce vomiting

Rinse mouth

#### Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

### Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Store contents under inert gas

Store in a dry place. Store in a closed container

### Disposal

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

Toxic to aquatic life with long lasting effects

Reacts violently with water

# 3. Composition/Information on Ingredients

Component	CAS No	Weight %	
Pentane	109-66-0	84.65	
Lithium, (1,1-dimethylethyl)-	594-19-4	15.35	

# 4. First-aid measures

General Advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

**Eye Contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. Remove and wash

contaminated clothing and gloves, including the inside, before re-use. Call a physician

immediately.

**Inhalation** If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use

mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately. Risk of serious damage to the lungs (by

aspiration).

**Ingestion** Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an

unconscious person. Call a physician immediately. Call a physician or poison control center

immediately. If vomiting occurs naturally, have victim lean forward.

Most important symptoms and

effects

Causes burns by all exposure routes. Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting: Product is a corrosive material. Use of gastric lavage or emesis is

contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of

perforation

Notes to Physician Treat symptomatically

# 5. Fire-fighting measures

Suitable Extinguishing Media Dry sand. Carbon dioxide (CO<sub>2</sub>). Powder. Do not use water or foam. CO<sub>2</sub>, dry chemical,

dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

Unsuitable Extinguishing Media No information available

**Flash Point** -49 °C / -56.2 °F

Method - No information available

**Autoignition Temperature** 

**Explosion Limits** 

No information available

Upper No data available
Lower No data available
Sensitivity to Mechanical Impact No information available
Sensitivity to Static Discharge No information available

### Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Reacts violently with water. Extremely flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

### **Hazardous Combustion Products**

Carbon monoxide (CO). Carbon dioxide (CO2). Lithium oxide. Isobutane.

### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health **Flammability** Instability **Physical hazards** W 3 2

# 6. Accidental release measures

**Personal Precautions** 

Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

**Environmental Precautions** 

Do not flush into surface water or sanitary sewer system. Should not be released into the environment. Do not allow material to contaminate ground water system.

Up

Methods for Containment and Clean Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Do not expose spill to water. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

# 7. Handling and storage

Handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water. Keep away from open flames, hot surfaces and sources of ignition. Use spark-proof tools and explosion-proof equipment. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Storage.

Corrosives area. Keep away from water or moist air. Keep containers tightly closed in a dry. cool and well-ventilated place. Keep away from heat, sparks and flame. Incompatible Materials. Acids. Alcohols. Oxidizing agent.

# 8. Exposure controls / personal protection

### **Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH	Mexico OEL (TWA)
Pentane	TWA: 1000 ppm	(Vacated) TWA: 600 ppm	IDLH: 1500 ppm	TWA: 600 ppm
		(Vacated) TWA: 1800 mg/m <sup>3</sup>	TWA: 120 ppm	
		(Vacated) STEL: 750 ppm	TWA: 350 mg/m <sup>3</sup>	
		(Vacated) STEL: 2250	Ceiling: 610 ppm	
		mg/m³	Ceiling: 1800 mg/m <sup>3</sup>	
		TWA: 1000 ppm		
		TWA: 2950 mg/m <sup>3</sup>		

### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

**Engineering Measures** 

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment.

**Personal Protective Equipment** 

**Eve/face Protection**Wear appropriate protective eveglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

**Skin and body protection**Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

**Recommended Filter type:** Organic gases and vapours filter.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

# 9. Physical and chemical properties

Physical State Liquid

Appearance Colorless - Light yellow
Odor No information available
No information available

Odor ThresholdNo information availablepHNo information availableMelting Point/RangeNo data available

Melting Point/RangeNo data availableBoiling Point/RangeNo information availableFlash Point-49 °C / -56.2 °FEvaporation RateNo information available

Flammability (solid,gas) Not applicable

Flammability or explosive limits

Upper<br/>LowerNo data available<br/>No data availableVapor Pressure23 hPa @ 20 °C

Vapor Density No information available

Specific Gravity 0.652 g/cm3

SolubilityNo information availablePartition coefficient; n-octanol/waterNo data availableAutoignition TemperatureNo information available

Decomposition Temperature

No information available
Viscosity

No information available

Molecular Formula C4 H9 Li
Molecular Weight 64.06

# 10. Stability and reactivity

Reactive Hazard Yes

Stability Air sensitive. Moisture sensitive. May form precipitate.

Conditions to Avoid Exposure to moist air or water. Exposure to moisture. Keep away from open flames, hot

surfaces and sources of ignition.

Incompatible Materials Acids, Alcohols, Oxidizing agent

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2), Lithium oxide, Isobutane

**Hazardous Polymerization** Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing. Reacts violently with water.

# 11. Toxicological information

**Acute Toxicity** 

**Product Information** 

Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg. Oral LD50 **Dermal LD50** Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg. Based on ATE data, the classification criteria are not met. ATE > 20 mg/l. Vapor LC50

**Component Information** 

Component	Component LD50 Oral		LC50 Inhalation		
Pentane	Pentane LD50 > 2000 mg/kg ( Rat )		LC50 = 364 g/m <sup>3</sup> (Rat) 4 h		

**Toxicologically Synergistic** 

No information available

**Products** 

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation No information available No information available Sensitization

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Pentane	109-66-0	Not listed				
Lithium, (1,1-dimethylethyl)-	594-19-4	Not listed				

**Mutagenic Effects** No information available

No information available. **Reproductive Effects** 

No information available. **Developmental Effects** 

**Teratogenicity** No information available.

STOT - single exposure Respiratory system Central nervous system (CNS)

STOT - repeated exposure None known

No information available **Aspiration hazard** 

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

delayed

tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and

danger of perforation

**Endocrine Disruptor Information** No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

# 12. Ecological information

### **Ecotoxicity**

The product contains following substances which are hazardous for the environment. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. May cause long-term adverse effects in the environment. Do not allow material to contaminate ground water system.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Pentane	Not listed	LC50: = 9.99 mg/L, 96h	Not listed	EC50: = 9.74 mg/L, 48h
		(Lepomis macrochirus)		(Daphnia magna)
		LC50: = 11.59 mg/L, 96h		
		(Pimephales promelas)		
		LC50: = 9.87 mg/L, 96h		
		(Oncorhynchus mykiss)		

Persistence and Degradability May persist based on information available.

**Bioaccumulation/ Accumulation** No information available.

**Mobility** Is not likely mobile in the environment due its low water solubility.

Component	log Pow
Pentane	3.45

# 13. Disposal considerations

**Waste Disposal Methods** 

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

# 14. Transport information

DOT

UN-No UN3394

Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE

Technical Name (tert-Butyllithium)

Hazard Class 4.2 Subsidiary Hazard Class 4.3 Packing Group

TDG

UN-No UN3394

Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE

Hazard Class 4.2 Subsidiary Hazard Class 4.3 Packing Group

<u>IATA</u>

**UN-No** UN3394

Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE

Hazard Class 4.2 Subsidiary Hazard Class 4.3 Packing Group

IMDG/IMO

UN-No UN3394

Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE

Hazard Class 4.2 Subsidiary Hazard Class 4.3 Packing Group I

# 15. Regulatory information

### **United States of America Inventory**

Component	CAS No	S No TSCA TSCA Inventory not Active-Inacti		TSCA - EPA Regulatory Flags
Pentane	109-66-0	X	ACTIVE	-
Lithium. (1.1-dimethylethyl)-	594-19-4	X	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA - Per 40 CFR 751, Regulation of Certain Chemical Substances & Mixtures, Under TSCA Section 6(h) (PBT)

Not applicable

TSCA 12(b) - Notices of Export

Not applicable

### International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Pentane	109-66-0	Х	-	203-692-4	Χ	Χ	Χ	Χ	Х	KE-27968
Lithium, (1,1-dimethylethyl)-	594-19-4	-	Х	209-831-5	Χ	Х	Χ	Х	Х	2014-3-6117

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

# U.S. Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

### SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act) Not applicable

Clean Air Act Not applicable

**OSHA** - Occupational Safety and

Health Administration

Not applicable

### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

**California Proposition 65** 

This product does not contain any Proposition 65 chemicals.

# U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island	
Pentane	Pentane X		X X		X	
•						

### **U.S. Department of Transportation**

Reportable Quantity (RQ): N
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

### U.S. Department of Homeland

This product contains the following DHS chemicals:

Security

Legend - STQs = Screening Threshold Quantities, APA = A placarded amount

Component	DHS Chemical Facility Anti-Terrorism Standard		
Pentane	Release STQs - 10000lb		

Other International Regulations

Mexico - Grade No information available

Authorisation/Restrictions according to EU REACH Not applicable

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization		REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Pentane	109-66-0	-	-	-
Lithium, (1,1-dimethylethyl)-	594-19-4	-	-	-

# Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	CAS No OECD HPV Persistent Org Pollutant		Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Pentane	109-66-0	Listed	Not applicable	Not applicable	Not applicable
Lithium, (1,1-dimethylethyl)-	um, (1,1-dimethylethyl)- 594-19-4		Not applicable	Not applicable	Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

### Other International Regulations

	Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident	(2012/18/EC) -	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
			Notification	Requirements		
Γ	Pentane	109-66-0	Not applicable	Not applicable	Not applicable	Not applicable
Γ	Lithium, (1,1-dimethylethyl)-	594-19-4	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information	

Health, Safety and Environmental Department Email: chem.techinfo@thermofisher.com

www.thermofisher.com

**Revision Date** 01-Apr-2024 **Print Date** 01-Apr-2024

**Revision Summary** New emergency telephone response service provider.

### **Disclaimer**

**Prepared By** 

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**