

according to Regulation (EC) No. 1907/2006

Creation Date 14-Sep-2009 Revision Date 12-Oct-2023 Revision Number 4

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: <u>n-Heptane</u>
Cat No.: <u>H360-1; H360-4</u>

Synonyms Normal heptane.; Heptane

 Index No
 601-008-00-2

 CAS No
 142-82-5

 EC No
 205-563-8

 Molecular Formula
 C7 H16

REACH registration number -

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended UseLaboratory chemicals.

Sector of use SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

Product category PC21 - Laboratory chemicals

Process categories PROC15 - Use as a laboratory reagent

Environmental release category ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)

Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

EU entity/business name

Thermo Fisher Scientific

Janssen Pharmaceuticalaan 3a, 2440 Geel,

Belaium

UK entity/business name

Fisher Scientific UK Bishop Meadow Road,

Loughborough, Leicestershire LE11 5RG,

United Kingdom

Swiss distributor - Fisher Scientific AG Neuhofstrasse 11, CH 4153 Reinach

Tel: +41 (0) 56 618 41 11

e-mail - infoch@thermofisher.com

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:

Tox Info Suisse Emergency Number: 145 (24hr)

Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)

Chemtrec (24h) Toll-Free: 0800 564 402 Chemtrec Local: +41-43 508 20 11 (Zurich)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Flammable liquids Category 2 (H225)

Health hazards

Aspiration Toxicity
Skin Corrosion/Irritation
Specific target organ toxicity - (single exposure)
Category 2 (H315)
Category 3 (H336)

Environmental hazards

Acute aquatic toxicity
Chronic aquatic toxicity
Category 1 (H400)
Category 1 (H410)

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H336 - May cause drowsiness or dizziness

H410 - Very toxic to aquatic life with long lasting effects

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

P331 - Do NOT induce vomiting

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water

P273 - Avoid release to the environment

2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
n-Heptane	142-82-5	EEC No. 205-563-8	>95	Flam. Liq. 2 (H225) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 (H336) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
n-Heptane	-	1	-

REACH registration number	-

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Get medical attention.

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting

occurs naturally, have victim lean forward.

Inhalation Remove to fresh air. Do not use mouth-to-mouth method if victim ingested or inhaled the

substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention. Risk of serious

damage to the lungs (by aspiration). If not breathing, give artificial respiration.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Do not allow run-off from fire-fighting to enter drains or water courses.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO2).

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and material for containment and cleaning up

Remove all sources of ignition. Soak up with inert absorbent material. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. Keep in suitable, closed containers for disposal.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Use only under a chemical fume hood. Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Do not breathe mist/vapors/spray. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. Wash hands before breaks and immediately after handling the product. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do

n-Heptane Revision Date 12-Oct-2023

not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

Technical Rules for Hazardous Substances (TRGS) 510 Storage Class (LGK) (Germany)

Class 3

Switzerland - Storage of hazardous substances

Storage class - SC 3

https://www.kvu.ch/de/themen/stoffe-und-produkte https://www.kvu.ch/fr/themes/substances-et-produits https://www.kvu.ch/it/temi/sostanze-e-prodotti

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
n-Heptane	TWA: 500 ppm (8h)	STEL: 1500 ppm 15 min	TWA / VME: 400 ppm (8	TWA: 400 ppm 8 uren	TWA / VLA-ED: 500
•	TWA: 2085 mg/m ³ (8h)	STEL: 6255 mg/m ³ 15	heures). restrictive limit	TWA: 1664 mg/m ³ 8	ppm (8 horas)
		min	TWA / VME: 1668	uren	TWA / VLA-ED: 2085
		TWA: 500 ppm 8 hr	mg/m³ (8 heures).	STEL: 500 ppm 15	mg/m³ (8 horas)
		TWA: 2085 mg/m ³ 8 hr	restrictive limit TWA /	minuten	
			VME: 1000 mg/m ³ (8	STEL: 2085 mg/m ³ 15	
			heures).	minuten	
			STEL / VLCT: 500 ppm.		
			restrictive limit		
			STEL / VLCT: 2085		
			mg/m ³ . restrictive limit		
			STEL / VLCT: 1500		
			mg/m³.		Į.

Component	Italy	Germany	Portugal	The Netherlands	Finland
n-Heptane	TWA: 500 ppm 8 ore.	TWA: 500 ppm (8	STEL: 500 ppm 15	STEL: 1600 mg/m ³ 15	TWA: 300 ppm 8
	Time Weighted Average	Stunden). AGW -	minutos	minuten	tunteina
	TWA: 2085 mg/m ³ 8	exposure factor 1	TWA: 500 ppm 8 horas	TWA: 1200 mg/m ³ 8	TWA: 1200 mg/m ³ 8
	ore. Time Weighted	TWA: 2100 mg/m ³ (8	TWA: 2085 mg/m ³ 8	uren	tunteina
	Average	Stunden). AGW -	horas		STEL: 500 ppm 15
		exposure factor 1			minuutteina
		TWA: 500 ppm (8			STEL: 2100 mg/m ³ 15
		Stunden). MAK			minuutteina
		TWA: 2100 mg/m ³ (8			
		Stunden). MAK			
		Höhepunkt: 500 ppm			
	1	Höhepunkt: 2100 mg/m ³			

L	Component	Austria	Denmark	Switzerland	Poland	Norway
Γ	n-Heptane	MAK-KZGW: 2000 ppm	TWA: 200 ppm 8 timer	STEL: 400 ppm 15	STEL: 2000 mg/m ³ 15	TWA: 200 ppm 8 timer
	•	15 Minuten	TWA: 820 mg/m ³ 8 timer	Minuten	minutach	TWA: 800 mg/m ³ 8 timer

n-Heptane Revision Date 12-Oct-2023

	MAK-KZGW: 8000	STEL: 400 ppm 15	STEL: 1600 mg/m ³ 15	TWA: 1200 mg/m ³ 8	TWA: 40 ppm 8 timer
	mg/m ³ 15 Minuten	minutter	Minuten	godzinach	TWA: 275 mg/m ³ 8 timer
MA	AK-TMW: 500 ppm 8	STEL: 1640 mg/m ³ 15	TWA: 400 ppm 8		STEL: 250 ppm 15
	Stunden	minutter	Stunden		minutter. value
MA MA	\K-TMW: 2000 mg/m ³		TWA: 1600 mg/m ³ 8		calculated
	8 Stunden		Stunden		STEL: 1000 mg/m ³ 15
					minutter. value
					calculated
		_		-	

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
n-Heptane	TWA: 1600 mg/m ³	kože	TWA: 500 ppm 8 hr.	TWA: 500 ppm	TWA: 1000 mg/m ³ 8
	_	TWA-GVI: 500 ppm 8	TWA: 2085 mg/m ³ 8 hr.	TWA: 2085 mg/m ³	hodinách.
		satima.	STEL: 1500 ppm 15 min	_	Ceiling: 2000 mg/m ³
		TWA-GVI: 2085 mg/m ³	STEL: 6255 mg/m ³ 15		
		8 satima.	min		

Compone	nt	Estonia	Gibraltar	Greece	Hungary	Iceland
n-Heptan	е	TWA: 500 ppm 8 tundides. TWA: 2085 mg/m³ 8 tundides.	TWA: 500 ppm 8 hr TWA: 2085 mg/m ³ 8 hr	STEL: 500 ppm STEL: 2000 mg/m³ TWA: 500 ppm TWA: 2000 mg/m³	TWA: 2000 mg/m³ 8 órában. AK	TWA: 200 ppm 8 klukkustundum. TWA: 820 mg/m³ 8 klukkustundum. Ceiling: 400 ppm
						Ceiling: 1640 mg/m ³

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
n-Heptane	STEL: 500 ppm	TWA: 500 ppm IPRD	TWA: 500 ppm 8	TWA: 500 ppm	TWA: 500 ppm 8 ore
	STEL: 2085 mg/m ³	TWA: 2085 mg/m ³	Stunden	TWA: 2085 mg/m ³	TWA: 2085 mg/m ³ 8 ore
	TWA: 85 ppm	IPRD	TWA: 2085 mg/m ³ 8	_	
	TWA: 350 mg/m ³	STEL: 750 ppm	Stunden		
	•	STEL: 3128 mg/m ³			

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
n-Heptane		TWA: 500 ppm	TWA: 500 ppm 8 urah	Indicative STEL: 300	TWA: 500 ppm 8 saat
		TWA: 2085 mg/m ³	applies to all isomers	ppm 15 minuter	TWA: 2085 mg/m ³ 8
		_	TWA: 2085 mg/m ³ 8	Indicative STEL: 1200	saat
			urah applies to all	mg/m³ 15 minuter	
			isomers	TLV: 200 ppm 8 timmar.	
			STEL: 500 ppm 15	NGV	
			minutah applies to all	TLV: 800 mg/m ³ 8	
			isomers	timmar. NGV	
			STEL: 2085 mg/m ³ 15		
			minutah applies to all		
			isomers		

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Component	European Union	United Kingdom	France	Spain	Germany
n-Heptane					Heptan-2,5-dione: 250
·					μg/L urine (end of shift)

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
n-Heptane 142-82-5 (>95)				DNEL = 300mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
n-Heptane 142-82-5 (>95)				DNEL = 2085mg/m ³

Predicted No Effect Concentration (PNEC)

No information available.

8.2. Exposure controls

Engineering Measures

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Wear safety glasses with side shields (or goggles) (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber	> 480 minutes	0.38 mm	Level 6	(minimum requirement)
Neoprene gloves	> 480 minutes	0.45 mm	EN 374	
Viton (R)	> 480 minutes	0.3 mm		

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the

Respiratory Protection	No protective equipment is needed under normal use conditions.
3 / I	er susceptibility, e.g. sensitisation effects, also take into consideration the specific local used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.
supplier of the gloves. (Refer to manu	facturer/supplier for information) gloves are suitable for the task: Chemical compatability,

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits Large scale/emergency use

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to

EN14387

Maintain adequate ventilation Use a NIOSH/MSHA or European Standard EN 149:2001 Small scale/Laboratory use

approved respirator if exposure limits are exceeded or if irritation or other symptoms are

experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

Environmental exposure controls Prevent product from entering drains. Do not allow material to contaminate ground water

system. Local authorities should be advised if significant spillages cannot be contained.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State Liquid

Appearance Colorless

Odor Petroleum distillates
Odor Threshold No data available
Melting Point/Range -91 °C / -131.8 °F
Softening Point No data available
Boiling Point/Range 98 °C / 208.4 °F

Flammability (liquid) Highly flammable On basis of test data

Flammability (solid,gas) Not applicable Liquid

Explosion Limits Lower 1 vol%

Upper 7 vol%

Flash Point -4 °C / 24.8 °F Method - No information available

Autoignition Temperature215 °C / 419 °FDecomposition TemperatureNo data availablepHNo information availableViscosity0.4 mPa s at 20 °C

Water Solubility Insoluble

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Componentlog Pown-Heptane4.66

Vapor Pressure 48 mbar @ 20 °C

Density / Specific Gravity 0.683

Bulk DensityNot applicableLiquidVapor Density3.5(Air = 1.0)

Particle characteristics Not applicable (liquid)

9.2. Other information

Molecular Formula C7 H16 Molecular Weight 100.20

Explosive Properties Vapors may form explosive mixtures with air

Evaporation Rate 2.8 (Butyl Acetate = 1.0)

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

10.4. Conditions to avoid

Incompatible products. Heat, flames and sparks. Keep away from open flames, hot

surfaces and sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral Based on available data, the classification criteria are not met
Dermal Based on available data, the classification criteria are not met
Inhalation Based on available data, the classification criteria are not met

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation	
n-Heptane	>2000 mg/kg (rat)	LD50 = 3000 mg/kg (Rabbit)	LC50 > 73.5 mg/L (Rat) 4 h	

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; Based on available data, the classification criteria are not met

(d) respiratory or skin sensitization;

RespiratoryBased on available data, the classification criteria are not met
Skin
Based on available data, the classification criteria are not met

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

(f) carcinogenicity; Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; Based on available data, the classification criteria are not met

(h) STOT-single exposure; Category 3

Results / Target organs Central nervous system (CNS).

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

Target Organs None known.

(j) aspiration hazard; Category 1

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

delayed tiredness, nausea and vomiting.

11.2. Information on other hazards

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effectsVery toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment. The product contains following substances which are hazardous for the

environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae
n-Heptane	LC50: = 375.0 mg/L, 96h (Cichlid fish)	EC50: >10 mg/L/24h	

Component	Microtox	M-Factor
n-Heptane		1

12.2. Persistence and degradability

Persistence

Persistence is unlikely.

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste

water treatment plants.

12.3. Bioaccumulative potential

Product has a high potential to bioconcentrate

Component	log Pow	Bioconcentration factor (BCF)
n-Heptane	4.66	No data available

12.4. Mobility in soil

The product is insoluble and floats on water Spillage unlikely to penetrate soil The product is insoluble and floats on water. Is not likely mobile in the environment due its low water solubility. Is not likely mobile in the environment due its low water solubility and propensity to bind to soil particles

12.5. Results of PBT and vPvB

assessment

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB).

12.6. Endocrine disrupting

properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused

Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

. ,

n-Heptane Revision Date 12-Oct-2023

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but

application specific.

Other Information Do not flush to sewer. Waste codes should be assigned by the user based on the

application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not let this chemical enter the environment. Do not

empty into drains.

Switzerland - Waste Ordinance Disposal should be in accordance with applicable regional, national and local laws and

regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance,

ADWO) SR 814.600

https://www.fedlex.admin.ch/eli/cc/2015/891/en

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number UN1206 **14.2. UN proper shipping name** Heptanes

14.3. Transport hazard class(es) 3 14.4. Packing group II

<u>ADR</u>

14.1. UN number UN1206 **14.2. UN proper shipping name** Heptanes

14.3. Transport hazard class(es) 3 14.4. Packing group II

<u>IATA</u>

14.1. UN numberUN120614.2. UN proper shipping nameHeptanes

14.3. Transport hazard class(es) 3 14.4. Packing group

14.5. Environmental hazards Dangerous for the environment

Product is a marine pollutant according to the criteria set by IMDG/IMO

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
n-Heptane	142-82-5	205-563-8	ı	-	Х	X	KE-18271	Χ	X
Component	CAS No	TSCA	TSCA In	ventory	DSL	NDSL	AICS	NZIoC	PICCS

n-Heptane Revision Date 12-Oct-2023

			notification - Active-Inactive					
n-Heptane	142-82-5	Х	ACTIVE	Х	-	Х	Х	Х

Legend: X - Listed '-' - Not Listed KI

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous	REACH Regulation (EC 1907/2006) article 59 - Candidate List of
		Subject to Authorization		Substances of Very High
				Concern (SVHC)
n-Heptane	142-82-5	-	Use restricted. See item	-
			75.	
			(see link for restriction	
			details)	

REACH links

https://echa.europa.eu/substances-restricted-under-reach

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) -	Seveso III Directive (2012/18/EC) -
		Qualifying Quantities for Major Accident	Qualifying Quantities for Safety Report
		Notification	Requirements
n-Heptane	142-82-5	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification See table for values

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
n-Heptane	WGK2	

Component France - INRS (Tables of occupational diseases) n-Heptane Tableaux des maladies professionnelles (TMP) - RG 84		France - INRS (Tables of occupational diseases)
		Tableaux des maladies professionnelles (TMP) - RG 84

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the	Switzerland - Ordinance on	Switzerland - Ordinance of the
	Reduction of Risk from	Incentive Taxes on Volatile	Rotterdam Convention on the

Revision Date 12-Oct-2023 n-Heptane

	handling of hazardous substances preparation (SR 814.81)	Organic Compounds (OVOC)	Prior Informed Consent Procedure
n-Heptane 142-82-5 (>95)	Prohibited and Restricted Substances	Group I	

15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has been conducted by the manufacturer/importer

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H336 - May cause drowsiness or dizziness

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b)

Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic

Substances/EU List of Notified Chemical Substances

Substances List **ENCS** - Japanese Existing and New Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances **IECSC** - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

AICS - Australian Inventory of Chemical Substances NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50% POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of

Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime

Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from

Ships

ATE - Acute Toxicity Estimate VOC - (volatile organic compound)

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Training Advice

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts. Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Chemical incident response training.

Creation Date 14-Sep-2009 12-Oct-2023 **Revision Date Revision Summary** Not applicable.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet