

Creation Date 16-Mar-2018

Revision Date 18-Mar-2024

Revision Number 5

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Graphite, colloidal, lubricant, aerosol spray
Cat No. : 41775

Unique Formula Identifier (UFI) EE4Q-A6GY-4X0R-94GQ

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

Thermo Fisher (Kandel) GmbH
Erlenbachweg 2, 76870 Kandel, Germany
Tel: +49 (0) 721 84007 280
Fax: +49 (0) 721 84007 300

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
<https://www.fishersci.ch/ch/en/customer-help-support/forms/email-us.html>

E-mail address

begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

Poison Centre - Emergency information services

Ireland : National Poisons Information Centre (NPIC) -
01 809 2166 (8am-10pm, 7 days a week)
Malta : +356 2395 2000
Cyprus : +357 2240 5611

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

SAFETY DATA SHEET

Graphite, colloidal, lubricant, aerosol spray

Revision Date 18-Mar-2024

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Extremely flammable aerosol

Category 1 (H222)

Health hazards

Aspiration Toxicity

Category 1 (H304)

Skin Corrosion/Irritation

Category 2 (H315)

Serious Eye Damage/Eye Irritation

Category 2 (H319)

Reproductive Toxicity

Category 2 (H361d)

Specific target organ toxicity - (single exposure)

Category 3 (H336)

Environmental hazards

Acute aquatic toxicity

Category 1 (H400)

Chronic aquatic toxicity

Category 1 (H410)

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H222 - Extremely flammable aerosol

H229 - Pressurised container: May burst if heated.

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H361d - Suspected of damaging the unborn child

H410 - Very toxic to aquatic life with long lasting effects

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P211 - Do not spray on an open flame or other ignition source

P251 - Pressurized container: Do not pierce or burn, even after use

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

SAFETY DATA SHEET

Graphite, colloidal, lubricant, aerosol spray

Revision Date 18-Mar-2024

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
n-Heptane	142-82-5	EEC No. 205-563-8	45	Flam. Liq. 2 (H225) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 (H336) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)
Propane	74-98-6	EEC No. 200-827-9	15	Flam. Gas 1 (H220) Press. Gas (H280)
Isopropyl alcohol	67-63-0	200-661-7	15	Flam. Liq. 2 (H225) Eye Irrit. 2 (H319) STOT SE 3 (H336)
n-Butane	106-97-8	EEC No. 203-448-7	15	Flam. Gas 1 (H220) Press. Gas (H280)
Toluene	108-88-3	203-625-9	5	Flam. Liq. 2 (H225) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 (H336) Repr. 2 (H361d) STOT RE 2 (H373)
Graphite	7782-42-5	EEC No. 231-955-3	5	-

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
n-Heptane	-	1	-

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	If symptoms persist, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Ingestion	Clean mouth with water and drink afterwards plenty of water.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.
Self-Protection of the First Aider	Remove all sources of ignition. Use personal protective equipment as required.

4.2. Most important symptoms and effects, both acute and delayed

None reasonably foreseeable. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: May cause pulmonary edema: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

SAFETY DATA SHEET

Graphite, colloidal, lubricant, aerosol spray

Revision Date 18-Mar-2024

vomiting: May cause central nervous system depression

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use water jetstream.

5.2. Special hazards arising from the substance or mixture

Flammable. Risk of ignition. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Do not allow run-off from fire-fighting to enter drains or water courses.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂).

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation.

6.2. Environmental precautions

Should not be released into the environment. See Section 12 for additional Ecological Information. Avoid release to the environment. Collect spillage.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.
Pressurized container: Do not pierce or burn, even after use

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Do not get in eyes, on skin, or on clothing. Wear personal protective equipment/face protection. Ensure adequate ventilation. Avoid ingestion and inhalation.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before

SAFETY DATA SHEET

Graphite, colloidal, lubricant, aerosol spray

Revision Date 18-Mar-2024

re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Flammables area. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Pressurized container: Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Storage Class/LGK 2B

Switzerland - Storage of hazardous substances

Storage class - SC 2
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
n-Heptane	TWA: 500 ppm (8h) TWA: 2085 mg/m ³ (8h)	STEL: 1500 ppm 15 min STEL: 6255 mg/m ³ 15 min TWA: 500 ppm 8 hr TWA: 2085 mg/m ³ 8 hr	TWA / VME: 400 ppm (8 heures). restrictive limit TWA / VME: 1668 mg/m ³ (8 heures). restrictive limit TWA / VME: 1000 mg/m ³ (8 heures). STEL / VLCT: 500 ppm. restrictive limit STEL / VLCT: 2085 mg/m ³ . restrictive limit STEL / VLCT: 1500 mg/m ³ .	TWA: 400 ppm 8 uren TWA: 1664 mg/m ³ 8 uren STEL: 500 ppm 15 minuten STEL: 2085 mg/m ³ 15 minuten	TWA / VLA-ED: 500 ppm (8 horas) TWA / VLA-ED: 2085 mg/m ³ (8 horas)
Propane				TWA: 1000 ppm 8 uren	TWA / VLA-ED: 1000 ppm (8 horas)
Isopropyl alcohol		STEL: 500 ppm 15 min STEL: 1250 mg/m ³ 15 min TWA: 400 ppm 8 hr TWA: 999 mg/m ³ 8 hr	STEL / VLCT: 400 ppm. STEL / VLCT: 980 mg/m ³ .	TWA: 200 ppm 8 uren TWA: 500 mg/m ³ 8 uren STEL: 400 ppm 15 minuten STEL: 1000 mg/m ³ 15 minuten	STEL / VLA-EC: 400 ppm (15 minutos). STEL / VLA-EC: 1000 mg/m ³ (15 minutos). TWA / VLA-ED: 200 ppm (8 horas) TWA / VLA-ED: 500 mg/m ³ (8 horas)
n-Butane		STEL: 750 ppm 15 min STEL: 1810 mg/m ³ 15 min TWA: 600 ppm 8 hr TWA: 1450 mg/m ³ 8 hr Carc. containing >0.1% Buta-1,3-diene	TWA / VME: 800 ppm (8 heures). TWA / VME: 1900 mg/m ³ (8 heures).	STEL: 980 ppm 15 minuten STEL: 2370 mg/m ³ 15 minuten	TWA / VLA-ED: 1000 ppm (8 horas)
Toluene	TWA: 50 ppm (8hr) TWA: 192 mg/m ³ (8hr) STEL: 100 ppm (15min) STEL: 384 mg/m ³	STEL: 100 ppm 15 min STEL: 384 mg/m ³ 15 min TWA: 50 ppm 8 hr	TWA / VME: 20 ppm (8 heures). restrictive limit TWA / VME: 76.8 mg/m ³ (8 heures). restrictive	TWA: 20 ppm 8 uren TWA: 77 mg/m ³ 8 uren STEL: 100 ppm 15 minuten	STEL / VLA-EC: 100 ppm (15 minutos). STEL / VLA-EC: 384 mg/m ³ (15 minutos).

SAFETY DATA SHEET

Graphite, colloidal, lubricant, aerosol spray

Revision Date 18-Mar-2024

	(15min) Skin	TWA: 191 mg/m ³ 8 hr Skin	limit TWA / VME: 1000 mg/m ³ (8 heures). STEL / VLCT: 100 ppm. restrictive limit STEL / VLCT: 384 mg/m ³ . restrictive limit STEL / VLCT: 1500 mg/m ³ . Peau	STEL: 384 mg/m ³ 15 minuten Huid	TWA / VLA-ED: 50 ppm (8 horas) TWA / VLA-ED: 192 mg/m ³ (8 horas) Piel
Graphite		STEL: 30 mg/m ³ 15 min STEL: 12 mg/m ³ 15 min TWA: 10 mg/m ³ 8 hr TWA: 4 mg/m ³ 8 hr	TWA / VME: 2 mg/m ³ (8 heures).	TWA: 2 mg/m ³ 8 uren	TWA / VLA-ED: 2 mg/m ³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
n-Heptane	TWA: 500 ppm 8 ore. Time Weighted Average TWA: 2085 mg/m ³ 8 ore. Time Weighted Average	TWA: 500 ppm (8 Stunden). AGW - exposure factor 1 TWA: 2100 mg/m ³ (8 Stunden). AGW - exposure factor 1 TWA: 500 ppm (8 Stunden). MAK TWA: 2100 mg/m ³ (8 Stunden). MAK Höhepunkt: 500 ppm Höhepunkt: 2100 mg/m ³	STEL: 500 ppm 15 minutos TWA: 500 ppm 8 horas TWA: 2085 mg/m ³ 8 horas	STEL: 1600 mg/m ³ 15 minuten TWA: 1200 mg/m ³ 8 uren	TWA: 300 ppm 8 tunteina TWA: 1200 mg/m ³ 8 tunteina STEL: 500 ppm 15 minuutteina STEL: 2100 mg/m ³ 15 minuutteina
Propane		TWA: 1000 ppm (8 Stunden). AGW - exposure factor 4 TWA: 1800 mg/m ³ (8 Stunden). AGW - exposure factor 4 TWA: 1000 ppm (8 Stunden). MAK TWA: 1800 mg/m ³ (8 Stunden). MAK Höhepunkt: 4000 ppm Höhepunkt: 7200 mg/m ³	TWA: 1000 ppm 8 horas		TWA: 800 ppm 8 tunteina TWA: 1500 mg/m ³ 8 tunteina STEL: 1100 ppm 15 minuutteina STEL: 2000 mg/m ³ 15 minuutteina
Isopropyl alcohol		TWA: 200 ppm (8 Stunden). AGW - exposure factor 2 TWA: 500 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 200 ppm (8 Stunden). MAK TWA: 500 mg/m ³ (8 Stunden). MAK Höhepunkt: 400 ppm Höhepunkt: 1000 mg/m ³	STEL: 400 ppm 15 minutos TWA: 200 ppm 8 horas		TWA: 200 ppm 8 tunteina TWA: 500 mg/m ³ 8 tunteina STEL: 250 ppm 15 minuutteina STEL: 620 mg/m ³ 15 minuutteina
n-Butane		TWA: 1000 ppm (8 Stunden). AGW - exposure factor 4 TWA: 2400 mg/m ³ (8 Stunden). AGW - exposure factor 4 TWA: 1000 ppm (8 Stunden). MAK TWA: 2400 mg/m ³ (8 Stunden). MAK Höhepunkt: 4000 ppm Höhepunkt: 9600 mg/m ³	STEL: 1000 ppm 15 minutos TWA: 1000 ppm 8 horas		TWA: 800 ppm 8 tunteina TWA: 1900 mg/m ³ 8 tunteina STEL: 1000 ppm 15 minuutteina STEL: 2400 mg/m ³ 15 minuutteina
Toluene	TWA: 50 ppm 8 ore. Time Weighted Average TWA: 192 mg/m ³ 8 ore. Time Weighted Average Pelle	TWA: 50 ppm (8 Stunden). AGW - exposure factor 2 TWA: 190 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 50 ppm (8 Stunden). MAK TWA: 190 mg/m ³ (8 Stunden). MAK	STEL: 100 ppm 15 minutos STEL: 384 mg/m ³ 15 minutos TWA: 50 ppm 8 horas TWA: 192 mg/m ³ 8 horas Pele	STEL: 384 mg/m ³ 15 minuten TWA: 150 mg/m ³ 8 uren	TWA: 25 ppm 8 tunteina TWA: 81 mg/m ³ 8 tunteina STEL: 100 ppm 15 minuutteina STEL: 380 mg/m ³ 15 minuutteina Iho

SAFETY DATA SHEET

Graphite, colloidal, lubricant, aerosol spray

Revision Date 18-Mar-2024

		Höhepunkt: 100 ppm Höhepunkt: 380 mg/m ³ Haut			
Graphite		TWA: 1.25 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 10 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 0.3 mg/m ³ (8 Stunden). MAK multiplied by the material density; except ultrafine particles TWA: 4 mg/m ³ (8 Stunden). MAK Höhepunkt: 2.4 mg/m ³	TWA: 2 mg/m ³ 8 horas		TWA: 2 mg/m ³ 8 tunteina

Component	Austria	Denmark	Switzerland	Poland	Norway
n-Heptane	MAK-KZGW: 2000 ppm 15 Minuten MAK-KZGW: 8000 mg/m ³ 15 Minuten MAK-TMW: 500 ppm 8 Stunden MAK-TMW: 2000 mg/m ³ 8 Stunden	TWA: 200 ppm 8 timer TWA: 820 mg/m ³ 8 timer STEL: 400 ppm 15 minutter STEL: 1640 mg/m ³ 15 minutter	STEL: 400 ppm 15 Minuten STEL: 1600 mg/m ³ 15 Minuten TWA: 400 ppm 8 Stunden TWA: 1600 mg/m ³ 8 Stunden	STEL: 2000 mg/m ³ 15 minutach TWA: 1200 mg/m ³ 8 godzinach	TWA: 200 ppm 8 timer TWA: 800 mg/m ³ 8 timer TWA: 40 ppm 8 timer TWA: 275 mg/m ³ 8 timer STEL: 250 ppm 15 minutter. value calculated STEL: 1000 mg/m ³ 15 minutter. value calculated
Propane	MAK-KZGW: 2000 ppm 15 Minuten MAK-KZGW: 3600 mg/m ³ 15 Minuten MAK-TMW: 1000 ppm 8 Stunden MAK-TMW: 1800 mg/m ³ 8 Stunden	TWA: 1000 ppm 8 timer TWA: 1800 mg/m ³ 8 timer STEL: 2000 ppm 15 minutter STEL: 3600 mg/m ³ 15 minutter	STEL: 4000 ppm 15 Minuten STEL: 7200 mg/m ³ 15 Minuten TWA: 1000 ppm 8 Stunden TWA: 1800 mg/m ³ 8 Stunden	TWA: 1800 mg/m ³ 8 godzinach	TWA: 500 ppm 8 timer TWA: 900 mg/m ³ 8 timer TWA: 40 ppm 8 timer TWA: 275 mg/m ³ 8 timer STEL: 625 ppm 15 minutter. value calculated STEL: 1125 mg/m ³ 15 minutter. value calculated
Isopropyl alcohol	MAK-KZGW: 800 ppm 15 Minuten MAK-KZGW: 2000 mg/m ³ 15 Minuten MAK-TMW: 200 ppm 8 Stunden MAK-TMW: 500 mg/m ³ 8 Stunden	TWA: 200 ppm 8 timer TWA: 490 mg/m ³ 8 timer STEL: 400 ppm 15 minutter STEL: 980 mg/m ³ 15 minutter	STEL: 400 ppm 15 Minuten STEL: 1000 mg/m ³ 15 Minuten TWA: 200 ppm 8 Stunden TWA: 500 mg/m ³ 8 Stunden	STEL: 1200 mg/m ³ 15 minutach TWA: 900 mg/m ³ 8 godzinach	TWA: 100 ppm 8 timer TWA: 245 mg/m ³ 8 timer STEL: 150 ppm 15 minutter. value calculated STEL: 306.25 mg/m ³ 15 minutter. value calculated
n-Butane	MAK-KZGW: 1600 ppm 15 Minuten MAK-KZGW: 3800 mg/m ³ 15 Minuten MAK-TMW: 800 ppm 8 Stunden MAK-TMW: 1900 mg/m ³ 8 Stunden	TWA: 500 ppm 8 timer TWA: 1200 mg/m ³ 8 timer STEL: 1000 ppm 15 minutter STEL: 2400 mg/m ³ 15 minutter	STEL: 3200 ppm 15 Minuten STEL: 7600 mg/m ³ 15 Minuten TWA: 800 ppm 8 Stunden TWA: 1900 mg/m ³ 8 Stunden	STEL: 3000 mg/m ³ 15 minutach TWA: 1900 mg/m ³ 8 godzinach	TWA: 250 ppm 8 timer TWA: 600 mg/m ³ 8 timer TWA: 40 ppm 8 timer TWA: 275 mg/m ³ 8 timer STEL: 312.5 ppm 15 minutter. value calculated STEL: 750 mg/m ³ 15 minutter. value calculated
Toluene	Haut MAK-KZGW: 100 ppm 15 Minuten MAK-KZGW: 380 mg/m ³ 15 Minuten MAK-TMW: 50 ppm 8 Stunden MAK-TMW: 190 mg/m ³ 8 Stunden	TWA: 25 ppm 8 timer TWA: 94 mg/m ³ 8 timer STEL: 384 mg/m ³ 15 minutter STEL: 100 ppm 15 minutter Hud	Haut/Peau STEL: 200 ppm 15 Minuten STEL: 760 mg/m ³ 15 Minuten TWA: 50 ppm 8 Stunden TWA: 190 mg/m ³ 8 Stunden	STEL: 200 mg/m ³ 15 minutach TWA: 100 mg/m ³ 8 godzinach	TWA: 25 ppm 8 timer TWA: 94 mg/m ³ 8 timer STEL: 37.5 ppm 15 minutter. value calculated STEL: 141 mg/m ³ 15 minutter. value calculated Hud
Graphite	MAK-KZGW: 10 mg/m ³ 15 Minuten MAK-TMW: 5 mg/m ³ 8 Stunden	TWA: 2.5 mg/m ³ 8 timer STEL: 5 mg/m ³ 15 minutter	TWA: 3 mg/m ³ 8 Stunden TWA: 10 mg/m ³ 8 Stunden	TWA: 4.0 mg/m ³ 8 godzinach TWA: 1.0 mg/m ³ 8 godzinach	TWA: 5 mg/m ³ 8 timer TWA: 2 mg/m ³ 8 timer TWA: 10 mg/m ³ 8 timer TWA: 4 mg/m ³ 8 timer STEL: 10 mg/m ³ 15 minutter. natural; value calculated total dust

SAFETY DATA SHEET

Graphite, colloidal, lubricant, aerosol spray

Revision Date 18-Mar-2024

					<p>STEL: 4 mg/m³ 15 minutter. natural;value calculated respirable dust</p> <p>STEL: 20 mg/m³ 15 minutter. synthetic;value calculated total dust</p> <p>STEL: 8 mg/m³ 15 minutter. synthetic;value calculated respirable dust</p>
--	--	--	--	--	---

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
n-Heptane	TWA: 1600 mg/m ³	kože TWA-GVI: 500 ppm 8 satima. TWA-GVI: 2085 mg/m ³ 8 satima.	TWA: 500 ppm 8 hr. TWA: 2085 mg/m ³ 8 hr. STEL: 1500 ppm 15 min STEL: 6255 mg/m ³ 15 min	TWA: 500 ppm TWA: 2085 mg/m ³	TWA: 1000 mg/m ³ 8 hodinách. Ceiling: 2000 mg/m ³
Propane	TWA: 1800.0 mg/m ³		STEL: 3000 ppm 15 min		
Isopropyl alcohol	TWA: 980.0 mg/m ³ STEL : 1225.0 mg/m ³	TWA-GVI: 400 ppm 8 satima. TWA-GVI: 999 mg/m ³ 8 satima. STEL-KGVI: 500 ppm 15 minutama. STEL-KGVI: 1250 mg/m ³ 15 minutama.	TWA: 200 ppm 8 hr. STEL: 400 ppm 15 min Skin		TWA: 500 mg/m ³ 8 hodinách. Potential for cutaneous absorption Ceiling: 1000 mg/m ³
n-Butane	TWA: 1900 mg/m ³	TWA-GVI: 600 ppm 8 satima. TWA-GVI: 1450 mg/m ³ 8 satima. TWA-GVI: 10 ppm 8 satima. containing >=0.1% Butadiene TWA-GVI: 22 mg/m ³ 8 satima. containing >=0.1% Butadiene STEL-KGVI: 750 ppm 15 minutama. STEL-KGVI: 1810 mg/m ³ 15 minutama.	TWA: 1000 ppm 8 hr. STEL: 3000 ppm 15 min		
Toluene	TWA: 50 ppm TWA: 192.0 mg/m ³ STEL : 100 ppm STEL : 384.0 mg/m ³ Skin notation	kože TWA-GVI: 50 ppm 8 satima. TWA-GVI: 192 mg/m ³ 8 satima. STEL-KGVI: 100 ppm 15 minutama. STEL-KGVI: 384 mg/m ³ 15 minutama.	TWA: 192 mg/m ³ 8 hr. TWA: 50 ppm 8 hr. STEL: 384 mg/m ³ 15 min STEL: 100 ppm 15 min Skin	Skin-potential for cutaneous absorption STEL: 100 ppm STEL: 384 mg/m ³ TWA: 50 ppm TWA: 192 mg/m ³	TWA: 200 mg/m ³ 8 hodinách. Potential for cutaneous absorption Ceiling: 500 mg/m ³
Graphite	TWA: 5.0 mg/m ³	TWA-GVI: 4 mg/m ³ 8 satima. respirable dust TWA-GVI: 10 mg/m ³ 8 satima. total dust, inhalable particles	TWA: 2 mg/m ³ 8 hr. all forms except fibres; respirable fraction STEL: 6 mg/m ³ 15 min		TWA: 2.0 mg/m ³ 8 hodinách. respirable fraction, <=5% Silica, Cristobalite, Tridymite and .gamma.-Aluminium oxide dust

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
n-Heptane	TWA: 500 ppm 8 tundides. TWA: 2085 mg/m ³ 8 tundides.	TWA: 500 ppm 8 hr TWA: 2085 mg/m ³ 8 hr	STEL: 500 ppm STEL: 2000 mg/m ³ TWA: 500 ppm TWA: 2000 mg/m ³	TWA: 2000 mg/m ³ 8 órában. AK	TWA: 200 ppm 8 klukkustundum. TWA: 820 mg/m ³ 8 klukkustundum. Ceiling: 400 ppm Ceiling: 1640 mg/m ³
Propane	TWA: 1000 ppm 8 tundides. TWA: 1800 mg/m ³ 8 tundides.		TWA: 1000 ppm TWA: 1800 mg/m ³		TWA: 1000 ppm 8 klukkustundum. TWA: 1800 mg/m ³ 8 klukkustundum. Ceiling: 2000 ppm Ceiling: 3600 mg/m ³
Isopropyl alcohol	TWA: 150 ppm 8 tundides.		STEL: 500 ppm STEL: 1225 mg/m ³	STEL: 1000 mg/m ³ 15 percekben. CK	TWA: 200 ppm 8 klukkustundum.

SAFETY DATA SHEET

Graphite, colloidal, lubricant, aerosol spray

Revision Date 18-Mar-2024

	TWA: 350 mg/m ³ 8 tündides. STEL: 250 ppm 15 minutites. STEL: 600 mg/m ³ 15 minutites.		TWA: 400 ppm TWA: 980 mg/m ³	TWA: 500 mg/m ³ 8 órában. AK lehetséges borön keresztül felszívódás	TWA: 490 mg/m ³ 8 klukkustundum. Skin notation Ceiling: 400 ppm Ceiling: 980 mg/m ³
n-Butane	TWA: 800 ppm 8 tündides. TWA: 1500 mg/m ³ 8 tündides.		TWA: 1000 ppm TWA: 2350 mg/m ³	STEL: 9400 mg/m ³ 15 percekben. CK TWA: 2350 mg/m ³ 8 órában. AK	TWA: 500 ppm 8 klukkustundum. TWA: 1200 mg/m ³ 8 klukkustundum. Ceiling: 1000 ppm Ceiling: 2400 mg/m ³
Toluene	Nahk TWA: 50 ppm 8 tündides. TWA: 192 mg/m ³ 8 tündides. STEL: 100 ppm 15 minutites. STEL: 384 mg/m ³ 15 minutites.	Skin notation TWA: 50 ppm 8 hr TWA: 192 mg/m ³ 8 hr STEL: 100 ppm 15 min STEL: 384 mg/m ³ 15 min	skin - potential for cutaneous absorption STEL: 100 ppm STEL: 384 mg/m ³ TWA: 50 ppm TWA: 192 mg/m ³	STEL: 380 mg/m ³ 15 percekben. CK TWA: 190 mg/m ³ 8 órában. AK lehetséges borön keresztül felszívódás	STEL: 50 ppm STEL: 188 mg/m ³ TWA: 25 ppm 8 klukkustundum. TWA: 94 mg/m ³ 8 klukkustundum. Skin notation
Graphite	TWA: 5 mg/m ³ 8 tündides. total dust		TWA: 10 mg/m ³ TWA: 5 mg/m ³	TWA: 5 mg/m ³ 8 órában. AK TWA: 2 mg/m ³ 8 órában. AK	TWA: 5 mg/m ³ 8 klukkustundum. total dust TWA: 2.5 mg/m ³ 8 klukkustundum. respirable fraction Ceiling: 10 mg/m ³ total dust Ceiling: 5 mg/m ³ respirable dust

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
n-Heptane	STEL: 500 ppm STEL: 2085 mg/m ³ TWA: 85 ppm TWA: 350 mg/m ³	TWA: 500 ppm IPRD TWA: 2085 mg/m ³ IPRD STEL: 750 ppm STEL: 3128 mg/m ³	TWA: 500 ppm 8 Stunden TWA: 2085 mg/m ³ 8 Stunden	TWA: 500 ppm TWA: 2085 mg/m ³	TWA: 500 ppm 8 ore TWA: 2085 mg/m ³ 8 ore
Propane	TWA: 1000 ppm TWA: 1800 mg/m ³				TWA: 778 ppm 8 ore TWA: 1400 mg/m ³ 8 ore STEL: 1000 ppm 15 minute STEL: 1800 mg/m ³ 15 minute
Isopropyl alcohol	STEL: 600 mg/m ³ TWA: 350 mg/m ³	TWA: 150 ppm IPRD TWA: 350 mg/m ³ IPRD STEL: 250 ppm STEL: 600 mg/m ³			TWA: 81 ppm 8 ore TWA: 200 mg/m ³ 8 ore STEL: 203 ppm 15 minute STEL: 500 mg/m ³ 15 minute
n-Butane	TWA: 300 mg/m ³				
Toluene	skin - potential for cutaneous exposure STEL: 40 ppm STEL: 150 mg/m ³ TWA: 14 ppm TWA: 50 mg/m ³	TWA: 50 ppm IPRD TWA: 192 mg/m ³ IPRD Oda STEL: 100 ppm STEL: 384 mg/m ³	Possibility of significant uptake through the skin TWA: 50 ppm 8 Stunden TWA: 192 mg/m ³ 8 Stunden STEL: 100 ppm 15 Minuten STEL: 384 mg/m ³ 15 Minuten	possibility of significant uptake through the skin TWA: 50 ppm TWA: 192 mg/m ³ STEL: 100 ppm 15 minuti STEL: 384 mg/m ³ 15 minuti	Skin notation TWA: 50 ppm 8 ore TWA: 192 mg/m ³ 8 ore STEL: 100 ppm 15 minute STEL: 384 mg/m ³ 15 minute
Graphite	TWA: 2 mg/m ³	TWA: 5 mg/m ³ dust IPRD			TWA: 2 mg/m ³ 8 ore

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
n-Heptane		TWA: 500 ppm TWA: 2085 mg/m ³	TWA: 500 ppm 8 urah applies to all isomers TWA: 2085 mg/m ³ 8 urah applies to all isomers STEL: 500 ppm 15 minutah applies to all	Indicative STEL: 300 ppm 15 minuter Indicative STEL: 1200 mg/m ³ 15 minuter TLV: 200 ppm 8 timmar. NGV TLV: 800 mg/m ³ 8	TWA: 500 ppm 8 saat TWA: 2085 mg/m ³ 8 saat

SAFETY DATA SHEET

Graphite, colloidal, lubricant, aerosol spray

Revision Date 18-Mar-2024

			isomers STEL: 2085 mg/m ³ 15 minutah applies to all isomers	timmar. NGV	
Propane			TWA: 1000 ppm 8 urah TWA: 1800 mg/m ³ 8 urah STEL: 4000 ppm 15 minutah STEL: 7200 mg/m ³ 15 minutah		
Isopropyl alcohol	TWA: 10 mg/m ³ 1761 MAC: 50 mg/m ³	Ceiling: 1000 mg/m ³ TWA: 200 ppm TWA: 500 mg/m ³	TWA: 200 ppm 8 urah TWA: 500 mg/m ³ 8 urah STEL: 400 ppm 15 minutah STEL: 1000 mg/m ³ 15 minutah	Indicative STEL: 250 ppm 15 minuter Indicative STEL: 600 mg/m ³ 15 minuter TLV: 150 ppm 8 timmar. NGV TLV: 350 mg/m ³ 8 timmar. NGV	
n-Butane	TWA: 300 mg/m ³ 0404 MAC: 900 mg/m ³	TWA: 1000 ppm 8 hodinách containing 0.1% or greater Butadiene TWA: 2400 mg/m ³ 8 hodinách containing 0.1% or greater Butadiene STEL: 5000 ppm 15 minútach containing 0.1% or greater Butadiene STEL: 12000 mg/m ³ 15 minútach containing 0.1% or greater Butadiene	TWA: 1000 ppm 8 urah containing >=0.1% Butadiene TWA: 2400 mg/m ³ 8 urah containing >=0.1% Butadiene STEL: 4000 ppm 15 minutah containing >=0.1% Butadiene STEL: 9600 mg/m ³ 15 minutah containing >=0.1% Butadiene		
Toluene	TWA: 50 mg/m ³ 1264 MAC: 150 mg/m ³	Ceiling: 384 mg/m ³ Potential for cutaneous absorption TWA: 50 ppm TWA: 192 mg/m ³	TWA: 50 ppm 8 urah TWA: 192 mg/m ³ 8 urah Koža STEL: 100 ppm 15 minutah STEL: 384 mg/m ³ 15 minutah	Binding STEL: 100 ppm 15 minuter Binding STEL: 384 mg/m ³ 15 minuter TLV: 50 ppm 8 timmar. NGV TLV: 192 mg/m ³ 8 timmar. NGV Hud	Deri TWA: 50 ppm 8 saat TWA: 192 mg/m ³ 8 saat STEL: 100 ppm 15 dakika STEL: 384 mg/m ³ 15 dakika
Graphite		TWA: 10 mg/m ³ total aerosol TWA: 2 mg/m ³ respirable fraction			

Biological limit values

List source(s):

Component	European Union	United Kingdom	France	Spain	Germany
n-Heptane					Heptan-2,5-dione: 250 µg/L urine (end of shift)
Isopropyl alcohol				Acetone: 40 mg/L urine end of workweek	Acetone: 25 mg/L whole blood (end of shift) Acetone: 25 mg/L urine (end of shift)
Toluene			Toluene: 1 mg/L venous blood end of shift Hippuric acid: 2500 mg/g creatinine urine end of shift	o-Cresol: 0.6 mg/L urine end of shift Toluene: 0.05 mg/L blood start of last shift of workweek Toluene: 0.08 mg/L urine end of shift	Toluene: 600 µg/L whole blood (immediately after exposure) Toluene: 75 µg/L urine (end of shift) o-Cresol (after hydrolysis): 1.5 mg/L urine (for long-term exposures: at the end of the shift after several shifts) o-Cresol (after

SAFETY DATA SHEET

Graphite, colloidal, lubricant, aerosol spray

Revision Date 18-Mar-2024

					hydrolysis): 1.5 mg/L urine (end of shift)
--	--	--	--	--	---

Component	Italy	Finland	Denmark	Bulgaria	Romania
Isopropyl alcohol					Acetone: 50 mg/L urine end of shift
Toluene		Toluene: 500 nmol/L blood in the morning after a working day.		Hippuric acid: 1.6 mmol/mmol Creatinine urine at the end of exposure or end of work shift	Hippuric acid: 2 g/L urine end of shift o-Cresol: 3 mg/L urine end of shift

Component	Gibraltar	Latvia	Slovak Republic	Luxembourg	Turkey
Toluene		Hippuric acid: 1.6 g/g Creatinine urine end of shift Toluene: 0.05 mg/L blood end of shift	Toluene: 600 µg/L blood end of exposure or work shift o-Cresol: 1.5 mg/L urine after all work shifts for long-term exposure o-Cresol: 1.5 mg/L urine end of exposure or work shift Hippuric acid: 1600 mg/g creatinine end of exposure or work shift		

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
n-Heptane 142-82-5 (45)				DNEL = 300mg/kg bw/day
Isopropyl alcohol 67-63-0 (15)				DNEL = 888mg/kg bw/day
Toluene 108-88-3 (5)				DNEL = 384mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
n-Heptane 142-82-5 (45)				DNEL = 2085mg/m ³
Isopropyl alcohol 67-63-0 (15)				DNEL = 500mg/m ³
Toluene 108-88-3 (5)	DNEL = 384mg/m ³	DNEL = 384mg/m ³	DNEL = 192mg/m ³	DNEL = 192mg/m ³
Graphite 7782-42-5 (5)			DNEL = 1.2mg/m ³	DNEL = 1.2mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water	Water Intermittent	Microorganisms in	Soil (Agriculture)
-----------	-------------	-------------	--------------------	-------------------	--------------------

SAFETY DATA SHEET

Graphite, colloidal, lubricant, aerosol spray

Revision Date 18-Mar-2024

		sediment		sewage treatment	
Isopropyl alcohol 67-63-0 (15)	PNEC = 140.9mg/L	PNEC = 552mg/kg sediment dw	PNEC = 140.9mg/L	PNEC = 2251mg/L	PNEC = 28mg/kg soil dw
Toluene 108-88-3 (5)	PNEC = 0.68mg/L	PNEC = 16.39mg/kg sediment dw	PNEC = 0.68mg/L	PNEC = 13.61mg/L	PNEC = 2.89mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Isopropyl alcohol 67-63-0 (15)	PNEC = 140.9mg/L	PNEC = 552mg/kg sediment dw		PNEC = 160mg/kg food	
Toluene 108-88-3 (5)	PNEC = 0.68mg/L	PNEC = 16.39mg/kg sediment dw			

8.2. Exposure controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting/equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Butyl rubber	> 480 minutes	0.5 mm	EN 374 Level 6	As tested under EN374-3 Determination of Resistance to Permeation by Chemicals
Neoprene gloves	< 30 minutes	0.45 mm		

Skin and body protection Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371

Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

SAFETY DATA SHEET

Graphite, colloidal, lubricant, aerosol spray

Revision Date 18-Mar-2024

Physical State	Liquid Aerosol	
Appearance	Black	
Odor	No information available	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flammability (liquid)	Highly flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	-97 °C / -142.6 °F	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	No data available	
Water Solubility	Partially miscible	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
n-Heptane	4.66	
Propane	1.09	
Isopropyl alcohol	0.05	
n-Butane	2.31	
Toluene	2.73	
Vapor Pressure	No data available	
Density / Specific Gravity	No data available	
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

VOC Content(%)	95
Explosive Properties	Vapors may form explosive mixtures with air

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F. Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂).

SAFETY DATA SHEET

Graphite, colloidal, lubricant, aerosol spray

Revision Date 18-Mar-2024

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral	No data available
Dermal	No data available
Inhalation	No data available

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
n-Heptane	>2000 mg/kg (rat)	LD50 = 3000 mg/kg (Rabbit)	LC50 > 73.5 mg/L (Rat) 4 h
Propane	-	-	LC50 > 20000 ppm (Rat) 4h
Isopropyl alcohol	5045 mg/kg (Rat) 3600 mg/kg (Mouse)	12800 mg/kg (Rat)	72.6 mg/L (Rat) 4 h
n-Butane	-	-	658 mg/L (Rat) 4 h
Toluene	> 5000 mg/kg (Rat)	LD50 = 12000 mg/kg (Rabbit)	26700 ppm (Rat) 1 h
Graphite	-	-	LC50 > 2000 mg/m ³ (Rat) 4 h

(b) skin corrosion/irritation; No data available

(c) serious eye damage/irritation; No data available

(d) respiratory or skin sensitization;

Respiratory	No data available
Skin	No data available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
n-Butane	Carc Cat. 1A			

(g) reproductive toxicity; No data available

(h) STOT-single exposure; No data available

Results / Target organs Central nervous system (CNS), Respiratory system.

(i) STOT-repeated exposure; No data available

Target Organs No information available.

(j) aspiration hazard; Category 1

Symptoms / effects, both acute and delayed Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. May cause pulmonary edema. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. May cause central

SAFETY DATA SHEET

Graphite, colloidal, lubricant, aerosol spray

Revision Date 18-Mar-2024

nervous system depression.

11.2. Information on other hazards

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

The product contains following substances which are hazardous for the environment. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae
n-Heptane	LC50: = 375.0 mg/L, 96h (Cichlid fish)	EC50: >10 mg/L/24h	
Isopropyl alcohol	LC50: = 9640 mg/L, 96h flow-through (Pimephales promelas) LC50: > 1400000 µg/L, 96h (Lepomis macrochirus) LC50: = 11130 mg/L, 96h static (Pimephales promelas) LC50: = 10000000 µg/L, 96h (Daphnia)	13299 mg/L EC50 = 48 h 9714 mg/L EC50 = 24 h	EC50: > 1000 mg/L, 72h (Desmodesmus subspicatus) EC50: > 1000 mg/L, 96h (Desmodesmus subspicatus)
Toluene	50-70 mg/L LC50 96 h 5-7 mg/L LC50 96 h 15-19 mg/L LC50 96 h 28 mg/L LC50 96 h 12 mg/L LC50 96 h	EC50: = 11.5 mg/L, 48h (Daphnia magna) EC50: 5.46 - 9.83 mg/L, 48h Static (Daphnia magna)	EC50: = 12.5 mg/L, 72h static (Pseudokirchneriella subcapitata) EC50: > 433 mg/L, 96h (Pseudokirchneriella subcapitata)
Graphite	LC50: > 100 mg/L, 96h semi-static (Danio rerio)		

Component	Microtox	M-Factor
n-Heptane		1
Isopropyl alcohol	= 35390 mg/L EC50 Photobacterium phosphoreum 5 min	
Toluene	EC50 = 19.7 mg/L 30 min	

12.2. Persistence and degradability

Persistence

Persistence is unlikely, based on information available.

Component	Degradability
Toluene 108-88-3 (5)	86% (20d)

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
n-Heptane	4.66	No data available
Propane	1.09	No data available
Isopropyl alcohol	0.05	No data available
n-Butane	2.31	No data available
Toluene	2.73	90

12.4. Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all

SAFETY DATA SHEET

Graphite, colloidal, lubricant, aerosol spray

Revision Date 18-Mar-2024

surfaces Will likely be mobile in the environment due to its volatility. Disperses rapidly in air

12.5. Results of PBT and vPvB assessment

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB).

12.6. Endocrine disrupting properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant

This product does not contain any known or suspected substance

Ozone Depletion Potential

This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information

Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not let this chemical enter the environment. Do not empty into drains.

Switzerland - Waste Ordinance

Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number

UN1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

2.1

14.4. Packing group

ADR

14.1. UN number

UN1950

14.2. UN proper shipping name

Aerosols

14.3. Transport hazard class(es)

2.1

Subsidiary Hazard Class

5F

14.4. Packing group

IATA

14.1. UN number

UN1950

14.2. UN proper shipping name

AEROSOLS, FLAMMABLE

SAFETY DATA SHEET

Graphite, colloidal, lubricant, aerosol spray

Revision Date 18-Mar-2024

14.3. Transport hazard class(es) 2.1

14.4. Packing group

14.5. Environmental hazards Dangerous for the environment
Product is a marine pollutant according to the criteria set by IMDG/IMO

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
n-Heptane	142-82-5	205-563-8	-	-	X	X	KE-18271	X	X
Propane	74-98-6	200-827-9	-	-	X	X	KE-29258	X	X
Isopropyl alcohol	67-63-0	200-661-7	-	-	X	X	KE-29363	X	X
n-Butane	106-97-8	203-448-7	-	-	X	X	KE-03751	X	X
Toluene	108-88-3	203-625-9	-	-	X	X	KE-33936	X	X
Graphite	7782-42-5	231-955-3	-	-	X	X	KE-18101	-	-

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
n-Heptane	142-82-5	X	ACTIVE	X	-	X	X	X
Propane	74-98-6	X	ACTIVE	X	-	X	X	X
Isopropyl alcohol	67-63-0	X	ACTIVE	X	-	X	X	X
n-Butane	106-97-8	X	ACTIVE	X	-	X	X	X
Toluene	108-88-3	X	ACTIVE	X	-	X	X	X
Graphite	7782-42-5	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
n-Heptane	142-82-5	-	Use restricted. See item 75. (see link for restriction details)	-
Propane	74-98-6	-	-	-
Isopropyl alcohol	67-63-0	-	Use restricted. See item 75. (see link for restriction details)	-
n-Butane	106-97-8	-	Use restricted. See item 28. (see link for restriction details) Use restricted. See item 29. (see link for restriction details) Use restricted. See item 75.	-

SAFETY DATA SHEET

Graphite, colloidal, lubricant, aerosol spray

Revision Date 18-Mar-2024

			(see link for restriction details)	
Toluene	108-88-3	-	Use restricted. See item 48. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-
Graphite	7782-42-5	-	-	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
n-Heptane	142-82-5	Not applicable	Not applicable
Propane	74-98-6	Not applicable	Not applicable
Isopropyl alcohol	67-63-0	Not applicable	Not applicable
n-Butane	106-97-8	Not applicable	Not applicable
Toluene	108-88-3	Not applicable	Not applicable
Graphite	7782-42-5	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

Take note of Directive 94/33/EC on the protection of young people at work

Take note of Dir 92/85/EC on the protection of pregnant and breastfeeding women at work

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 2 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
n-Heptane	WGK2	
Propane	nwg	
Isopropyl alcohol	WGK1	
n-Butane	nwg	
Toluene	WGK3	
Graphite	nwg	

Component	France - INRS (Tables of occupational diseases)
n-Heptane	Tableaux des maladies professionnelles (TMP) - RG 84
Isopropyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84
Toluene	Tableaux des maladies professionnelles (TMP) - RG 4bis, RG 84
Graphite	Tableaux des maladies professionnelles (TMP) - RG 16 Tableaux des maladies professionnelles (TMP) - RG 25

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER

SAFETY DATA SHEET

Graphite, colloidal, lubricant, aerosol spray

Revision Date 18-Mar-2024

regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
n-Heptane 142-82-5 (45)	Prohibited and Restricted Substances	Group I	
Propane 74-98-6 (15)	Prohibited and Restricted Substances	Group I	
Isopropyl alcohol 67-63-0 (15)		Group I	
n-Butane 106-97-8 (15)	Prohibited and Restricted Substances	Group I	
Toluene 108-88-3 (5)	Prohibited and Restricted Substances	Group I	

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H361d - Suspected of damaging the unborn child

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards

On basis of test data

Health Hazards

Calculation method

Environmental hazards

Calculation method

SAFETY DATA SHEET

Graphite, colloidal, lubricant, aerosol spray

Revision Date 18-Mar-2024

Training Advice

Chemical incident response training.

Prepared By

Health, Safety and Environmental Department

Creation Date

16-Mar-2018

Revision Date

18-Mar-2024

Revision Summary

New emergency telephone response service provider.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No
1907/2006 .**

**For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2,
Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and
Preparations).**

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet