

# **SAFETY DATA SHEET**

Creation Date 03-Aug-2010 Revision Date 23-Feb-2022 Revision Number 6

# 1. Identification

Product Name Lithium thiophenolate, 1M solution in THF

Cat No.: AC433500000; AC433501000

Synonyms Thiophenol lithium salt, 1M solution in THF

**Recommended Use** Laboratory chemicals.

**Uses advised against** Food, drug, pesticide or biocidal product use.

# Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410
Fair Lawn, NJ 07410

**Emergency Telephone Number** 

For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

# 2. Hazard(s) identification

# Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids

Acute oral toxicity

Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Category 1

Carcinogenicity

Category 2

Specific target organ toxicity (single exposure)

Category 3

Target Organs - Respiratory system, Central nervous system (CNS).

# Label Elements

# Signal Word

Danger

### **Hazard Statements**

Highly flammable liquid and vapor Harmful if swallowed

Causes severe skin burns and eye damage May cause respiratory irritation May cause drowsiness or dizziness Suspected of causing cancer



### **Precautionary Statements**

# Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

#### Response

Immediately call a POISON CENTER or doctor/physician

# Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

#### Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

#### Lyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

### Ingestion

Rinse mouth

Do NOT induce vomiting

#### **Fire**

In case of fire: Use CO2, dry chemical, or foam for extinction

# Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

#### Disposa

Dispose of contents/container to an approved waste disposal plant

# Hazards not otherwise classified (HNOC)

May form explosive peroxides

WARNING. Cancer - https://www.p65warnings.ca.gov/.

# 3. Composition/Information on Ingredients

Component	CAS No	Weight %
Tetrahydrofuran	109-99-9	87-88
Lithium thiophenolate	2973-86-6	12-13

# 4. First-aid measures

**General Advice** Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. Remove and wash

contaminated clothing and gloves, including the inside, before re-use. Call a physician

immediately.

**Inhalation** If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use

mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory

medical device. Call a physician immediately.

**Ingestion** Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an

unconscious person. Call a physician immediately.

Most important symptoms and

effects

Causes burns by all exposure routes. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Causes central nervous system

depression

Notes to Physician Treat symptomatically

# 5. Fire-fighting measures

Suitable Extinguishing Media CO<sub>2</sub>, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool

closed containers.

Unsuitable Extinguishing Media No information available

Flash Point -19 °C / -2.2 °F

Method - No information available

**Autoignition Temperature** 

**Explosion Limits** 

No information available

Upper No data available
Lower No data available
Sensitivity to Mechanical Impact No information available

Sensitivity to Static Discharge No information available

# **Specific Hazards Arising from the Chemical**

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

### **Hazardous Combustion Products**

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Sulfur oxides.

# **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health Flammability Instability Physical hazards

# 6. Accidental release measures

**Personal Precautions** 

Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges. Should not be released into the environment.

**Environmental Precautions** 

**Methods for Containment and Clean** Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. **Up**Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

# 7. Handling and storage

Handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. If peroxide formation is suspected, do not open or move container. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Storage.

Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area. Flammables area. Keep away from heat, sparks and flame. Keep under nitrogen. Shelf life 12 months. May form explosive peroxides on prolonged storage. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. Incompatible Materials. Strong oxidizing agents.

# 8. Exposure controls / personal protection

# **Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Tetrahydrofuran	TWA: 50 ppm	(Vacated) TWA: 200 ppm	IDLH: 2000 ppm	TWA: 200 ppm
	STEL: 100 ppm	(Vacated) TWA: 590 mg/m <sup>3</sup>	TWA: 200 ppm	TWA: 590 mg/m <sup>3</sup>
	Skin	(Vacated) STEL: 250 ppm	TWA: 590 mg/m <sup>3</sup>	STEL: 250 ppm
		(Vacated) STEL: 735 mg/m <sup>3</sup>	STEL: 250 ppm	STEL: 735 mg/m <sup>3</sup>
		TWA: 200 ppm	STEL: 735 mg/m <sup>3</sup>	_
		TWA: 590 mg/m <sup>3</sup>		

### **Legend**

ACGIH - American Conference of Governmental Industrial Hygienists OSHA - Occupational Safety and Health Administration NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

**Engineering Measures**Use only under a chemical fume hood. Ensure that eyewash stations and safety showers

are close to the workstation location. Use explosion-proof electrical/ventilating/lighting

equipment. Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

**Eye/face Protection** Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

**Skin and body protection**Wear appropriate protective gloves and clothing to prevent skin exposure.

\_\_\_\_\_

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State Liquid

Appearance
Odor
No information available

Melting Point/Range No data available

Boiling Point/Range 67 °C / 152.6 °F @ 760 mmHg

Flash Point -19 °C / -2.2 °F
Evaporation Rate No information available
Flammability (solid,gas) Not applicable

Flammability or explosive limits

Upper No data available
Lower No data available
Vapor Pressure No information available
Vapor Density No information available

Specific Gravity 0.934

Solubility
Water reactive
Partition coefficient; n-octanol/water
Autoignition Temperature
Decomposition Temperature
Viscosity
Water reactive
No data available
No information available
No information available
No information available

10. Stability and reactivity

Reactive Hazard None known, based on information available

**Stability** May form explosive peroxides.

Conditions to Avoid Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition.

Incompatible Materials Strong oxidizing agents

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2), Sulfur oxides

Hazardous Polymerization Hazardous polymerization does not occur.

**Hazardous Reactions** None under normal processing.

11. Toxicological information

**Acute Toxicity** 

**Product Information** 

Oral LD50 Category 4. ATE = 300 - 2000 mg/kg.

**Dermal LD50**Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg. **Vapor LC50**Based on ATE data, the classification criteria are not met. ATE > 20 mg/l.

**Component Information** 

 Component
 LD50 Oral
 LD50 Dermal
 LC50 Inhalation

 Tetrahydrofuran
 1650 mg/kg ( Rat )
 > 2000 mg/kg (Rabbit)
 180 mg/L ( Rat ) 1 h

 53.9 mg/L ( Rat ) 4 h
 53.9 mg/L ( Rat ) 4 h

**Toxicologically Synergistic** 

**Products** 

No information available

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation No information available

Sensitization No information available

Limited evidence of a carcinogenic effect. Carcinogenicity

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Tetrahydrofuran	109-99-9	Group 2B	Not listed	A3	X	A3
Lithium thiophenolate	2973-86-6	Not listed				

ACGIH: (American Conference of Governmental Industrial

A1 - Known Human Carcinogen A2 - Suspected Human Carcinogen

Hygienists)

A3 - Animal Carcinogen

ACGIH: (American Conference of Governmental Industrial Hygienists)

No information available **Mutagenic Effects** 

No information available. **Reproductive Effects** 

**Developmental Effects** No information available.

**Teratogenicity** No information available.

Respiratory system Central nervous system (CNS) STOT - single exposure

None known STOT - repeated exposure

No information available **Aspiration hazard** 

delayed

Symptoms / effects,both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Causes central nervous system depression

# **Endocrine Disruptor Information**

Component	EU - Endocrine Disrupters Candidate List	EU - Endocrine Disruptors - Evaluated Substances	Japan - Endocrine Disruptor Information
Tetrahydrofuran	Group III Chemical	Not applicable	Not applicable

**Other Adverse Effects** 

The toxicological properties have not been fully investigated.

# 12. Ecological information

### **Ecotoxicity**

No information available. Reacts with water so no ecotoxicity data for the substance is available.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Tetrahydrofuran	Not listed	2160 mg/l LC50 = 96 h	Not listed	EC50 48 h 3485 mg/l
		Pimephales promelas		EC50: >10000 mg/L/24h
		Leuciscus idus: LC50: 2820		_
		mg/L/48h		

Persistence and Degradability Persistence is unlikely based on information available.

**Bioaccumulation/ Accumulation** No information available.

**Mobility** Will likely be mobile in the environment due to its volatility.

Component	log Pow
Tetrahydrofuran	0.45

# 13. Disposal considerations

# **Waste Disposal Methods**

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Tetrahydrofuran - 109-99-9	U213	-

# 14. Transport information

DOT

**UN-No** UN2924

Proper Shipping Name Alcohols,n.o.s., (Ethanol, Methanol)
Technical Name Tetrahydrofuran, Lithium thiophenolate

Hazard Class 3 Subsidiary Hazard Class 8 Packing Group II

TDG

**UN-No** UN2924

**Proper Shipping Name** Flammable liquid, corrosive, n.o.s.

Hazard Class 3 Subsidiary Hazard Class 8 Packing Group II

<u>IATA</u>

**UN-No** UN2924

**Proper Shipping Name** Flammable liquid, corrosive, n.o.s.

Hazard Class 3
Subsidiary Hazard Class 8
Packing Group ||

IMDG/IMO

UN-No UN2924

**Proper Shipping Name** Flammable liquid, corrosive, n.o.s.

Hazard Class 3 Subsidiary Hazard Class 8 Packing Group II

# 15. Regulatory information

# **United States of America Inventory**

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Tetrahydrofuran	109-99-9	X	ACTIVE	-
Lithium thiophenolate	2973-86-6	=	=	-

# Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA - Per 40 CFR 751, Regulation of Certain Chemical Substances & Mixtures, Under TSCA Section 6(h) (PBT)

Not applicable

### TSCA 12(b) - Notices of Export

Component	CAS No	TSCA 12(b) - Notices of Export	
Tetrahydrofuran	109-99-9	Section 4, 1 % de minimus concentration	

### **International Inventories**

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Tetrahydrofuran	109-99-9	Χ	-	203-726-8	Χ	Χ	Χ	Χ	Χ	KE-33454
Lithium thiophenolate	2973-86-6	-	-	-	-	-		-	-	-

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

# U.S. Federal Regulations

SARA 313 Not applicable

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act) Not applicable

Clean Air Act Not applicable

**OSHA** - Occupational Safety and

**Health Administration** 

Not applicable

**CERCLA** This material, as supplied, contains one or more substances regulated as a hazardous

substance under the Comprehensive Environmental Response Compensation and Liability

Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Tetrahydrofuran	1000 lb	-

# **California Proposition 65**

This product contains the following Proposition 65 chemicals.

Component	CAS No	California Prop. 65	Prop 65 NSRL	Category
Tetrahydrofuran	109-99-9	Carcinogen	-	Carcinogen

# U.S. State Right-to-Know

Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Tetrahydrofuran	X	X	X	-	X

# **U.S. Department of Transportation**

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

# U.S. Department of Homeland

Security

This product does not contain any DHS chemicals.

# Other International Regulations

Mexico - Grade Serious risk, Grade 3

# Authorisation/Restrictions according to EU REACH

Component		REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	
Tetrahydrofuran	-	Use restricted. See item 75. (see link for restriction details)	-

https://echa.europa.eu/substances-restricted-under-reach

# Safety, health and environmental regulations/legislation specific for the substance or mixture

Component CAS No OECD HPV Persistent Organic Ozone Depletion Restriction of
---

			Pollutant	Potential	Hazardous Substances (RoHS)
Tetrahydrofuran	109-99-9	Listed	Not applicable	Not applicable	Not applicable
Lithium thiophenolate	2973-86-6	Not applicable	Not applicable	Not applicable	Not applicable

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Tetrahydrofuran	109-99-9	Not applicable	Not applicable	Not applicable	Not applicable
Lithium thiophenolate	2973-86-6	Not applicable	Not applicable	Not applicable	Not applicable

1	6	Ot	ha	· ir	fo	rn	12+	ion	
_	<b>(</b> ).	()I		- 11	11 ( )		141	1()1	

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 03-Aug-2010

 Revision Date
 23-Feb-2022

 Print Date
 23-Feb-2022

Revision Summary

This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Harmonized System of Classification and Labeling of Chemicals (GHS).

### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**