

SAFETY DATA SHEET

Creation Date 01-Feb-2010 Revision Date 09-May-2025 Revision Number 10

1. Identification

Product Name Formaldehyde, 37 wt% solution, stabilized with methanol

Cat No.: AC119690000; AC119690010; AC119690025; AC119690050;

AC119690250

Synonyms Formalin; Formol; Methanal

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Fair Lawn, NJ 07410

Tel: (201) 796-7100

Emergency Telephone Number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Category 4 Flammable liquids Acute oral toxicity Category 3 Category 3 Acute dermal toxicity Acute Inhalation Toxicity - Vapors Category 3 Skin Corrosion/Irritation Category 1 B Serious Eye Damage/Eye Irritation Category 1 Skin Sensitization Category 1 Category 2 Germ Cell Mutagenicity Category 1A Carcinogenicity Specific target organ toxicity (single exposure) Category 1 Target Organs - Respiratory system, Central nervous system (CNS), Optic nerve.

Label Elements

Signal Word

Danger

Hazard Statements

Combustible liquid

Causes severe skin burns and eye damage

May cause respiratory irritation

May cause an allergic skin reaction

Suspected of causing genetic defects

May cause cancer

Causes damage to organs

Toxic if swallowed, in contact with skin or if inhaled



Precautionary Statements

Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Do not breathe dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep cool

Response

Immediately call a POISON CENTER or doctor/physician

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Skin

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

If skin irritation or rash occurs: Get medical advice/attention

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Ingestion

Rinse mouth

Do NOT induce vomiting

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other hazards

Poison, may be fatal or cause blindness if swallowed. Vapor harmful. CANNOT BE MADE NON-POISONOUS. WARNING. Cancer and Reproductive Harm - https://www.p65warnings.ca.gov/.

3. Composition/information on Ingredients

Component	CAS No	Weight %
Water	7732-18-5	40-46
Formaldehyde	50-00-0	35-41
Methyl alcohol	67-56-1	5-14

4. First-aid measures

General Advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In

the case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

Inhalation If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim

ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Remove to fresh

air. Immediate medical attention is required.

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately.

Most important symptoms and

effects

Causes burns by all exposure routes. May cause allergic skin reaction. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Ingestion causes severe swelling,

severe damage to the delicate tissue and danger of perforation

Notes to Physician Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media Water mist may be used to cool closed containers. CO 2, dry chemical, dry sand,

alcohol-resistant foam.

Unsuitable Extinguishing Media No information available

Flash Point 63 - 75 °C / 145.4 - 167 °F

Method - No information available

Autoignition Temperature 424 °C / 795.2 °F

Explosion Limits

Upper 73 vol % **Lower** 7 vol %

Sensitivity to Mechanical Impact No information available **Sensitivity to Static Discharge** No information available

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Combustible material. Containers may explode when heated.

Hazardous Combustion Products

Formic acid. Oxygen from the air can oxidize formaldehyde to formic acid, especially when heated. Carbon monoxide (CO). Carbon dioxide (CO₂).

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health	Flammability	Instability	Physical hazards
3	2	0	N/A

6. Accidental release measures

Personal Precautions Use personal protective equipment as required. Ensure adequate ventilation. Evacuate

personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all

sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions Do not flush into surface water or sanitary sewer system.

Methods for Containment and Clean Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. **Up**Remove all sources of ignition.

	7. Handling and Storage
Handling	Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition.

Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area. Keep away from heat, sparks and flame. Incompatible Materials. Strong oxidizing agents. Potassium permanganate. Peroxides. Perchloric acid + aniline. Strong bases. Sodium hydroxide. Ammonia. Hydroxides. Sodium bisulfite. Strong acids. Hydrogen chloride.

Isocyanates. Acid anhydrides. Magnesium carbonates. Iodine.

8. Exposure controls / personal protection

Exposure Guidelines

Storage.

Component	ACGIH TLV	OSHA PEL NIOSH		Mexico OEL (TWA)
Formaldehyde	TWA: 0.1 ppm	(Vacated) TWA: 3 ppm	IDLH: 20 ppm	Ceiling: 0.3 ppm
	STEL: 0.3 ppm	(Vacated) STEL: 10 ppm	REL = 0.016 ppm (TWA)	
		(Vacated) Ceiling: 5 ppm	Ceiling: 0.1 ppm	
		TWA: 0.75 ppm		
		STEL: 2 ppm		
Methyl alcohol	TWA: 200 ppm	(Vacated) TWA: 200 ppm	IDLH: 6000 ppm	TWA: 200 ppm
	STEL: 250 ppm	(Vacated) TWA: 260 mg/m ³	REL = 200 ppm (TWA)	STEL: 250 ppm
	Skin	(Vacated) STEL: 250 ppm	$REL = 260 \text{ mg/m}^3 \text{ (TWA)}$	
		(Vacated) STEL: 325 mg/m ³	STEL: 250 ppm	
		Skin	STEL: 325 mg/m ³	
		TWA: 200 ppm		
		TWA: 260 mg/m ³		

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures Use only under a chemical fume hood. Ensure that eyewash stations and safety showers

are close to the workstation location. Use explosion-proof electrical/ventilating/lighting

equipment. Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face ProtectionWear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

Skin and body protectionWear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Recommended Filter type: Organic gases and vapours filter. Type A. Brown. conforming to EN14387.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical StateLiquidAppearanceColorlessOdorIrritating pungent

Odor Threshold 0.8 - 1 ppm pH 3-4.2

Melting Point/Range -15 °C / 5 °F

 Boiling Point/Range
 97 °C / 206.6 °F @ 760 mmHg

 Flash Point
 63 - 75 °C / 145.4 - 167 °F

Evaporation Rate No information available

Flammability (solid,gas) Not applicable

Flammability or explosive limits

 Upper
 73 vol %

 Lower
 7 vol %

Vapor Pressure 2 mbar @ 20 °C

Vapor Density> 1.0Specific Gravity1.083Solubilitymiscible

Partition coefficient; n-octanol/water

No data available

424 °C / 795.2 °F

Decomposition Temperature > 150°C

Viscosity 1.0 mPas @ 20°C

Molecular FormulaC H2 OMolecular Weight30.02

10. Stability and reactivity

Reactive Hazard None known, based on information available

Stability Stable under normal conditions. Stabilized with Methanol. Hazardous polymerization may

occur upon depletion of inhibitor.

Conditions to Avoid Temperatures above 65°C. Keep away from open flames, hot surfaces and sources of

ignition.

Incompatible Materials Strong oxidizing agents, Potassium permanganate, Peroxides, Perchloric acid + aniline,

Strong bases, Sodium hydroxide, Ammonia, Hydroxides, Sodium bisulfite, Strong acids, Hydrogen chloride, Isocyanates, Acid anhydrides, Magnesium carbonates, Iodine

Hazardous Decomposition Products Formic acid, Oxygen from the air can oxidize formaldehyde to formic acid, especially when

heated, Carbon monoxide (CO), Carbon dioxide (CO2)

Hazardous Polymerization Hazardous polymerization may occur upon depletion of inhibitor.

Hazardous Reactions None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information

 Oral LD50
 Category 3. ATE = 50 - 300 mg/kg.

 Dermal LD50
 Category 3. ATE = 200 - 1000 mg/kg.

 Vapor LC50
 Category 3. ATE = 2 - 10 mg/l.

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Water	-	-	-
Formaldehyde	500 mg/kg (Rat)	LD50 = 270 mg/kg (Rabbit)	0.578 mg/L (Rat) 4 h
Methyl alcohol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg (Rabbit)	LC50 = 128.2 mg/L (Rat) 4 h

Toxicologically Synergistic

No information available

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Causes burns by all exposure routes

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Water	7732-18-5	Not listed				
Formaldehyde	50-00-0	Group 1	Known	A1	X	A2
Methyl alcohol	67-56-1	Not listed				

IARC (International Agency for Research on Cancer)

NTP: (National Toxicity Program)

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human

Carcinogen

ACGIH: (American Conference of Governmental Industrial

Mexico - Occupational Exposure Limits - Carcinogens

Hygienists)

A1 - Known Human Carcinogen

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

ACGIH: (American Conference of Governmental Industrial Hygienists)

Mexico - Occupational Exposure Limits - Carcinogens

A1 - Confirmed Human Carcinogen A2 - Suspected Human Carcinogen

A3 - Confirmed Animal Carcinogen

A4 - Not Classifiable as a Human Carcinogen

A5 - Not Suspected as a Human Carcinogen

Mutagenic Effects Mutagenic effects have occurred in humans.

Reproductive Effects

No information available.

Developmental Effects

No information available.

Teratogenicity No information available.

Formaldehyde, 37 wt% solution, stabilized with methanol

STOT - single exposure

Respiratory system Central nervous system (CNS) Optic nerve

STOT - repeated exposure

None known

Aspiration hazard

No information available

Symptoms / effects,both acute and Product is a corrosive material. Use of gastric lavage or emesis is contraindicated.

delayed

Possible perforation of stomach or esophagus should be investigated: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Ingestion

causes severe swelling, severe damage to the delicate tissue and danger of perforation

Endocrine Disruptor Information No information available

Other Adverse Effects

The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

The product contains following substances which are hazardous for the environment. Contains a substance which is:. Toxic to aquatic organisms.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Formaldehyde	EC50 (72h) = 4.89 mg/L	Leuciscus idus: LC50 = 15	Not listed	EC50 = 20 mg/L 96h
_	(Desmodesmus	mg/L 96h		EC50 = 2 mg/L 48 h
	subspicatus)			
Methyl alcohol	Not listed	Pimephales promelas: LC50	EC50 = 39000 mg/L 25 min	EC50 > 10000 mg/L 24h
•		> 10000 mg/L 96h	EC50 = 40000 mg/L 15 min	_
		_	EC50 = 43000 mg/L 5 min	

Persistence and Degradability

Soluble in water Persistence is unlikely based on information available. Miscible with water

Bioaccumulation/ Accumulation

No information available.

Mobility

. Will likely be mobile in the environment due to its water solubility.

Component	log Pow
Formaldehyde	-0.35
Methyl alcohol	-0.74

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Formaldehyde - 50-00-0	U122	-
Methyl alcohol - 67-56-1	U154	-

14. Transport information

DOT

UN-No UN2209

Proper Shipping Name FORMALDEHYDE SOLUTIONS

Hazard Class 8
Packing Group III

TDG

UN-No UN2209

Proper Shipping Name FORMALDEHYDE SOLUTION

Hazard Class 8
Packing Group III

Formaldehyde, 37 wt% solution, stabilized with methanol

IATA

UN-No UN2209

Proper Shipping Name FORMALDEHYDE SOLUTION

Hazard Class 8
Packing Group III

IMDG/IMO

UN-No UN2209

Proper Shipping Name FORMALDEHYDE SOLUTION

Hazard Class 8
Packing Group III

15. Regulatory Information

United States of America Inventory

	Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
	Water	7732-18-5	Χ	ACTIVE	-
Γ	Formaldehyde	50-00-0	X	ACTIVE	-
Γ	Methyl alcohol	67-56-1	Χ	ACTIVE	-

Leaend

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA - Per 40 CFR 751, Regulation of Certain Chemical Substances & Mixtures, Under TSCA Section 6(h) (PBT)

Not applicable

oubstances a mixtures, order 100% occito

Not applicable

TSCA 12(b) - Notices of Export

International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Water	7732-18-5	Х	-	231-791-2	Х	Х		Х	Х	KE-35400
Formaldehyde	50-00-0	Х	-	200-001-8	Х	Х	Х	Х	Х	KE-17074
Methyl alcohol	67-56-1	X	-	200-659-6	Х	Х	Х	X	Х	KE-23193

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

U.S. Federal Regulations

SARA 313

Component	CAS No	Weight %	SARA 313 - Threshold Values %	SARA 313 - Reporting threasholds
Formaldehyde	50-00-0	35-41	0.1 %	-
Methyl alcohol	67-56-1	5-14	1.0 %	-

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Formaldehyde	Χ	100 lb	-	-

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Formaldehyde	X		-
Methyl alcohol	X		-

OSHA - Occupational Safety and

Not applicable

Health Administration

Component	Specifically Regulated Chemicals	Highly Hazardous Chemicals
Formaldehyde	2 ppm STEL 0.5 ppm Action Level 0.75 ppm TWA	TQ: 1000 lb

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

Component	Hazardous Substances RQs	CERCLA Extremely Hazardous Substances RQs	SARA Reportable Quantity (RQ)
Formaldehyde	100 lb	100 lb	100 lb 45.4 kg
Methyl alcohol	5000 lb	-	5000 lb 2270 kg

California Proposition 65

This product contains the following Proposition 65 chemicals.

	Component	CAS No	California Prop. 65	Prop 65 NSRL	Category	
ſ	Formaldehyde	50-00-0	Carc. (Gaseous only)	40 μg/day	Carcinogen	
ſ	Methyl alcohol	67-56-1	Developmental	-	Developmental	

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Water	-	-	X	-	-
Formaldehyde	X	Х	X	X	X
Methyl alcohol	X	Х	X	Х	Х

U.S. Department of Transportation

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland

This product contains the following DHS chemicals:

Security Legend - STQs = Screening Threshold Quantities, APA = A placarded amount

Component	DHS Chemical Facility Anti-Terrorism Standard
Formaldehyde	Release STQs - 15000lb (solution)

Other International Regulations

Mexico - Grade Moderate risk, Grade 2

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) -	REACH (1907/2006) -	REACH Regulation (EC
_		Annex XIV - Substances	Annex XVII - Restrictions	1907/2006) article 59 -
		Subject to Authorization	on Certain Dangerous	Candidate List of

			Substances	Substances of Very High Concern (SVHC)
Water	7732-18-5	-	-	-
Formaldehyde	50-00-0	-	Use restricted. See entry 72.	-
			(see link for restriction details)	
			Use restricted. See entry 77.	
			(see link for restriction details)	
			Use restricted. See entry 28.	
			(see link for restriction details)	
			Use restricted. See entry 75.	
			(see link for restriction details)	
Methyl alcohol	67-56-1	-	Use restricted. See entry	-
			69. (see link for restriction	
			details)	
			Use restricted. See entry	
			75. (see link for restriction	
			(see link for restriction details)	

REACH links

https://echa.europa.eu/substances-restricted-under-reach

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Water	7732-18-5	Listed	Not applicable	Not applicable	Not applicable
Formaldehyde	50-00-0	Listed	Not applicable	Not applicable	Not applicable
Methyl alcohol	67-56-1	Listed	Not applicable	Not applicable	Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Other International Regulations

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Water	7732-18-5	Not applicable	Not applicable	Not applicable	Not applicable
Formaldehyde	50-00-0	5 tonne	50 tonne	Not applicable	Not applicable
Methyl alcohol	67-56-1	500 tonne	5000 tonne	Not applicable	Not applicable

16. Other Information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 01-Feb-2010

 Revision Date
 09-May-2025

 Print Date
 09-May-2025

Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS