

Page 1 / 10 Revision Date 26-Mar-2025 Version 4

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THECOMPANY/UNDERTAKING

Product Identifier

Perihalan Produk: Methyl acrylate
Product Description: Methyl acrylate

Cat No. : A13128

Synonyms Methyl 2-propenoate

CAS No 96-33-3 Molecular Formula C4 H6 O2

Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

Company Thermo Fisher Scientific Fisher Scientific (M) Sdn Bhd

Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square, No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,

Selangor Darul Ehsan, Malaysia. Main line: +60 3-5525 7888

Supplier

E-mail address Enquiry.my@thermofisher.com

Emergency Telephone Number Tel: +03-5525 7888

CHEMTREC Malaysia 1-800-815-308 (Malay)

CHEMTREC Malaysia (Kuala Lumpur) +(60)-327884561 (Malay)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

Flammable liquids	Category 2 (H225)
Acute oral toxicity	Category 4 (H302)
Acute dermal toxicity	Category 4 (H312)
Acute Inhalation Toxicity - Vapors	Category 3 (H331)
Skin Corrosion/Irritation	Category 2 (H315)
Serious Eye Damage/Eye Irritation	Category 2 (H319)
Skin Sensitization	Category 1 (H317)
Specific target organ toxicity - (single exposure)	Category 3 (H335)
Chronic aquatic toxicity	Category 3 (H412)

Label Elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H302 + H312 - Harmful if swallowed or in contact with skin

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H331 - Toxic if inhaled

H335 - May cause respiratory irritation

H412 - Harmful to aquatic life with long lasting effects

Precautionary Statements

Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P240 - Ground and bond container and receiving equipment

P241 - Use explosion-proof electrical/ ventilating/ lighting equipment

P270 - Do not eat, drink or smoke when using this product

P271 - Use only outdoors or in a well-ventilated area

P272 - Contaminated work clothing should not be allowed out of the workplace

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P242 - Use non-sparking tools

P243 - Take action to prevent static discharges

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P264 - Wash face, hands and any exposed skin thoroughly after handling

Response

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P311 - Call a POISON CENTER or doctor

P330 - Rinse mouth

P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

P362 + P364 - Take off contaminated clothing and wash it before reuse

Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other Hazards

Lachrymator (substance which increases the flow of tears)

Stench

Toxicity to Soil Dwelling Organisms

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No	Weight %
Methyl acrylate	96-33-3	>95
4-Methoxyphenol	150-76-5	0.001-0.002

SECTION 4: FIRST AID MEASURES

Description of first aid measures

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

Skin Contact Get medical attention. Wash off immediately with plenty of water for at least 15 minutes.

Ingestion Do NOT induce vomiting. Get medical attention.

Inhalation Remove to fresh air. Get medical attention. If not breathing, give artificial respiration.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Difficulty in breathing. May cause allergic skin reaction. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing.

pain or nushing

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media

Water spray. Carbon dioxide (CO 2). Dry chemical. Chemical foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

No information available.

Special hazards arising from the substance or mixture

Flammable. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO2).

Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Methyl acrylate Revision Date 26-Mar-2025

Personal Precautions, Protective Equipment and Emergency Procedures

Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental precautions

Do not flush into surface water or sanitary sewer system.

Methods and Material for Containment and Cleaning Up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Prevent product from entering drains. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Do not flush into surface water or sanitary sewer system.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Avoid contact with skin and eyes. Wear personal protective equipment/face protection. Do not breathe mist/vapors/spray. Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. Use only non-sparking tools. Keep away from open flames, hot surfaces and sources of ignition. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Conditions for Safe Storage, Including any Incompatibilities

To maintain product quality Refrigerator/flammables. Keep container tightly closed. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Specific End Uses

Use in laboratories.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	Malaysia	ACGIH TLV	OSHA PEL
Methyl acrylate		TWA: 2 ppm	(Vacated) TWA: 10 ppm
		Skin	(Vacated) TWA: 35 mg/m ³
			Skin
			TWA: 10 ppm
			TWA: 35 mg/m ³
4-Methoxyphenol		TWA: 5 mg/m ³	(Vacated) TWA: 5 mg/m ³

Component	European Union	The United Kingdom	Germany
Methyl acrylate	TWA: 5 ppm (8h)	STEL: 10 ppm 15 min	TWA: 2 ppm (8 Stunden). AGW -
	TWA: 18 mg/m ³ (8h)	STEL: 36 mg/m ³ 15 min	exposure factor 2
	STEL: 10 ppm (15min)	TWA: 5 ppm 8 hr	TWA: 7.1 mg/m³ (8 Stunden). AGW
	STEL: 36 mg/m ³ (15min)	TWA: 18 mg/m ³ 8 hr	 exposure factor 2
			TWA: 2 ppm (8 Stunden). MAK
			even if the MAK value is adhered to,
			"odor-associated" symptoms cannot
			be ruled out in individual cases
			TWA: 7.1 mg/m³ (8 Stunden). MAK
			even if the MAK value is adhered to,
			"odor-associated" symptoms cannot
			be ruled out in individual cases
			Höhepunkt: 4 ppm

Methyl acrylate Revision Date 26-Mar-2025

	Höhepunkt: 14.2 mg/m ³
	Haut

Exposure Controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles Hand Protection Protective gloves

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators

Recommended Filter type: Particulates filter conforming to EN 143 Acid gases filter Type E Yellow conforming to

EN14387

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

When RPE is used a face piece Fit Test should be conducted

Handle in accordance with good industrial hygiene and safety practice

Environmental exposure controls Prevent product from entering drains Do not allow material to contaminate ground water

system

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance Colorless
Physical State Liquid
Odor Stench

Odor Threshold

Ph

No data available

No information available

Melting Point/Range-75 °C / -103 °FSoftening PointNo data availableBoiling Point/Range80 °C / 176 °F

Boiling Point/Range80 °C / 176 °F@ 760 mmHgFlash Point-3 °C / 26.6 °FMethod - No information available

Evaporation Rate No data available

Flammability (solid,gas) Not applicable Liquid

Explosion Limits Lower 2.8 Vol%

Methyl acrylate Revision Date 26-Mar-2025

Upper 25 Vol%

Vapor Pressure
No data available

Vapor Density No data available (Air = 1.0)

Specific Gravity / Density 0.956

Bulk Density
Not applicable
Water Solubility
Not applicable
60 g/l (20°C)

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Componentlog PowMethyl acrylate0.7394-Methoxyphenol1.3

Autoignition Temperature

Decomposition Temperature Viscosity

Explosive Properties
Oxidizing Properties

463 °C / 865.4 °F No data available

Dynamic 0.50 mPa.s at 20 °C

No information available

Molecular FormulaC4 H6 O2Molecular Weight86.09

SECTION 10: STABILITY AND REACTIVITY

Reactivity

None known, based on information available.

Chemical Stability

Light sensitive. Hazardous polymerization does not occur. Hazardous polymerization may

Vapors may form explosive mixtures with air

Liquid

occur upon depletion of inhibitor.

Possibility of Hazardous Reactions

Hazardous Polymerization Hazardous Reactions

Hazardous polymerization may occur upon depletion of inhibitor.

No information available.

Conditions to Avoid

Keep away from open flames, hot surfaces and sources of ignition. Excess heat. Exposure

to light. Incompatible products.

Incompatible Materials

Acids. Bases. Peroxides.

Hazardous Decomposition Products

Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects

Product Information

(a) acute toxicity;

Oral Category 4 Dermal Category 4 Inhalation Category 3

Component	LD50 Oral LD50 Dermal L		LC50 Inhalation
Methyl acrylate	LD50 = 277 mg/kg (Rat)	LD50 = 1243 mg/kg (Rabbit)	LC50 = 3.58 mg/L (Rat) 4 h
4-Methoxyphenol	1600 mg/kg (Rat)	LD50 > 2000 mg/kg (Rabbit)	-

(b) skin corrosion/irritation; Category 2

Category 2 (c) serious eye damage/irritation;

(d) respiratory or skin sensitization;

Respiratory Based on available data, the classification criteria are not met

Skin Category 1

May cause sensitization by skin contact

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

Based on available data, the classification criteria are not met (f) carcinogenicity;

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Methyl acrylate				Group 2B

Based on available data, the classification criteria are not met (g) reproductive toxicity;

(h) STOT-single exposure; Category 3

Results / Target organs Respiratory system.

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

None known. **Target Organs**

(j) aspiration hazard; Based on available data, the classification criteria are not met

delayed

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest

pain, muscle pain or flushing.

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any

known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity effects The product contains following substances which are hazardous for the environment.

Contains a substance which is:. Toxic to aquatic organisms.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Methyl acrylate	LC50: = 1.81 mg/L, 96h semi-static (Oncorhynchus mykiss) LC50: = 2.11 mg/L, 96h flow-through (Pimephales promelas)	EC50: = 2.2 mg/L, 48h (Daphnia magna)	EC50: <= 46.78 mg/L, 96h static (Pseudokirchneriella subcapitata) EC50: = 15 mg/L, 72h (Desmodesmus subspicatus)	EC50 = 260 mg/L 17 h
4-Methoxyphenol	LC50: = 28.5 mg/L, 96h flow-through (Oncorhynchus mykiss) LC50: = 84.3 mg/L, 96h flow-through (Pimephales promelas)			EC50 = 3.66 mg/L 5 min EC50 = 4.30 mg/L 15 min EC50 = 4.61 mg/L 30 min

Persistence and degradability

Persistence

Degradation in sewage treatment plant

Readily biodegradable

Persistence is unlikely, based on information available.

Contains substances known to be hazardous to the environment or not degradable in waste

water treatment plants.

Bioaccumulative potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Methyl acrylate	0.739	No data available
4-Methoxyphenol	1.3	No data available

Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all

surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in

air.

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

Other adverse effects No information available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from Residues/Unused

Products

Waste is classified as hazardous Dispose of in accordance with the European Directives on waste and hazardous waste Dispose of in accordance with local regulations

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous Keep product and

empty container away from heat and sources of ignition

Other Information Do not flush to sewer Waste codes should be assigned by the user based on the

application for which the product was used Can be landfilled or incinerated, when in compliance with local regulations Do not let this chemical enter the environment Do not

empty into drains

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

UN-No UN1919
Hazard Class 3
Packing Group II

Proper Shipping Name METHYL ACRYLATE, STABILIZED

Road and Rail Transport

UN-No UN1919 Hazard Class 3 Packing Group II

Proper Shipping Name METHYL ACRYLATE, STABILIZED

IATA

UN-No UN1919
Hazard Class 3
Packing Group II

Proper Shipping Name METHYL ACRYLATE, STABILIZED

Special Precautions for User Inhibitors have been added to stabilize this product Inhibitor levels should be maintained

Hazardous polymerization may occur upon depletion of inhibitor

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories X = listed

Component	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	IECSC	AICS	KECL
Methyl acrylate	202-500-6	Х	Х	X	Х	X	Х	Х	KE-29592
4-Methoxyphenol	205-769-8	Х	Х	Х	Х	Х	X	Х	KE-23353

Component	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Methyl acrylate	500 tonne	2000 tonne	•	

National Regulations

Persistent Organic Pollutant This process of the Pollutant This pr

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 16: OTHER INFORMATION

Legend

Methyl acrylate Revision Date 26-Mar-2025

CAS - Chemical Abstracts Service

WEL - Workplace Exposure Limit

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic

Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TWA - Time Weighted Average

ACGIH - American Conference of Governmental Industrial Hygienists

RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50% POW - Partition coefficient Octanol:Water IARC - International Agency for Research on Cancer

NZIoC - New Zealand Inventory of Chemicals

LD50 - Lethal Dose 50%

Substances List

EC50 - Effective Concentration 50%

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air **Transport Association**

MARPOL - International Convention for the Prevention of Pollution from

Ships

ATE - Acute Toxicity Estimate VOC - (Volatile Organic Compound)

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Health, Safety and Environmental Department **Prepared By**

Revision Date 26-Mar-2025

SDS sections updated, 2, 3, 7, 9, 14. **Revision Summary**

In accordance with local and national regulations: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet