

Creation Date 15-Nov-2011 Revision Date 10-Dec-2021 Revision Number 3

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: BactiDrop Ninhydrin Reagent TM

Cat No. : R21534

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals. Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company Oxoid Ltd

Wade Road

Basingstoke, Hants, UK

RG24 8PW

Tel: +44 (0) 1256 841144

EU entity/business name Oxoid Deutschland GmbH

Postfach 10 07 53

D-46483 Wesel GERMANY

Tel: + 49 (0) 281 1520 Fax: 49 (0) 281 1521

E-mail address mbd-sds@thermofisher.com

1.4. Emergency telephone number

Chemtrec EU: 001-703-527-3887 Chemtrec US: (800) 424-9300

For customers in Switzerland:

Tox Info Suisse Emergency Number: 145 (24hr)

Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)

Chemtrec (24h) Toll-Free: 0800 564 402 Chemtrec Local: +41-43 508 20 11 (Zurich)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

BactiDrop Ninhydrin Reagent TM

Revision Date 10-Dec-2021

Flammable liquids Category 2 (H225)

Health hazards

Acute oral toxicity

Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Specific target organ toxicity - (single exposure)

Category 4 (H302)

Category 2 (H315)

Category 1 (H318)

Category 3 (H335) (H336)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H302 - Harmful if swallowed

H315 - Causes skin irritation

H318 - Causes serious eye damage

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements

P301 + P330 + P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting

P332 + P313 - If skin irritation occurs: Get medical advice/attention

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/physician

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

2.3. Other hazards

Toxic to terrestrial vertebrates

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

BactiDrop Ninhydrin Reagent TM

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Acetone	67-64-1	EEC No. 200-662-2	48.25	Flam. Liq. 2 (H225) Eye Irrit. 2 (H319) STOT SE 3 (H336) EUH066
1-Butanol	71-36-3	EEC No. 200-751-6	48.25	Flam. Liq. 3 (H226) Acute Tox. 4 (H302) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) STOT SE 3 (H335) STOT SE 3 (H336)
1H-Indene-1,3(2H)-dione, 2,2-dihydroxy-	485-47-2	EEC No. 207-618-1	3.5	STOT SE 3 (H335) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Acute Tox. 4 (H302)

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice If symptoms persist, call a physician.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

Ingestion Clean mouth with water and drink afterwards plenty of water.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Causes eye burns. Causes severe eye damage. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

BactiDrop Ninhydrin Reagent TM

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon oxides.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Should not be released into the environment. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep away from heat, sparks and flame.

Technical Rules for Hazardous Substances (TRGS) 510 Class 3 **Storage Class (LGK) (Germany)**

Revision Date 10-Dec-2021

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): EU - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC UK - EH40/2005 Work Exposure Limits, Third edition. Published 2018. IRE - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. CH - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am arbeitplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Acetone	TWA: 500 ppm (8h)	TWA: 500 ppm	TWA / VME: 500 ppm (8	TWA: 500 ppm 8 uren	TWA / VLA-ED: 500
	TWA: 1210 mg/m³ (8h)	TWA: 1210 mg/m ³	heures). restrictive limit	TWA: 1210 mg/m ³ 8	ppm (8 horas)
		STEL: 1500 ppm	TWA / VME: 1210	uren	TWA / VLA-ED: 1210
		STEL: 3620 mg/m ³	mg/m³ (8 heures).	STEL: 1000 ppm 15	mg/m³ (8 horas)
			restrictive limit	minuten	
			STEL / VLCT: 1000	STEL: 2420 mg/m ³ 15	
			ppm. restrictive limit	minuten	
			STEL / VLCT: 2420		
			mg/m ³ . restrictive limit		
1-Butanol		50ppm STEL; 154mg/m ³		50ppm VLE; 154mg/m ³	STEL / VLA-EC: 50 ppm
		STEL	STEL / VLCT: 150	VLE	(15 minutos).
			mg/m³.		STEL / VLA-EC: 154
					mg/m³ (15 minutos).
					TWA / VLA-ED: 20 ppm
					(8 horas)
					TWA / VLA-ED: 61
					mg/m³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
Acetone	TWA: 500 ppm 8 ore.	TWA: 500 ppm	STEL: 750 ppm 15	STEL: 2420 mg/m ³ 15	TWA: 500 ppm 8
	Media Ponderata nel	TWA: 1200 mg/m ³	minutos	minuten	tunteina
	Tempo		TWA: 500 ppm 8 horas	TWA: 1210 mg/m ³ 8	TWA: 1200 mg/m ³ 8
	TWA: 1210 mg/m ³ 8		TWA: 1210 mg/m ³ 8	uren	tunteina
	ore. Media Ponderata		horas		STEL: 630 ppm 15
	nel Tempo				minuutteina
					STEL: 1500 mg/m ³ 15
					minuutteina
1-Butanol		100ppm TWA;	TWA: 20 ppm 8 horas	, ,,	TWA: 50 ppm 8 tunteina
		310mg/m³ TWA		STEL	TWA: 150 mg/m ³ 8
					tunteina
					STEL: 75 ppm 15
					minuutteina
					STEL: 230 mg/m ³ 15
					minuutteina
					lho

Component	Austria	Denmark	Switzerland	Poland	Norway
Acetone	MAK-KZGW: 2000 ppm	TWA: 250 ppm 8 timer	STEL: 1000 ppm 15	STEL: 1800 mg/m ³ 15	TWA: 125 ppm 8 timer
	15 Minuten	TWA: 600 mg/m ³ 8 timer	Minuten	minutach	TWA: 295 mg/m ³ 8 timer
	MAK-KZGW: 4800	_	STEL: 2400 mg/m ³ 15	TWA: 600 mg/m ³ 8	STEL: 156.25 ppm 15
	mg/m ³ 15 Minuten		Minuten	godzinach	minutter. value
	MAK-TMW: 500 ppm 8		TWA: 500 ppm 8	_	calculated
	Stunden		Stunden		STEL: 368.75 mg/m ³ 15
	MAK-TMW: 1200 mg/m ³		TWA: 1200 mg/m ³ 8		minutter. value
	8 Stunden		Stunden		calculated
1-Butanol	MAK-KZGW: 200 ppm	Ceiling: 50 ppm	STEL: 100 ppm 15	STEL: 150 mg/m ³ 15	Hud
	15 Minuten	Ceiling: 150 mg/m ³	Minuten	minutach	Ceiling: 25 ppm

BactiDrop Ninhydrin Reagent TM

Revision Date 10-Dec-2021

MAK-KZGW: 600 mg/m ³ 15 Minuten MAK-TMW: 50 ppm 8 Stunden MAK-TMW: 150 mg/m ³ 8 Stunden		STEL: 310 mg/m ³ 15 Minuten TWA: 100 ppm 8 Stunden TWA: 310 mg/m ³ 8 Stunden	TWA: 50 mg/m³ 8 godzinach	Ceiling: 75 mg/m ³
--	--	---	------------------------------	-------------------------------

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Acetone	TWA: 600 mg/m ³	TWA-GVI: 500 ppm 8	TWA: 500 ppm 8 hr.	Skin-potential for	TWA: 800 mg/m ³ 8
	STEL: 1400 mg/m ³	satima.	TWA: 1210 mg/m ³ 8 hr.	cutaneous absorption	hodinách.
		TWA-GVI: 1210 mg/m ³	STEL: 1500 ppm 15 min	TWA: 500 ppm	Ceiling: 1500 mg/m ³
		8 satima.	STEL: 3630 mg/m ³ 15	TWA: 1210 mg/m ³	
			min	_	
1-Butanol	TWA: 100 mg/m ³	kože	TWA: 20 ppm 8 hr.		TWA: 300 mg/m ³ 8
	STEL: 150 mg/m ³	STEL-KGVI: 50 ppm 15	STEL: 60 ppm 15 min		hodinách.
		minutama.	Skin		Potential for cutaneous
		STEL-KGVI: 154 mg/m ³			absorption
		15 minutama.			Ceiling: 600 mg/m ³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Acetone	TWA: 500 ppm 8 tundides. TWA: 1210 mg/m ³ 8 tundides.	TWA: 500 ppm 8 hr TWA: 1210 mg/m ³ 8 hr	STEL: 3560 mg/m³ TWA: 1780 mg/m³	TWA: 1210 mg/m³ 8 órában. AK	TWA: 250 ppm 8 klukkustundum. TWA: 600 mg/m³ 8 klukkustundum. Ceiling: 500 ppm Ceiling: 1200 mg/m³
1-Butanol	Nahk TWA: 15 ppm 8 tundides. TWA: 45 mg/m³ 8 tundides. STEL: 30 ppm 15 minutites. STEL: 90 mg/m³ 15 minutites.		skin - potential for cutaneous absorption STEL: 100 ppm STEL: 300 mg/m³ TWA: 100 ppm TWA: 300 mg/m³	STEL: 90 mg/m ³ 15 percekben. CK TWA: 45 mg/m ³ 8 órában. AK lehetséges borön keresztüli felszívódás	STEL: 50 ppm STEL: 150 mg/m ³ Skin notation

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Acetone	TWA: 500 ppm	TWA: 500 ppm IPRD	TWA: 500 ppm 8	TWA: 500 ppm	TWA: 500 ppm 8 ore
	TWA: 1210 mg/m ³	TWA: 1210 mg/m ³	Stunden	TWA: 1210 mg/m ³	TWA: 1210 mg/m ³ 8 ore
		IPRD	TWA: 1210 mg/m ³ 8	_	_
		STEL: 1000 ppm	Stunden		
		STEL: 2420 mg/m ³			
1-Butanol	TWA: 10 mg/m ³	Ceiling: 30 ppm			TWA: 33 ppm 8 ore
		Ceiling: 90 mg/m ³			TWA: 100 mg/m ³ 8 ore
		TWA: 15 ppm IPRD			STEL: 66 ppm 15
		TWA: 45 mg/m ³ IPRD			minute
		Oda			STEL: 200 mg/m ³ 15
					minute

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Acetone	TWA: 200 mg/m ³ 1763	TWA: 500 ppm	TWA: 500 ppm 8 urah	Indicative STEL: 500	TWA: 500 ppm 8 saat
	MAC: 800 mg/m ³	TWA: 1210 mg/m ³	TWA: 1210 mg/m ³ 8	ppm 15 minuter	TWA: 1210 mg/m ³ 8
			urah	Indicative STEL: 1200	saat
			STEL: 2420 mg/m ³ 15	mg/m ³ 15 minuter	
				TLV: 250 ppm 8 timmar.	
			STEL: 1000 ppm 15	NGV	
			minutah	TLV: 600 mg/m ³ 8	
				timmar. NGV	
1-Butanol	TWA: 10 mg/m ³ 0418	Ceiling: 310 mg/m ³	TWA: 100 ppm 8 urah	Binding STEL: 30 ppm	
	MAC: 30 mg/m ³	TWA: 100 ppm	TWA: 310 mg/m ³ 8 urah		
		TWA: 310 mg/m ³	STEL: 100 ppm 15	Binding STEL: 90	
			minutah	mg/m ³ 15 minuter	
			STEL: 310 mg/m ³ 15	TLV: 15 ppm 8 timmar.	
			minutah	NGV	
				TLV: 45 mg/m ³ 8	
				timmar. NGV	
				Hud	

BactiDrop Ninhydrin Reagent TM

Revision Date 10-Dec-2021

Biological limit values

List source(s):

Component	European Union	United Kingdom	France	Spain	Germany
Acetone			Acetone: 100 mg/L urine	Acetone: 50 mg/L urine	Acetone: 80 mg/L urine
			end of shift	end of shift	(end of shift)
1-Butanol					1-Butanol (after
					hydrolysis): 10 mg/g
					Creatinine urine (end of
					shift)
					1-Butanol (after
					hydrolysis): 2 mg/g
					Creatinine urine (before
					beginning of next shift)

Component	Italy	Finland	Denmark	Bulgaria	Romania
Acetone				Acetone: 80 mg/L urine	Acetone: 50 mg/L urine
				at the end of exposure	end of shift
				or end of work shift	

Component	Gibraltar	Latvia	Slovak Republic	Luxembourg	Turkey
Acetone			Acetone: 80 mg/L urine end of exposure or work shift		
1-Butanol			n-Butyl alcohol: 2 mg/g creatinine urine after all work shifts for long-term exposure n-Butyl alcohol: 10 mg/g creatinine urine end of exposure or work shift		

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Acetone 67-64-1 (48.25)				DNEL = 186mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Acetone 67-64-1 (48.25)	DNEL = 2420mg/m ³			DNEL = 1210mg/m ³
1-Butanol 71-36-3 (48.25)			DNEL = 310mg/m ³	

Predicted No Effect Concentration (PNEC)

See values below.

Component Fresh water Fresh water Water Intermittent Microorganisms in Soil (Agricultum

BactiDrop Ninhydrin Reagent TM

		sediment		sewage treatment	
Acetone	PNEC = 10.6mg/L	PNEC = 30.4mg/kg	PNEC = 21mg/L	PNEC = 100mg/L	PNEC = 29.5mg/kg
67-64-1 (48.25)		sediment dw			soil dw
1-Butanol	PNEC = 0.082mg/L	PNEC =	PNEC = 2.25mg/L	PNEC = 2476mg/L	PNEC =
71-36-3 (48.25)		0.324mg/kg			0.0166mg/kg soil
		sediment dw			dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Acetone	PNEC = 1.06mg/L	PNEC = 3.04mg/kg			
67-64-1 (48.25)	_	sediment dw			
1-Butanol	PNEC =	PNEC =			
71-36-3 (48.25)	0.0082mg/L	0.0324mg/kg			
		sediment dw			

8.2. Exposure controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

ſ	Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
١	Viton (R)	See manufacturers	-	EN 374	(minimum requirement)
-		recommendations			

Skin and body protection Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

141

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls No information available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

OXDR21534

BactiDrop Ninhydrin Reagent TM

Revision Date 10-Dec-2021

9.1. Information on basic physical and chemical properties

Physical State Liquid

Colourless - Light yellow **Appearance** Odor No information available **Odor Threshold** No data available **Melting Point/Range** No data available **Softening Point** No data available **Boiling Point/Range** Not applicable

Flammability (liquid) Highly flammable On basis of test data

Not applicable Flammability (solid,gas) Liquid

No data available **Explosion Limits**

Flash Point 18.889 °C / 66 °F Method - CC (closed cup)

Autoignition Temperature No data available **Decomposition Temperature** No data available No information available Hq No data available **Viscosity** No information available **Water Solubility** Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Component log Pow Acetone -0.241-Butanol 0.785

Vapor Pressure No data available **Density / Specific Gravity** No data available

Bulk Density Not applicable Liquid **Vapor Density** No data available (Air = 1.0)

Particle characteristics Not applicable (liquid)

9.2. Other information

Explosive Properties Vapors may form explosive mixtures with air

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity None known, based on information available

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous polymerization does not occur.

None under normal processing. **Hazardous Reactions**

10.4. Conditions to avoid

Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of

Page 9/15

ignition.

10.5. Incompatible materials

Strong oxidizing agents. Acids.

10.6. Hazardous decomposition products

Carbon oxides.

Revision Date 10-Dec-2021

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral Category 4

DermalBased on available data, the classification criteria are not metInhalationBased on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Acetone	5800 mg/kg (Rat)	> 15800 mg/kg (rabbit) > 7400 mg/kg (rat)	76 mg/l, 4 h, (rat)
1-Butanol	LD50 = 700 mg/kg (Rat)	LD50 = 3402 mg/kg (Rabbit)	LC50 > 8000 ppm (Rat) 4 h

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

Respiratory No data available Skin No data available

Component	Test method	Test species	Study result
Acetone	Guinea Pig Maximisation Test	guinea pig	non-sensitising
67-64-1 (48.25)	(GPMT)		_

As a precaution the product should be treated as a sensitizer

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

Component	Test method	Test species	Study result
Acetone	OECD Test Guideline 471	in vivo	negative
67-64-1 (48.25)	AMES test		
	OECD Test Guideline 476	in vitro	negative
	Mammalian		
	Gene cell mutation		

Mutagenic effects have occurred in experimental animals

(f) carcinogenicity; No data available

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; No data available

(h) STOT-single exposure; Category 3

Results / Target organsRespiratory system, Central nervous system (CNS).

(i) STOT-repeated exposure; No data available

BactiDrop Ninhydrin Reagent TM

Revision Date 10-Dec-2021

No information available. **Target Organs**

No data available (j) aspiration hazard;

delayed

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

11.2. Information on other hazards

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity **Ecotoxicity effects**

. Contains no substances known to be hazardous to the environment or that are not degradable in waste water treatment plants.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Acetone	Oncorhynchus mykiss: LC50 = 5540 mg/l 96h Alburnus alburnus: LC50 = 11000 mg/l 96h Leuciscus idus: LC50 = 11300 mg/L/48h Salmo gairdneri: LC50 = 6100 mg/L/24h	EC50 = 8800 mg/L/48h EC50 = 12700 mg/L/48h EC50 = 12600 mg/L/48h	NOEC = 430 mg/l (algae; 96 h)
1-Butanol	LC50: 1376 mg/L, 96h (Pimephales promelas) OECD Guideline 203: 100000 - 500000 µg/L, 96h static (Lepomis macrochirus) LC50: = 1740 mg/L, 96h flow-through (Pimephales promelas) LC50: = 1910000 µg/L, 96h static (Pimephales promelas) LC50: 1730 - 1910 mg/L, 96h static (Pimephales promelas)	EC50: 1897 - 2072 mg/L, 48h Static (Daphnia magna) EC50: = 1983 mg/L, 48h (Daphnia magna)	EC50: 225 mg/L, 96h (Pseudokirchneriella subcapitata) OECD Guideline 201 EC50: > 500 mg/L, 72h (Desmodesmus subspicatus) EC50: > 500 mg/L, 96h (Desmodesmus subspicatus)

Component	Microtox	M-Factor
Acetone	EC50 = 14500 mg/L/15 min	
1-Butanol	EC50 = 2041.4 mg/L 5 min EC50 = 2186 mg/L 30 min	
	EC50 = 3980 mg/L 24 h	
	EC50 = 4400 mg/L 17 h	

12.2. Persistence and degradability No information available

Component	Degradability
Acetone 67-64-1 (48.25)	91 % (28 d) (OECD 301 B)
1-Butanol 71-36-3 (48.25)	70 %

12.3. Bioaccumulative potential No information available

Component	log Pow	Bioconcentration factor (BCF)
Acetone	-0.24	0.69

BactiDrop Ninhydrin Reagent TM

Revision Date 10-Dec-2021

1-Butanol 0.785 0.64

No information available . 12.4. Mobility in soil

12.5. Results of PBT and vPvB

assessment

No data available for assessment.

12.6. Endocrine disrupting

properties

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused

Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives

on waste and hazardous waste. Dispose of in accordance with local regulations.

Dispose of this container to hazardous or special waste collection point. Empty containers **Contaminated Packaging**

retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but

application specific.

Other Information Waste codes should be assigned by the user based on the application for which the product

was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with

local regulations. Do not empty into drains.

Switzerland - Waste Ordinance Disposal should be in accordance with applicable regional, national and local laws and

regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance.

ADWO) SR 814.600

https://www.fedlex.admin.ch/eli/cc/2015/891/en

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

UN1993 14.1. UN number

Flammable liquid, n.o.s. (Acetone, Butanols mixture) 14.2. UN proper shipping name

14.3. Transport hazard class(es) 3 14.4. Packing group

II

ADR

14.1. UN number

14.2. UN proper shipping name Flammable liquid, n.o.s. (Acetone, Butanols mixture)

14.3. Transport hazard class(es)

3

14.4. Packing group

П

IATA

BactiDrop Ninhydrin Reagent TM

14.1. UN number UN1993

14.2. UN proper shipping name Flammable liquid, n.o.s. (Acetone, Butanols mixture)

14.3. Transport hazard class(es) 3 14.4. Packing group II

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required

14.7. Maritime transport in bulk according to IMO instruments

Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Acetone	67-64-1	200-662-2	-	-	Х	X	KE-29367	X	Х
1-Butanol	71-36-3	200-751-6	-	-	Х	X	KE-03867	X	X
1H-Indene-1,3(2H)-dione,	485-47-2	207-618-1	-	-	Х	X	KE-10839	X	Х
2,2-dihydroxy-									

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Acetone	67-64-1	X	ACTIVE	X	-	X	Х	X
1-Butanol	71-36-3	X	ACTIVE	Х	-	Х	Х	Х
1H-Indene-1,3(2H)-dione, 2.2-dihydroxy-	485-47-2	Х	ACTIVE	Х	-	Х	Х	Х

Legend: X - Listed '-' - Not Listed **KECL** - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	· · · · · · · · · · · · · · · · · · ·
Acetone	-	Use restricted. See item 75. (see link for restriction details)	-
1-Butanol	-	Use restricted. See item 75. (see link for restriction details)	-

https://echa.europa.eu/substances-restricted-under-reach

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Acetone	67-64-1	Not applicable	Not applicable
1-Butanol	71-36-3	Not applicable	Not applicable
1H-Indene-1,3(2H)-dione, 2,2-dihydroxy-	485-47-2	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

OXDR21534

BactiDrop Ninhydrin Reagent TM

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 1 (self classification)

Component	Germany - Water Classification (VwVwS)	Germany - TA-Luft Class
Acetone	WGK1	
1-Butanol	WGK1	

Component	France - INRS (Tables of occupational diseases)
Acetone	Tableaux des maladies professionnelles (TMP) - RG 84
1-Butanol	Tableaux des maladies professionnelles (TMP) - RG 84
1H-Indene-1,3(2H)-dione,	Tableaux des maladies professionnelles (TMP) - RG 66
2,2-dihydroxy-	

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Acetone 67-64-1 (48.25)		Group I	
1-Butanol 71-36-3 (48.25)		Group I	

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H302 - Harmful if swallowed

H315 - Causes skin irritation

H318 - Causes serious eye damage

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

EUH066 - Repeated exposure may cause skin dryness or cracking

H225 - Highly flammable liquid and vapor

H226 - Flammable liquid and vapor

H319 - Causes serious eye irritation

Legend

CAS - Chemical Abstracts Service TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances Substances List

PICCS - Philippines Inventory of Chemicals and Chemical Substances **ENCS** - Japanese Existing and New Chemical Substances

OXDR21534

BactiDrop Ninhydrin Reagent TM

Revision Date 10-Dec-2021

IECSC - Chinese Inventory of Existing Chemical Substances AICS - Australian Inventory of Chemical Substances NZIoC - New Zealand Inventory of Chemicals **KECL** - Korean Existing and Evaluated Chemical Substances

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50% NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

LD50 - Lethal Dose 50% EC50 - Effective Concentration 50% POW - Partition coefficient Octanol:Water vPvB - very Persistent, very Bioaccumulative

Predicted No Effect Concentration (PNEC)

IARC - International Agency for Research on Cancer

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from

ATE - Acute Toxicity Estimate VOC - (volatile organic compound)

TWA - Time Weighted Average

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data **Health Hazards** Calculation method **Environmental hazards** Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Creation Date 15-Nov-2011 **Revision Date** 10-Dec-2021

Revision Summary Update to CLP Format.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet