SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Creation Date 09-Nov-2010 **Revision Date** 30-Nov-2024 **Revision Number** 4

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Ethylmagnesium bromide, 3M in ether
Cat No. : **41675**
Molecular Formula C2 H5 Br Mg

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

Thermo Fisher (Kandel) GmbH
Erlenbachweg 2, 76870 Kandel, Germany
Tel: +49 (0) 721 84007 280
Fax: +49 (0) 721 84007 300

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
https://www.fishersci.ch/ch/en/customer-help-support/forms/email-us.html

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US:**001-201-796-7100 / **Europe:** +32 14 57 52 99
CHEMTREC Tel. No.**US:**001-800-424-9300 / **Europe:**001-703-527-3887

customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

Poison Centre - Emergency information services

Ireland : National Poisons Information Centre (NPIC) -
01 809 2166 (8am-10pm, 7 days a week)
Malta : +356 2395 2000
Cyprus : +357 2240 5611

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Flammable liquids	Category 1 (H224)
Substances/mixtures which, in contact with water, emit flammable gases	Category 1 (H260)

Health hazards

Acute oral toxicity	Category 4 (H302)
Skin Corrosion/Irritation	Category 1 B (H314)
Serious Eye Damage/Eye Irritation	Category 1 (H318)
Specific target organ toxicity - (single exposure)	Category 3 (H336)

Environmental hazards
Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements

Signal Word **Danger**

Hazard Statements
H224 - Extremely flammable liquid and vapor
H260 - In contact with water releases flammable gases which may ignite spontaneously
H302 - Harmful if swallowed
H314 - Causes severe skin burns and eye damage
H336 - May cause drowsiness or dizziness
EUH014 - Reacts violently with water
EUH019 - May form explosive peroxides

Precautionary Statements
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P223 - Do not allow contact with water
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P302 + P335 + P334 - IF ON SKIN: Brush off loose particles from skin. Immerse in cool water
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor/physician

2.3. Other hazards

Toxic to terrestrial vertebrates
This product does not contain any known or suspected endocrine disruptors

Section 3: Composition/information on ingredients

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Ethyl ether	60-29-7	EEC No. 200-467-2	60	Flam. Liq. 1 (H224) Acute Tox. 4 (H302) STOT SE 3 (H336) (EUH019) (EUH066)
Magnesium, bromoethyl-	925-90-6	EEC No. 213-127-3	40	Flam. Liq. 2 (H225) Skin Corr. 1B (H314) Eye Dam. 1 (H318) Water-react. 1 (H260) (EUH014)

Components	Reach Registration Number	
Magnesium, bromoethyl-	01-2120065578-44	
Ethyl ether	01-2119535785-29	

Full text of Hazard Statements: see section 16

Section 4: First aid measures

4.1. Description of first aid measures

Eye Contact Immediate medical attention is required. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Skin Contact Immediate medical attention is required. Wash off immediately with plenty of water for at least 15 minutes.

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately.

Inhalation Remove to fresh air. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required. If not breathing, give artificial respiration.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Causes burns by all exposure routes. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Symptoms may be delayed.

Section 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media
Dry chemical. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons
Water. Carbon dioxide (CO_2).

5.2. Special hazards arising from the substance or mixture

Extremely flammable. Water reactive. Vapors may travel to source of ignition and flash back. Produce flammable gases on contact with water. Containers may explode when heated. Vapors may form explosive mixtures with air.

Hazardous Combustion Products
Carbon monoxide (CO), Carbon dioxide (CO_2), Hydrogen halides, Magnesium oxides, Ethane.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Avoid contact with skin, eyes or clothing. Remove all sources of ignition.

6.2. Environmental precautions

See Section 12 for additional Ecological Information. Should not be released into the environment.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Provide adequate ventilation. Do not expose spill to water.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

Section 7: Handling and storage

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not breathe mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Handle product only in closed system or provide appropriate exhaust ventilation. Handle under inert gas, protect from moisture. Use spark-proof tools and explosion-proof equipment. Use only non-sparking tools. Do not allow contact with water. Keep away from open flames, hot surfaces and sources of ignition. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges. If peroxide formation is suspected, do not open or move container.

Hygiene Measures
Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a dry place. Keep container tightly closed. Store at room temperature. Keep from any possible contact with water. Corrosives area. Flammables area. Store under an inert atmosphere. Store indoors. Keep away from heat, sparks and flame. Keep containers tightly closed in a dry, cool and well-ventilated place. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals.

Technical Rules for Hazardous Substances (TRGS) 510 Storage Class (LGK) (Germany)	Storage Class/LGK 4.3
Switzerland - Storage of hazardous substances	Storage class - SC 4.3 https://www.kvu.ch/de/themen/stoffe-und-produkte https://www.kvu.ch/fr/themes/substances-et-produits https://www.kvu.ch/it/temi/sostanze-e-prodotti

7.3. Specific end use(s)

Use in laboratories

Section 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits
List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE -** 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Ethyl ether	TWA: 100 ppm (8h) TWA: 308 mg/m³ (8h) STEL: 200 ppm (15min) STEL: 616 mg/m³ (15min)	STEL: 200 ppm 15 min STEL: 620 mg/m³ 15 min TWA: 100 ppm 8 hr TWA: 310 mg/m³ 8 hr	TWA / VME: 100 ppm (8 heures). restrictive limit TWA / VME: 308 mg/m³ (8 heures). restrictive limit STEL / VLCT: 200 ppm. restrictive limit STEL / VLCT: 616 mg/m³. restrictive limit	TWA: 100 ppm 8 uren TWA: 308 mg/m³ 8 uren STEL: 200 ppm 15 minuten STEL: 616 mg/m³ 15 minuten	STEL / VLA-EC: 200 ppm (15 minutos). STEL / VLA-EC: 616 mg/m³ (15 minutos). TWA / VLA-ED: 100 ppm (8 horas) TWA / VLA-ED: 308 mg/m³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
Ethyl ether	TWA: 100 ppm 8 ore. Time Weighted Average TWA: 308 mg/m³ 8 ore. Time Weighted Average STEL: 200 ppm 15 minuti. Short-term STEL: 616 mg/m³ 15 minuti. Short-term	TWA: 400 ppm (8 Stunden). AGW - exposure factor 1 TWA: 1200 mg/m³ (8 Stunden). AGW - exposure factor 1 TWA: 400 ppm (8 Stunden). MAK TWA: 1200 mg/m³ (8 Stunden). MAK Höhepunkt: 400 ppm Höhepunkt: 1200 mg/m³	STEL: 200 ppm 15 minutos STEL: 616 mg/m³ 15 minutos TWA: 100 ppm 8 horas TWA: 308 mg/m³ 8 horas	STEL: 200 ppm 15 minuten STEL: 616 mg/m³ 15 minuten TWA: 100 ppm 8 uren TWA: 308 mg/m³ 8 uren	TWA: 100 ppm 8 tunteina TWA: 310 mg/m³ 8 tunteina STEL: 200 ppm 15 minuutteina STEL: 620 mg/m³ 15 minuutteina

Component	Austria	Denmark	Switzerland	Poland	Norway
Ethyl ether	MAK-KZGW: 200 ppm 15 Minuten MAK-KZGW: 600 mg/m³ 15 Minuten MAK-TMW: 100 ppm 8 Stunden MAK-TMW: 300 mg/m³ 8 Stunden	TWA: 100 ppm 8 timer TWA: 309 mg/m³ 8 timer STEL: 616 mg/m³ 15 minutter STEL: 200 ppm 15 minutter	STEL: 400 ppm 15 Minuten STEL: 1200 mg/m³ 15 Minuten TWA: 400 ppm 8 Stunden TWA: 1200 mg/m³ 8 Stunden	STEL: 600 mg/m³ 15 minutach TWA: 300 mg/m³ 8 godzinach	TWA: 100 ppm 8 timer TWA: 300 mg/m³ 8 timer STEL: 150 ppm 15 minutter. value calculated STEL: 375 mg/m³ 15 minutter. value calculated

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Ethyl ether	TWA: 100 ppm TWA: 308 mg/m³ STEL : 200 ppm STEL : 616 mg/m³	TWA-GVI: 100 ppm 8 satima. TWA-GVI: 308 mg/m³ 8 satima. STEL-KGVI: 200 ppm 15 minutama. STEL-KGVI: 616 mg/m³ 15 minutama.	TWA: 100 ppm 8 hr. TWA: 308 mg/m³ 8 hr. STEL: 200 ppm 15 min STEL: 616 mg/m³ 15 min	STEL: 200 ppm STEL: 616 mg/m³ TWA: 100 ppm TWA: 308 mg/m³	TWA: 300 mg/m³ 8 hodinách. Ceiling: 600 mg/m³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Ethyl ether	TWA: 100 ppm 8 tundides. TWA: 308 mg/m³ 8 tundides. STEL: 200 ppm 15 minutites. STEL: 616 mg/m³ 15 minutites.	TWA: 100 ppm 8 hr TWA: 308 mg/m³ 8 hr STEL: 200 ppm 15 min STEL: 616 mg/m³ 15 min	STEL: 500 ppm STEL: 1500 mg/m³ TWA: 400 ppm TWA: 1200 mg/m³	STEL: 200 ppm 15 percekben. CK STEL: 616 mg/m³ 15 percekben. CK TWA: 100 ppm 8 órában. AK TWA: 308 mg/m³ 8 órában. AK lehetséges borön keresztüli felszívódás	STEL: 200 ppm STEL: 616 mg/m³ TWA: 100 ppm 8 klukkustundum. TWA: 308 mg/m³ 8 klukkustundum.

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Ethyl ether	STEL: 200 ppm STEL: 616 mg/m³ TWA: 100 ppm TWA: 308 mg/m³	TWA: 308 mg/m³ IPRD TWA: 100 ppm IPRD STEL: 616 mg/m³ STEL: 200 ppm	TWA: 100 ppm 8 Stunden TWA: 308 mg/m³ 8 Stunden STEL: 200 ppm 15 Minuten STEL: 616 mg/m³ 15 Minuten	TWA: 100 ppm TWA: 308 mg/m³ STEL: 200 ppm 15 minuti STEL: 616 mg/m³ 15 minuti	TWA: 100 ppm 8 ore TWA: 308 mg/m³ 8 ore STEL: 200 ppm 15 minute STEL: 616 mg/m³ 15 minute

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Ethyl ether	TWA: 300 mg/m³ 2469 MAC: 900 mg/m³	Ceiling: 616 mg/m³ TWA: 100 ppm TWA: 308 mg/m³	TWA: 100 ppm 8 urah TWA: 308 mg/m³ 8 urah STEL: 200 ppm 15 minutah STEL: 616 mg/m³ 15 minutah	Binding STEL: 200 ppm 15 minuter Binding STEL: 616 mg/m³ 15 minuter TLV: 100 ppm 8 timmar. NGV TLV: 308 mg/m³ 8 timmar. NGV	TWA: 100 ppm 8 saat TWA: 308 mg/m³ 8 saat STEL: 200 ppm 15 dakika STEL: 616 mg/m³ 15 dakika

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas

chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)
See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Ethyl ether 60-29-7 (60)				DNEL = 44mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Ethyl ether 60-29-7 (60)		DNEL = 616mg/m^3		DNEL = 308mg/m^3

Predicted No Effect Concentration (PNEC)
See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Ethyl ether 60-29-7 (60)	PNEC = 2mg/L	PNEC = 9.14mg/kg sediment dw	PNEC = 1.65mg/L	PNEC = 4.2mg/L	PNEC = 0.66mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Ethyl ether 60-29-7 (60)	PNEC = 0.2mg/L	PNEC = 0.914mg/kg sediment dw			

8.2. Exposure controls

Engineering Measures
Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting/equipment.
Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber Viton (R)	See manufacturers recommendations	-	EN 374	(minimum requirement)

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use	Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced **Recommended Filter type:** low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387
Small scale/Laboratory use	Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. **Recommended half mask:-** Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141 When RPE is used a face piece Fit Test should be conducted
Environmental exposure controls	No information available.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Dark brown	
Odor	Petroleum distillates	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flammability (liquid)	Extremely flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	-40 °C / -40 °F	**Method -** No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	No data available	
Water Solubility	No information available	
Solubility in other solvents	No information available	

Partition Coefficient (n-octanol/water)

Component	**log Pow**
Ethyl ether	0.82

Vapor Pressure	No data available	
Density / Specific Gravity	1.030	
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

Molecular Formula	C2 H5 Br Mg
Molecular Weight	133.27
Explosive Properties	Vapors may form explosive mixtures with air
Substances/mixtures which, in contact with water, emit flammable gases	Emitted gas ignites spontaneously Gas(es) = Ethane

Section 10: Stability and reactivity

10.1. Reactivity

Yes

10.2. Chemical stability

Moisture sensitive. Air sensitive.

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous polymerization does not occur.
Hazardous Reactions No information available.

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition. Incompatible products. Exposure to air. Exposure to moist air or water.

10.5. Incompatible materials

Acids. Alcohols.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO_2). Hydrogen halides. Magnesium oxides. Ethane.

Section 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;
Oral Category 4
Dermal Based on available data, the classification criteria are not met
Inhalation Based on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl ether	1215 mg/kg (Rat)	20 mL/kg (Rabbit)	32000 ppm (Rat) 4 h

(b) skin corrosion/irritation; Category 1 B

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;
Respiratory No data available
Skin No data available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; No data available

(h) STOT-single exposure; Category 3

Results / Target organs Central nervous system (CNS).

(i) STOT-repeated exposure; No data available

Target Organs No information available.

(j) aspiration hazard; No data available

Other Adverse Effects The toxicological properties have not been fully investigated.

Symptoms / effects,both acute and delayed Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity effects .

Component	Freshwater Fish	Water Flea	Freshwater Algae
Ethyl ether	LC50: > 10000 mg/L, 96h static (Lepomis macrochirus) LC50: = 2560 mg/L, 96h flow-through (Pimephales promelas)	EC50 = 165 mg/L/24h	

Component	Microtox	M-Factor
Ethyl ether	EC50 = 5600 mg/L 15 min	

12.2. Persistence and degradability

No information available

12.3. Bioaccumulative potential

No information available

Component	log Pow	Bioconcentration factor (BCF)
Ethyl ether	0.82	No data available

12.4. Mobility in soil

No information available

12.5. Results of PBT and vPvB assessment

No data available for assessment.

12.6. Endocrine disrupting properties

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant	This product does not contain any known or suspected substance
Ozone Depletion Potential	This product does not contain any known or suspected substance

Section 13: Disposal considerations

13.1. Waste treatment methods

Waste from Residues/Unused Products	Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.
Contaminated Packaging	Dispose of this container to hazardous or special waste collection point.
European Waste Catalogue (EWC)	According to the European Waste Catalog, Waste Codes are not product specific, but application specific.
Other Information	Waste codes should be assigned by the user based on the application for which the product was used. Do not empty into drains. Do not flush to sewer. Large amounts will affect pH and harm aquatic organisms.
Switzerland - Waste Ordinance	Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600 https://www.fedlex.admin.ch/eli/cc/2015/891/en

Section 14: Transport information

IMDG/IMO

14.1. UN number	UN3399
14.2. UN proper shipping name	ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE, FLAMMABLE
Technical Shipping Name	(ETHYLMAGNESIUM BROMIDE, DIETHYL ETHER)
14.3. Transport hazard class(es)	4.3
Subsidiary Hazard Class	3, 8
14.4. Packing group	I

ADR

14.1. UN number	UN3399
14.2. UN proper shipping name	ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE, FLAMMABLE
Technical Shipping Name	(ETHYLMAGNESIUM BROMIDE, DIETHYL ETHER)
14.3. Transport hazard class(es)	4.3
Subsidiary Hazard Class	3
14.4. Packing group	I

IATA

14.1. UN number	UN3399
14.2. UN proper shipping name	ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE, FLAMMABLE*
Technical Shipping Name	(ETHYLMAGNESIUM BROMIDE, DIETHYL ETHER)
14.3. Transport hazard class(es)	4.3
Subsidiary Hazard Class	3, 8
14.4. Packing group	I

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Ethyl ether	60-29-7	200-467-2	-	-	X	X	KE-27690	X	X
Magnesium, bromoethyl-	925-90-6	213-127-3	-	-	-	X	-	-	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Ethyl ether	60-29-7	X	ACTIVE	X	-	X	X	X
Magnesium, bromoethyl-	925-90-6	X	ACTIVE	-	X	X	X	-

Legend: X - Listed '-' - Not Listed **KECL** - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

Authorisation/Restrictions according to EU REACH Not applicable

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Ethyl ether	60-29-7	-	-	-
Magnesium, bromoethyl-	925-90-6	-	-	-

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Ethyl ether	60-29-7	Not applicable	Not applicable
Magnesium, bromoethyl-	925-90-6	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification Water endangering class = 1 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Ethyl ether	WGK1	
Magnesium, bromoethyl-	WGK1	

Component	France - INRS (Tables of occupational diseases)
Ethyl ether	Tableaux des maladies professionnelles (TMP) - RG 84

Swiss Regulations
Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).
Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Ethyl ether 60-29-7 (60)		Group I	

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

Section 16: Other information

Full text of H-Statements referred to under sections 2 and 3
H224 - Extremely flammable liquid and vapor
H225 - Highly flammable liquid and vapor
H260 - In contact with water releases flammable gases which may ignite spontaneously
H302 - Harmful if swallowed
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H336 - May cause drowsiness or dizziness
EUH014 - Reacts violently with water
EUH019 - May form explosive peroxides
EUH066 - Repeated exposure may cause skin dryness or cracking

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
IECSC - Chinese Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
ENCS - Japanese Existing and New Chemical Substances
AICS - Australian Inventory of Chemical Substances
NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit
ACGIH - American Conference of Governmental Industrial Hygienists
DNEL - Derived No Effect Level
RPE - Respiratory Protective Equipment
LC50 - Lethal Concentration 50%
NOEC - No Observed Effect Concentration
PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average
IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)
LD50 - Lethal Dose 50%
EC50 - Effective Concentration 50%
POW - Partition coefficient Octanol:Water
vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road
IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code
OECD - Organisation for Economic Co-operation and Development
BCF - Bioconcentration factor
ICAO/IATA - International Civil Aviation Organization/International Air Transport Association
MARPOL - International Convention for the Prevention of Pollution from Ships
ATE - Acute Toxicity Estimate
VOC - (volatile organic compound)

Key literature references and sources for data
https://echa.europa.eu/information-on-chemicals
Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health Hazards	Calculation method
Environmental hazards	Calculation method

Training Advice
Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.
Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.
First aid for chemical exposure, including the use of eye wash and safety showers.
Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.
Chemical incident response training.

Prepared By	Health, Safety and Environmental Department
Creation Date	09-Nov-2010
Revision Date	30-Nov-2024
Revision Summary	Not applicable.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006 .

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet