

according to Regulation (EC) No. 1907/2006

Creation Date 30-Apr-2010 Revision Date 09-Feb-2024 Revision Number 6

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Ninhydrin solution 0.5% in butan-1-ol

Cat No. : N/2160/90

Molecular Formula CH3(CH2)2CH2OH

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.

Sector of use SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

Product category PC21 - Laboratory chemicals

Process categories PROC15 - Use as a laboratory reagent

Environmental release category ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)

Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

EU entity/business name

Thermo Fisher Scientific
Janssen Pharmaceuticalaan 3a

2440 Geel, Belgium

UK entity/business name

Fisher Scientific UK

Bishop Meadow Road, Loughborough, Leicestershire LE11 5RG, United Kingdom

Swiss distributor - Fisher Scientific AG Neuhofstrasse 11, CH 4153 Reinach

Tel: +41 (0) 56 618 41 11

e-mail - infoch@thermofisher.com

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

Tel: 01509 231166

Chemtrec US: (800) 424-9300 Chemtrec EU: 001-703-527-3887

For customers in Switzerland:

Tox Info Suisse Emergency Number: 145 (24hr)

Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)

Chemtrec (24h) Toll-Free: 0800 564 402 Chemtrec Local: +41-43 508 20 11 (Zurich)

SECTION 2: HAZARDS IDENTIFICATION

FSUN2160

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Flammable liquids Category 3 (H226)

Health hazards

Acute oral toxicity

Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Specific target organ toxicity - (single exposure)

Category 4 (H302)

Category 2 (H315)

Category 1 (H318)

Category 3 (H335) (H336)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

- H226 Flammable liquid and vapor
- H315 Causes skin irritation
- H302 Harmful if swallowed
- H336 May cause drowsiness or dizziness
- H318 Causes serious eye damage
- H335 May cause respiratory irritation

Precautionary Statements

P280 - Wear eye protection/ face protection

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/physician

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P301 + P312 - IF SWALLOWED: Čall a POISON CENTER or doctor/physician if you feel unwell

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water

2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
1H-Indene-1,3(2H)-dione, 2,2-dihydroxy-	485-47-2	EEC No. 207-618-1	0.5	Acute Tox. 4 (H302) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) STOT SE 3 (H335)
1-Butanol	71-36-3	EEC No. 200-751-6	99.5	Flam. Liq. 3 (H226) Acute Tox. 4 (H302) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) STOT SE 3 (H335) STOT SE 3 (H336)

Components	Reach Registration Number	
n-Butyl alcohol	01-2119484630-38	

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Get medical attention.

Remove and wash contaminated clothing and gloves, including the inside, before re-use.

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately. Never give

anything by mouth to an unconscious person. Aspiration hazard. Clean mouth with water.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Do not use mouth-to-mouth

method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get

medical attention.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Causes severe eye damage. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Ninhydrin solution 0.5% in butan-1-ol

Revision Date 09-Feb-2024

Suitable Extinguishing Media

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Flammable. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Vapors may accumulate in confined areas (basement, tanks, hopper/tank cars, etc.). May be ignited by heat, sparks or flames. Containers may explode when heated. Vapors may form explosive mixtures with air.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO2), Thermal decomposition can lead to release of irritating gases and vapors.

5.3. Advice for firefighters

Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges. Ensure adequate ventilation.

6.2. Environmental precautions

Should not be released into the environment. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Wash hands before breaks and immediately after handling the product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area. Keep away from heat, sparks and flame.

Ninhydrin solution 0.5% in butan-1-ol

Revision Date 09-Feb-2024

Switzerland - Storage of hazardous substances

Storage class - SC 3

https://www.kvu.ch/de/themen/stoffe-und-produkte https://www.kvu.ch/fr/themes/substances-et-produits https://www.kvu.ch/it/temi/sostanze-e-prodotti

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is

- The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
1-Butanol		50ppm STEL; 154mg/m ³	STEL / VLCT: 50 ppm.	50ppm VLE; 154mg/m ³	STEL / VLA-EC: 50 ppm
		STEL	STEL / VLCT: 150	VLE	(15 minutos).
			mg/m³.		STEL / VLA-EC: 154
					mg/m³ (15 minutos).
					TWA / VLA-ED: 20 ppm
					(8 horas)
					TWA / VLA-ED: 61
					mg/m³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
1-Butanol		100ppm TWA;	TWA: 20 ppm 8 horas	15ppm STEL; 45mg/m ³	TWA: 50 ppm 8 tunteina
		310mg/m ³ TWA		STEL	TWA: 150 mg/m ³ 8
					tunteina
					STEL: 75 ppm 15
					minuutteina
					STEL: 230 mg/m ³ 15
					minuutteina
					lho

Component	Austria	Denmark	Switzerland	Poland	Norway
1-Butanol	MAK-KZGW: 200 ppm	Ceiling: 50 ppm	STEL: 100 ppm 15	STEL: 150 mg/m ³ 15	Hud
	15 Minuten	Ceiling: 150 mg/m ³	Minuten	minutach	Ceiling: 25 ppm
	MAK-KZGW: 600 mg/m ³	Hud	STEL: 310 mg/m ³ 15	TWA: 50 mg/m ³ 8	Ceiling: 75 mg/m ³
	15 Minuten		Minuten	godzinach	
	MAK-TMW: 50 ppm 8		TWA: 100 ppm 8	_	
	Stunden		Stunden		
	MAK-TMW: 150 mg/m ³		TWA: 310 mg/m ³ 8		
	8 Stunden		Stunden		

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
1-Butanol	TWA: 100 mg/m ³	kože	TWA: 20 ppm 8 hr.		TWA: 300 mg/m ³ 8
	STEL: 150 mg/m ³	STEL-KGVI: 50 ppm 15	STEL: 60 ppm 15 min		hodinách.
	_	minutama.	Skin		Potential for cutaneous
		STEL-KGVI: 154 mg/m ³			absorption
		15 minutama.			Ceiling: 600 mg/m ³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
1-Butanol	Nahk TWA: 15 ppm 8 tundides. TWA: 45 mg/m³ 8 tundides. STEL: 30 ppm 15 minutites. STEL: 90 mg/m³ 15 minutites.		skin - potential for cutaneous absorption STEL: 100 ppm STEL: 300 mg/m³ TWA: 100 ppm TWA: 300 mg/m³	STEL: 90 mg/m³ 15 percekben. CK TWA: 45 mg/m³ 8 órában. AK lehetséges borön keresztüli felszívódás	STEL: 50 ppm STEL: 150 mg/m³ Skin notation

Revision Date 09-Feb-2024

Ninhydrin solution 0.5% in butan-1-ol

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
1-Butanol	TWA: 10 mg/m ³	Ceiling: 30 ppm			TWA: 33 ppm 8 ore
		Ceiling: 90 mg/m ³			TWA: 100 mg/m ³ 8 ore
		TWA: 15 ppm IPRD			STEL: 66 ppm 15
		TWA: 45 mg/m ³ IPRD			minute
		Oda			STEL: 200 mg/m ³ 15
					minute

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
1-Butanol	TWA: 10 mg/m ³ 0418	Ceiling: 310 mg/m ³	TWA: 100 ppm 8 urah	Binding STEL: 30 ppm	
	MAC: 30 mg/m ³	TWA: 100 ppm	TWA: 310 mg/m ³ 8 urah	15 minuter	
		TWA: 310 mg/m ³	STEL: 100 ppm 15	Binding STEL: 90	
		_	minutah	mg/m ³ 15 minuter	
			STEL: 310 mg/m ³ 15	TLV: 15 ppm 8 timmar.	
			minutah	NGV	
				TLV: 45 mg/m ³ 8	
				timmar. NGV	
				Hud	

Biological limit values

List source(s):

Component	European Union	United Kingdom	France	Spain	Germany
1-Butanol					1-Butanol (after
					hydrolysis): 10 mg/g
					Creatinine urine (end c
					shift)
					1-Butanol (after
					hydrolysis): 2 mg/g
					Creatinine urine (befor
					beginning of next shift

Component	Gibraltar	Latvia	Slovak Republic	Luxembourg	Turkey
1-Butanol			n-Butyl alcohol: 2 mg/g		
			creatinine urine after all		
			work shifts for long-term		
			exposure		
			n-Butyl alcohol: 10 mg/g		
			creatinine urine end of		
			exposure or work shift		

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
1-Butanol 71-36-3 (99.5)			DNEL = 310mg/m ³	

Predicted No Effect Concentration (PNEC)

See values below.

Composit	Erock water	Fresh water	Motor Intermittent	Mieroergenieme in	Coil / Agriculture)
Component	Fresh water	l Fresh water	i water intermittent	Microorganisms in	Soil (Aariculture)

Ninhydrin solution 0.5% in butan-1-ol

		sediment		sewage treatment	
1-Butanol	PNEC = 0.082mg/L	PNEC =	PNEC = 2.25mg/L	PNEC = 2476mg/L	PNEC =
71-36-3 (99.5)		0.324mg/kg			0.0166mg/kg soil
		sediment dw			dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
1-Butanol	PNEC =	PNEC =			
71-36-3 (99.5)	0.0082mg/L	0.0324mg/kg			
		sediment dw			

8.2. Exposure controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Viton (R)	See manufacturers	-	EN 374	(minimum requirement)
	recommendations			

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to

EN14387

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

141

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls No information available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State Liquid

Appearance Colorless
Odor sweet

Odor Threshold No data available

Revision Date 09-Feb-2024

Ninhydrin solution 0.5% in butan-1-ol

Revision Date 09-Feb-2024

-90 °C / -130 °F Melting Point/Range **Softening Point** No data available 117.4 °C / 243.3 °F **Boiling Point/Range**

On basis of test data Flammability (liquid) Flammable

Flammability (solid,gas) Not applicable Liquid

Explosion Limits No data available Lower 1.4 vol%

Upper 11.2 vol%

37 °C / 98.6 °F **Flash Point** Method - No information available

Autoignition Temperature No data available **Decomposition Temperature** No data available No information available рH 2.94cP @ 20°C **Viscosity**

Water Solubility Soluble

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Component log Pow

1-Butanol

Vapor Pressure 25 mmHg @ 6.52°C

Density / Specific Gravity 0.81

Bulk Density Not applicable Liquid Vapor Density No data available (Air = 1.0)

Not applicable (liquid) **Particle characteristics**

9.2. Other information

Molecular Formula CH3(CH2)2CH2OH

Molecular Weight 74.0694

Explosive Properties explosive air/vapour mixtures possible

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

10.4. Conditions to avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition.

10.5. Incompatible materials

Reducing Agent. Copper alloys. copper. Halogens. Acids. Acid chlorides. Acid anhydrides.

Oxidizing agent.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂). Thermal decomposition can lead to release

of irritating gases and vapors.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

Ninhydrin solution 0.5% in butan-1-ol

Revision Date 09-Feb-2024

(a) acute toxicity;

Oral Category 4

DermalBased on available data, the classification criteria are not metInhalationBased on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation		
		LD50 = 3402 mg/kg (Rabbit)	LC50 > 8000 ppm (Rat) 4 h		

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

RespiratorySkin

Based on available data, the classification criteria are not met
Based on available data, the classification criteria are not met

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

(f) carcinogenicity; Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; Based on available data, the classification criteria are not met

(h) STOT-single exposure; Category 3

Results / Target organs Respiratory system, Central nervous system (CNS).

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

Target Organs None known.

(j) aspiration hazard; Based on available data, the classification criteria are not met

Symptoms / effects,both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. delayed

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any

known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity Ecotoxicity effects

Component	Freshwater Fish	Water Flea	Freshwater Algae	
1-Butanol	LC50: 1376 mg/L, 96h	EC50: 1328 mg/L, 48h (Daphnia	EC50: 225 mg/L, 96h	
	(Pimephales promelas) OECD	magna) OECD Guideline 202	(Pseudokirchneriella subcapitata)	
	Guideline 203: 100000 -	EC50: 1897 - 2072 mg/L, 48h	OECD Guideline 201	
	500000 μg/L, 96h static (Lepomis	Static (Daphnia magna)	EC50: > 500 mg/L, 72h	
	macrochirus)	EC50: = 1983 mg/L, 48h	(Desmodesmus subspicatus)	

Ninhydrin solution 0.5% in butan-1-ol

flow-through (Pimephales promelas) LC50: = 1910000 µg/L, 96h static (Pimephales promelas) LC50: 1730 - 1910 mg/L, 96h static (Pimephales promelas)
--

Component	Microtox	M-Factor
1-Butanol	EC50 = 2041.4 mg/L 5 min	
	EC50 = 2186 mg/L 30 min	
	EC50 = 3980 mg/L 24 h	
	EC50 = 4400 mg/L 17 h	

12.2. Persistence and degradability

Persistence Persistence is unlikely.

Component	Degradability		
1-Butanol	70 %		
71-36-3 (99.5)			

12.3. Bioaccumulative potential Bioaccumulation is unlikely

Component		log Pow	Bioconcentration factor (BCF)
	1-Butanol	1	0.64 dimensionless

12.4. Mobility in soil The product is water soluble, and may spread in water systems . Will likely be mobile in the

environment due to its water solubility. Highly mobile in soils

12.5. Results of PBT and vPvB

assessment

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent

Revision Date 09-Feb-2024

and very bioaccumulative (vPvB).

12.6. Endocrine disrupting

properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects
Persistent Organic Pollutant
Ozone Depletion Potential

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused

Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information

Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with

local regulations. Do not empty into drains.

Switzerland - Waste Ordinance

Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance,

ADWO) SR 814.600

https://www.fedlex.admin.ch/eli/cc/2015/891/en

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN numberUN112014.2. UN proper shipping nameButanols14.3. Transport hazard class(es)314.4. Packing groupIII

<u>ADR</u>

14.1. UN numberUN112014.2. UN proper shipping nameButanols14.3. Transport hazard class(es)314.4. Packing groupIII

IATA

14.1. UN numberUN112014.2. UN proper shipping nameButanols14.3. Transport hazard class(es)314.4. Packing groupIII

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
1H-Indene-1,3(2H)-dione,	485-47-2	207-618-1	-	-	X	X	KE-10839	X	X
2,2-dihydroxy-									
1-Butanol	71-36-3	200-751-6	-	-	X	Χ	KE-03867	Χ	X

	Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
1⊦	I-Indene-1,3(2H)-dione, 2,2-dihydroxy-	485-47-2	Х	ACTIVE	Х	-	Х	Х	Х
	1-Butanol	71-36-3	Х	ACTIVE	Х	-	Х	Х	Х

Legend: X - Listed '-' - Not Listed KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) -	REACH (1907/2006) -	REACH Regulation (EC
-		Annex XIV - Substances	Annex XVII - Restrictions	1907/2006) article 59 -
		Subject to Authorization	on Certain Dangerous	Candidate List of

Revision Date 09-Feb-2024

Ninhydrin solution 0.5% in butan-1-ol

			Substances	Substances of Very High Concern (SVHC)
1H-Indene-1,3(2H)-dione, 2,2-dihydroxy-	485-47-2	-	-	-
1-Butanol	71-36-3	-	Use restricted. See item 75. (see link for restriction details)	-

REACH links

https://echa.europa.eu/substances-restricted-under-reach

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
1H-Indene-1,3(2H)-dione, 2,2-dihydroxy-	485-47-2	Not applicable	Not applicable
1-Butanol	71-36-3	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification Water endangering class = 1 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class	
1-Butanol	WGK1		

Component	France - INRS (Tables of occupational diseases)	
1H-Indene-1,3(2H)-dione,	Tableaux des maladies professionnelles (TMP) - RG 66	
2,2-dihydroxy-		
1-Butanol	Tableaux des maladies professionnelles (TMP) - RG 84	

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
1-Butanol 71-36-3 (99.5)		Group I	

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H226 - Flammable liquid and vapor

H302 - Harmful if swallowed

H315 - Causes skin irritation

H318 - Causes serious eye damage

H319 - Causes serious eye irritation H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b)

Inventory

Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

> **ENCS** - Japanese Existing and New Chemical Substances AICS - Australian Inventory of Chemical Substances NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50% POW - Partition coefficient Octanol:Water vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air **Transport Association**

MARPOL - International Convention for the Prevention of Pollution from

Ships

ATE - Acute Toxicity Estimate VOC - (volatile organic compound)

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data **Health Hazards** Calculation method **Environmental hazards** Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Creation Date 30-Apr-2010 **Revision Date** 09-Feb-2024 **Revision Summary** Not applicable.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and

Ninhydrin solution 0.5% in butan-1-ol

Revision Date 09-Feb-2024

Preparations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet