

according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended

Creation Date 06-Aug-2009 Revision Date 06-Dec-2024 Revision Number 13

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THECOMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Potassium tert-butoxide, 20 wt.% solution in THF

Cat No. : 364990000; 364990500 Synonyms Potassium tert-butylate

Molecular Formula C4 H9 K O

Unique Formula Identifier (UFI) KY2T-MT0T-KW0F-A3JH

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

UK entity/business name

Fisher Scientific UK Bishop Meadow Road,

Loughborough, Leicestershire LE11 5RG, United Kingdom

EU entity/business name

Thermo Fisher Scientific

Janssen Pharmaceuticalaan 3a, 2440 Geel, Belgium

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

Poison Centre - Emergency information services

Ireland: National Poisons Information Centre (NPIC) -

01 809 2166 (8am-10pm, 7 days a week)

Malta: +356 2395 2000 Cyprus: +357 2240 5611

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Physical hazards

Flammable liquids Category 2 (H225)

Health hazards

Skin Corrosion/Irritation
Serious Eye Damage/Eye Irritation
Carcinogenicity
Specific target organ toxicity - (single exposure)

Category 1 A (H314) Category 1 (H318) Category 2 (H351) Category 3 (H335) (H336)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H314 - Causes severe skin burns and eye damage

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

H351 - Suspected of causing cancer

EUH014 - Reacts violently with water

EUH019 - May form explosive peroxides

Precautionary Statements

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/physician

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

2.3. Other hazards

Reacts violently with water

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Tetrahydrofuran	109-99-9	203-726-8	80	Flam. Liq. 2 (H225) Acute Tox. 4 (H302) Eye Irrit. 2 (H319) STOT SE 3 (H335) STOT SE 3 (H336) Carc. 2 (H351) (EUH019)
Potassium tert-butoxide	865-47-4	EEC No. 212-740-3	20	Flam. Sol. 1 (H228) Self-heat. 2 (H252) Skin Corr. 1A (H314) Eye Dam. 1 (H318) (EUH014)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Tetrahydrofuran	Acute Tox. 4 :: C>82.5%	-	-
	Eye Irrit. 2 :: C>=25%		
	STOT SE 3 :: C>=25%		

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Remove and wash

contaminated clothing and gloves, including the inside, before re-use. Call a physician

immediately.

Ingestion Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an

unconscious person. Call a physician immediately.

Inhalation If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use

mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory

medical device. Call a physician immediately.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Causes central nervous system depression

Revision Date 06-Dec-2024

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons

Water.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Reacts violently with water.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO2).

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

6.2. Environmental precautions

Should not be released into the environment.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Do not expose spill to water.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water.

Hygiene Measures

Potassium tert-butoxide, 20 wt.% solution in THF

Revision Date 06-Dec-2024

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Shelf life 12 months. May form explosive peroxides on prolonged storage, Containers should be dated when opened and tested periodically for the presence of peroxides, Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from water or moist air. Keep away from heat, sparks and flame. Keep under nitrogen. Corrosives area.

Technical Rules for Hazardous Substances (TRGS) 510 Storage Class (LGK) (Germany)

Class 3

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Tetrahydrofuran	STEL: 100 ppm 15 min	TWA: 50 ppm (8h)	TWA: 50 ppm 8 hr.
	STEL: 300 mg/m ³ 15 min	TWA: 150 mg/m ³ (8h)	TWA: 150 mg/m ³ 8 hr.
	TWA: 50 ppm 8 hr	STEL: 100 ppm (15min)	STEL: 100 ppm 15 min
	TWA: 150 mg/m ³ 8 hr	STEL: 300 mg/m ³ (15min)	STEL: 300 mg/m ³ 15 min
	Skin	Skin	Skin

Biological limit values

List source(s):

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Tetrahydrofuran				DNEL = 12.6mg/kg
109-99-9 (80)				bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Tetrahydrofuran 109-99-9 (80)	DNEL = 300mg/m ³	DNEL = 96mg/m ³	DNEL = 150mg/m ³	DNEL = 72.4mg/m ³
Potassium tert-butoxide 865-47-4 (20)	DNEL = 1mg/m ³	DNEL = 1mg/m ³	DNEL = 1mg/m ³	DNEL = 1mg/m ³

Predicted No Effect Concentration (PNEC)

Potassium tert-butoxide, 20 wt.% solution in THF

Revision Date 06-Dec-2024

See values below.

Component	Fresh water	Fresh water	Water Intermittent	Microorganisms in	Soil (Agriculture)
		sediment		sewage treatment	
Tetrahydrofuran	PNEC = 4.32mg/L	PNEC = 23.3mg/kg	PNEC = 21.6mg/L	PNEC = 4.6mg/L	PNEC = 2.13mg/kg
109-99-9 (80)		sediment dw			soil dw
Potassium tert-butoxide	PNEC = 0.11mg/L	PNEC =	PNEC = 1.1mg/L	PNEC = 10mg/L	PNEC =
865-47-4 (20)		0.419mg/kg	-		0.0192mg/kg soil
		sediment dw			dw

Component	Marine water	Marine water	Marine water	Food chain	Air
		sediment	intermittent		
Tetrahydrofuran	PNEC = 0.432mg/L	PNEC = 2.33mg/kg		PNEC = 67mg/kg	
109-99-9 (80)		sediment dw		food	
Potassium tert-butoxide	PNEC = 0.011mg/L	PNEC =			
865-47-4 (20)		0.0419mg/kg			
		sediment dw			

8.2. Exposure controls

Engineering Measures

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material Butyl rubber Nitrile rubber Viton (R)	Breakthrough time See manufacturers recommendations	Glove thickness	EU standard EN 374	Glove comments (minimum requirement)
Neoprene gloves				

Skin and body protection Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory ProtectionWhen workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

Potassium tert-butoxide, 20 wt.% solution in THF

Revision Date 06-Dec-2024

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls No information available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State Liquid

Amber **Appearance**

Odor Petroleum distillates **Odor Threshold** No data available **Melting Point/Range** No data available **Softening Point** No data available **Boiling Point/Range** 66 °C / 150.8 °F

Tetrahydrofuran On basis of test data Flammability (liquid) No data available Liquid

Flammability (solid,gas) Not applicable

Explosion Limits No data available

-21 °C / -5.8 °F **Flash Point** Method - No information available

Autoignition Temperature 321 - °C / 609.8 - °F **Decomposition Temperature** No data available pН No information available **Viscosity** 0.55 cps @ 20 °C

Reacts violently with water **Water Solubility** Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

log Pow Component Tetrahydrofuran 0.45

200 mmHg @ 20°C **Vapor Pressure**

Density / Specific Gravity 0.929 **Bulk Density** Not applicable

Liquid **Vapor Density** 2.5 (Air = 1.0)

Particle characteristics Not applicable (liquid)

9.2. Other information

Molecular Formula C4 H9 K O **Molecular Weight** 112.21

Explosive Properties Vapors may form explosive mixtures with air

Evaporation Rate

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity Yes Reacts violently with water

10.2. Chemical stability

Water reactive. Air sensitive. May form explosive peroxides. Moisture sensitive.

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing. Reacts violently with water.

Potassium tert-butoxide, 20 wt.% solution in THF

Revision Date 06-Dec-2024

10.4. Conditions to avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition. Exposure to moist air or water. Exposure to moisture.

10.5. Incompatible materials

Strong oxidizing agents. Acids.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

OralNo data availableDermalNo data availableInhalationNo data available

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Tetrahydrofuran	1650 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	180 mg/L (Rat) 1 h
			53.9 mg/L (Rat) 4 h

(b) skin corrosion/irritation; Category 1 A

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

Respiratory No data available Skin No data available

Component	Test method	Test species	Study result
Tetrahydrofuran	Local Lymph Node Assay	mouse	non-sensitising
109-99-9 (80)	OECD Test Guideline 429		_

(e) germ cell mutagenicity; No data available

Component	Test method	Test species	Study result
Tetrahydrofuran	OECD Test Guideline 476	in vivo	negative
109-99-9 (80)	Gene cell mutation	Mammalian	_
	OECD Test Guideline 473		
	Chromosomal aberration assay	in vitro	negative
		Mammalian	

(f) carcinogenicity; No data available

The table below indicates whether each agency has listed any ingredient as a carcinogen Limited evidence of a carcinogenic effect

Component	EU	UK	Germany	IARC
Tetrahydrofuran				Group 2B

Potassium tert-butoxide, 20 wt.% solution in THF

Revision Date 06-Dec-2024

(g) reproductive toxicity;	No data available		
Component	Test method	Test species / Duration	Study result
Tetrahydrofuran	OECD Test Guideline 416	Rat	NOAEL = 3,000 ppm
109-99-9 (80)		2 Generation	

(h) STOT-single exposure; No data available

Results / Target organs Respiratory system, Central nervous system (CNS).

(i) STOT-repeated exposure; No data available

Target Organs No information available.

(j) aspiration hazard; No data available

Symptoms / effects,both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

delayed

Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Causes central nervous system depression.

11.2. Information on other hazards

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

Reacts with water so no ecotoxicity data for the substance is available.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Tetrahydrofuran	2160 mg/l LC50 = 96 h	EC50 48 h 3485 mg/l	
•	Pimephales promelas	EC50: >10000 mg/L/24h	
	Leuciscus idus: LC50: 2820	-	
	mg/L/48h		

12.2. Persistence and degradability

Persistence Persistence is unlikely, based on information available.

Degradability Reacts with water.

Degradation in sewage

treatment plant

Reacts violently with water.

12.3. Bioaccumulative potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Tetrahydrofuran	0.45	No data available

12.4. Mobility in soil The product contains volatile organic compounds (VOC) which will evaporate easily from all

surfaces Will likely be mobile in the environment due to its volatility. Disperses rapidly in

air

Potassium tert-butoxide, 20 wt.% solution in THF

Revision Date 06-Dec-2024

12.5. Results of PBT and vPvB

Reacts violently with water.

assessment

12.6. Endocrine disrupting

properties

Endocrine Disruptor Information

Component	EU - Endocrine Disrupters Candidate List	EU - Endocrine Disruptors - Evaluated Substances
Tetrahydrofuran	Group III Chemical	

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused

Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives

on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but

application specific.

Other Information

Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms.

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number UN2920

14.2. UN proper shipping name
Technical Shipping Name
Corrosive liquid, flammable, n.o.s.
Tetrahydrofuan, Potassium tert-butoxide

14.3. Transport hazard class(es) 8
Subsidiary Hazard Class 3
14.4. Packing group I

ADR

14.1. UN number UN2920

Technical Shipping Name

Technical Shipping Name

14.3. Transport hazard class(es)

Corrosive liquid, flammable, n.o.s.
Tetrahydrofuan, Potassium tert-butoxide

14.3. Transport hazard class(es)8Subsidiary Hazard Class314.4. Packing groupI

IATA

Potassium tert-butoxide, 20 wt.% solution in THF

14.1. UN number UN2920

14.2. UN proper shipping name Technical Shipping NameCorrosive liquid, flammable, n.o.s.
Tetrahydrofuan, Potassium tert-butoxide

14.3. Transport hazard class(es)8Subsidiary Hazard Class314.4. Packing groupI

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Tetrahydrofuran	109-99-9	203-726-8	-	-	X	X	KE-33454	X	X
Potassium tert-butoxide	865-47-4	212-740-3	-	-	Х	X	KE-24897	X	Х

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Tetrahydrofuran	109-99-9	Х	ACTIVE	X	-	X	Х	Х
Potassium tert-butoxide	865-47-4	Х	ACTIVE	Х	-	Х	Х	Х

Legend: X - Listed '-' - Not Listed KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) -	REACH (1907/2006) -	REACH Regulation (EC
		Annex XIV - Substances	Annex XVII - Restrictions	1907/2006) article 59 -
		Subject to Authorization	on Certain Dangerous	Candidate List of
			Substances	Substances of Very High
				Concern (SVHC)
Tetrahydrofuran	109-99-9	-	Use restricted. See entry	-
			75.	
			(see link for restriction	
			details)	
Potassium tert-butoxide	865-47-4	-	-	-

REACH links

https://echa.europa.eu/substances-restricted-under-reach

Seveso III Directive (2012/18/EC)

	Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident	, , ,	
I			Notification	Requirements	
	Tetrahydrofuran	109-99-9	Not applicable	Not applicable	
Ī	Potassium tert-butoxide	865-47-4	Not applicable	Not applicable	

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and

ACR36499

Revision Date 06-Dec-2024

Potassium tert-butoxide, 20 wt.% solution in THF

Revision Date 06-Dec-2024

import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 1 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Tetrahydrofuran	WGK1	
Potassium tert-butoxide	WGK1	

Component	France - INRS (Tables of occupational diseases)
Tetrahydrofuran	Tableaux des maladies professionnelles (TMP) - RG 84

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Tetrahydrofuran 109-99-9 (80)		Group I	

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H252 - Self-heating in large quantities; may catch fire

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

H351 - Suspected of causing cancer

EUH014 - Reacts violently with water

EUH019 - May form explosive peroxides

Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical **DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

Substances List

Potassium tert-butoxide, 20 wt.% solution in THF

Revision Date 06-Dec-2024

ENCS - Japanese Existing and New Chemical Substances PICCS - Philippines Inventory of Chemicals and Chemical Substances IECSC - Chinese Inventory of Existing Chemical Substances AICS - Australian Inventory of Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

NZIoC - New Zealand Inventory of Chemicals

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50% POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of

ACGIH - American Conference of Governmental Industrial Hygienists

Dangerous Goods by Road

WEL - Workplace Exposure Limit

DNEL - Derived No Effect Level

LC50 - Lethal Concentration 50%

RPE - Respiratory Protective Equipment

NOEC - No Observed Effect Concentration PBT - Persistent, Bioaccumulative, Toxic

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from

BCF - Bioconcentration factor

ATE - Acute Toxicity Estimate VOC - (Volatile Organic Compound)

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data **Health Hazards** Calculation method **Environmental hazards** Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts. Chemical incident response training.

Creation Date 06-Aug-2009 **Revision Date** 06-Dec-2024 Not applicable. **Revision Summary**

This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet