

# SAFETY DATA SHEET

Page 1/9 Creation Date 25-May-2009 Revision Date 24-Mar-2025 Version 4

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THECOMPANY/UNDERTAKING

Product Identifier

Perihalan Produk: 1-Chlorobutane
Product Description: 1-Chlorobutane

Cat No.: 97995

Synonymsn-Butyl chlorideCAS No109-69-3Molecular FormulaC4 H9 Cl

Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Research and development.

Uses advised against All other uses

Company Thermo Fisher Scientific Fisher Scientific (M) Sdn Bhd

Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square, No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,

Selangor Darul Ehsan, Malaysia. Main line: +60 3-5525 7888

**Supplier** 

E-mail address Enquiry.my@thermofisher.com

Emergency Telephone Number Tel: +03-5525 7888

CHEMTREC Malaysia 1-800-815-308 (Malay)

CHEMTREC Malaysia (Kuala Lumpur) +(60)-327884561 (Malay)

# **SECTION 2: HAZARDS IDENTIFICATION**

## Classification of the substance or mixture

Flammable liquids	Category 2 (H225)
Aspiration Toxicity	Category 1 (H304)
Chronic aquatic toxicity	Category 3 (H412)

#### Label Elements



Signal Word Danger

#### **Hazard Statements**

H225 - Highly flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H412 - Harmful to aquatic life with long lasting effects

## **Precautionary Statements**

#### Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P233 - Keep container tightly closed

P240 - Ground and bond container and receiving equipment

P241 - Use explosion-proof electrical/ ventilating/ lighting equipment

P242 - Use non-sparking tools

P243 - Take action to prevent static discharges

P270 - Do not eat, drink or smoke when using this product

P280 - Wear protective gloves/protective clothing/eye protection/face protection

#### Response

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor

P301 + P312 - IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P331 - Do NOT induce vomiting

P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

#### Storage

P403 + P235 - Store in a well-ventilated place. Keep cool

#### Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

## Other Hazards

This product does not contain any known or suspected endocrine disruptors

# **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS No	Weight %
1-Chlorobutane	109-69-3	<=100

# **SECTION 4: FIRST AID MEASURES**

## Description of first aid measures

**General Advice** If symptoms persist, call a physician.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

Ingestion Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call

a physician or poison control center immediately. If vomiting occurs naturally, have victim

lean forward.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur. Risk of serious damage to the lungs (by aspiration).

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

ALFAA97995

# Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

#### Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Symptoms may be delayed.

# **SECTION 5: FIREFIGHTING MEASURES**

#### Extinguishing media

## **Suitable Extinguishing Media**

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

## Extinguishing media which must not be used for safety reasons

No information available.

## Special hazards arising from the substance or mixture

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

#### **Hazardous Combustion Products**

Carbon monoxide (CO), Carbon dioxide (CO2), Hydrogen chloride gas.

## Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# **SECTION 6: ACCIDENTAL RELEASE MEASURES**

# Personal Precautions, Protective Equipment and Emergency Procedures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

#### **Environmental precautions**

Should not be released into the environment. Do not flush into surface water or sanitary sewer system.

## Methods and Material for Containment and Cleaning Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

## Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

# **SECTION 7: HANDLING AND STORAGE**

## Precautions for Safe Handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Avoid ingestion and inhalation. Do not get in eyes, on skin, or on clothing. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To

# SAFETY DATA SHEET

1-Chlorobutane Revision Date 24-Mar-2025

avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

## Conditions for Safe Storage, Including any Incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area. Keep away from heat, sparks and flame.

#### Specific End Uses

Use in laboratories.

# **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### **Control Parameters**

Component	European Union	The United Kingdom	Germany
1-Chlorobutane			TWA: 3 ppm (8 Stunden). AGW -
			exposure factor 2
			TWA: 12 mg/m <sup>3</sup> (8 Stunden). AGW -
			exposure factor 2

#### **Exposure Controls**

## **Engineering Measures**

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

**Eye Protection** Wear safety glasses with side shields (or goggles)

Hand Protection Protective gloves
Skin and body protection Long sleeved clothing

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

**Respiratory Protection** When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators

**Recommended Filter type:** Organic gases and vapours filter Type A Brown conforming to EN14387

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

When RPE is used a face piece Fit Test should be conducted

Handle in accordance with good industrial hygiene and safety practice

**Environmental exposure controls** Prevent product from entering drains

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

ALFAA97995

Information on basic physical and chemical properties

Appearance Colorless
Physical State Liquid

Odor No information available
Odor Threshold No data available
pH No information available

Melting Point/Range -123 °C / -189.4 °F Softening Point No data available

**Boiling Point/Range** 77 - 78 °C / 170.6 - 172.4 °F @ 760 mmHg

Flash Point -12 °C / 10.4 °F Method - No information available

**Evaporation Rate** No information available

Flammability (solid,gas) Not applicable Liquid

Explosion Limits Lower 1 Vol% Upper 10.1 Vol%

 Vapor Pressure
 108 mbar @ 20 °C

 Vapor Density
 3.19 (Air = 1.0)

 Vapor Density
 3.19 (Air = 1.0)
 (Air = 1.0)

 Specific Gravity / Density
 0.880

Bulk Density

Not applicable

Liquid

Water Solubility
Solubility in other solvents

Moderately soluble
No information available

Partition Coefficient (n-octanol/water)

Componentlog Pow1-Chlorobutane2.66

Autoignition Temperature 245 °C / 473 °F Decomposition Temperature No data available Viscosity 0.45 mPa.s (20°C)

Viscosity 0.45 mPa.s (20°C)
Explosive Properties

Oxidizing Properties No information available

Molecular FormulaC4 H9 ClMolecular Weight92.57

# **SECTION 10: STABILITY AND REACTIVITY**

Reactivity

None known, based on information available.

Chemical Stability

No information available.

Possibility of Hazardous Reactions

Hazardous Polymerization Hazardous polymerization does not occur.

**Hazardous Reactions** None under normal processing.

ALFAA97995

Vapors may form explosive mixtures with air

Conditions to Avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition.

Incompatible Materials

Strong oxidizing agents. Strong bases.

**Hazardous Decomposition Products** 

Carbon monoxide (CO). Carbon dioxide (CO2). Hydrogen chloride gas.

# **SECTION 11: TOXICOLOGICAL INFORMATION**

## Information on Toxicological Effects

#### **Product Information**

(a) acute toxicity;

OralBased on available data, the classification criteria are not metDermalBased on available data, the classification criteria are not metInhalationBased on available data, the classification criteria are not met

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation		
1-Chlorobutane	LD50 = 2670 mg/kg (Rat)	LD50 > 20000 mg/kg ( Rabbit )	LC50 > 7.74 mg/L (Rat) 4 h		

(b) skin corrosion/irritation; No data available

(c) serious eye damage/irritation; No data available

(d) respiratory or skin sensitization;

Respiratory No data available Skin No data available

(e) germ cell mutagenicity; No data available

Mutagenic effects have occurred in experimental animals

(f) carcinogenicity; No data available

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; No data available

(h) STOT-single exposure; No data available

(i) STOT-repeated exposure; No data available

Target Organs No information available.

(j) aspiration hazard; Category 1

**Other Adverse Effects** Tumorigenic effects have been reported in experimental animals.

delayed

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

Assess endocrine disrupting properties for human health. This product does not contain any **Endocrine Disrupting Properties** 

known or suspected endocrine disruptors.

## **SECTION 12: ECOLOGICAL INFORMATION**

**Ecotoxicity effects** Do not empty into drains. Harmful to aquatic organisms, may cause long-term adverse

effects in the aquatic environment. The product contains following substances which are

hazardous for the environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
1-Chlorobutane	LC50: = 71.4 mg/L, 96h	EC50: = 3020 mg/L, 48h	EC50: > 450 mg/L, 72h	EC50 = 485 mg/L 5 min
	semi-static (Danio rerio)	Static (Daphnia magna)	(Desmodesmus	EC50 = 732 mg/L 30
		EC50: = 452 mg/L, 48h	subspicatus)	min
		(Daphnia magna)		
		EC50: = 16 mg/L, 21d		
		(Daphnia magna)		

Persistence and degradability

**Persistence** 

Degradation in sewage treatment plant

Not readily biodegradable

Persistence is unlikely, based on information available.

Contains substances known to be hazardous to the environment or not degradable in waste

water treatment plants.

Bioaccumulative potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
1-Chlorobutane	2.66	7.6-21

The product contains volatile organic compounds (VOC) which will evaporate easily from all **Mobility in soil** 

surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in

**Endocrine Disruptor Information** This product does not contain any known or suspected endocrine disruptors

No information available Other adverse effects

# **SECTION 13: DISPOSAL CONSIDERATIONS**

Waste treatment methods

Waste from Residues/Unused

**Products** 

Waste is classified as hazardous Dispose of in accordance with the European Directives on waste and hazardous waste Dispose of in accordance with local regulations

**Contaminated Packaging** Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous Keep product and

empty container away from heat and sources of ignition

Other Information Waste codes should be assigned by the user based on the application for which the product

was used Do not flush to sewer Can be landfilled or incinerated, when in compliance with local regulations Do not let this chemical enter the environment Do not empty into drains

# **SECTION 14: TRANSPORT INFORMATION**

IMDG/IMO

UN-No UN1127 Hazard Class 3 Packing Group II

Proper Shipping Name CHLOROBUTANES

Road and Rail Transport

UN-No UN1127 Hazard Class 3 Packing Group II

Proper Shipping Name CHLOROBUTANES

<u>IATA</u>

UN-No UN1127 Hazard Class 3 Packing Group II

Proper Shipping Name CHLOROBUTANES

Special Precautions for User No special precautions required

# **SECTION 15: REGULATORY INFORMATION**

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories X = listed

Component	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	IECSC	AICS	KECL
1-Chlorobutane	203-696-6	X	X	X	X	X	Χ	Χ	KE-05561

Component	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
1-Chlorobutane				Annex I - Y45

National Regulations

Persistent Organic Pollutant Ozone Depletion Potential This product does not contain any known or suspected substance This product does not contain any known or suspected substance

# **SECTION 16: OTHER INFORMATION**

Legend

# SAFETY DATA SHEET

1-Chlorobutane Revision Date 24-Mar-2025

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b)

**ENCS** - Japanese Existing and New Chemical Substances

Inventory

Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic

Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

AICS - Australian Inventory of Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

LC50 - Lethal Concentration 50% POW - Partition coefficient Octanol:Water

IARC - International Agency for Research on Cancer RPE - Respiratory Protective Equipment LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

TWA - Time Weighted Average

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air **Transport Association** 

MARPOL - International Convention for the Prevention of Pollution from

Ships

ATE - Acute Toxicity Estimate VOC - (Volatile Organic Compound)

#### Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Health, Safety and Environmental Department **Prepared By** 

**Revision Date** 24-Mar-2025 Not applicable. **Revision Summary** 

In accordance with local and national regulations: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

## **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet** 

**ALFAA97995**