

according to Regulation (EC) No. 1907/2006

Creation Date 27-Oct-2009 Revision Date 19-Oct-2023 Revision Number 9

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product Description: <u>Ethanol, absolute</u>

 Cat No. :
 E/0600/05, E/0600/08, E/0600/17

 Synonyms
 Ethyl alcohol; Absolute ethanol

 Index No
 603-002-00-5

 CAS No
 64-17-5

 CAS No
 64-17-5

 EC No
 200-578-6

 Molecular Formula
 C2 H6 O

REACH registration number 01-2119457610-43

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

## 1.3. Details of the supplier of the safety data sheet

Company

**EU entity/business name** Thermo Fisher Scientific Janssen Pharmaceuticalaan 3a

2440 Geel, Belgium

UK entity/business name

Fisher Scientific UK

Bishop Meadow Road, Loughborough, Leicestershire LE11 5RG, United Kingdom

**Swiss distributor -** Fisher Scientific AG Neuhofstrasse 11, CH 4153 Reinach

Tel: +41 (0) 56 618 41 11

e-mail - infoch@thermofisher.com

**E-mail address** begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

Tel: 01509 231166

Chemtrec US: (800) 424-9300 Chemtrec EU: 001-703-527-3887

For customers in Switzerland:

Tox Info Suisse Emergency Number: 145 (24hr)

Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)

Chemtrec (24h) Toll-Free: 0800 564 402 Chemtrec Local: +41-43 508 20 11 (Zurich)

## **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1. Classification of the substance or mixture

#### CLP Classification - Regulation (EC) No 1272/2008

## **Physical hazards**

Flammable liquids Category 2 (H225)

#### **Health hazards**

Serious Eye Damage/Eye Irritation Category 2 (H319)

## **Environmental hazards**

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

#### 2.2. Label elements



Signal Word

Danger

## **Hazard Statements**

H225 - Highly flammable liquid and vapor

H319 - Causes serious eye irritation

## **Precautionary Statements**

P280 - Wear eye protection/ face protection

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P337 + P313 - If eye irritation persists: Get medical advice/attention

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

#### 2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

This product does not contain any known or suspected endocrine disruptors

## **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1. Substances

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Ethyl alcohol	64-17-5	200-578-6	>99	Flam. Liq. 2 (H225) Eye Irrit. 2 (H319)

Component	Component Specific concentration limits (SCL's)		Component notes
Ethyl alcohol	Eye Irrit. 2 :: C>=50%	-	-

REACH registration number	01-2119457610-43
---------------------------	------------------

Full text of Hazard Statements: see section 16

## **SECTION 4: FIRST AID MEASURES**

#### 4.1. Description of first aid measures

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Obtain medical attention if irritation persists.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. Get medical attention if

symptoms occur.

Ingestion Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Get

medical attention if symptoms occur.

**Inhalation** Remove to fresh air. Keep patient warm and at rest. If not breathing, give artificial

respiration. If symptoms persist, call a physician.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness,

nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

## **SECTION 5: FIREFIGHTING MEASURES**

## 5.1. Extinguishing media

#### **Suitable Extinguishing Media**

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

#### Extinguishing media which must not be used for safety reasons

No information available.

#### 5.2. Special hazards arising from the substance or mixture

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air.

Ethanol, absolute Revision Date 19-Oct-2023

#### **Hazardous Combustion Products**

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

#### 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Use personal protective equipment as required. Take precautionary measures against static discharges. Do not get in eyes, on skin, or on clothing.

## 6.2. Environmental precautions

Should not be released into the environment. See Section 12 for additional Ecological Information. Do not flush into surface water or sanitary sewer system.

## 6.3. Methods and material for containment and cleaning up

Remove all sources of ignition. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment.

#### 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

## **SECTION 7: HANDLING AND STORAGE**

## 7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not breathe mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

#### **Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

## 7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Flammables area.

Technical Rules for Hazardous Substances (TRGS) 510 Storage Class (LGK) (Germany)

Class 3

Switzerland - Storage of hazardous substances

Storage class - SC 3

https://www.kvu.ch/de/themen/stoffe-und-produkte https://www.kvu.ch/fr/themes/substances-et-produits https://www.kvu.ch/it/temi/sostanze-e-prodotti

#### 7.3. Specific end use(s)

Use in laboratories

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

## 8.1. Control parameters

#### **Exposure limits**

List source(s): **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CF** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Ethyl alcohol		TWA: 1000 ppm TWA;	TWA / VME: 1000 ppm	TWA: 1000 ppm 8 uren	STEL / VLA-EC: 1000
		1920 mg/m <sup>3</sup> TWA	(8 heures).	TWA: 1907 mg/m <sup>3</sup> 8	ppm (15 minutos).
		WEL - STEL: 3000 ppm	TWA / VME: 1900	uren	STEL / VLA-EC: 1910
		STEL; 5760 mg/m <sup>3</sup>	mg/m³ (8 heures).		mg/m <sup>3</sup> (15 minutos).
		STEL	STEL / VLCT: 5000		
			ppm.		
			STEL / VLCT: 9500		
			mg/m³.		

Component	Italy	Germany	Portugal	The Netherlands	Finland
Ethyl alcohol		200 ppm TWA MAK;	STEL: 1000 ppm 15	huid	TWA: 1000 ppm 8
		380 mg/m³ TWA MAK	minutos	STEL: 1900 mg/m <sup>3</sup> 15	tunteina
				minuten	TWA: 1900 mg/m <sup>3</sup> 8
				TWA: 260 mg/m <sup>3</sup> 8 uren	tunteina
					STEL: 1300 ppm 15
					minuutteina
					STEL: 2500 mg/m <sup>3</sup> 15
					minuutteina

Component	Austria	Denmark	Switzerland	Poland	Norway
Ethyl alcohol	MAK-KZGW: 2000 ppm	TWA: 1000 ppm 8 timer	STEL: 1000 ppm 15	TWA: 1900 mg/m <sup>3</sup> 8	TWA: 500 ppm 8 timer
	15 Minuten	TWA: 1900 mg/m <sup>3</sup> 8	Minuten	godzinach	TWA: 950 mg/m <sup>3</sup> 8 timer
	MAK-KZGW: 3800	timer	STEL: 1920 mg/m <sup>3</sup> 15	-	STEL: 625 ppm 15
	mg/m <sup>3</sup> 15 Minuten	STEL: 2000 ppm 15	Minuten		minutter. value
	MAK-TMW: 1000 ppm 8	minutter	TWA: 500 ppm 8		calculated
	Stunden	STEL: 3800 mg/m <sup>3</sup> 15	Stunden		STEL: 1187.5 mg/m <sup>3</sup> 15
	MAK-TMW: 1900 mg/m <sup>3</sup>	minutter	TWA: 960 mg/m <sup>3</sup> 8		minutter. value
	8 Stunden		Stunden		calculated

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Ethyl alcohol	TWA: 1000 mg/m <sup>3</sup>	TWA-GVI: 1000 ppm 8	STEL: 1000 ppm 15 min		TWA: 1000 mg/m <sup>3</sup> 8
	_	satima.			hodinách.
		TWA-GVI: 1900 mg/m <sup>3</sup>			Ceiling: 3000 mg/m <sup>3</sup>
		8 satima.			

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Ethyl alcohol	TWA: 500 ppm 8		TWA: 1000 ppm	STEL: 3800 mg/m <sup>3</sup> 15	TWA: 1000 ppm 8
	tundides.		TWA: 1900 mg/m <sup>3</sup>	percekben. CK	klukkustundum.
	TWA: 1000 mg/m <sup>3</sup> 8			TWA: 1900 mg/m <sup>3</sup> 8	TWA: 1900 mg/m <sup>3</sup> 8
	tundides.			órában. AK	klukkustundum.
	STEL: 1000 ppm 15				Ceiling: 2000 ppm
	minutites.				Ceiling: 3800 mg/m <sup>3</sup>
	STEL: 1900 mg/m <sup>3</sup> 15				0 0
	minutites.				

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Ethyl alcohol	TWA: 1000 mg/m <sup>3</sup>	TWA: 500 ppm IPRD			TWA: 1000 ppm 8 ore
	_	TWA: 1000 mg/m <sup>3</sup>			TWA: 1900 mg/m <sup>3</sup> 8 ore
		IPRD			STEL: 5000 ppm 15
		STEL: 1000 ppm			minute
		STEL: 1900 mg/m <sup>3</sup>			STEL: 9500 mg/m <sup>3</sup> 15

\_\_\_\_\_

#### Ethanol, absolute

Revision Date 19-Oct-2023

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Ethyl alcohol	TWA: 1000 mg/m <sup>3</sup> 2391	Ceiling: 1920 mg/m <sup>3</sup>	TWA: 960 mg/m <sup>3</sup> 8 urah	Indicative STEL: 1000	
•	MAC: 2000 mg/m <sup>3</sup>	TWA: 500 ppm	TWA: 500 ppm 8 urah	ppm 15 minuter	
		TWA: 960 mg/m <sup>3</sup>	STEL: 1000 ppm 15	Indicative STEL: 1900	
		_	minutah	mg/m <sup>3</sup> 15 minuter	
			STEL: 1920 mg/m <sup>3</sup> 15	TLV: 500 ppm 8 timmar.	
			minutah	NGV	
				TLV: 1000 mg/m <sup>3</sup> 8	
				timmar. NGV	

## **Biological limit values**

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

## **Monitoring methods**

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

## Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

	Component	Acute effects local (Oral)	Acute effects systemic (Oral)	Chronic effects local (Oral)	Chronic effects systemic (Oral)
Ī	Ethyl alcohol 64-17-5 ( >99 )		DNEL = 87 mg/kg bw/d		

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Ethyl alcohol 64-17-5 ( >99 )				DNEL = 343mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)	
Ethyl alcohol 64-17-5 ( >99 )	DNEL = 1900mg/m <sup>3</sup>			DNEL = 950mg/m <sup>3</sup>	

## **Predicted No Effect Concentration (PNEC)**

See values below.

## 8.2. Exposure controls

## **Engineering Measures**

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to

control hazardous materials at source

Personal protective equipment

**Eye Protection** Goggles (European standard - EN 166)

Hand Protection Protective gloves

	Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
ĺ	Butyl rubber	> 480 minutes	0.38 mm - 0.56 mm	Level 6	As tested under EN374-3 Determination of
	Neoprene	> 480 minutes	0.45 mm	EN 374	Resistance to Permeation by Chemicals
	Viton (R)	> 480 minutes	0.7 mm		·

**Skin and body protection**Wear appropriate protective gloves and clothing to prevent skin exposure.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

**Respiratory Protection** No protective equipment is needed under normal use conditions.

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to

Method - No information available

EN14387

Small scale/Laboratory use Maintain adequate ventilation

**Environmental exposure controls** No information available.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

## 9.1. Information on basic physical and chemical properties

Physical State Liquid

Appearance Colorless

Odor sweet, Characteristic
Odor Threshold No data available
Melting Point/Range -114 °C / -173.2 °F
Softening Point No data available
Boiling Point/Range 78 °C / 172.4 °F
Flammability (liquid) Highly flammable

Flammability (liquid) Highly flammable On basis of test data

Flammability (solid,gas) Not applicable Liquid

Explosion Limits Lower 3.3 vol % Upper 19.0 vol %

Flash Point 12 °C / 53.6 °F

Autoignition Temperature

Decomposition Temperature
pH

Viscosity

363 °C / 685.4 °F

No data available
No information available
1.2 mPa.s @ 20°C

Water Solubility Miscible

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Component log Pow
Ethyl alcohol -0.32

Vapor Pressure 59 hPa @ 20°C

Density / Specific Gravity 0.790

Bulk Density Not applicable Liquid

\_\_\_\_\_

Ethanol, absolute Revision Date 19-Oct-2023

Vapor Density 1.59 (Air = 1.0)

Particle characteristics (liquid) Not applicable

9.2. Other information

Molecular Formula C2 H6 O Molecular Weight 46.07

Explosive Properties Vapors may form explosive mixtures with air

## **SECTION 10: STABILITY AND REACTIVITY**

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

10.4. Conditions to avoid

Incompatible products. Heat, flames and sparks. Keep away from open flames, hot

surfaces and sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids. Acid anhydrides. Acid chlorides.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO2).

## **SECTION 11: TOXICOLOGICAL INFORMATION**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Product Information**

(a) acute toxicity;

OralBased on available data, the classification criteria are not metDermalBased on available data, the classification criteria are not metInhalationBased on available data, the classification criteria are not met

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl alcohol LD50 = 10470 mg/kg		-	LC50 = 117-125 mg/l (4h)
	OECD 401 (Rat)		OECD 403 (rat)
	3450 mg/kg ( Mouse )		20000 ppm/10H (rat)

(b) skin corrosion/irritation; Based on available data, the classification criteria are not met

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;

**Respiratory** Based on available data, the classification criteria are not met

Ethanol, absolute Revision Date 19-Oct-2023

Skin Based on available data, the classification criteria are not met

Component	Test method	Test species	Study result
Ethyl alcohol	Mouse Ear Swelling Test (MEST)	mouse	non-sensitising
64-17-5 (>99)			
		mouse	non-sensitising
	OECD Test Guideline 429		·
	Local Lymph Node Assay		

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

Component	Test method	Test species	Study result
Ethyl alcohol	Ethyl alcohol AMES test		negative
64-17-5 ( >99 )	OECD Test Guideline 471	Bacteria	_
	Gene cell mutation		
	OECD Test Guideline 476	in vitro	negative
		Mammalian	_

(f) carcinogenicity; Based on available data, the classification criteria are not met

> The table below indicates whether each agency has listed any ingredient as a carcinogen Ethanol has been shown to be carcinogenic in long-term studies only when consumed and abused as an alcoholic beverage.

(a) reproductive toxicity: Based on available data, the classification criteria are not met

(3)	,,		-
Component	Test method	Test species / Duration	Study result
Ethyl alcohol	OECD Test Guideline 416	Oral / mouse	NOAEL = 13.8 g/kg/day
64-17-5 ( >99 )		2 Generation	
	OECD Test Guideline 414		
		Inhalation / Rat	NOAEC =
			mag 00061

Based on available data, the classification criteria are not met (h) STOT-single exposure;

Based on available data, the classification criteria are not met (i) STOT-repeated exposure;

**Target Organs** None known.

(j) aspiration hazard; Based on available data, the classification criteria are not met

Symptoms / effects, both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. delayed

11.2. Information on other hazards

**Endocrine Disrupting Properties** Assess endocrine disrupting properties for human health. This product does not contain any

known or suspected endocrine disruptors.

## **SECTION 12: ECOLOGICAL INFORMATION**

12.1. Toxicity **Ecotoxicity effects** 

Component	Freshwater Fish	Water Flea	Freshwater Algae		
Ethyl alcohol	Fathead minnow (Pimephales	EC50 = 9268 mg/L/48h	EC50 (72h) = 275 mg/l (Chlorella		

## Ethanol, absolute Revision Date 19-Oct-2023

promelas) LC50 = 14200 mg/l/96h	EC50 = 10800 mg/L/24h	vulgaris)
1119/1/3011		

Component	Microtox	M-Factor
Ethyl alcohol	Ethyl alcohol Photobacterium phosphoreum:EC50 = 34634	
	mg/L/30 min	
	Photobacterium phosphoreum:EC50 = 35470	
	mg/L/5 min	

#### 12.2. Persistence and degradability Readily biodegradable

**Persistence** Persistence is unlikely, based on information available.

Component	Degradability
Ethyl alcohol	OECD 301E = 94%
64-17-5 (>99)	

#### **12.3. Bioaccumulative potential** Bioaccumulation is unlikely

Component log Pow		Bioconcentration factor (BCF)
Ethyl alcohol	-0.32	No data available

**12.4. Mobility in soil**The product contains volatile organic compounds (VOC) which will evaporate easily from all

surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in

air

12.5. Results of PBT and vPvB

assessment

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent

and very bioaccumulative (vPvB).

12.6. Endocrine disrupting

properties

**Endocrine Disruptor Information** 

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant
Ozone Depletion Potential

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

## **SECTION 13: DISPOSAL CONSIDERATIONS**

#### 13.1. Waste treatment methods

Waste from Residues/Unused

**Products** 

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

**Contaminated Packaging** 

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

**European Waste Catalogue (EWC)** 

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information

Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations.

**Switzerland - Waste Ordinance** 

Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance,

ADWO) SR 814.600

https://www.fedlex.admin.ch/eli/cc/2015/891/en

## **SECTION 14: TRANSPORT INFORMATION**

## IMDG/IMO

14.1. UN numberUN117014.2. UN proper shipping nameETHANOL14.3. Transport hazard class(es)3

14.4. Packing group

## <u>ADR</u>

14.1. UN number UN1170 14.2. UN proper shipping name ETHANOL

14.3. Transport hazard class(es) 3 14.4. Packing group II

#### IATA

**14.1. UN number 14.2. UN proper shipping name**UN1170
ETHANOL

14.3. Transport hazard class(es) 3 14.4. Packing group II

14.5. Environmental hazards No hazards identified

**14.6. Special precautions for user** No special precautions required.

14.7. Maritime transport in bulk Not applicable, packaged goods

according to IMO instruments

## **SECTION 15: REGULATORY INFORMATION**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## **International Inventories**

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Ethyl alcohol	64-17-5	200-578-6	-	ı	X	Χ	KE-13217	Х	Х

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Ethyl alcohol	64-17-5	X	ACTIVE	X	-	X	Х	Х

**Legend:** X - Listed '-' - Not Listed **KECL** - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

## Authorisation/Restrictions according to EU REACH Not applicable

	Component		REACH (1907/2006) - Annex XVII - Restrictions	
- 1		Subject to Authorization	on Certain Dangerous	Candidate List of
			Substances	Substances of Very High
				Concern (SVHC)

#### Ethanol, absolute Revision Date 19-Oct-2023

Ethyl alcohol	64-17-5	-	-	-
---------------	---------	---	---	---

## Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) -	Seveso III Directive (2012/18/EC) -	
		Qualifying Quantities for Major Accident	Qualifying Quantities for Safety Report	
		Notification	Requirements	
Ethyl alcohol	64-17-5	Not applicable	Not applicable	

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

## **National Regulations**

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification See table for values

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class	
Ethyl alcohol	WGK1		

Component	France - INRS (Tables of occupational diseases)
Ethyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84

## **Swiss Regulations**

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Ethyl alcohol 64-17-5 ( >99 )		Group I	

## 15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has been conducted by the manufacturer/importer

## **SECTION 16: OTHER INFORMATION**

## Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor

H319 - Causes serious eye irritation

Legend

Ethanol, absolute Revision Date 19-Oct-2023

Substances List

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

ICAO/IATA - International Civil Aviation Organization/International Air

MARPOL - International Convention for the Prevention of Pollution from

**ENCS** - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

IARC - International Agency for Research on Cancer

NZIoC - New Zealand Inventory of Chemicals

Predicted No Effect Concentration (PNEC)

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

EC50 - Effective Concentration 50%

TWA - Time Weighted Average

LD50 - Lethal Dose 50%

Transport Association

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic

Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances IECSC - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

WEL - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

**RPE** - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration PBT - Persistent. Bioaccumulative. Toxic

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

Key literature references and sources for data

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

https://echa.europa.eu/information-on-chemicals

## **Training Advice**

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts. Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and

Ships

First aid for chemical exposure, including the use of eye wash and safety showers.

**Creation Date** 27-Oct-2009 **Revision Date** 19-Oct-2023 Not applicable. **Revision Summary** 

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

## **End of Safety Data Sheet**