

## SAFETY DATA SHEET

Creation Date 21-May-2012

Revision Date 25-Dec-2021

Revision Number 6

### 1. Identification

**Product Name** tert-Butylmagnesium chloride, solution in diethylether

**Cat No. :** AC394300000; AC394301000; AC394308000

**Synonyms** No information available

**Recommended Use** Laboratory chemicals.  
**Uses advised against** Food, drug, pesticide or biocidal product use.

#### Details of the supplier of the safety data sheet

##### Company

Fisher Scientific Company  
One Reagent Lane  
Fair Lawn, NJ 07410  
Tel: (201) 796-7100

Acros Organics  
One Reagent Lane  
Fair Lawn, NJ 07410

**Emergency Telephone Number** For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11  
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99  
**CHEMTREC** Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

### 2. Hazard(s) identification

#### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 1
Substances/mixtures which, in contact with water, emit flammable gases	Category 1
Acute oral toxicity	Category 4
Skin Corrosion/Irritation	Category 1 B
Serious Eye Damage/Eye Irritation	Category 1
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Respiratory system, Central nervous system (CNS).	

#### Label Elements

**Signal Word**  
Danger

**Hazard Statements**  
Extremely flammable liquid and vapor

In contact with water releases flammable gases which may ignite spontaneously  
Harmful if swallowed  
Causes severe skin burns and eye damage  
May cause respiratory irritation  
May cause drowsiness or dizziness



### Precautionary Statements

#### Prevention

Wash face, hands and any exposed skin thoroughly after handling  
Do not eat, drink or smoke when using this product  
Do not breathe dust/fume/gas/mist/vapors/spray  
Wear protective gloves/protective clothing/eye protection/face protection  
Use only outdoors or in a well-ventilated area  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
Keep container tightly closed  
Ground/bond container and receiving equipment  
Use explosion-proof electrical/ventilating/lighting equipment  
Use only non-sparking tools  
Take precautionary measures against static discharge  
Keep away from any possible contact with water, because of violent reaction and possible flash fire  
Handle under inert gas. Protect from moisture  
Keep cool

#### Response

Immediately call a POISON CENTER or doctor/physician

#### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

#### Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
Wash contaminated clothing before reuse  
Brush off loose particles from skin. Immerse in cool water/wrap with wet bandages

#### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

#### Ingestion

Rinse mouth  
Do NOT induce vomiting

#### Fire

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

#### Storage

Store locked up  
Store in a well-ventilated place. Keep container tightly closed  
Store in a dry place. Store in a closed container

#### Disposal

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Reacts violently with water  
May form explosive peroxides  
Repeated exposure may cause skin dryness or cracking

## 3. Composition/Information on Ingredients

Component	CAS No	Weight %
Ethyl ether	60-29-7	72-75
tert-Butylmagnesium chloride	677-22-5	25-28

#### 4. First-aid measures

<b>General Advice</b>	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
<b>Skin Contact</b>	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately.
<b>Inhalation</b>	If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately.
<b>Ingestion</b>	Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately.
<b>Most important symptoms and effects</b>	Causes burns by all exposure routes. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
<b>Notes to Physician</b>	Treat symptomatically

#### 5. Fire-fighting measures

<b>Suitable Extinguishing Media</b>	CO <sub>2</sub> , dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.
<b>Unsuitable Extinguishing Media</b>	DO NOT USE WATER
<b>Flash Point</b>	-40 °C / -40 °F
<b>Method -</b>	(based on components)
<b>Autoignition Temperature</b>	No information available
<b>Explosion Limits</b>	
<b>Upper</b>	No data available
<b>Lower</b>	No data available
<b>Sensitivity to Mechanical Impact</b>	No information available
<b>Sensitivity to Static Discharge</b>	No information available

#### Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Reacts violently with water. Extremely flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

#### Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Magnesium oxides. Hydrogen chloride gas. Isobutane.

#### Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

**NFPA**

**Health**  
3

**Flammability**  
4

**Instability**  
2

**Physical hazards**  
W

## 6. Accidental release measures

<b>Personal Precautions</b>	Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.
<b>Environmental Precautions</b>	Should not be released into the environment.
<b>Methods for Containment and Clean Up</b>	Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Do not expose spill to water. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

## 7. Handling and storage

<b>Handling</b>	Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water. If peroxide formation is suspected, do not open or move container. Keep away from open flames, hot surfaces and sources of ignition. Use spark-proof tools and explosion-proof equipment. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.
<b>Storage.</b>	Keep away from water or moist air. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. Keep away from heat, sparks and flame. Corrosives area. Keep containers tightly closed in a dry, cool and well-ventilated place. Incompatible Materials. Acids. Bases. Water. Alcohols.

## 8. Exposure controls / personal protection

**Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Ethyl ether	TWA: 400 ppm STEL: 500 ppm	(Vacated) TWA: 400 ppm (Vacated) TWA: 1200 mg/m <sup>3</sup> (Vacated) STEL: 500 ppm (Vacated) STEL: 1500 mg/m <sup>3</sup> TWA: 400 ppm TWA: 1200 mg/m <sup>3</sup>	IDLH: 1900 ppm	TWA: 400 ppm STEL: 500 ppm

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

<b>Engineering Measures</b>	Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.
-----------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Personal Protective Equipment**

<b>Eye/face Protection</b>	Tight sealing safety goggles. Face protection shield.
<b>Skin and body protection</b>	Wear appropriate protective gloves and clothing to prevent skin exposure.
<b>Respiratory Protection</b>	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
<b>Hygiene Measures</b>	Handle in accordance with good industrial hygiene and safety practice.

## 9. Physical and chemical properties

<b>Physical State</b>	Liquid
<b>Appearance</b>	Brown
<b>Odor</b>	pungent, Ether
<b>Odor Threshold</b>	No information available
<b>pH</b>	No information available
<b>Melting Point/Range</b>	No data available
<b>Boiling Point/Range</b>	34 °C / 93.2 °F
<b>Flash Point</b>	-40 °C / -40 °F
<b>Method -</b>	(based on components)
<b>Evaporation Rate</b>	No information available
<b>Flammability (solid,gas)</b>	Not applicable
<b>Flammability or explosive limits</b>	
<b>Upper</b>	No data available
<b>Lower</b>	No data available
<b>Vapor Pressure</b>	No information available
<b>Vapor Density</b>	No information available
<b>Specific Gravity</b>	0.800
<b>Solubility</b>	Reacts violently with water
<b>Partition coefficient; n-octanol/water</b>	No data available
<b>Autoignition Temperature</b>	No information available
<b>Decomposition Temperature</b>	No information available
<b>Viscosity</b>	No information available
<b>Molecular Formula</b>	C4 H9 Cl Mg
<b>Molecular Weight</b>	116.87

## 10. Stability and reactivity

<b>Reactive Hazard</b>	Yes
<b>Stability</b>	Air sensitive. Moisture sensitive.
<b>Conditions to Avoid</b>	Exposure to moist air or water. Exposure to air. Keep away from open flames, hot surfaces and sources of ignition. Exposure to moisture.
<b>Incompatible Materials</b>	Acids, Bases, Water, Alcohols
<b>Hazardous Decomposition Products</b>	Carbon monoxide (CO), Carbon dioxide (CO <sub>2</sub> ), Magnesium oxides, Hydrogen chloride gas, Isobutane
<b>Hazardous Polymerization</b>	Hazardous polymerization does not occur.
<b>Hazardous Reactions</b>	Reacts violently with water.

## 11. Toxicological information

### Acute Toxicity

### Product Information

**Oral LD50**

Category 4. ATE = 300 - 2000 mg/kg.

**Dermal LD50**

Based on ATE data, the classification criteria are not met. ATE &gt; 2000 mg/kg.

**Vapor LC50**

Based on ATE data, the classification criteria are not met. ATE &gt; 20 mg/l.

**Component Information**

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl ether	1215 mg/kg (Rat)	20 mL/kg (Rabbit)	32000 ppm ( Rat ) 4 h

**Toxicologically Synergistic Products**

No information available

**Delayed and immediate effects as well as chronic effects from short and long-term exposure****Irritation**

No information available

**Sensitization**

No information available

**Carcinogenicity**

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Ethyl ether	60-29-7	Not listed	Not listed	Not listed	Not listed	Not listed
tert-Butylmagnesium chloride	677-22-5	Not listed	Not listed	Not listed	Not listed	Not listed

**Mutagenic Effects**

No information available

**Reproductive Effects**

No information available.

**Developmental Effects**

No information available.

**Teratogenicity**

No information available.

**STOT - single exposure**

Respiratory system Central nervous system (CNS)

**STOT - repeated exposure**

None known

**Aspiration hazard**

No information available

**Symptoms / effects, both acute and delayed**

Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

**Endocrine Disruptor Information**

No information available

**Other Adverse Effects**

The toxicological properties have not been fully investigated.

## 12. Ecological information

**Ecotoxicity**

Reacts with water so no ecotoxicity data for the substance is available.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Ethyl ether	Not listed	LC50: > 10000 mg/L, 96h static (Lepomis macrochirus) LC50: = 2560 mg/L, 96h flow-through (Pimephales promelas)	EC50 = 5600 mg/L 15 min	EC50 = 165 mg/L/24h

**Persistence and Degradability**

Persistence is unlikely based on information available.

**Bioaccumulation/ Accumulation**

No information available.

**Mobility**

Will likely be mobile in the environment due to its volatility.

Component	log Pow
Ethyl ether	0.82

### 13. Disposal considerations

**Waste Disposal Methods** Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Ethyl ether - 60-29-7	U117	-

### 14. Transport information

#### DOT

UN-No UN3399  
 Proper Shipping Name Organometallic substance, liquid, water-reactive, flammable  
 Technical Name Ethyl ether, tert-Butylmagnesium chloride  
 Hazard Class 4.3  
 Packing Group I

#### TDG

UN-No UN3399  
 Proper Shipping Name Organometallic substance, liquid, water-reactive, flammable  
 Hazard Class 4.3  
 Subsidiary Hazard Class 3  
 Packing Group I

#### IATA

UN-No UN3399  
 Proper Shipping Name Organometallic substance, liquid, water-reactive, flammable  
 Hazard Class 4.3  
 Subsidiary Hazard Class 3  
 Packing Group I

#### IMDG/IMO

UN-No UN3399  
 Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE, FLAMMABLE  
 Hazard Class 4.3  
 Subsidiary Hazard Class 3  
 Packing Group I

### 15. Regulatory information

#### United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Ethyl ether	60-29-7	X	ACTIVE	-
tert-Butylmagnesium chloride	677-22-5	-	-	-

#### Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA 12(b) - Notices of Export Not applicable

#### International Inventories

Canada (DSL/NDL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
-----------	--------	-----	-----	--------	-------	------	------	------	-------	------

Ethyl ether	60-29-7	X	-	200-467-2	X	X	X	X	X	KE-27690
tert-Butylmagnesium chloride	677-22-5	-	-	211-638-6	-	X	X	-	-	-

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

### U.S. Federal Regulations

**SARA 313** Not applicable

**SARA 311/312 Hazard Categories** See section 2 for more information

**CWA (Clean Water Act)** Not applicable

**Clean Air Act** Not applicable

**OSHA - Occupational Safety and Health Administration** Not applicable

**CERCLA** This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Ethyl ether	100 lb	-

**California Proposition 65** This product does not contain any Proposition 65 chemicals.

### U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Ethyl ether	X	X	X	-	X

### U.S. Department of Transportation

Reportable Quantity (RQ): Y  
DOT Marine Pollutant N  
DOT Severe Marine Pollutant N

**U.S. Department of Homeland Security** This product contains the following DHS chemicals:  
**Legend** - STQs = Screening Threshold Quantities, APA = A placarded amount

Component	DHS Chemical Facility Anti-Terrorism Standard
Ethyl ether	Release STQs - 10000lb

### Other International Regulations

**Mexico - Grade** Severe risk, Grade 4

**Authorisation/Restrictions according to EU REACH**

### Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Ethyl ether	60-29-7	Listed	Not applicable	Not applicable	Not applicable
tert-Butylmagnesium chloride	677-22-5	Not applicable	Not applicable	Not applicable	Not applicable

Component	CAS No	Seveso III Directive (2012/18/EC) -	Seveso III Directive (2012/18/EC) -	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
-----------	--------	-------------------------------------	-------------------------------------	----------------------------	------------------------------------



		Qualifying Quantities for Major Accident Notification	Qualifying Quantities for Safety Report Requirements		
Ethyl ether	60-29-7	Not applicable	Not applicable	Not applicable	Annex I - Y40 Annex I - Y42
tert-Butylmagnesium chloride	677-22-5	Not applicable	Not applicable	Not applicable	Not applicable

## 16. Other information

**Prepared By** Regulatory Affairs  
Thermo Fisher Scientific  
Email: EMSDS.RA@thermofisher.com

**Creation Date** 21-May-2012  
**Revision Date** 25-Dec-2021  
**Print Date** 25-Dec-2021  
**Revision Summary** This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**