

SAFETY DATA SHEET

Page 1/9 Creation Date 13-Apr-2009 Revision Date 22-Mar-2025 Version 6

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THECOMPANY/UNDERTAKING

Product Identifier

Perihalan Produk: 2-Butanone **Product Description:** 2-Butanone

Cat No.: 396950000; 396950010; 396951000

Synonyms Methyl ethyl ketone; MEK; Ethyl methyl ketone

CAS No 78-93-3 **Molecular Formula** C4 H8 O

Relevant identified uses of the substance or mixture and uses advised against

Laboratory chemicals. **Recommended Use** No Information available Uses advised against

Company Thermo Fisher Scientific Fisher Scientific (M) Sdn Bhd

> Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square, No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,

Selangor Darul Ehsan, Malaysia. Main line: +60 3-5525 7888

E-mail address Enquiry.my@thermofisher.com

Tel: +03-5525 7888 **Emergency Telephone Number**

CHEMTREC Malaysia 1-800-815-308 (Malay)

CHEMTREC Malaysia (Kuala Lumpur) +(60)-327884561 (Malay)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

Flammable liquids	Category 2 (H225)
Serious Eye Damage/Eye Irritation	Category 2 (H319)
Specific target organ toxicity - (single exposure)	Category 3 (H336)

Label Elements



Signal Word **Danger**

Hazard Statements

H225 - Highly flammable liquid and vapor

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

Precautionary Statements

Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P240 - Ground and bond container and receiving equipment

P241 - Use explosion-proof electrical/ ventilating/ lighting equipment

P242 - Use non-sparking tools

P243 - Take action to prevent static discharges

P264 - Wash face, hands and any exposed skin thoroughly after handling

P270 - Do not eat, drink or smoke when using this product

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection

Response

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P312 - Call a POISON CENTER or doctor if you feel unwell

P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other Hazards

EUH066 - Repeated exposure may cause skin dryness or cracking

Contains a substance on the National Authorities Endocrine Disruptor Lists

Contains a known or suspected endocrine disruptor

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No	Weight %
Methyl ethyl ketone	78-93-3	<=100

SECTION 4: FIRST AID MEASURES

Description of first aid measures

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Get medical attention if

symptoms occur.

Ingestion Do NOT induce vomiting. Get medical attention.

Inhalation Remove to fresh air. Get medical attention if symptoms occur. If not breathing, give artificial

respiration.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO2).

Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation.

Environmental precautions

Avoid release to the environment. See Section 12 for additional Ecological Information.

Methods and Material for Containment and Cleaning Up

Remove all sources of ignition. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Use spark-proof tools and explosion-proof equipment.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Use spark-proof tools and explosion-proof equipment. Avoid contact with skin, eyes or clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces

and sources of ignition. Take precautionary measures against static discharges. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Conditions for Safe Storage, Including any Incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

Specific End Uses

Use in laboratories.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	Malaysia	ACGIH TLV	OSHA PEL
Methyl ethyl ketone		TWA: 200 ppm	(Vacated) TWA: 200 ppm
		STEL: 300 ppm	(Vacated) TWA: 590 mg/m ³
			(Vacated) STEL: 300 ppm
			(Vacated) STEL: 885 mg/m ³
			TWA: 200 ppm
			TWA: 590 mg/m ³

Component	European Union	The United Kingdom	Germany
Methyl ethyl ketone	TWA: 200 ppm (8h)	STEL: 300 ppm 15 min	TWA: 200 ppm (8 Stunden). AGW -
	TWA: 600 mg/m ³ (8h)	STEL: 899 mg/m ³ 15 min	exposure factor 1
	STEL: 300 ppm (15min)	TWA: 200 ppm 8 hr	TWA: 600 mg/m ³ (8 Stunden). AGW
	STEL: 900 mg/m ³ (15min)	TWA: 600 mg/m ³ 8 hr	- exposure factor 1
		Skin	TWA: 200 ppm (8 Stunden). MAK
			TWA: 600 mg/m³ (8 Stunden). MAK
			Höhepunkt: 200 ppm
			Höhepunkt: 600 mg/m ³
			Haut

Exposure Controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles **Hand Protection** Protective gloves

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators

Recommended Filter type: Type A Organic gases and vapours filter Brown conforming to EN14387

<u>Hygiene Measures</u> Handle in accordance with good industrial hygiene and safety practice

Environmental exposure controls No information available

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance Colorless
Physical State Liquid

Odor Characteristic - sweet
Odor Threshold No data available
pH No information available

Melting Point/Range-87 °C / -124.6 °FSoftening PointNo data availableBoiling Point/Range80 °C / 176 °FFlash Point-7 °C / 19.4 °F

Flash Point -7 °C / 19.4 °F Method - CC (closed cup)

Evaporation Rate 3.7 (Butyl Acetate = 1.0)

Flammability (solid,gas) Not applicable Liquid

Explosion Limits Lower 1.8 Vol%

Upper 11.5 Vol%

Vapor Pressure 105 mbar @ 20 °C

Vapor Density 2.41 (Air = 1.0)

Specific Gravity / Density 0.806

Bulk Density

Not applicable
Liquid
Water Solubility

290 g/L (20°C)

Solubility in other solvents

No information available

Partition Coefficient (n-octanol/water)

Component log Pow Methyl ethyl ketone 0.29

Autoignition Temperature 404 °C / 759.2 °F Decomposition Temperature No data available Viscosity 0.42 mPa.s @ 15°C

Explosive Properties Not explosive Vapors may form explosive mixtures with air

Oxidizing Properties Not oxidising

Molecular FormulaC4 H8 OMolecular Weight72.11

SECTION 10: STABILITY AND REACTIVITY

Reactivity

None known, based on information available.

Chemical Stability

Hygroscopic.

Possibility of Hazardous Reactions

Hazardous Polymerization Hazardous Reactions

Hazardous polymerization does not occur.

None under normal processing.

Conditions to Avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition. Exposure to moist air or water.

Incompatible Materials

Strong oxidizing agents. Strong acids. Strong bases. Strong reducing agents. Ammonia.

copper. Amines.

Hazardous Decomposition Products

Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects

Product Information

(a) acute toxicity;

Oral Based on available data, the classification criteria are not met
Dermal Based on available data, the classification criteria are not met
Inhalation Based on available data, the classification criteria are not met

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation	
Methyl ethyl ketone	LD50 = 2483 mg/kg (Rat)	LD50 = 5000 mg/kg (Rabbit)	LC50 = 11700 ppm (Rat) 4 h	

(b) skin corrosion/irritation; Based on available data, the classification criteria are not met

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;

RespiratorySkin
Based on available data, the classification criteria are not met
Based on available data, the classification criteria are not met

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

Not mutagenic in AMES Test

(f) carcinogenicity; Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

Revision Date 22-Mar-2025 2-Butanone

(g) reproductive toxicity; Based on available data, the classification criteria are not met

Category 3 (h) STOT-single exposure;

Central nervous system (CNS). Results / Target organs

(i) STOT-repeated exposure: Based on available data, the classification criteria are not met

None known. **Target Organs**

Based on available data, the classification criteria are not met (j) aspiration hazard;

delayed

Symptoms / effects, both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health

Contains a substance on the National Authorities Endocrine Disruptor Lists

Component	EU National Authorities Endocrine Disruptor Lists - Health
Methyl ethyl ketone 78-93-3 (<=100)	List II

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity effects

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Methyl ethyl ketone	Lepomis macrochirus: LC50=3,22 g/L 96 h	EC50: = 5091 mg/L, 48h (Daphnia magna) EC50: 4025 - 6440 mg/L, 48h Static (Daphnia magna) EC50: > 520 mg/L, 48h (Daphnia magna)		EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min

Readily biodegradable Persistence and degradability

Persistence Persistence is unlikely, based on information available.

1 01010101100	r croictorice is armitory, bacca cri	mioritation available.
	Component	Degradability
Methyl ethyl ketone		98% (28d)
	78-93-3 (<=100)	

Bioaccumulation is unlikely Bioaccumulative potential

Dioassamalative peteritian	ziedeediiidaanen le diiliitely	
Component	log Pow	Bioconcentration factor (BCF)
Methyl ethyl ketone	0.29	No data available

Mobility in soil The product contains volatile organic compounds (VOC) which will evaporate easily from all

surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in

air.

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

Other adverse effects No information available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from Residues/Unused

Products

Waste is classified as hazardous Dispose of in accordance with the European Directives on

waste and hazardous waste Dispose of in accordance with local regulations

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous Keep product and

empty container away from heat and sources of ignition

Other Information Waste codes should be assigned by the user based on the application for which the product

was used Do not flush to sewer Can be landfilled or incinerated, when in compliance with

local regulations

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

UN-No UN1193
Hazard Class 3
Packing Group II

Proper Shipping Name Ethyl methyl ketone (Methyl ethyl ketone)

Road and Rail Transport

UN-No UN1193 Hazard Class 3 Packing Group II

Proper Shipping Name Ethyl methyl ketone (Methyl ethyl ketone)

IATA

UN-No UN1193 Hazard Class 3 Packing Group II

Proper Shipping Name Methyl ethyl ketone

Special Precautions for User No special precautions required

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories X = listed

	Component	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	IECSC	AICS	KECL
Ì	Methyl ethyl ketone	201-159-0	Х	Х	Х	X	Χ	X	X	KE-24094

Component	Seveso III Directive	Seveso III Directive	Rotterdam Convention	Basel Convention
-	(2012/18/EC) - Qualifying	(2012/18/EC) - Qualifying	(PIC)	(Hazardous Waste)
	Quantities for Major	Quantities for Safety	- *	,

SAFETY DATA SHEET

Revision Date 22-Mar-2025 2-Butanone

	Accident Notification	Report Requirements	
Methyl ethyl ketone			Annex I - Y42

National Regulations

Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 16: OTHER INFORMATION

Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50%

POW - Partition coefficient Octanol:Water

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Substances List **ENCS** - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

ICAO/IATA - International Civil Aviation Organization/International Air

Transport Association MARPOL - International Convention for the Prevention of Pollution from

Ships

ATE - Acute Toxicity Estimate VOC - (Volatile Organic Compound)

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Revision Date 22-Mar-2025 **Revision Summary** Not applicable.

In accordance with local and national regulations: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet