

Creation Date 16-Nov-2010

Revision Date 04-Oct-2023

Revision Number 9

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: **Wood's metal**
Cat No. : **388550000; 388551000; 388555000**
Index No **048-001-00-5**
CAS No **76093-98-6**
Molecular Formula **Bi . Cd . Pb . Sn**

Unique Formula Identifier (UFI) **R2RM-XU67-3W0J-CM60**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use **Laboratory chemicals.**
Uses advised against **No Information available**

1.3. Details of the supplier of the safety data sheet

Company

EU entity/business name
Thermo Fisher Scientific
Janssen Pharmaceuticaaan 3a, 2440 Geel, Belgium

UK entity/business name
Fisher Scientific UK
Bishop Meadow Road,
Loughborough, Leicestershire LE11 5RG, United Kingdom

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
e-mail - infoch@thermofisher.com

E-mail address **begel.sdsdesk@thermofisher.com**

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

Poison Centre - Emergency information services

Ireland : National Poisons Information Centre (NPIC) -
01 809 2166 (8am-10pm, 7 days a week)
Malta : +356 2395 2000
Cyprus : +357 2240 5611

SAFETY DATA SHEET

Wood"s metal

Revision Date 04-Oct-2023

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Based on available data, the classification criteria are not met

Health hazards

Acute Inhalation Toxicity - Dusts and Mists
Germ Cell Mutagenicity
Carcinogenicity
Reproductive Toxicity
Effects on or via lactation
Specific target organ toxicity - (repeated exposure)

Category 2 (H330)
Category 2 (H341)
Category 1B (H350)
Category 1A (H360FD)
(H362)
Category 1 (H372)

Environmental hazards

Acute aquatic toxicity
Chronic aquatic toxicity

Category 1 (H400)
Category 1 (H410)

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H330 - Fatal if inhaled
H341 - Suspected of causing genetic defects
H350 - May cause cancer
H362 - May cause harm to breast-fed children
H372 - Causes damage to organs through prolonged or repeated exposure
H360FD - May damage fertility. May damage the unborn child
H410 - Very toxic to aquatic life with long lasting effects

Precautionary Statements

P201 - Obtain special instructions before use
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P310 - Immediately call a POISON CENTER or doctor/physician
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P263 - Avoid contact during pregnancy and while nursing

SAFETY DATA SHEET

Wood"s metal

Revision Date 04-Oct-2023

Additional EU labelling

Restricted to professional users

2.3. Other hazards

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Bismuth alloy, base, Bi 50, Pb 25, Cd 12, Sn 12 (L-PbBi50Sn12.5Cd12.5)	76093-98-6		100	Acute Tox. 2 (H330) Muta. 2 (H341) Carc. 1B (H350) Repr. 2 (H360df) STOT RE 1 (H372) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)
Bismuth	7440-69-9	EEC No. 231-177-4	-	-
Cadmium	7440-43-9	EEC No. 231-152-8	-	Acute Tox. 2 (H330) Muta. 2 (H341) Carc. 1B (H350) Repr. 2 (H361fd) STOT RE 1 (H372) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)
Tin	7440-31-5	EEC No. 231-141-8	-	-
Lead	7439-92-1	EEC No. 231-100-4	-	Repr. 1A (H360DF) STOT RE 1 (H372) Lact. (H362)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Bismuth alloy, base, Bi 50, Pb 25, Cd 12, Sn 12 (L-PbBi50Sn12.5Cd12.5)	Repr. 2 (H361f) :: C>=2.5% STOT RE 2 (H373) :: C>=0.5%	-	-
Cadmium	-	10	-
Lead	Repr. 1A : C ≥ 0.03 % STOT RE 1 : C ≥ 0.5 %	-	-

Note

Note 1: The concentration stated or, in the absence of such concentrations, the generic concentrations of this Regulation (Table 3.1) or the generic concentrations of Directive 1999/45/EC (Table 3.2), are the percentages by weight of the metallic element calculated with reference to the total weight of the mixture

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

SAFETY DATA SHEET

Wood"s metal

Revision Date 04-Oct-2023

Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

None reasonably foreseeable.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Non-combustible. Do not allow run-off from fire-fighting to enter drains or water courses.

Hazardous Combustion Products

Toxic fumes, Heavy metal oxides.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Avoid dust formation. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained. Should not be released into the environment.

6.3. Methods and material for containment and cleaning up

SAFETY DATA SHEET

Wood"s metal

Revision Date 04-Oct-2023

Sweep up and shovel into suitable containers for disposal. Avoid dust formation.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Avoid dust formation. Use only under a chemical fume hood. Do not breathe (dust, vapor, mist, gas). Do not ingest. If swallowed then seek immediate medical assistance.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a dry, cool and well-ventilated place. Keep container tightly closed.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Storage Class/LGK 6.1B

Switzerland - Storage of hazardous substances

Storage class - SC 6.1
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority.
CH - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund). **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC

Component	European Union	The United Kingdom	France	Belgium	Spain
Bismuth alloy, base, Bi 50, Pb 25, Cd 12, Sn 12 (L-PbBi50Sn12.5Cd1 2.5)		STEL: 4 mg/m ³ 15 min TWA: 2 mg/m ³ 8 hr STEL: 0.075 mg/m ³ 15 min TWA: 0.025 mg/m ³ 8 hr STEL: 0.45 mg/m ³ 15 min TWA: 0.15 mg/m ³ 8 hr	TWA / VME: 0.004 mg/m ³ (8 heures). restrictive limit TWA / VME: 0.1 mg/m ³ (8 heures). restrictive limit		TWA / VLA-ED: 2 mg/m ³ (8 horas) TWA / VLA-ED: 0.15 mg/m ³ (8 horas) TWA / VLA-ED: 0.01 mg/m ³ (8 horas) TWA / VLA-ED: 0.002 mg/m ³ (8 horas)
Cadmium	TWA: 0.001 mg/m ³ (8h)	STEL: 0.075 mg/m ³ 15 min TWA: 0.025 mg/m ³ 8 hr	TWA / VME: 0.004 mg/m ³ (8 heures). restrictive limit	TWA: 0.01 mg/m ³ 8 uren TWA: 0.004 mg/m ³ 8	TWA / VLA-ED: 0.01 mg/m ³ (8 horas) TWA / VLA-ED: 0.002

SAFETY DATA SHEET

Wood's metal

Revision Date 04-Oct-2023

		Carc. metal		uren	mg/m ³ (8 horas)
Tin		STEL: 4 mg/m ³ 15 min TWA: 2 mg/m ³ 8 hr		TWA: 2 mg/m ³ 8 uren Huid	TWA / VLA-ED: 2 mg/m ³ (8 horas)
Lead	TWA: 0.15 mg/m ³ (8h)	STEL: 0.45 mg/m ³ 15 min TWA: 0.15 mg/m ³ 8 hr	TWA / VME: 0.1 mg/m ³ (8 heures). restrictive limit		TWA / VLA-ED: 0.15 mg/m ³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
Bismuth alloy, base, Bi 50, Pb 25, Cd 12, Sn 12 (L-PbBi50Sn12.5Cd1 2.5)		TWA: 0.002 mg/m ³ (8 Stunden). AGW - TWA: 0.004 mg/m ³ (8 Stunden). MAK except lead arsenate and lead chromate Höhepunkt: 0.032 mg/m ³ Haut	TWA: 2 mg/m ³ 8 horas TWA: 0.05 mg/m ³ 8 horas TWA: 0.002 mg/m ³ 8 horas TWA: 0.004 mg/m ³ 8 horas		
Cadmium	TWA: 0.001 mg/m ³ 8 ore. Time Weighted Average TWA: 0.004 mg/m ³ 8 ore. Time Weighted Average until July 11, 2027	TWA: 0.002 mg/m ³ (8 Stunden). AGW - exposure factor 8 TWA: 0.002 mg/m ³ (8 Stunden). AGW - Haut	TWA: 0.001 mg/m ³ 8 horas TWA: 0.004 mg/m ³ 8 horas	TWA: 0.004 mg/m ³ 8 uren	TWA: 0.004 mg/m ³ 8 tunteina
Tin			TWA: 2 mg/m ³ 8 horas		TWA: 2 mg/m ³ 8 tunteina
Lead	TWA: 0.15 mg/m ³ 8 ore. Time Weighted Average	TWA: 0.004 mg/m ³ (8 Stunden). MAK Höhepunkt: 0.032 mg/m ³	TWA: 0.05 mg/m ³ 8 horas	TWA: 0.15 mg/m ³ 8 uren	TWA: 0.1 mg/m ³ 8 tunteina

Component	Austria	Denmark	Switzerland	Poland	Norway
Bismuth alloy, base, Bi 50, Pb 25, Cd 12, Sn 12 (L-PbBi50Sn12.5Cd1 2.5)	MAK-KZGW: 4 mg/m ³ 15 Minuten MAK-KZGW: 0.4 mg/m ³ 15 Minuten MAK-TMW: 2 mg/m ³ 8 Stunden MAK-TMW: 0.1 mg/m ³ 8 Stunden		Haut/Peau STEL: 4 mg/m ³ 15 Minuten STEL: 0.8 mg/m ³ 15 Minuten TWA: 2 mg/m ³ 8 Stunden TWA: 0.001 mg/m ³ 8 Stunden TWA: 0.1 mg/m ³ 8 Stunden		TWA: 2 mg/m ³ 8 timer TWA: 0.05 mg/m ³ 8 timer TWA: 0.001 mg/m ³ 8 timer
Cadmium	TRK-KZGW: 0.016 mg/m ³ 15 Minuten TRK-KZGW: 0.004 mg/m ³ 15 Minuten TRK-TMW: 0.004 mg/m ³ TRK-TMW: 0.001 mg/m ³	TWA: 0.001 mg/m ³ 8 timer STEL: 0.002 mg/m ³ 15 minutter	Haut/Peau TWA: 0.001 mg/m ³ 8 Stunden	TWA: 0.004 mg/m ³ 8 godzinach	TWA: 0.001 mg/m ³ 8 timer STEL: 0.003 mg/m ³ 15 minutter. value calculated inhalable fraction
Tin	MAK-KZGW: 4 mg/m ³ 15 Minuten MAK-TMW: 2 mg/m ³ 8 Stunden		Haut/Peau STEL: 0.004 ppm 15 Minuten STEL: 0.02 mg/m ³ 15 Minuten STEL: 4 mg/m ³ 15 Minuten TWA: 2 mg/m ³ 8 Stunden	TWA: 2 mg/m ³ 8 godzinach	TWA: 2 mg/m ³ 8 timer
Lead	MAK-KZGW: 0.4 mg/m ³ 15 Minuten MAK-TMW: 0.1 mg/m ³ 8 Stunden	TWA: 0.05 mg/m ³ 8 timer STEL: 0.1 mg/m ³ 15 minutter	STEL: 0.8 mg/m ³ 15 Minuten TWA: 0.1 mg/m ³ 8 Stunden	TWA: 0.05 mg/m ³ 8 godzinach	TWA: 0.05 mg/m ³ 8 timer STEL: 0.15 mg/m ³ 15 minutter. value calculated dust and fume

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Bismuth	TWA: 5.0 mg/m ³				
Cadmium	TWA: 0.004 mg/m ³	TWA-GVI: 0.004 mg/m ³ 8 satima. applies during the transition period until July 11, 2027 inhalable fraction	TWA: 0.001 mg/m ³ 8 hr. inhalable fraction TWA: 0.004 mg/m ³ 8 hr. limit value 0.004 mg/m ³ until 11 July 2027	TWA: 0.001 mg/m ³	TWA: 0.004 mg/m ³ 8 hodinách. 0.002 mg Cd/g Creatinine in urine inhalable fraction of aerosol

SAFETY DATA SHEET

Wood"s metal

Revision Date 04-Oct-2023

			inhalable fraction STEL: 0.003 mg/m ³ 15 min STEL: 0.012 mg/m ³ 15 min		Potential for cutaneous absorption Ceiling: 0.008 mg/m ³
Tin	TWA: 0.1 mg/m ³ TWA: 2.0 mg/m ³	TWA-GVI: 2 mg/m ³ 8 satima.	TWA: 2 mg/m ³ 8 hr. Sn STEL: 6 mg/m ³ 15 min	TWA: 2 mg/m ³	
Lead	TWA: 0.05 mg/m ³	TWA-GVI: 0.15 mg/m ³ 8 satima.	TWA: 0.15 mg/m ³ 8 hr. STEL: 0.45 mg/m ³ 15 min	TWA: 0.15 mg/m ³	TWA: 0.05 mg/m ³ 8 hodinách. Ceiling: 0.2 mg/m ³ biological test, toxic for reproduction

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Cadmium	TWA: 0.004 mg/m ³ 8 tundides. valid until July 10, 2027		TWA: 0.001 mg/m ³	TWA: 0.004 mg/m ³ 8 órában. AK	TWA: 0.001 mg/m ³ 8 klukkustundum. inhalable fraction TWA: 0.004 mg/m ³ 8 klukkustundum. valid until July 11, 2027 inhalable fraction Ceiling: 0.002 mg/m ³ inhalable fraction Ceiling: 0.008 mg/m ³ valid until July 11, 2027 inhalable fraction
Tin			TWA: 2 mg/m ³		
Lead	TWA: 0.1 mg/m ³ 8 tundides. total dust TWA: 0.05 mg/m ³ 8 tundides. respirable dust	TWA: 0.15 mg/m ³ 8 hr	TWA: 0.15 mg/m ³	TWA: 0.1 mg/m ³ 8 órában. AK TWA: 0.05 mg/m ³ 8 órában. AK	TWA: 0.05 mg/m ³ 8 klukkustundum. dust, fume, and powder Ceiling: 0.1 mg/m ³ dust, fume, and powder

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Bismuth	TWA: 0.5 mg/m ³	TWA: 0.5 mg/m ³ IPRD			
Cadmium	TWA: 0.001 mg/m ³	TWA: 0.004 mg/m ³ inhalable fraction IPRD			TWA: 0.05 mg/m ³ 8 ore
Tin				TWA: 2 mg/m ³	
Lead	STEL: 0.1 mg/m ³ TWA: 0.05 mg/m ³	TWA: 0.15 mg/m ³ inhalable fraction IPRD TWA: 0.07 mg/m ³ respirable fraction IPRD	TWA: 0.15 mg/m ³ 8 Stunden		TWA: 0.15 mg/m ³ 8 ore

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Bismuth	MAC: 0.5 mg/m ³				
Cadmium	TWA: 0.01 mg/m ³ 1051 MAC: 0.05 mg/m ³	TWA: 0.03 mg/m ³ 8 hodinách manufactured TWA: 0.15 mg/m ³ 8 hodinách others STEL: 0.15 mg/m ³ 15 minútach manufactured STEL: 0.75 mg/m ³ 15 minútach others	TWA: 0.004 mg/m ³ 8 urah applies until July 11, 2027 inhalable fraction	TLV: 0.001 mg/m ³ 8 timmar. NGV TLV: 0.004 mg/m ³ 8 timmar. NGV	
Tin		Potential for cutaneous absorption	TWA: 2 mg/m ³ 8 urah applies to Tin(IV) inorganic compounds inhalable fraction TWA: 8 mg/m ³ 8 urah applies to Tin(II) inorganic compounds inhalable fraction	TLV: 2 mg/m ³ 8 timmar. NGV	TWA: 2 mg/m ³ 8 saat
Lead	TWA: 0.05 mg/m ³ 1826	TWA: 0.15 mg/m ³ inhalable fraction TWA: 0.5 mg/m ³ respirable fraction	TWA: 0.1 mg/m ³ 8 urah inhalable fraction STEL: 0.4 mg/m ³ 15 minutah inhalable fraction	TLV: 0.1 mg/m ³ 8 timmar. NGV TLV: 0.05 mg/m ³ 8 timmar. NGV	TWA: 0.15 mg/m ³ 8 saat

SAFETY DATA SHEET

Wood"s metal

Revision Date 04-Oct-2023

Biological limit values

List source(s):

Component	European Union	United Kingdom	France	Spain	Germany
Cadmium			Cadmium: 0.005 mg/g creatinine urine not critical Cadmium: 0.004 mg/L blood not critical	Cadmium: 2 µg/g Creatinine urine not critical Cadmium: 5 µg/L blood not critical	
Lead			Lead: 400 µg/L blood Lead: 180 µg/L blood indifferent sampling time Lead: 300 µg/L blood Lead: 200 µg/L blood Lead: 100 µg/L blood	Lead: 70 µg/dL blood not critical	Lead: 150 µg/L whole blood (no restriction)

Component	Italy	Finland	Denmark	Bulgaria	Romania
Cadmium		Cadmium: 20 nmol/L urine at the end of a working week; time of day does not matter.			Cadmium: 2 µg/g Creatinine urine end of shift Cadmium: 5 µg/L blood end of shift Protein: 2 mg/L urine end of shift
Lead	60 Pb µg/100 mL blood end of workweek	Lead: 1.4 µmol/L blood time of day does not matter.	Lead: 20 µg/100 mL blood	Lead: 300 µg/L blood not fixed for women under 45 years old Lead: 400 µg/L blood not fixed	Lead: 150 µg/L urine end of shift Lead: 70 µg/100 mL blood end of shift Lead: 3 mg/cm hair end of shift .delta.-Aminolevulinic acid: 10 mg/L urine end of shift Coproporphyrin: 300 µg/L urine end of shift free erythrocytes protoporphyrin: 100 µg/100 mL erythrocyte blood end of shift

Component	Gibraltar	Latvia	Slovak Republic	Luxembourg	Turkey
Cadmium		Cadmium: 2 µg/L urine	Cadmium: 3.1 µg/L urine not critical carcinogen, category 2		
Lead	70 µg/100 mL blood Lead binding biological limit value;biological monitoring must include measuring the blood-lead level using absorption spectrometry or a method giving equivalent results 0.075 mg/m ³ air 40 hours per week Lead medical surveillance must be carried out;threshold measured in individual employees 40 µg/100 mL blood Lead medical surveillance must be carried out;threshold measured in individual employees	Lead: 30 µg/100 mL blood Coproporphyrin: 100 µg/g Creatinine urine Aminolevulinic acid: 5 mg/g Creatinine urine	Lead: 400 µg/L blood not critical Lead: 100 µg/L blood not critical women younger than 45 years of age .delta.-Aminolevulinic acid: 15 mg/L urine not critical .delta.-Aminolevulinic acid: 6 mg/L urine not critical women younger than 45 years of age Coproporphyrins: 0.30 mg/L urine not critical	Lead: 70 µg/100 mL blood. Lead: 0.072 mg/m ³ blood. medical surveillance threshold in air measured as a time weighted average over 40 hours per week Lead: 40 µg/100 mL blood. medical surveillance threshold measured in individual workers	Lead: 70 µg/100 mL blood

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of

SAFETY DATA SHEET

Wood"s metal

Revision Date 04-Oct-2023

exposure to chemical and biological agents.

MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust

MDHS 91 Metals and metalloids in workplace air by X-ray fluorescence spectrometry

MDHS 99 Metals in air by ICP-AES

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Tin 7440-31-5 (-)				DNEL = 10mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Bismuth 7440-69-9 (-)				DNEL = 13.1mg/m ³
Cadmium 7440-43-9 (-)			DNEL = 4µg/m ³	
Tin 7440-31-5 (-)				DNEL = 71mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Bismuth 7440-69-9 (-)				PNEC = 17.5mg/L	
Cadmium 7440-43-9 (-)	PNEC = 0.19µg/L	PNEC = 1.8mg/kg sediment dw		PNEC = 20µg/L	PNEC = 0.9mg/kg soil dw
Lead 7439-92-1 (-)	PNEC = 2.4µg/L	PNEC = 186mg/kg sediment dw		PNEC = 100µg/L	PNEC = 212mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Cadmium 7440-43-9 (-)	PNEC = 1.14µg/L	PNEC = 0.64mg/kg sediment dw		PNEC = 0.16mg/kg food	
Lead 7439-92-1 (-)	PNEC = 3.3µg/L	PNEC = 168mg/kg sediment dw		PNEC = 10.9mg/kg food	

8.2. Exposure controls

Engineering Measures

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Natural rubber	See manufacturers	-		(minimum requirement)

SAFETY DATA SHEET

Wood"s metal

Revision Date 04-Oct-2023

Nitrile rubber Neoprene PVC	recommendations	EN 374
-----------------------------------	-----------------	--------

Skin and body protection Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced
Recommended Filter type: Particulates filter conforming to EN 143

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Recommended half mask:- Particle filtering: EN149:2001
When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls Prevent product from entering drains. Do not allow material to contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Solid	
Appearance	Grey	
Odor	No information available	
Odor Threshold	No data available	
Melting Point/Range	70 °C / 158 °F	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flammability (liquid)	Not applicable	Solid
Flammability (solid,gas)	No information available	
Explosion Limits	No data available	
Flash Point	No information available	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	Not applicable	Solid
Water Solubility	Insoluble	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Vapor Pressure	No data available	
Density / Specific Gravity	No data available	
Bulk Density	No data available	
Vapor Density	Not applicable	Solid
Particle characteristics	No data available	

9.2. Other information

SAFETY DATA SHEET

Wood"s metal

Revision Date 04-Oct-2023

Molecular Formula
Evaporation Rate

Bi . Cd . Pb . Sn
Not applicable - Solid

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization
Hazardous Reactions

Hazardous polymerization does not occur.
None under normal processing.

10.4. Conditions to avoid

Incompatible products.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Toxic fumes. Heavy metal oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

Based on available data, the classification criteria are not met

Inhalation

Category 2

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Bismuth	LD50 = 5 g/kg (Rat)	-	-
Cadmium	LD50 = 2330 mg/kg (Rat)	-	LC50 = 25 mg/m ³ (Rat) 30 min
Tin	> 2000 mg/kg (Rat)	> 2000 mg/kg (Rat)	LC50 > 4.75 mg/L (Rat) 4 h

(b) skin corrosion/irritation;

No data available

(c) serious eye damage/irritation;

No data available

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

No data available

May cause sensitization by skin contact

SAFETY DATA SHEET

Wood"s metal

Revision Date 04-Oct-2023

(e) germ cell mutagenicity; Category 2
Contains a known or suspected mutagen

(f) carcinogenicity; Category 1B
Possible cancer hazard. May cause cancer based on animal data This product contains one or more substances which are classified by IARC as carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly carcinogenic to humans (Group 2B) The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Cadmium	Carc Cat. 1B		Cat. 1	Group 1
Lead				Group 2A

(g) reproductive toxicity; Category 1A
Reproductive Effects Product is or contains a chemical which is a known or suspected reproductive hazard. May impair fertility. Possible risk of harm to the unborn child.

(h) STOT-single exposure; No data available

(i) STOT-repeated exposure; Category 1
Target Organs Kidney, Central nervous system (CNS), Blood, Liver.

(j) aspiration hazard; Not applicable
Solid

Other Adverse Effects May cause respiratory irritation May be harmful if absorbed through the skin. May cause irritation of the digestive tract. The toxicological properties have not been fully investigated.

Symptoms / effects,both acute and delayed No information available.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity Ecotoxicity effects

The product contains following substances which are hazardous for the environment. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. May cause long-term adverse effects in the environment. Do not allow material to contaminate ground water system.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Cadmium	LC50: 0.0004 - 0.003 mg/L, 96h (Pimephales promelas) LC50: = 0.016 mg/L, 96h (Oryzias latipes) LC50: = 21.1 mg/L, 96h flow-through (Lepomis macrochirus)	EC50: = 0.0244 mg/L, 48h Static (Daphnia magna)	

SAFETY DATA SHEET

Wood"s metal

Revision Date 04-Oct-2023

	LC50: = 0.24 mg/L, 96h static (Cyprinus carpio) LC50: = 4.26 mg/L, 96h semi-static (Cyprinus carpio) LC50: = 0.002 mg/L, 96h (Cyprinus carpio) LC50: = 0.006 mg/L, 96h static (Oncorhynchus mykiss) LC50: = 0.003 mg/L, 96h flow-through (Oncorhynchus mykiss)		
Lead	LC50: = 1.32 mg/L, 96h static (Oncorhynchus mykiss) LC50: = 1.17 mg/L, 96h flow-through (Oncorhynchus mykiss) LC50: = 0.44 mg/L, 96h semi-static (Cyprinus carpio)	EC50: = 600 µg/L, 48h (water flea)	

Component	Microtox	M-Factor
Cadmium		10

12.2. Persistence and degradability Product contains heavy metals. Discharge into the environment must be avoided. Special pre-treatment is necessary
Persistence Insoluble in water, May persist.
Degradability Not relevant for inorganic substances.
Degradation in sewage treatment plant Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential May have some potential to bioaccumulate; Product has a high potential to bioconcentrate

12.4. Mobility in soil Spillage unlikely to penetrate soil Is not likely mobile in the environment due its low water solubility.

12.5. Results of PBT and vPvB assessment No data available for assessment.

12.6. Endocrine disrupting properties
Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects
Persistent Organic Pollutant This product does not contain any known or suspected substance
Ozone Depletion Potential This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products Should not be released into the environment. Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point.

SAFETY DATA SHEET

Wood"s metal

Revision Date 04-Oct-2023

European Waste Catalogue (EWC)	According to the European Waste Catalog, Waste Codes are not product specific, but application specific.
Other Information	Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Do not empty into drains. Do not let this chemical enter the environment.
Switzerland - Waste Ordinance	Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600 https://www.fedlex.admin.ch/eli/cc/2015/891/en

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number	UN2570
14.2. UN proper shipping name	CADMIUM COMPOUND
Technical Shipping Name	Contains Cadmium, Lead
14.3. Transport hazard class(es)	6.1
14.4. Packing group	II

ADR

14.1. UN number	UN2570
14.2. UN proper shipping name	CADMIUM COMPOUND
Technical Shipping Name	Contains Cadmium, Lead
14.3. Transport hazard class(es)	6.1
14.4. Packing group	II

IATA

14.1. UN number	UN2570
14.2. UN proper shipping name	CADMIUM COMPOUND
Technical Shipping Name	Contains Cadmium, Lead
14.3. Transport hazard class(es)	6.1
14.4. Packing group	II

14.5. Environmental hazards	Dangerous for the environment Product is a marine pollutant according to the criteria set by IMDG/IMO
------------------------------------	--

14.6. Special precautions for user	No special precautions required.
---	----------------------------------

14.7. Maritime transport in bulk according to IMO instruments	Not applicable, packaged goods
--	--------------------------------

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Bismuth alloy, base, Bi 50, Pb 25,	76093-98-6	-	-	-	-	X	-	-	-

SAFETY DATA SHEET

Wood"s metal

Revision Date 04-Oct-2023

Cd 12, Sn 12 (L-PbBi50Sn12.5Cd12.5)									
Bismuth	7440-69-9	231-177-4	-	-	X	X	KE-03313	X	-
Cadmium	7440-43-9	231-152-8	-	-	X	X	KE-04397	X	-
Tin	7440-31-5	231-141-8	-	-	X	X	KE-33838	X	-
Lead	7439-92-1	231-100-4	-	-	X	X	KE-21887	X	-

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Bismuth alloy, base, Bi 50, Pb 25, Cd 12, Sn 12 (L-PbBi50Sn12.5Cd12.5)	76093-98-6	-	-	-	-	-	-	-
Bismuth	7440-69-9	X	ACTIVE	X	-	X	X	X
Cadmium	7440-43-9	X	ACTIVE	X	-	X	X	X
Tin	7440-31-5	X	ACTIVE	X	-	X	X	X
Lead	7439-92-1	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Bismuth alloy, base, Bi 50, Pb 25, Cd 12, Sn 12 (L-PbBi50Sn12.5Cd12.5)	76093-98-6	-	Use restricted. See item 23. (see link for restriction details) Use restricted. See item 75. (see link for restriction details) Use restricted. See item 30. (see link for restriction details) Use restricted. See item 63. (see link for restriction details)	-
Bismuth	7440-69-9	-	-	-
Cadmium	7440-43-9	-	Use restricted. See item 72. (see link for restriction details) Use restricted. See item 23. (see link for restriction details) Use restricted. See item 28. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	SVHC Candidate list - 231-152-8 - Carcinogenic, Article 57a; Specific target organ toxicity after repeated exposure, Article 57(f) - human health
Tin	7440-31-5	-	Use restricted. See item 75. (see link for restriction details)	-
Lead	7439-92-1	-	Use restricted. See item 72. (see link for restriction details)	SVHC Candidate list - 231-100-4 - Toxic for reproduction (Article 57c)

SAFETY DATA SHEET

Wood"s metal

Revision Date 04-Oct-2023

			Use restricted. See item 30. (see link for restriction details) Use restricted. See item 63. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	
--	--	--	--	--

After the sunset date the use of this substance requires either an authorization or can only be used for exempted uses, e.g. use in scientific research and development which includes routine analytics or use as intermediate.

REACH links

<https://echa.europa.eu/authorisation-list>

<https://echa.europa.eu/substances-restricted-under-reach>

<https://echa.europa.eu/candidate-list-table>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Bismuth alloy, base, Bi 50, Pb 25, Cd 12, Sn 12 (L-PbBi50Sn12.5Cd12.5)	76093-98-6	Not applicable	Not applicable
Bismuth	7440-69-9	Not applicable	Not applicable
Cadmium	7440-43-9	Not applicable	Not applicable
Tin	7440-31-5	Not applicable	Not applicable
Lead	7439-92-1	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Component	ANNEX I - PART 1 List of chemicals subject to export notification procedure (referred to in Article 8)	ANNEX I - PART 2 List of chemicals qualifying for PIC notification (referred to in Article 11)	ANNEX I - PART 3 List of chemicals subject to the PIC procedure (referred to in Articles 13 and 14)
Bismuth alloy, base, Bi 50, Pb 25, Cd 12, Sn 12 (L-PbBi50Sn12.5Cd12.5) 76093-98-6 (100)	i(1) — industrial chemical for professional use sr — severe restriction i(2) — industrial chemical for public sr — severe restriction	i — industrial chemical sr — severe restriction	-
Cadmium 7440-43-9 (-)	i(1) — industrial chemical for professional use sr — severe restriction i(2) — industrial chemical for public sr — severe restriction	i — industrial chemical sr — severe restriction	-
Lead 7439-92-1 (-)	sr — severe restriction i(2) — industrial chemical for public	-	-

<https://eur-lex.europa.eu/legal-content/EN/TXT/?uri=CELEX%3A32012R0649&qid=1604065742303>.

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

SAFETY DATA SHEET

Wood"s metal

Revision Date 04-Oct-2023

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

Take note of Directive 94/33/EC on the protection of young people at work

Take note of Dir 92/85/EC on the protection of pregnant and breastfeeding women at work

Take note of Dir 76/769/EEC relating to restrictions on the marketing and use of certain dangerous substances and preparations

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 3 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Bismuth	nwg	
Cadmium	WGK3	Krebserzeugende Stoffe - Class I : 0.05 mg/m ³ (Massenkonzentration)
Tin	nwg	Class III : 1 mg/m ³ (Massenkonzentration)
Lead	nwg	Class II : 0.5 mg/m ³ (Massenkonzentration)

Component	France - INRS (Tables of occupational diseases)
Cadmium	Tableaux des maladies professionnelles (TMP) - RG 61, RG 61bis
Lead	Tableaux des maladies professionnelles (TMP) - RG 1

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Bismuth alloy, base, Bi 50, Pb 25, Cd 12, Sn 12 (L-PbBi50Sn12.5Cd12.5) 76093-98-6 (100)	Prohibited and Restricted Substances		Annex I - industrial chemical
Cadmium 7440-43-9 (-)	Prohibited and Restricted Substances		Annex I - industrial chemical
Lead 7439-92-1 (-)	Prohibited and Restricted Substances		

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H360FD - May damage fertility. May damage the unborn child

H330 - Fatal if inhaled

H341 - Suspected of causing genetic defects

H350 - May cause cancer

H361fd - Suspected of damaging fertility. Suspected of damaging the unborn child

H362 - May cause harm to breast-fed children

H372 - Causes damage to organs through prolonged or repeated exposure

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

SAFETY DATA SHEET

Wood"s metal

Revision Date 04-Oct-2023

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Creation Date 16-Nov-2010

Revision Date 04-Oct-2023

Revision Summary Not applicable.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006 .

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

SAFETY DATA SHEET

Wood"s metal

Revision Date 04-Oct-2023

End of Safety Data Sheet