

according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended

Creation Date 27-Apr-2009 Revision Date 31-Mar-2025 Revision Number 1

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THECOMPANY/UNDERTAKING

1.1. Product identifier

 Product Description:
 Methanol

 Cat No. :
 TS/0720/25SS

 Synonyms
 Methyl alcohol

 Index No
 603-001-00-X

 CAS No
 67-56-1

 EC No
 200-659-6

 Molecular Formula
 C H4 O

REACH registration number 01-2119433307-44

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.

Sector of use SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

Product category PC21 - Laboratory chemicals Environmental release category ERC1 - Manufacture of substances

ERC2 - Formulation of preparations (mixtures)

ERC4 - Industrial use of processing aids in processes and products, not becoming part of

articles

ERC8a - Wide dispersive indoor use of processing aids in open systems

Uses advised against SU21 - Consumer uses: Private households (= general public = consumers); PC13 - Fuels.

REACH Annex XVII Restriction - refer to SECTION 15

1.3. Details of the supplier of the safety data sheet

Company

UK entity/business name Fisher Scientific UK

Bishop Meadow Road, Loughborough, Leicestershire LE11 5RG, United Kingdom

EU entity/business nameThermo Fisher Scientific
Janssen Pharmaceuticalaan 3a

2440 Geel, Belgium

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

Tel: 01509 231166

Chemtrec US: (800) 424-9300 Chemtrec EU: 001-703-527-3887

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Physical hazards

Flammable liquids Category 2 (H225)

Health hazards

Acute oral toxicity

Acute dermal toxicity

Acute Inhalation Toxicity - Vapors

Specific target organ toxicity - (single exposure)

Category 3 (H301)

Category 3 (H311)

Category 3 (H331)

Category 1 (H370)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H301 + H311 + H331 - Toxic if swallowed, in contact with skin or if inhaled

H370 - Causes damage to organs: Optic nerve, Central nervous system (CNS)

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P240 - Ground and bond container and receiving equipment

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

P302 + P350 - IF ON SKIN: Gently wash with plenty of soap and water

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

2.3. Other hazards

Substance is not considered to be persistent, bioaccumulative and toxic (PBT). Substance is not considered to be very persistent and very bioaccumulative (vPvB).

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

| Component | CAS No | EC No | Weight % | GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567 |
|----------------|---------|-----------|----------|--|
| Methyl alcohol | 67-56-1 | 200-659-6 | >95 | Flam. Liq. 2 (H225) Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370) |

| Component | Specific concentration limits (SCL's) | M-Factor | Component notes |
|----------------|---|----------|-----------------|
| Methyl alcohol | STOT Single Exp. 1 :: >= 10 STOT Single Exp. 2 :: 3 - < 10 | - | - |

| REACH registration number | 01-2119433307-44 |
|---------------------------|------------------|
|---------------------------|------------------|

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately.

Inhalation Remove to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth

method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Immediate medical attention is required.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Remove all sources of ignition. No artificial respiration, mouth-to-mouth or mouth to nose. Use suitable

instruments/apparatus. Avoid contact with skin.

4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. May cause blindness: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air.

Hazardous Combustion Products

Carbon monoxide (CO), Formaldehyde.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Should not be released into the environment. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not breathe mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Hygiene Measures

When using do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition.

Methanol Revision Date 31-Mar-2025

Flammables area.

Technical Rules for Hazardous Substances (TRGS) 510 Class 3 Storage Class (LGK) (Germany)

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

| Component | The United Kingdom | European Union | Ireland |
|----------------|----------------------------------|---------------------------------|------------------------------------|
| Methyl alcohol | WEL - TWA: 200 ppm TWA; | TWA: 200 ppm 8 hr | TWA: 200 ppm 8 hr. |
| | 266 mg/m³ TWA | TWA: 260 mg/m ³ 8 hr | TWA: 260 mg/m ³ 8 hr. |
| | WEL - STEL: 250 ppm | Skin | STEL: 600 ppm 15 min |
| | STEL; 333 mg/m ³ STEL | | STEL: 780 mg/m ³ 15 min |
| | | | Skin |

Biological limit values

List source(s):

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

| Component | Acute effects local (Dermal) | Acute effects systemic (Dermal) | Chronic effects local (Dermal) | Chronic effects systemic (Dermal) |
|-----------------------------------|------------------------------|---------------------------------|--------------------------------|-----------------------------------|
| Methyl alcohol 67-56-1 (>95) | | DNEL = 20mg/kg bw/day | | DNEL = 20mg/kg bw/day |

| Component | Acute effects local (Inhalation) | Acute effects systemic (Inhalation) | Chronic effects local (Inhalation) | Chronic effects systemic (Inhalation) |
|-----------------------------------|----------------------------------|-------------------------------------|------------------------------------|---------------------------------------|
| Methyl alcohol 67-56-1 (>95) | DNEL = 130mg/m ³ | DNEL = 130mg/m ³ | DNEL = 130mg/m ³ | DNEL = 130mg/m ³ |

Predicted No Effect Concentration (PNEC)

See values below.

| Component | Fresh water | Fresh water | Water Intermittent | Microorganisms in | Soil (Agriculture) |
|----------------|-----------------|----------------|--------------------|-------------------|--------------------|
| | | sediment | | sewage treatment | |
| Methyl alcohol | PNEC = 20.8mg/L | PNEC = 77mg/kg | PNEC = 1540mg/L | PNEC = 100mg/L | PNEC = 100mg/kg |
| 67-56-1 (>95) | - | sediment dw | - | _ | soil dw |

| Component | Marine water | Marine water sediment | Marine water intermittent | Food chain | Air |
|-----------------------------------|-----------------|--------------------------------|---------------------------|------------|-----|
| Methyl alcohol 67-56-1 (>95) | PNEC = 2.08mg/L | PNEC = 7.7mg/kg sediment dw | | | |
| 07-30-1 (>93) | | Sediment dw | | | |

8.2. Exposure controls

Engineering Measures

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Tight sealing safety goggles (European standard - EN 166)

Hand Protection Protective gloves

| Glove material | Breakthrough time | Glove thickness | EU standard | Glove comments |
|-----------------|-------------------|-----------------|-------------|--|
| Butyl rubber | > 480 minutes | 0.35 mm | Level 6 | As tested under EN374-3 Determination of |
| Viton (R) | > 480 minutes | 0.70 mm | EN 374 | Resistance to Permeation by Chemicals |
| Neoprene gloves | < 60 minutes | 0.45 mm | | · |
| Nitrile rubber | < 30 minutes | 0.38 mm | | |

Skin and body protection Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: low boiling organic solvent Type AX Brown conforming to

EN371

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

141

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls No information available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State Liquid

AppearanceColorlessOdorAlcohol-likeOdor ThresholdNo data availableMelting Point/Range-98 °C / -144.4 °FSoftening PointNo data available

Boiling Point/Range 64.7 °C / 148.5 °F @ 760 mmHg

Methanol Revision Date 31-Mar-2025

Flammability (liquid) Highly flammable On basis of test data

Flammability (solid,gas) Not applicable Liquid

Explosion Limits Lower 6 vol% Upper 31 vol%

Flash Point 10 °C / 50 °F Method - CC (closed cup) Abel-Pensky (DIN

51755) Directive 84/449/EEC, A.9

Autoignition Temperature
Decomposition Temperature
pH
Viscosity

455 °C / 851 °F
No data available
No information available
0.55 cP at 20 °C

Water Solubility Miscible

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Componentlog PowMethyl alcohol-0.74

Vapor Pressure 128 hPa @ 20 °C

Density / Specific Gravity 0.791

Bulk DensityNot applicableLiquidVapor Density1.11(Air = 1.0)

Particle characteristics Not applicable (liquid)

9.2. Other information

Molecular Formula C H4 O
Molecular Weight 32.04
VOC Content(%) 100

Explosive PropertiesNot explosive Vapors may form explosive mixtures with air

Evaporation Rate 5.2 (ether = 1) **Surface tension** 0.02255 N/m @ 20°C

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

10.4. Conditions to avoid

Incompatible products. Heat, flames and sparks. Keep away from open flames, hot

surfaces and sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids. Acid anhydrides. Acid chlorides. Strong bases.

Metals. Peroxides.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Formaldehyde.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral Category 3 **Dermal** Category 3 Inhalation Category 3

| Component | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|----------------|--------------------------------|-------------------------------|-----------------------------|
| Methyl alcohol | LD50 = 1187 – 2769 mg/kg (Rat) | LD50 = 17100 mg/kg (Rabbit) | LC50 = 128.2 mg/L (Rat) 4 h |

Based on available data, the classification criteria are not met (b) skin corrosion/irritation;

(c) serious eye damage/irritation; Based on available data, the classification criteria are not met

(d) respiratory or skin sensitization;

Respiratory Based on available data, the classification criteria are not met Skin Based on available data, the classification criteria are not met

| Component | Test method | Test species | Study result |
|-----------------|------------------------------|--------------|-----------------|
| Methyl alcohol | OECD Test Guideline 406 | guinea pig | non-sensitising |
| 67-56-1 (>95) | Guinea Pig Maximisation Test | | _ |
| | (GPMT) | | |

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

(f) carcinogenicity; Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; Based on available data, the classification criteria are not met

| (3) | , | | | |
|----------------|-------------------------|-------------------------|----------------|--|
| Component | Test method | Test species / Duration | Study result | |
| Methyl alcohol | OECD Test Guideline 416 | Rat / Inhalation | NOAEC = | |
| 67-56-1 (>95) | | 2 Generation | 1.3 mg/l (air) | |

Developmental Effects Component substance is listed on California Proposition 65 as a developmental hazard.

(h) STOT-single exposure; Category 1

Results / Target organs Optic nerve, Central nervous system (CNS).

Based on available data, the classification criteria are not met (i) STOT-repeated exposure;

Target Organs None known.

(j) aspiration hazard; Based on available data, the classification criteria are not met

delayed

Symptoms / effects,both acute and May cause blindness. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any

known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity Ecotoxicity effects

 Component
 Freshwater Fish
 Water Flea
 Freshwater Algae

 Methyl alcohol
 Pimephales promelas: LC50 > 10000 mg/L 24h 10000 mg/L 96h
 EC50 > 10000 mg/L 24h 100000 mg/L 24h 10000 mg/L 24h 100000 mg/L 24h 10000 mg/L

| Component | Microtox | M-Factor |
|----------------|--------------------------|----------|
| Methyl alcohol | EC50 = 39000 mg/L 25 min | |
| | EC50 = 40000 mg/L 15 min | |
| | EC50 = 43000 mg/L 5 min | |

12.2. Persistence and degradability Readily biodegradable

Persistence Persistence is unlikely, based on information available.

| Component | Degradability | |
|----------------|----------------|--|
| Methyl alcohol | DT50 ~ 17.2d | |
| 67-56-1 (>95) | >94% after 20d | |

12.3. Bioaccumulative potential Bioaccumulation is unlikely

| Component | log Pow | Bioconcentration factor (BCF) |
|----------------|---------|-------------------------------|
| Methyl alcohol | -0.74 | <10 dimensionless |

12.4. Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all

surfaces Will likely be mobile in the environment due to its volatility. Disperses rapidly in

aır

Surface tension 0.02255 N/m @ 20°C

12.5. Results of PBT and vPvB

assessment

Substance is not considered to be persistent, bioaccumulative and toxic (PBT). Substance

is not considered to be very persistent and very bioaccumulative (vPvB).

12.6. Endocrine disrupting

properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

Page 9/13

empty container away from heat and sources of ignition.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but

application specific.

Other Information

Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations.

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN numberUN123014.2. UN proper shipping nameMETHANOL

14.3. Transport hazard class(es) 3 Subsidiary Hazard Class 6.1 14.4. Packing group II

ADR

14.1. UN number UN1230 **14.2. UN proper shipping name** WETHANOL

14.3. Transport hazard class(es)3Subsidiary Hazard Class6.114.4. Packing groupII

IATA

14.1. UN numberUN123014.2. UN proper shipping nameMETHANOL

14.3. Transport hazard class(es)3Subsidiary Hazard Class6.114.4. Packing groupII

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

| Component | CAS No | EINECS | ELINCS | NLP | IECSC | TCSI | KECL | ENCS | ISHL |
|----------------|---------|-----------|---------|--------------------------------|-------|------|----------|-------|-------|
| Methyl alcohol | 67-56-1 | 200-659-6 | ı | 1 | X | X | KE-23193 | X | X |
| | | | | | | | | | |
| Component | CAS No | TSCA | notific | ventory ation - Inactive | DSL | NDSL | AICS | NZIoC | PICCS |
| Methyl alcohol | 67-56-1 | X | ACT | IVE | X | - | X | X | X |

Methanol Revision Date 31-Mar-2025

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

Authorisation/Restrictions according to EU REACH

| Component | CAS No | REACH (1907/2006) - Annex XIV - Substances Subject to Authorization | | REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC) |
|----------------|---------|---|---|---|
| Methyl alcohol | 67-56-1 | - | Use restricted. See entry 69. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details) | <u>-</u> |

REACH links

https://echa.europa.eu/substances-restricted-under-reach

Seveso III Directive (2012/18/EC)

| Component | CAS No | Seveso III Directive (2012/18/EC) - | Seveso III Directive (2012/18/EC) - |
|----------------|---------|--|---|
| | | Qualifying Quantities for Major Accident | Qualifying Quantities for Safety Report |
| | | Notification | Requirements |
| Methyl alcohol | 67-56-1 | 500 tonne | 5000 tonne |

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification See table for values

| Component | Germany - Water Classification (AwSV) | Germany - TA-Luft Class |
|----------------|---------------------------------------|---|
| Methyl alcohol | WGK 2 | Class I: 20 mg/m³ (Massenkonzentration) |

| Component | France - INRS (Tables of occupational diseases) |
|----------------|--|
| Methyl alcohol | Tableaux des maladies professionnelles (TMP) - RG 84 |

| Componen | t Sw | witzerland - Ordinance on the | Switzerland - Ordinance on | Switzerland - Ordinance of the |
|----------|------|-------------------------------|-----------------------------|--------------------------------|
| | | Reduction of Risk from | Incentive Taxes on Volatile | Rotterdam Convention on the |
| | | handling of hazardous | Organic Compounds (OVOC) | Prior Informed Consent |
| | s | substances preparation (SR | . , | Procedure |

Methanol Revision Date 31-Mar-2025

| | 814.81) | | |
|-----------------|---------------------------|---------|--|
| Methyl alcohol | Prohibited and Restricted | Group I | |
| 67-56-1 (>95) | Substances | | |

15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has not been conducted

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor

H301 - Toxic if swallowed

H311 - Toxic in contact with skin

H331 - Toxic if inhaled

H370 - Causes damage to organs

Legend

AICS - Australian Inventory of Chemical Substances

IARC - International Agency for Research on Cancer

ICAO/IATA - International Civil Aviation Organization/International Air

MARPOL - International Convention for the Prevention of Pollution from

NZIoC - New Zealand Inventory of Chemicals

Predicted No Effect Concentration (PNEC)

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

TWA - Time Weighted Average

EC50 - Effective Concentration 50%

LD50 - Lethal Dose 50%

Transport Association

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

CAS - Chemical Abstracts Service TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic

Substances/EU List of Notified Chemical Substances Substances List **ENCS** - Japanese Existing and New Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances **IECSC** - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

ADR - European Agreement Concerning the International Carriage of

Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime

Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and

Ships

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

27-Apr-2009 **Creation Date** 31-Mar-2025 **Revision Date Revision Summary** Not applicable.

This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

Methanol

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

FSUTS0720

Revision Date 31-Mar-2025