

SAFETY DATA SHEET

Classified as hazardous in accordance with the criteria of EPA New Zealand

Section 1 - Identification

Product Identifier

Product Name <u>Isopropanol</u>

CAS No 67-63-0

Synonyms 2-Propanol; IPA; Isopropyl alcohol; Propan-2-ol; Isopropanol

Molecular FormulaC3 H8 OMolecular Weight60.1

Recommended Use Laboratory chemicals.
Uses advised against No Information available

Product Code C14932

Address Thermo Fisher Scientific New Zealand Ltd

244 Bush Road, Albany, Auckland, New Zealand

Emergency Tel. CHEMTREC®

09 980 6780 or +64 9 980 6780

Telephone / Fax Numbers Tel: 09 980 6700

Fax: 09 980 6788

E-mail address ANZinfo@thermofisher.com

Section 2 - Hazard(s) Identification

Classification under Work Safe New Zealand

Classified as hazardous in accordance with the criteria of EPA New Zealand

HSNO Approval Number HSR001180

GHS Classification

Physical hazards

Flammable liquids Category 2

Health hazards

Serious Eye Damage/Eye Irritation Category 2
Specific target organ toxicity - (single exposure) Category 3

Environmental hazards

Based on available data, the classification criteria are not met

Label Elements

ALFAAC14932 Version 2 22-Mar-2023 Page 1 / 11



Signal Word Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

Precautionary Statements

Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P233 - Keep container tightly closed

P240 - Ground and bond container and receiving equipment

P241 - Use explosion-proof electrical/ ventilating/ lighting equipment

P242 - Use non-sparking tools

P243 - Take action to prevent static discharges

P264 - Wash face, hands and any exposed skin thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection

Response

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P312 - Call a POISON CENTER or doctor if you feel unwell

P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other hazards which do not result in classification

Section 3 - Composition and Information on Ingredients

Component	CAS No	Weight %
Isopropyl alcohol	67-63-0	>95

Section 4 - First Aid Measures

Description of first aid measures

New Zealand Emergency Tel. CHEMTREC®

09 980 6780 or +64 9 980 6780

Inhalation Remove to fresh air. Get medical attention. If not breathing, give artificial respiration.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Get medical attention if

ALFAAC14932 Version 2 22-Mar-2023 Page 2 / 11

symptoms occur.

Ingestion Do NOT induce vomiting. Get medical attention.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

First Aid Facilities Eyewash, safety shower and washroom.

Most important symptoms and

effects

Difficulty in breathing. May cause central nervous system depression: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea

and vomiting

Notes to Physician Treat symptomatically. Symptoms may be delayed.

Section 5 - Fire Fighting Measures

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use water jetstream. Do not use a solid water stream as it may scatter and spread fire.

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO2), peroxides.

Special protective equipment and precautions for fire fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

Section 6 - Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures

Emergency procedures

Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges. Avoid contact with skin, eyes or clothing.

Environmental Precautions

Should not be released into the environment. See Section 12 for additional Ecological Information.

Methods for Containment and Clean Up

Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. Keep in suitable, closed containers for disposal.

Precautions to prevent secondary hazards

Clean contaminated objects and areas thoroughly observing environmental regulations

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

Section 7 - Handling and Storage

Precautions for Safe Handling

ALFAAC14932 Version 2 22-Mar-2023 Page 3 / 11

Advice on safe handling

Wear personal protective equipment/face protection. Keep away from open flames, hot surfaces and sources of ignition. Use spark-proof tools and explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Do not get in eyes, on skin, or on clothing. Do not breathe mist/vapors/spray. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

Conditions for Safe Storage, Including any Incompatibilities

Storage Conditions

Keep away from heat, sparks and flame. Flammables area. Keep container tightly closed in a dry and well-ventilated place.

Incompatible Materials

Strong oxidizing agents. Acids. Halogens. Acid anhydrides.

AS/NZS 2243.10:2004, Safety in laboratories - Storage of chemicals AS 1940-2004 - The storage and handling of flammable and combustible liquids

Section 8 - Exposure Controls and Personal Protection

Control parameters

Exposure limits

NZ - Workplace Exposure Standards and Biological Exposure Indices (6th edition). New Zealand Department of Labor **ACGIH** - Threshold Limit Values - Ceiling (TLV-C) guidelines by the American Conference of Governmental Industrial Hygienists (ACGIH) for controlling worker exposure to airborne chemical concentrations in the workplace.

UK - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020.

AUS - Exposure Standards for Atmospheric Contaminants in the Occupational Environment - Guidance Note on the Interpretation of Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:3008(1995)] Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)] updated in August, 2005. Safe Work Australia

Component	New Zealand WEL	Australia	ACGIH TLV	The United Kingdom	
Isopropyl alcohol	TWA: 400 ppm	STEL: 500 ppm	TWA: 200 ppm	STEL: 500 ppm 15 min	
	TWA: 983 mg/m ³	STEL: 1230 mg/m ³	STEL: 400 ppm	STEL: 1250 mg/m ³ 15 min	
	STEL: 500 ppm	TWA: 400 ppm		TWA: 400 ppm 8 hr	
	STEL: 1230 mg/m ³	ng/m³ TWA: 983 mg/m³		TWA: 999 mg/m ³ 8 hr	

Biological limit values

ACGIH - American Conference of Governmental Industrial Hygienists (ACGIH) TLVs® and BEIs®- Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices. 2022 Edition

Component	New Zealand	Australia	ACGIH - Biological	United Kingdom
			Exposure Indices	
Isopropyl alcohol			40 mg/L	
			Medium: urine	
			Time: end of shift at end of	
			workweek	
			Determinant: Acetone	

Appropriate engineering controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Individual protection measures, such as personal protective equipment

ALFAAC14932 Version 2 22-Mar-2023 Page 4/11

applications)

Hand Protection Protective gloves

Γ	Glove material	Breakthrough time	Glove thickness	AUS/NZ Standard	Glove comments
	Butyl rubber, Nitrile	> 480 minutes	0.5 mm	AS/NZS 2161	Permeation rate < 0.9 μg/cm2/min As
	rubber.	> 360 - 480 minutes	0.35 - 0.55 mm		tested under EN374-3 Determination of
					Resistance to Permeation by Chemicals
١	Viton (R)	> 480 minutes	0.4 mm		•
	Neoprène	< 40 minutes	0.7 mm		

Inspect gloves before use.

Eye Protection

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure

Repiratory Protection Use an AS/NZS 1716 approved respirator if exposure limits are exceeded or if irritation or

other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained in line with AS/NZS 1715 on the use

1% aq. sol

@ 760 mmHg

ASTM E-659

Liquid

On basis of test data

Goggles (Australian/New Zealand Standard AS/NZS 1337 - Eye protectors for Industrial

and maintenance of repiratory protective devices

Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to EN14387 (or AUS/NZ

Recommended half mask:-Valve filtering: EN405 Half mask: EN140 plus filter, EN 141 (or AUS/NZ equivalent)

When RPE is used a face piece Fit Test should be conducted

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

No information available. **Environmental exposure controls**

Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties

Physical State Liquid

Appearance Colorless Odor Alcohol-like **Odor Threshold** No data available

Hq -89.5 °C / -129.1 °F **Melting Point/Range**

Softening Point No data available

Boiling Point/Range 81 - 83 °C / 177.8 - 181.4 °F Flammability (liquid) Highly flammable Flammability (solid,gas) Not applicable

Explosion Limits Lower 2 Vol% Upper 12 Vol%

Flash Point 12 °C / 53.6 °F Method - Abel Closed Cup (BS 2000 Part 170, IP

170, AS/NZS 2106)

425 °C / 797 °F **Autoignition Temperature Decomposition Temperature** No data available **Viscosity** 2.27 mPa.s at 20 °C

Water Solubility Miscible

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

log Pow Component Isopropyl alcohol 0.05

ALFAAC14932 Version 2 22-Mar-2023 Page 5/11

SAFETY DATA SHEET

Vapor Pressure 43 mmHg @ 20 °C

Density / Specific Gravity0.785ASTM D-4052Bulk DensityNot applicableLiquidVapor Density2.1 @ 20 °C / 68 °F(Air = 1.0)

Particle characteristics Not applicable (liquid)

Other information

Molecular Formula C3 H8 O Molecular Weight 60.1

VOC Content(%) 100% (Organic Carbon (by mass) = 59.9 %) (EC/1999/13)

Explosive Properties Not explosive explosive air/vapour mixtures possible Vapors may form explosive mixtures

with air

Evaporation Rate 1.7 - ASTM D 3539 (Butyl acetate = 1.0)

Thermal conductivity 0.137 W/m °C at 20 °C / 68 °F

Refractive index 1.377 at 20 °C / 68 °F (ASTM D-1218)

Surface tension 22.7 mN/m at 20 °C / 68 °F

Coefficient of expansion 0.0009 / °C

Specific heat capacity 3 kJ/kg °C at 20 °C / 68 °F Dielectric constant 18.6 at 20 °C / 68 °F

Heat of vapourisation 665 J/g

Section 10 - Stability and Reactivity

Reactivity None known, based on information available

Stability Stable under normal conditions.

Sensitivity to Mechanical Impact No information available

Sensitivity to Static Discharge No information available

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

Conditions to Avoid Heat, flames and sparks, Keep away from open flames, hot surfaces and sources of

ignition.

Incompatible Materials Strong oxidizing agents, Acids, Halogens, Acid anhydrides.

Hazardous Decomposition Products Carbon monoxide (CO). Carbon dioxide (CO₂), peroxides.

Section 11 - Toxicological Information

Acute Effects

Information on likely routes of exposure

Product Information

Inhalation May be harmful if inhaled. May cause drowsiness and dizziness. May cause irritation of

respiratory tract.

Eyes Irritating to eyes.

Skin Irritating to skin. May be harmful in contact with skin.

Ingestion May cause central nervous system effects. Ingestion may cause gastrointestinal irritation,

nausea, vomiting and diarrhea.

Numerical measures of toxicity

(a) acute toxicity;

ALFAAC14932 Version 2 22-Mar-2023 Page 6/11

Oral	Based on available data, the classification criteria are not met
Dermal	Based on available data, the classification criteria are not met
Inhalation	Based on available data, the classification criteria are not met

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Isopropyl alcohol	5045 mg/kg (Rat)	12800 mg/kg (Rat)	72.6 mg/L (Rat) 4 h
	3600 mg/kg (Mouse)		

(b) skin corrosion/irritation; Based on available data, the classification criteria are not met

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;

RespiratoryBased on available data, the classification criteria are not met **Skin**Based on available data, the classification criteria are not met

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

(f) carcinogenicity; Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; Based on available data, the classification criteria are not met

(h) STOT-single exposure; Category 3

Results / Target organs Central nervous system (CNS)

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

Target Organs None known.

(j) aspiration hazard; Based on available data, the classification criteria are not met

Symptoms / effects, both acute and delayed

May cause central nervous system depression. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Section 12 - Ecological Information

Ecotoxicity

Aquatic ecotoxicity . Do not empty into drains.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox	
Isopropyl alcohol	LC50: = 9640 mg/L, 96h	13299 mg/L EC50 = 48	EC50: > 1000 mg/L, 72h	= 35390 mg/L EC50	
	flow-through	h	(Desmodesmus	Photobacterium	
	(Pimephales promelas)	9714 mg/L EC50 = 24 h	subspicatus)	phosphoreum 5 min	
	LC50: > 1400000 μg/L,		EC50: > 1000 mg/L, 96h		
	96h (Lepomis		(Desmodesmus		
	macrochirus)		subspicatus)		
	LC50: = 11130 mg/L,				
	96h static (Pimephales				
	promelas)				
	$LC50$: = 10000000 μ g/L,				
	96h (Daphnia)				
				,	

ALFAAC14932 Version 2 22-Mar-2023 Page 7/11

Terrestrial ecotoxicity There is no data for this product

Persistence Persistence is unlikely, based on information available.

Bioaccumulative Potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Isopropyl alcohol	0.05	No data available

Mobility The product contains volatile organic compounds (VOC) which will evaporate easily from all

surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in

air

Other adverse effects

Endocrine Disruptor Information Persistent Organic Pollutant Ozone Depletion Potential This product does not contain any known or suspected endocrine disruptors

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

Section 13 - Disposal Considerations

Waste treatment methods

Waste from Residues/Unused

Products

Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with all federal, E.P.A., state and local regulations. Assure

conformity with all applicable regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

Other Information Disposal agencies or waste contractors must comply with the New Zealand Hazardous

Substances (Disposal) Regulations. Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled

or incinerated, when in compliance with local regulations.

Section 14 - Transport Information

Component	Hazchem Code
Isopropyl alcohol	1Z
67-63-0 (>95)	

NZS 5433:2020

UN-No UN1219

Proper Shipping Name Isopropanol (Isopropyl alcohol)

Hazard Class 3
Packing Group ||

IATA

ALFAAC14932 Version 2 22-Mar-2023 Page 8 / 11

UN-No UN1219
Proper Shipping Name Isopropanol

Hazard Class 3
Packing Group

IMDG/IMO

UN-No UN1219

Proper Shipping Name Isopropanol (Isopropyl alcohol)

Hazard Class 3
Packing Group ||

Environmental hazards No hazards identified

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable, packaged goods

Special Precautions

No special precautions required. Please refer to the applicable dangerous goods

regulations for additional information.

Additional information None known

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

HSNO Approval Number	HSR001180

National Regulations

There are no applicable tolerable exposure limits or environmental exposure limits according to the EPA Controls for Hazardous Substances

Certified handlers, tracking and controlled substance license requirements

Certified handlers are required for some substances. This includes substances requiring a controlled substance license, and most explosives, vertebrates toxic agents, and certain fumigants. Acutely toxic substances which are a Category 1 or 2, such as pesticides also require Certified handlers. Please check the Health and Safety at Work Act 2015 for further information. Tracking is required for some highly hazardous substances. These substances need to be under the control of an appropriately trained person or appropriately secured. Please check the Health and Safety at Work Act 2015 for further information.

Prohibition or notification/licensing requirements

Shown below are details of specific prohibition/notifications or licencing requirements when they apply.

International Regulations

Ozone Depletion Potential This product does not contain any known or suspected substance

Persistent Organic Pollutant This product does not contain any known or suspected substance

Rotterdam Convention (PIC) Not applicable

Authorisation/Restrictions according to EU REACH

Component		REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	
Isopropyl alcohol	-	Use restricted. See item 75. (see link for restriction details)	-

ALFAAC14932 Version 2 22-Mar-2023 Page 9 / 11

https://echa.europa.eu/substances-restricted-under-reach

International Inventories

New Zealand (NZIoC), Australia (AICS), Europe (EINECS/ELINCS/NLP), Korea (KECL), China (IECSC), Taiwan (TCSI), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

	Component	CAS No	NZIoC	AICS	EINECS	ELINCS	NLP	KECL	IECSC	TCSI
130 propyr alcohol 67 66 6 X X	Isopropyl alcohol	67-63-0	X	X	-	-	-	KE-29363	Χ	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	PICCS	ISHL	ENCS
Isopropyl alcohol	67-63-0	Х	ACTIVE	X	-	Х	X	Х

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

Section 16 - Other Information

This safety data sheet complies with the requirements of the EPA Hazardous Substances (Hazard Classification) Notice 2020 and WorkSafe New Zealand Regulations

Legend

NZIoC - New Zealand Inventory of Chemicals

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

IECSC - Chinese Inventory of Existing Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer NZS 5433:2020 - Transport of Dangerous Goods on Land

ICAO/IATA - International Civil Aviation Organization/International Air

Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

WEL - Workplace Exposure Limit

DNEL - Derived No Effect Level

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

VOC - (Volatile Organic Compound)

AICS - Australian Inventory of Chemical Substances

EINECS/ELINCS - European Inventory of Existing Commercial Chemical

Substances/EU List of Notified Chemical Substances **ENCS** - Japanese Existing and New Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

CAS - Chemical Abstracts Service

ACGIH - American Conference of Governmental Industrial Hygienists

PNEC - Predicted No Effect Concentration

OECD - Organisation for Economic Co-operation and Development

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

ADG - Australian Code for the Transport of Dangerous Goods by Road and Rail

LC50 - Lethal Concentration 50%

ATE - Acute Toxicity Estimate

RPE - Respiratory Protective Equipment

NOEC - No Observed Effect Concentration

BCF - Bioconcentration factor

PBT - Persistent, Bioaccumulative, Toxic

Key literature references and sources for data

HSNO classifications provided in the New Zealand Chemical Classification Information Database (CCID).

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

EPA Guide to classifying hazardous substances in New Zealand

EPA - Assigning a product to an existing HSNO approval guide

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Revision Date 22-Mar-2023 **Revision Summary** Initial Release

ALFAAC14932 Version 2 22-Mar-2023 Page 10 / 11

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

ALFAAC14932 Version 2 22-Mar-2023 Page 11 / 11