

Page 1/9 Revision Date 31-Mar-2025 Version 3

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THECOMPANY/UNDERTAKING

Product Identifier

Perihalan Produk: Sulfur in Diesel Fuel standard solution, Specpure, 50µg/g (0.0050%)
Product Description: Sulfur in Diesel Fuel standard solution, Specpure, 50µg/g (0.0050%)

Cat No.: 45313

Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

Company Thermo Fisher Scientific (M) Sdn Bhd

Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square, No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,

Selangor Darul Ehsan, Malaysia. Main line: +60 3-5525 7888

**Supplier** 

E-mail address Enquiry.my@thermofisher.com

Emergency Telephone Number CHEMTREC Malaysia 1-800-815-308 (Malay)

CHEMTREC Malaysia (Kuala Lumpur) +(60)-327884561 (Malay)

Tel: +03-5525 7888

## **SECTION 2: HAZARDS IDENTIFICATION**

Classification of the substance or mixture

Carcinogenicity Category 2 (H351)

### Label Elements



Signal Word Warning

**Hazard Statements** 

H351 - Suspected of causing cancer

**Precautionary Statements** 

Sulfur in Diesel Fuel standard solution, Specpure, 50µg/g (0.0050%)

#### Prevention

P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P280 - Wear protective gloves/protective clothing/eye protection/face protection

#### Response

P308 + P313 - IF exposed or concerned: Get medical advice/attention

P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

#### Storage

P403 + P235 - Store in a well-ventilated place. Keep cool

#### **Disposal**

P501 - Dispose of contents/ container to an approved waste disposal plant

#### Other Hazards

Combustible liquid

This product does not contain any known or suspected endocrine disruptors

## **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS No	Weight %	
Fuels, diesel, no. 2	68476-34-6	99.97	
Butane, 1,1'-thiobis-	544-40-1	0.03	

## **SECTION 4: FIRST AID MEASURES**

Description of first aid measures

General Advice If symptoms persist, call a physician.

**Eye Contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

**Ingestion** Clean mouth with water and drink afterwards plenty of water.

**Inhalation** Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

## Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness,

nausea and vomiting.

#### Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

# **SECTION 5: FIREFIGHTING MEASURES**

ALFAA45313

Revision Date 31-Mar-2025

Sulfur in Diesel Fuel standard solution, Specpure, 50µg/g (0.0050%)

Revision Date 31-Mar-2025

#### Extinguishing media

## Suitable Extinguishing Media

Carbon dioxide (CO<sub>2</sub>). Powder. Water spray. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. Water mist may be used to cool closed containers.

#### Extinguishing media which must not be used for safety reasons

No information available.

#### Special hazards arising from the substance or mixture

Combustible material. Containers may explode when heated.

#### **Hazardous Combustion Products**

Sulfur oxides.

#### Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### Personal Precautions, Protective Equipment and Emergency Procedures

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.

## **Environmental precautions**

Should not be released into the environment. See Section 12 for additional Ecological Information. Do not flush into surface water or sanitary sewer system.

### Methods and Material for Containment and Cleaning Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition.

#### Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

## **SECTION 7: HANDLING AND STORAGE**

#### Precautions for Safe Handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition.

## Conditions for Safe Storage, Including any Incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame.

#### Specific End Uses

Use in laboratories.

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### Control Parameters

Sulfur in Diesel Fuel standard solution, Specpure, 50µg/g (0.0050%)

Component	Malaysia	ACGIH TLV	OSHA PEL
Fuels, diesel, no. 2		TWA: 100 mg/m <sup>3</sup>	
		Skin	

#### **Exposure Controls**

#### **Engineering Measures**

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

**Eve Protection** Goggles

Hand Protection Protective gloves
Skin and body protection Long sleeved clothing

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators

Recommended Filter type: Particulates filter conforming to EN 143

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

When RPE is used a face piece Fit Test should be conducted

Handle in accordance with good industrial hygiene and safety practice

system

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

## Information on basic physical and chemical properties

**Appearance** 

Physical State Liquid

Odor No information available
Odor Threshold No data available
pH No information available

Melting Point/RangeNo data availableSoftening PointNo data availableBoiling Point/RangeNo information available

Flash Point 69 °C / 156.2 °F Method - No information available

ALFAA45313

Revision Date 31-Mar-2025

Sulfur in Diesel Fuel standard solution, Specpure, 50µg/g (0.0050%)

Evaporation Rate No data available

Flammability (solid,gas)
Explosion Limits

Not applicable No data available Liquid

(Air = 1.0)

Liquid

Vapor PressureNo data availableVapor DensityNo data available

Specific Gravity / Density

No data available

Bulk Density

Not applicable

Bulk Density
Not applicable
Water Solubility
Not applicable
Immiscible

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Autoignition Temperature Decomposition Temperature

Viscosity

**Explosive Properties Oxidizing Properties** 

No data available No data available No data available

No information available

explosive air/vapour mixtures possible

Revision Date 31-Mar-2025

**SECTION 10: STABILITY AND REACTIVITY** 

Reactivity

None known, based on information available.

**Chemical Stability** 

Stable under normal conditions.

Possibility of Hazardous Reactions

Hazardous Polymerization Hazardous Reactions

No information available. None under normal processing.

Conditions to Avoid

Keep away from open flames, hot surfaces and sources of ignition.

**Incompatible Materials** 

Oxidizing agent.

**Hazardous Decomposition Products** 

Sulfur oxides.

**SECTION 11: TOXICOLOGICAL INFORMATION** 

Information on Toxicological Effects

Sulfur in Diesel Fuel standard solution, Specpure, 50µg/g (0.0050%)

#### **Product Information**

(a) acute toxicity;

OralBased on available data, the classification criteria are not metDermalBased on available data, the classification criteria are not metInhalationBased on available data, the classification criteria are not met

#### Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation		
Fuels, diesel, no. 2	-	LD50 > 2000 mg/kg (Rabbit)	LC50 = 5.4 mg/L (Rat) 4 h LC50 = 3.6 mg/L (Rat) 4 h		
Butane, 1,1'-thiobis-	LD50 = 2220 mg/kg (Rat)	-	-		

(b) skin corrosion/irritation; No data available

(c) serious eye damage/irritation; No data available

(d) respiratory or skin sensitization;

**Respiratory Skin**No data available
No data available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; Category 2

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; No data available

(h) STOT-single exposure; No data available

(i) STOT-repeated exposure; No data available

Target Organs None known.

(j) aspiration hazard; Category 1

Symptoms / effects,both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

delayed

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any

known or suspected endocrine disruptors.

### **SECTION 12: ECOLOGICAL INFORMATION**

**Ecotoxicity effects**The product contains following substances which are hazardous for the environment. Toxic

to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Contains a substance which is:. Harmful to aquatic organisms.

Revision Date 31-Mar-2025

Sulfur in Diesel Fuel standard solution, Specpure, 50µg/g (0.0050%)

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Fuels, diesel, no. 2	LC50: = 35 mg/L, 96h flow-through (Pimephales promelas)			
Butane, 1,1'-thiobis-	LC50: = 3.58 mg/L, 96h flow-through (Pimephales promelas)			

Persistence and degradability

**Persistence** 

Immiscible with water.

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste

Revision Date 31-Mar-2025

water treatment plants.

Bioaccumulative potential

May have some potential to bioaccumulate

Mobility in soil

Spillage unlikely to penetrate soil. Is not likely mobile in the environment due its low water

solubility.

**Endocrine Disruptor Information** 

This product does not contain any known or suspected endocrine disruptors

Other adverse effects

No information available

### **SECTION 13: DISPOSAL CONSIDERATIONS**

Waste treatment methods

Waste from Residues/Unused

**Products** 

Waste is classified as hazardous Dispose of in accordance with the European Directives on

waste and hazardous waste Dispose of in accordance with local regulations

**Contaminated Packaging** 

Dispose of this container to hazardous or special waste collection point.

Other Information

Do not flush to sewer Waste codes should be assigned by the user based on the

application for which the product was used Do not empty into drains Do not let this chemical

enter the environment

## **SECTION 14: TRANSPORT INFORMATION**

IMDG/IMO Not regulated

Road and Rail Transport Not regulated

<u>IATA</u> Not regulated

Special Precautions for User No special precautions required

## **SECTION 15: REGULATORY INFORMATION**

Safety, health and environmental regulations/legislation specific for the substance or mixture

Sulfur in Diesel Fuel standard solution, Specpure, 50µg/g (0.0050%)

International Inventories X = listed

Component	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	IECSC	AICS	KECL
Fuels, diesel, no. 2	270-676-1	Х	Х	X	-		Х	Х	KE-17287
Butane, 1,1'-thiobis-	208-870-5	Х	Х	Х	Х	X	Х	Х	-

#### **National Regulations**

**Persistent Organic Pollutant Ozone Depletion Potential** 

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

## **SECTION 16: OTHER INFORMATION**

#### Legend

**CAS** - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b)

Revision Date 31-Mar-2025

Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic

Substances/EU List of Notified Chemical Substances

Substances List **ENCS** - Japanese Existing and New Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances IECSC - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

AICS - Australian Inventory of Chemical Substances NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

POW - Partition coefficient Octanol:Water

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

ADR - European Agreement Concerning the International Carriage of

Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime

Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from

Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

#### Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Health, Safety and Environmental Department **Prepared By** 

**Revision Date** 31-Mar-2025 Not applicable. **Revision Summary** 

In accordance with local and national regulations: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information

Sulfur in Diesel Fuel standard solution, Specpure, 50µg/g (0.0050%)

Revision Date 31-Mar-2025

relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**